



Cisco Product Quick Reference Guide

FEBRUARY 2006

Corporate Headquarters

Cisco Systems, Inc.
170 West Tasman Drive
San Jose, CA 95134-1706
USA
<http://www.cisco.com>
Tel: 408 526-4000
800 553-NETS (6387)



Cisco Product Quick Reference Guide
Copyright © 2006, Cisco Systems, Inc.
All rights reserved.

General Disclaimer

Although Cisco has attempted to provide accurate information in this Guide, Cisco assumes no responsibility for the accuracy of the information. Cisco may change the programs or products mentioned at any time without prior notice. Mention of non-Cisco products or services is for information purposes only and constitutes neither an endorsement nor a recommendation of such products or services or of any company that develops or sells such products or services.

ALL INFORMATION PROVIDED ON THIS WEBSITE IS PROVIDED “AS IS,” WITH ALL FAULTS, AND WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED. CISCO AND ITS SUPPLIERS DISCLAIM ALL WARRANTIES, EXPRESSED OR IMPLIED INCLUDING, WITHOUT LIMITATION, THOSE OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT, OR ARISING FROM A COURSE OF DEALING, USAGE, OR TRADE PRACTICE.

CISCO AND ITS SUPPLIERS SHALL NOT BE LIABLE FOR ANY INDIRECT, SPECIAL, CONSEQUENTIAL, OR INCIDENTAL DAMAGES INCLUDING, WITHOUT LIMITATION, LOST PROFITS OR REVENUES, COSTS OF REPLACEMENT GOODS OR SERVICES, LOSS OR DAMAGE TO DATA ARISING OUT OF THE USE OF THE GUIDE OR ANY CISCO PRODUCT OR SERVICE, OR DAMAGES RESULTING FROM USE OF OR RELIANCE ON THE INFORMATION PROVIDED, EVEN IF CISCO OR ITS SUPPLIERS HAVE BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

Many of the Cisco products and services identified in this Guide are provided with written software licenses and limited warranties.

Those licenses and warranties provide the purchasers of those products with certain rights. Nothing in this Guide shall be deemed to expand, alter, or modify any warranty or license provided by Cisco with any Cisco product, or to create any new or additional warranties or licenses.



Introduction

CPQRC Background	i
Additional Cisco Documentation	i
Cisco Systems Overview	ii
Partner and Customer Support	ii
Foundation Advantage Program	ii
Cisco Authorized Refurbished Equipment (Select Countries Only)	1-iii
Cisco Systems Capital Financing	iv
Cisco Learning Credit Program	v
Product Warranty Information	v
Cisco Lifecycle Services	vi
Helpful Cisco Websites	vii

CHAPTER 1 Routing

Routing at a Glance	1-1
Cisco Routers Port Matrix	1-2
Memory Information for Routers Cisco 7000 Series Port Adapter Compatibility Matrix	1-4
Cisco SB 100 Series	1-6
Cisco 800 Series	1-7
Cisco 1800 Series	1-10
Cisco 2800 Series	1-16
Cisco 3800 Series	1-22
Cisco 7200 VXR Series	1-27
Cisco 7300 Series	1-30
Cisco 7600 Series	1-32
Cisco 10700 Series	1-35
Cisco XR 12000 and 12000 Series	1-36

CHAPTER 2 LAN Switching

LAN Switching Products at a Glance	2-1
Cisco LAN and MAN Products Port Matrix	2-2
Cisco Catalyst Express 500 Series	2-3
Cisco Catalyst 2940 Series	2-4
Cisco Catalyst 2960 Series	2-6
CiscoCisco Catalyst 3750 Series	2-10
Cisco Catalyst 4948 Series	2-14
Cisco Catalyst 4500 Series	2-15
Cisco Catalyst 6500 Series	2-19

CHAPTER 3 Wireless LAN

- Wireless LAN at a Glance (IEEE 802.11 a/b/g) **3-1**
- Cisco Aironet 1000 Series Lightweight Access Point **3-2**
- Cisco Aironet 1130AG Series Access Point **3-3**
- Cisco Aironet 1200 Series Access Points **3-5**
- Cisco Aironet 1230AG Series Access Point **3-7**
- Cisco Aironet 1240AG Series Access Point **3-9**
- Cisco Aironet 1300 Series **3-11**
- Cisco Aironet 1500 Series Lightweight Outdoor Wireless Mesh Access Point **3-13**
- Cisco Aironet 802.11a/b/g Wireless CardBus and PCI Adapters **3-14**
- Cisco Aironet 1400 Series Wireless Bridge **3-15**
- Cisco Antennas and Accessories **3-17**
- Cisco 2000 Series Wireless LAN Controller **3-20**
- Cisco 4400 Series Wireless LAN Controller **3-22**
- Cisco Wireless Control System (WCS) **3-23**
- Cisco Wireless Location Appliance **3-24**

CHAPTER 4 Voice and IP Communications

- Voice and IP Communications at a Glance **4-1**
 - Cisco CallManager 4.1 **4-4**
 - Cisco CallManager Express **4-7**
 - Cisco Survivable Remote Site Telephony (SRST) **4-8**
 - Cisco Unity—Unified Messaging and Voice Mail **4-9**
 - Cisco Unity Connection **4-11**
 - Cisco Unity Express **4-12**
 - Cisco Personal Assistant **4-13**
 - Cisco IP Contact Center (IPCC) Enterprise Edition **4-14**
 - Cisco IPCC Express Edition **4-15**
 - Cisco IPCC Hosted Edition **4-16**
 - Cisco ICM Enterprise Edition **4-17**
 - Cisco ICM Hosted Edition **4-17**
 - Cisco IP IVR **4-18**
 - Cisco Customer Voice Portal **4-19**
 - Cisco 7900 Series IP Phones **4-19**
 - Cisco ATA Series of Analog Telephone Adaptors **4-21**
 - Cisco IP Communicator **4-23**
 - Cisco VT Advantage **4-23**
 - Cisco Emergency Responder **4-24**
 - Cisco IP Manager Assistant **4-25**
 - Cisco MCS 7800 Series Media Convergence Servers **4-26**
 - Cisco Voice Gateways **4-27**
 - Memory Information for Universal Gateways **4-28**
 - Cisco AS5350 Series Universal Gateway **4-28**
 - Cisco AS5400 Series Universal Gateways **4-30**
 - Cisco AS5850 Universal Gateway **4-32**
 - Cisco IP/VC 3500 Series Videoconferencing Products **4-34**
 - Cisco MeetingPlace **4-35**
 - Cisco MeetingPlace Express **4-37**
 - Cisco Voice Router Bundles **4-38**
 - Cisco CallManager Express Bundles **4-39**
- 

SRST Bundles **4-39**

Cisco V3PN Bundles **4-40**

CHAPTER 5 VPN and Security

VPN and Security Products at a Glance **5-1**

Cisco ASA 5500 Series Adaptive Security
Appliance **5-3**

Cisco PIX Security Appliance Series **5-6**

Cisco Intrusion Protection System (IPS)

Network Sensors **5-8**

Cisco Incident Control System (ICS) **5-10**

Cisco Security Monitoring and Response System (CS-MARS) **5-11**

Cisco VPN 3000 Family **5-14**

Network Admission Control (NAC) **5-17**

Cisco NAC Appliance (Cisco Clean Access) **5-17**

Cisco Security Agent **5-19**

Cisco Security Auditor **5-20**

Cisco Secure Access Control Server (ACS) for Windows **5-22**

Cisco Secure Access Control Solution Engine **5-23**

Cisco Guard Appliance **5-24**

Cisco Router and Security Device Manager **5-25**

Cisco IOS® Firewall **5-27**

Cisco Security Router Bundles with Integrated Network Security **5-28**

CHAPTER 6 Content Networking

Content Networking at a Glance **6-1**

Content Networking Overview **6-2**

Cisco Content Engines (CE) **6-2**

Cisco CSS 11500 Series Content Services Switches **6-4**

Cisco Content Switching Module (CSM) **6-5**

Cisco SSL Module for Catalyst 6500 **6-6**

Cisco DistributedDirector **6-7**

Cisco GSS 4491 Global Site Selector **6-8**

CHAPTER 7 Broadband and Dial Access

Broadband and Dial Access Products at a Glance **7-1**

SS7 Signaling & Softswitch Products **7-3**

Cisco BTS 10200 Softswitch **7-3**

Cisco uBR7100 Series Universal Broadband Router **7-4**

Cisco uBR7246VXR Universal Broadband Router **7-5**

Cisco uBR10012 Universal Broadband Router **7-6**

Cisco uBR 3x10 RF Switch **7-7**

Remote Cable Access—Network Management Products **7-8**

Cisco Broadband Troubleshooter **7-8**

Cisco Broadband Configurator **7-8**

DSL Remote Access—Customer Premise Equipment (CPE) **7-9**

Broadband Services Aggregation **7-9**

ATM Multiservice WAN Switching **7-10**

Cisco MGX 8850 ATM Multiservice Switch **7-10**

Cisco MGX 8830 ATM Multiservice Switch **7-10**

Cisco Long Reach Ethernet Solution **7-11**

Cisco Building Broadband Service Manager (BBSM) Version 5.3 **7-13**



CHAPTER 8 Optical Networking

- Optical Networking at a Glance **8-1**
- Cisco ONS 15600 Multiservice Switching Platform **8-3**
- Cisco ONS 15454 SONET/SDH Multiservice Transport Platform (MSTP) **8-3**
- Cisco ONS 15454 Multiservice Provisioning Platforms **8-4**
- Cisco ONS 15530 **8-4**
- Cisco ONS 15540 Extended Services Platform (ESPx) **8-5**
- Cisco ONS 15216 Metro DWDM Series **8-6**
- Cisco ONS 15327 SONET Multiservice Provisioning Platform **8-6**
- Cisco ONS 15310-CL SONET Multiservice Provisioning Platform **8-7**
- Cisco ONS 15302/15305 SDH Multiservice Access Platforms (MSAP) **8-7**
- Cisco Transport Manager (CTM 6.0)
(Optical Element/Network Management) **8-8**

CHAPTER 9 IOS® Software and Network Management

- Cisco IOS® Software and Network Management at a Glance **9-1**
- Cisco IOS® Software **9-3**
- Cisco IOS® Technologies **9-6**
 - Broadband **9-6**
 - High Availability **9-7**
 - IPv6 **9-7**
 - IP Mobility **9-7**
 - IP Multicast **9-8**
 - IP Routing **9-8**
 - Management Instrumentation **9-8**
 - Multiprotocol Label Switching (MPLS) **9-9**
 - Quality of Service (QoS) **9-9**
 - Security **9-10**
 - Voice **9-10**
- Key Cisco IOS Tools **9-11**
- Cisco Network Management Overview **9-11**
- CiscoWorks Small Network Management Solution (SNMS) **9-11**
- CiscoWorks LAN Management Solution **9-12**
- CiscoWorks VPN/Security Management Solution (VMS) **9-13**
- CiscoWorks Security Information Management Solution and CiscoWorks Security Information Management Solution Engine **9-15**
- CiscoWorks IP Communications Operations Manager **9-16**
- CiscoWorks IP Communications Service Monitor **9-18**
- CiscoWorks Voice Manager for Voice Gateways **9-19**
- CiscoWorks QoS Policy Manager **9-20**
- CiscoWorks Wireless LAN Solution Engine and CiscoWorks Wireless Solution Engine Express **9-22**
- Cisco Catalyst 6500 Series Network Analysis Module 1 and 2(with NAM software version 3.3) **9-23**

CHAPTER 10 Storage Networking

- Storage Networking at a Glance **10-1**
- Cisco MDS 9000 Family Multilayer Directors and Fabric Switches **10-2**
- Additional Storage Networking Solutions **10-7**
 - Cisco MDS 9000 Port Analyzer Adapter—Reducing Time to Problem Resolution **10-7**
 - Cisco MDS 9000 Optical Modules—Optimizing SAN Interconnect **10-7**









Introduction

CPQRG Background

The Cisco Product Quick Reference Guide (CPQRG) is a handy, compact reference tool that includes brief product overviews, key features, sample part numbers, and abbreviated technical specifications for many of Cisco's products sold through our Channel partners. The CPQRG is primarily published to support Cisco partners, resellers, sales account teams, and even end-user customers who need a broad, high-level overview of Cisco products, but at that moment do not have access to Cisco's website, Cisco.com at <http://www.cisco.com>.

Additional Information

For questions, comments, and to register a copy of the CPQRG, visit <http://www.cisco.com/go/guide>.

Additional Cisco Documentation

For a complete listing of the latest Cisco product documentation, visit the product documentation store on Marketplace.

Key Features

- A complete listing of the latest documentation to accompany your Cisco products including Installation guides, Quick reference guides, Accessory guides, User guides, Configurations guides, Command references, and Release notes.
- Customized CD-ROM—Pick the documents that you want, and Marketplace puts them onto a CD-ROM. It's like having your own customized library of Cisco documents.
- Cisco Product Documentation DVD—A comprehensive library of technical product documentation on a portable medium; Access multiple versions of installation, configuration, and command guides for Cisco hardware and software products; View the HTML documents found on our website without being connected to the Internet. Order one copy or a one-year subscription.

For More Information

See the Cisco Marketplace Web site: <http://www.cisco.com/go/marketplace/>

Cisco Systems Overview

Cisco Systems, Inc. is the worldwide leader in networking for the Internet. Today, networks are an essential part of business, education, government and home communications, and Cisco Internet Protocol-based (IP) networking solutions are the foundation of these networks. Cisco hardware, software, and service offerings are used to create Internet solutions that allow individuals, companies, and countries to increase productivity, improve customer satisfaction and strengthen competitive advantage. The Cisco name has become synonymous with the Internet, as well as with the productivity improvements that Internet business solutions provide. At Cisco, our vision is to change the way people work, live, play and learn.

Cisco was founded in 1984 by a small group of computer scientists from Stanford University. Since the company's inception, Cisco engineers have been leaders in the development of Internet Protocol (IP)-based networking technologies. This tradition of IP innovation continues with industry-leading products in the core areas of routing and switching, as well as advanced technologies in areas such as: Home Networking, Optical, Storage Networking, IP Telephony, Network Security, and Wireless LAN

Today, with more than 34,000 employees worldwide, Cisco remains committed to creating networks that are smarter, thanks to built-in intelligent network services; faster, in their ability to perform at ever-increasing speeds; and more durable, with a generational approach to an evolutionary infrastructure.

Partner and Customer Support

Partner Sales and Technical Assistance Contact Information

Customer Help Lines	Contact Information
Presales—Partner/Reseller Helpline	800 553-6387 (within U.S.) 408 526-7208 (outside U.S.) http://CiscoPartner.custhelp.com/
Post-Sales—Technical Assistance Center (TAC)	800 553-2447 (within U.S.) 408 526-7209 (outside U.S.) tac@cisco.com (e-mail) http://www.cisco.com/warp/customer/687/Directory/DirTAC.shtml

Foundation Advantage Program

Learn about the new Channel Incentive Program that will you help your customers identify old equipment and modernize their infrastructure with Cisco technology helping them grow, protect and optimize their networks. The Foundation Advantage Program for Channel Partners represents a consolidation of Cisco's most successful equipment trade-in programs, as well as innovative, new programs.

For More Information

See the Foundation Advantage Web site:

<http://www.cisco.com/web/partners/pr11/incentive/fa.html>

Cisco Authorized Refurbished Equipment (Select Countries Only)

Customers looking for used Cisco equipment can now be assured of the quality and support they come to expect from new Cisco products, through the Cisco Authorized Refurbished Equipment program. Cisco Authorized Refurbished Equipment gives customers a price competitive alternative to buying uncertified and unlicensed products off the secondary market. All equipment sold through this program is labeled “Refurbished by Cisco Systems,” indicating that the product is Cisco tested, refurbished, authorized, and supported.

Advantages to customer

- Fully tested and refurbished by Cisco
- Current revision IP-only software and new software license included
- Full warranty protection (same as new) through Cisco’s Technical Assistance Center
- Automatically eligible to add SMARTnet Maintenance or other service contracts for extra support
- Both current and end-of-sale products available
- Competitive pricing

Key Features

- The Cisco Authorized Refurbished Equipment program is currently limited to certain countries (US, Canada, EMEA, Japan, and selected countries in Asia Pacific). More countries will be added in the future. Please contact your Cisco Account Manager or Partner to check the availability of the program in your country and the applicable conditions.
- Products are mainly available through distribution, so customers should contact a Cisco authorized reseller for more inventory information. Customers can find a Cisco authorized reseller by clicking [here](#).
- Inventory varies daily, and sales are on a first-come, first-served basis. For current inventory and pricing, Cisco authorized resellers can go to the Distribution Products Reference Guide (DPRG) at www.cisco.com/dprg (click on "Refurbished Products")
- Both individual features and standard configurations are available
- Standard configurations and pricing are based on minimum configuration required to run current revision IP-only software. Please review Standard Configurations to see parts included
- Part numbers are similar to new Cisco part numbers but with an “-RF” suffix added
- All Cisco Authorized Refurbished Equipment are clearly marked as “Refurbished by Cisco Systems”

In conjunction with offering Cisco Authorized Refurbished Equipment, Cisco Systems has established a program for resellers and customers to purchase software licenses for their used Cisco equipment that is not purchased through the Cisco Authorized Refurbished Equipment program.

For More Information

End Users/Customers:

cisco.com/en/US/ordering/or6/or17/order_refurbished_equipment_program_description.html

Resellers: <http://www.cisco.com/go/refurb> (click on “Refurbished Products”)

Cisco Systems Capital Financing

Cisco Systems Capital® Corporation (“Cisco Capital”)—a wholly owned subsidiary of Cisco Systems, Inc.—provides innovative financing programs for Cisco Systems’ customers and partners to acquire networking solutions on a global basis. It provides inventory and short-term project financing to channel partners. These programs provide credit support for Cisco distributors and channel partners worldwide to help manage the cash flow needs in longer project payment cycles. All Cisco Systems hardware, software and SmartNet are eligible to be financed. Additionally, partner services and installation may be financed as part of the total lease transaction. Cisco Capital Lease financing enables customers to:

- **Better Manage Cash Flow**—By distributing the acquisition cost of the latest Cisco technology over a longer period of time (vs. upfront purchase).
- **Create Flexible Repayment Options**—By matching the benefit/revenue of the technology to the acquisition expense.
- **Access Opex Budgets**—By structuring an operating lease thereby utilizing operating expense budgets(freeing up Capex budgets for other projects)
- **Utilize a Sale and Lease Back**—By converting existing assets into cash
- **Take Advantage of Technology Refresh**—By replacing outdated equipment during the lease term, thereby providing a natural hedge against technology obsolescence

The key to capturing the value of Cisco Systems Capital is to engage early and often with your local Leasing Manager. Finance professionals helps the account team bridge the gap to the financial decision maker by delivering a financing solutions matching Cisco’s leading edge technology solutions.

For More Information

See the Cisco Systems Capital Website:

http://www.cisco.com/en/US/ordering/or6/order_finance_and_payments_concept_home.html

Within the United States, call 800 730-4090.

Cisco Learning Credit Program

Cisco Learning Credits are a purchase method for authorized training redeemable with Cisco Learning Partners and for a subscription to Networkers Online. Cisco Learning Credits can be added to your purchase order when ordering Cisco products and offer several benefits:

- Ensures staff is expertly trained to get the best value out of the purchase of new equipment
- Enables internal staff to optimize network efficiencies and gain overall productivity for your organization
- Safeguards training budget by adding Learning Credits to the equipment purchase order
- Reduces administrative costs by reducing the need to open multiple purchase orders.
- Keeps Cisco representatives aware of and involved in the training levels and needs of your organization

Purchase Learning Credits

Credits are ordered along with a hardware purchase or as a standalone item. By integrating training from the start, you set the stage for the most productive use of your network. Each Learning Credit (sold in packs of 10, 100, 500 or 1500) pays for US\$100 worth of training. Credits are valid for one year and may be redeemed individually.

Learning Credit Pack

Part Number	Credits	Value
TRN-CLC-000	10	\$1,000
TRN-CLC-001	100	\$10,000
TRN-CLC-002	500	\$50,000
TRN-CLC-003	1500	\$150,000

For More Information

See the Cisco Learning Credit Program Website at

http://www.cisco.com/en/US/learning/le31/l59/learning_credits_purchase.html

Product Warranty Information

All Cisco hardware and software products are covered for a minimum of 90 days. Some products have a longer or more appropriate coverage. All Cisco warranties apply to the Customer or Original Owner (the individual who purchased the product for their own use) also referred to as the End User.

Warranty ¹	Entitlements Description
Cisco Standard 90-day Hardware Warranty, Software Warranty and License Agreement (78-5235-vvrr)	• Advance Replacement shipping within 10 business days from RMA Request Date within 90 Days of original shipment from Cisco or from Cisco Reseller • 90-Day Assurance that the SW Media is defect-free and the SW conforms to its published specifications • Guest Access to Cisco Connection Online (CCO)
90-Day Limited Hardware Warranty(78-5236-vvrr)	• Advance Replacement shipping within 10 business days from RMA Request Date within 90 Days of original shipment from Cisco or from Cisco Reseller • 90-Day Assurance that the SW Media is defect-free and the SW conforms to its published specifications • Guest Access to Cisco Connection Online (CCO)
One-Year Limited Hardware Warranty (78-10747-vvrr)	• Advance Replacement shipping within 10 business days from RMA Request Date within One Year of original shipment from Cisco or from Cisco Reseller • 90-Day Assurance that the SW Media is defect-free and the SW conforms to its published specifications • Guest Access to Cisco Connection Online (CCO)

Warranty ¹	Entitlements Description
Limited Lifetime Hardware Warranty (78-6310-vvrr)	• Advance Replacement shipping within 10 business days from RMA Request Date during supported life of the product, starting original ship date from Cisco or Cisco reseller. (Fan and power supply warranty limited to 5 years from ship-date) • 90-Day Assurance that the SW Media is defect-free and the SW conforms to its published specifications • Guest Access to Cisco Connection Online (CCO)
End-User Software License Agreement and Software Warranty (78-3621-vvrr)	• 90-Day Assurance that the SW Media is defect-free and the SW conforms to its published specifications • End User License Agreement terms • Guest Access to Cisco Connection Online (CCO)
5-Years Limited Hardware and 1-Year Limited Software Warranty (78-13712-vvrr)	• Replacement shipping within 15 business days from RTF Date within 5 Years from the original ship date from Cisco or Cisco reseller • One-Year Assurance that the SW Media is defect-free and the SW conforms to its published specifications • Guest Access to Cisco Connection Online (CCO)
5-Years Limited Hardware and 5-Year Limited Software Warranty² (78-13712-vvrr)	• Replacement shipping within 15 business days from RTF Date within 5 Years from the original ship date from Cisco or Cisco reseller • Five-Year Assurance that the SW Media is defect-free and the SW conforms to its published specifications • Guest Access to Cisco Connection Online (CCO)

1. “vv” and “rr” suffixes of the warranty document numbers represent the revision and version numbers respectively.
2. The Cisco Limited 5-Year Hardware and 5-Year Software Warranty is available only to qualified World Wide Service Providers which Cisco defines as owners and operators of the world’s collection of voice-oriented Public Switched Telephone Networks (PSTNs)

For More Information

See the Cisco Product Warranties Website:

http://www.cisco.com/en/US/products/prod_warranties_listing.html

Cisco Lifecycle Services

As the network has become a more strategic asset, the need for higher availability, security, and reliability has increased. Delivering what companies require to achieve a converged, complex network takes specialized knowledge and skills in a growing list of advanced technologies that includes security, voice, wireless LAN, and storage networking. Successful adoption of advanced technologies requires an approach that aligns business and technical requirements through all six phases of the network lifecycle:

- Prepare—Establish a technology vision, business case, and high-level conceptual architecture
- Plan—Assess the existing environment to determine whether it can support the proposed system
- Design—Devise a system that meets business and technical requirements
- Implement—Integrate the new solution without disrupting the network or creating points of vulnerability
- Operate—Maintain network health through day-to-day operations
- Optimize—Achieve operational excellence by adapting the architecture, operation, and performance of the network to ever-changing business goals
- Helps companies to lower the cost of owning and operating the network, improve their ability to respond to rapidly changing market conditions, speed access to applications and services, and increase network availability

For More Information

See the Cisco Services Website:

http://www.cisco.com/en/US/products/svcs/ps2961/serv_category_home.html

Introduction

Helpful Cisco Websites

Partner Resources

Associate Myself With A Partner	If you are an employee of Cisco Registered and Cisco Certified or Specialized Partners, you can associate yourself with your company and upgrade your current Cisco.com ID to partner level http://tools.cisco.com/WWChannels/GETLOG/jsp/GetLogin.jsp?page=PartnerUserHomePage
Channel Partner Tools Index	http://www.cisco.com/web/partners/tools.html
Partner Registration	Begin your relationship with Cisco by registering as a Cisco Registered or Certified Partner http://tools.cisco.com/WWChannels/IPA/welcome.do
Partner Self-Service	These tools provide streamlined data and access management to you and your sales representatives, giving partner administrators and sales representatives a simple way to manage company data -- including contacts, locations, and access. http://tools.cisco.com/WWChannels/GETLOG/login.do
Partner Locator	Lets potential customers locate a qualified channel partner identified on the basis of specific criteria such as certification level, specialization, Advanced Technology Provider (ATP), or geography. This tool also provides an easy way to obtain or verify partner information. Channel partners can use the tool to verify company information or identify other channel partners for collaboration. http://tools.cisco.com/WWChannels/LOCATR/jsp/partner_locator.jsp
Channel Account Manager (CAM) Locator	Search for a CAM assigned to a specific partner. http://tools.cisco.com/WWChannels/CAMLLOC/jsp/cam_locator.jsp
Channel Partner Program	http://www.cisco.com/en/US/partners/pr11/index.shtml
Marketing Fund Builder (U.S. only)	Cisco offers the Marketing Fund Builder program to provide financial support for certified partners that want to expand their business. Get funding for pre-approved activities, including events, direct mail pieces, e-mail blasts, and advertising. http://www.cisco.com/web/partners/market/funds/index.html
Market Cisco Technologies and Services	Marketing is a crucial component of a company's business strategy. Because you are a valued channel partner, Cisco would like to help simplify your organization's marketing plan. Cisco has provided three options to assist your company with its marketing efforts, and links to our most frequently used marketing tools and resources. http://www.cisco.com/en/US/partners/pr61/marketing.shtml
Campaign Builder (Available in certain countries)	Build your end-to-end solution with Campaign Builder from Cisco, formerly Collateral Builder. Create customizable e-mail blasts, postcards, ads, flyers and more to build customer awareness, while reducing time-to-market and overall costs. http://www.cisco.com/web/partners/market/campaign-builder/index.html
Partner Access onLine (PAL)	Provides free real-time partner-customized access to trend-tracking data and to a data-collection system. PAL helps identify areas for improvement, strengthens customer relationships, and builds long-term customer loyalty. http://www.cisco.com/en/US/partner/applicat/partacccs/applications_overview.html
Partner Business Central (PBC)	A portal to all commerce-enabling applications used by channel partners and channel account managers (CAMs) worldwide. PBC streamlines product selection, comparison, configuration, and validation processes, and provides easy access to distributor part numbers. http://www.cisco.com/appcontent/echannels/pbc/
Partner Business Planning	Helps you and channel account managers (CAMs) collaborate on strategic planning by identifying incremental revenue streams, aligning objectives, and optimizing market opportunities to help ensure mutual success. http://tools.cisco.com/WWChannels/UNIFY/welcome.jsp
Partner E-Learning Connection (PEC)	The primary learning source for channel partners who want fast, accessible training solutions in several formats. http://www.cisco.com/go/pec_publicizedirect/
Partner Events	http://www.cisco.com/web/partners/pr47/events.html
Partner Help Online	An up-to-date knowledgebase of support information. If the answer is not available in the knowledgebase, this tool provides fast access to support cases. http://www.cisco.com/en/US/partner/partners/partners_esupport_tool_launch.html
Partner Help Online - Direct FAQ access	Search partners' frequently asked questions and ask for the help you need http://ciscopartner.custhelp.com/
Partner News@Cisco	http://www.cisco.com/web/partners/pr47/partners_whats_new.html
Partner Incentives and Promotions	To encourage our channel partners to do their best, Cisco has created multiple programs to help boost your profitability and success in specific vertical markets and across several technology areas. Choose from proven programs that offer rewards, incentives, or extra discounts. http://www.cisco.com/en/US/partner/partners/pr61/pr73/partners_promotions_concept_home.shtml

Selling Resources

End-of-Sale and End-of-Life Products	http://www.cisco.com/en/US/products/prod_end_of_life.html
RMA US and Canada Service Order Returns	Schedule an on-line return of your contracted Service RMA at Cisco's expense. http://www.cisco.com/warp/customer/708/GPSTools/RMAWebReturns/rma_web_based_returns.html
RMA/Service Order	With your open service request, request or view your order for replacement hardware. http://tools.cisco.com/serviceordertools/svosubmit/tools.do
Sales Resources	http://www.cisco.com/en/US/partners/pr61/partners_marketing_category_home.shtml
Distributor Locator	Locate a Cisco distributor in any country. http://tools.cisco.com/WWChannels/LOCATR/jsp/distributor_locator.jsp
Get Cisco.com Access	Register for a guest-level Cisco.com ID as a prerequisite for partner level access http://tools.cisco.com/RPF/register/register.do
IOS Upgrade Planner	Browse to find the information you need to upgrade your Cisco IOS software. http://www.cisco.com/cgi-bin/Software/Iosplanner/Planner-tool/iosplanner.cgi?majorRel=
Learning & Events	http://www.cisco.com/en/US/learning/

Technical Resources

Technical Support	For customer support tips, software center, online documents, and more. http://www.cisco.com/go/support
Command Lookup Tool for Cisco IOS	Look up a detailed description or configuration guidelines for a particular Cisco IOS, Catalyst or PIX command. http://www.cisco.com/cgi-bin/Support/Cmdlookup/home.pl
Discussion Forums	Share questions, suggestions, and information about networking solutions, products, and technologies in discussion forms, Tech Talks and Ask the Expert forums. http://forums.cisco.com/eforum/servlet/NetProf?page=main http://www.cisco.com/go/netpro/
Developer Services FAQs Central	http://www.cisco.com/pcgi-bin/front.x/cse/DSFC/DSFCGuestLogin.pl
Developer Support Central Supported Products	http://www.cisco.com/pcgi-bin/dev_support/access_level/product_support
Error Message Decoder	Look up explanations for console error message strings listed in the Cisco Software System Messages guide. http://www.cisco.com/cgi-bin/Support/Errordecoder/index.cgi
Field Notices	Review the list of the Product Field Notices issued by Cisco. http://www.cisco.com/kobayashi/support/tac/fn_index.html
Product Alert Tool	Set up a profile to receive email updates about reliability, safety, network security and end-of-sale issues for the Cisco products you specify. http://tools.cisco.com/Support/PAT/do/ViewMyProfiles.do
Product Upgrade Tool	Request hardware upgrades, software on media or software that is not available in the Software Center, and hard-copies of UniverCD documentation. http://tools.cisco.com/gct/Upgrade/jsp/productUpgrade.jsp
Report Product Security Incidents	Report security problems you have with a Cisco product. http://www.cisco.com/en/US/customer/products/products_security_vulnerability_policy.html
Security Advisories	Stop an active security attack or prevent an imminent security risk. http://www.cisco.com/en/US/customer/products/products_security_advisories_listing.html
Software Advisor	Find software compatible with my hardware and with the features I need, compare the features in different software releases, or research a software release. http://tools.cisco.com/Support/Fusion/FusionHome.do



Routing

Routing at a Glance

Product	Features	Page
Cisco IOS® Software	See the Chapter 9—Cisco IOS Software and Network Management for an overview of Cisco IOS Software	9-1
Cisco Small Business (SB) 100 Series	- Fixed-configuration, small-office secure broadband routers that support up to five users - Security features including stateful inspection firewall and access control lists - Security Device manager (SDM) GUI tool for simple and advanced configuration	1-6
Cisco 800 Series	- Integrated services routers allow small offices to operate secure concurrent services, including firewall, VPNs, and wireless LANs, at broadband speeds - Wireless support: Optional IEEE 802.11 b/g on 850 and 870 Series - Enhanced security features including stateful inspection firewall and hardware assisted encryption (830 and 870 series) and QoS features for VoIP - DMZ, Dial back up and out-of-band management (Cisco 830, 850, and 870 series) - SDM GUI tool for simple and advanced configuration	1-7
Cisco 1800 Series	- Modular and fixed architectures—Offers wide variety of LAN and WAN options; network interfaces on Cisco 1841 are field-upgradeable for flexibility and to accommodate future technologies - Fixed configuration models offer 10/100 ethernet, ADSL over ISDN, ADSL over POTS, or G.SHDSL WAN interfaces with integrated ISDN BRI (1801, 1802, 1803, and 1812) or analog modem (1811) backup interfaces - Wireless LAN access using IEEE 802.11 a/b/g is available for all models of the 1800 Series	1-10
Cisco 2800 Series	- Integrated services routers that are optimized for the secure, wire-speed delivery of concurrent data, voice, and video services for small- to- midsize business and enterprise branch routing - Superior performance with multiple services enabled for 1-6 T1/E1 links - Advanced security features including Stateful Firewall, IPS, VPN and NAC. - Built-in encryption using DES, 3DES, and AES. - Wireless Access Point supporting IEEE 802.11 a/b/g WLANs	1-16
Cisco 3800 Series	- Integrated Services Routers - Highest performance and densities with the ability to run concurrent data, security, voice, and advanced services at wire speed up to T3/E3 - Higher availability and resiliency with Online Insertion and Removal (OIR); redundant system and inline power options - High-speed WAN Interface Cards (HWICs) free up network module slots for other services - Enhanced security - Expanded default and maximum memory capacity with Error Correction Code (ECC) DDR SDRAM memory to detect and correct SDRAM errors without user intervention	1-22
Cisco 7200 Series	- Optimized OC3/GE WAN-edge router providing intelligent services, high modularity, high performance, investment protection, and scalability in a small form factor - Modular 3 RU Chassis 4- or 6-slot models for Port Adapters 1 I/O slot - Choice of system processors (NPE) for up to 1 Mpps performance - Built in Gigabit Ethernet connectivity (3-ports on NPE-G1) (copper or fiber) - Wide variety of LAN and WAN options, including Ethernet, Fast Ethernet, Gigabit Ethernet, Token Ring, serial, ISDN, HSSI, ATM, and Packet over SONET as well as voice support including IP-IP Gateway and QoS.	1-27
Cisco 7300 Series	7304: Network Edge router with high performance IP services delivered at optical speeds for service providers and enterprise networks 7301: WAN-edge router providing intelligent services, PA modularity, high performance, investment protection, and scalability in a 1 RU form factor	1-30

Product	Features	Page
Cisco 7600 Series	- Consolidated WAN/MAN/LAN in a single platform - Scalable backplane bandwidth from 32 Gbps to 720 Gbps and performance from 30 Mpps to over 400 Mpps with new Sup720 engine and distributed forwarding line cards - Scalable backplane bandwidth from 32 Gbps to 720 Gbps and performance from 30 Mpps to over 400 Mpps with new Sup720 engine and distributed forwarding line cards - High-volume aggregation of service-enabled Ethernet - Wide range of WAN/MAN interfaces from NxDS0, T1, T3 to OC-48 with line rate services - Ideal for service provider edge, metropolitan area network, & triple-play deployments, and high-end enterprise solutions - Also supports Catalyst 6500 series line cards and 75/7200 port adapters	1-32
Cisco 10700 Series	- Service provider-class metro edge services router - Optimized building block for the next generation metro Ethernet/IP access networks - Equipped with either (24) 10/100 or 4 GbE and 8 FE ports for customer access and OC-48c/STM-16c dynamic packet transport/resilient packet ring (DPT/RPR) technology or Packet Over SONET (POS) for metro optical connectivity - Supports IEEE 802.17 standard compliant RPR technology	1-35
Cisco XR 12000/12000 Series	- Service provider-class multiservice-edge router to enable customer to transition toward a converged IP Network Infrastructure - Supports edge-optimized line cards maximizing the value of line-rate edge applications with 10G uplinks while sustaining line-rate performance - Up to nine chassis options with new power supply and blower enhancements supporting a portfolio of SPAs and SIPs - Extensive portfolio of line cards and SPAs that support POS, ATM, Ethernet, DPT/RPR and copper, channelized physical interfaces - Service-related enhancements (L3VPN, L2VPN, QoS) that ensures traffic differentiation while meeting the strictest customer service-level agreements	1-36
Product Ordering Website	To place an order, visit the Cisco Ordering Website: http://www.cisco.com/en/US/ordering/index.shtml	

Cisco Routers Port Matrix

	SB 100 Series	800 Series	1800 Series	2800 Series	3800 Series	7100 Series	7200 Series	7300 Series	7600 Series	10700 Series	12000 Series
Fixed Ports Only	X	X									
Fixed & Modular Ports			X	X	X	X	X	X	X		X
Modular Ports Only										X	
LAN Ports											
10-Mbps Ethernet		X				X	X		X	X	
10-Mbps Ethernet (fiber)						X	X		X		
100-Mbps Ethernet		X	X	X	X	X	X		X	X	X
100-Mbps Ethernet (fiber)					X	X	X	X	X	X	X
10/100-Mbps Ethernet	X	X	X	X	X	X	X	X	X	X	X
10/100 Mbps Switch Port	X	X	X	X	X				X		
Token Ring					X	X	X	X ¹			
ATM				X	X		X	X	X		
Gigabit Ethernet				X ²	X	X	X	X	X	X	X
10 Gigabit Ethernet									X		X
Wireless LAN Access Point		X	X	X	X						
WAN Ports											
Sync Serial		X	X	X	X		X	X	X		
Sync Serial w/ CSU			X	X	X						
ISDN BRI (S/T)		X	X	X	X	X	X	X ¹			
ISDN BRI (U)		X	X	X	X	X	X	X ¹			
ISDN PRI/Ch T1				X	X	X	X	X ¹			
ISDN PRI w/ CSU				X	X		X	X ¹			
Async		X	X	X	X						
Analog/POTS		X		X	X						
Integrated Modems			X	X	X						

Chapter 1

	SB 100 Series	800 Series	1800 Series	2800 Series	3800 Series	7100 Series	7200 Series	7300 Series	7600 Series	10700 Series	12000 Series
Integrated Modem WICs			X	X	X						
HSSI					X	X	X	X	X		
DS3				X ²	X	X	X	X	X		X
ATM OC-3						X	X	X	X		X
ATM OC-12								X	X		X
ATM		X		X	X		X	X	X		
ATM - T1/E1				X	X	X	X	X	X		
POS OC-x/STM-x						X	X	X	X		X
DPT/RPR OC-12/STM-4											X
DPT/RPR OC-48/STM-16									X	X	X
DPT/RPR OC-192/STM-64											X
ADSL, ADSL 2+	X	X	X	X	X						
ADSL over ISDN	X	X	X	X	X						
G.SHDSL		X	X	X	X						
IDSL			X	X	X						
DPT										X	X
Voice Over IP (VoIP)											
Analog Voice Interfaces				X	X						
Digital Voice Interfaces				X	X		X	X	X		
ISDN BRI Digital Voice Interfaces				X	X						
Integrated Switching											
Integrated 4-port Switch	X	X									
Integrated 8-port Switch			X ³								
Integrated 4-port Switch HWIC			X ⁴	X	X						
Integrated 9-port Switch HWIC				X	X						
Integrated 16-port Switching				X ⁵	X						
Integrated 24-port Switching				X ⁶	X						
Integrated 36-port Switching				X ⁷	X						
Integrated 48-port Switching				X ⁶	X						
Power over Ethernet (PoE)		X	X	X	X						
Content Acceleration											
Content Engine				X	X				X		
Security VPN											
IPS		X	X	X	X	X	X	X ¹	X		
Encryption Advanced Integration Modules		X	X	X	X				X		
Encryption Service Adapter							X	X ¹	X		

1. 7301 only
2. Supported on the 2691 only
3. Except 1841
4. 1841 only
5. Cisco 2811, 2821, and 2851 only
6. Cisco 2821 and 2851 only
7. Supported on CISC02851 only

Memory Information for Routers Cisco 7000 Series Port Adapter

Router	Memory Type	Slots	Default Memory	Max Memory	Default Configuration (Notes)
SB 100 Series	Flash	N/A	12 MB	12 MB	12 MB
	DRAM		64 MB	64 MB	64 MB
801	Flash	1	8 MB	12 MB	4 MB on board and 4 MB or 8 MB Mini flash card
	DRAM	1	8 MB	12 MB	4 MB onboard and 4 MB or 8 MB DIMM module
805	Flash	1	8 MB	12 MB	
	DRAM	1	8 MB (On board)	16 MB	4 MB On board + 4 MB Mini Flash
831, 836, 837	Flash	1	12 MB	24 MB	8MB On board + 4MB, 8MB or 16MB Mini Flash
	DRAM	1	64 MB	80 MB	64 MB On board + 16MB DIMM module
851, 857	Flash	1	20 MB	20 MB	20 MB On board
	DRAM	1	64 MB	64 MB	64 MB On board
871, 876, 877, 878	Flash	1	24 MB or 28 MB ¹	52 MB	20MB On board + 4MB or 8MB* Mini Flash
	DRAM	1	128 MB	256 MB	128 MB On board + 128MB DIMM module * Advanced IP Services image includes 28MB flash
1800 Series	Flash	1	32 MB	128 MB	External compact flash
	DRAM	1	128 MB	384 MB	128 MB on motherboard, plus one slot
2800 Series	DRAM (2801)		128 MB	384 MB	Slot 0 = 128 MB, Slot 1 = Empty
	DRAM (2811)		256 MB	768 MB	Slot 0 = 256MB, Slot 1 = Empty
	DRAM (2821)		256 MB	1 GB	Slot 0 = 256MB, Slot 1 = Empty
	DRAM (2851)		256 MB	1 GB	Slot 0 = 256MB, Slot 1 = Empty
	Compact Flash (2801)		64 MB	128 MB	Single 64 MB Compact Flash default
	Compact Flash (2811)		64 MB	256 MB	Single 64 MB Compact Flash default
	Compact Flash (2821)		64 MB	256 MB	Single 64 MB Compact Flash default
	Compact Flash (2851)		64 MB	256 MB	Single 64 MB Compact Flash default
3800 Series	Flash (External Compact Flash)	1	64 MB	256 MB	Single 64 MB Compact Flash default
	DDR SDRAM (ECC)	2	256 MB	1 GB	Slot 0 = 256MB, Slot 1 = Empty
7100 Series	Flash (PCMCIA)	2	48 MB	110 MB	Slot 0 = 48 MB
	System SDRAM	2	64 MB	256 MB	Slot 0 = 64 MB
	Packet SDRAM		64 MB	64 MB	
7200 Series	Flash (PCMCIA) (for IO controller 2 cards)		64 MB	128 MB	
	Flash (Compact Flash) for NPE-G11		128 MB	256 MB	
	DRAM	1 (NPE-225, NPE-400)	256 MB	256 MB (NPE-225) 512 MB (NPE-400)	1 GB (NPE-G1)
		2 (NPE-G1)			
7301 Series	Flash (CFM)	1	64 MB	128 MB	
	DRAM	1	256 MB	1 GB	
7304 NSE-100	Flash (CFM)	1	128 MB	256 MB	
	DRAM	1	512 MB	512 MB	
7304 NPE-G100	Flash (CFM)	1	256 MB	256 MB	
	DRAM	1	1024 MB	1 GB	
7600 Series	Flash (PCMCIA)	1	16 MB	512 MB	
	DRAM (Sup 2)	1	128 MB	512 MB	
	DRAM (MSFC2)	1	128 MB	512 MB	
	DRAM (PFC2)	1	128 MB	256 MB	
	DRAM (Sup720-3B)	1	512 MB	512 MB	
	DRAM (Sup720-3BXL)	1	1 GB	1 GB	
10700 Series	Flash (Internal)	1	64 MB	64 MB	Maximum memory is configured with No Option
	SDRAM RP	1	512 MB	512 MB	
	Packet Buffer	1	64 MB	64 MB	
XR 12000/12000 Series	Flash (PCMCIA)	2	48 MB	256 MB	
	SDRAM (PRP-1)	1	512 MB	1 GB	Route Memory
	SDRAM (PRP-2)	1	1 GB	4 GB	Route Memory
	DRAM (Line Cards)	1/2	128-256 MB	256 MB - 1 GB	

1. Advanced IP Services image includes 28MB flash

Compatibility Matrix

Port Adapter	7200VXR	7301	7304 Carrier Card	7600
ATM Port Adapters				
PA-A3-8T1IMA 8-port ATM inverse Mux T1 port adapter	•	•	•	•
PA-A3-8E1IMA: 8-port ATM inverse Mux E1 (120 ohm) port adapter	•	•	•	•
PA-A3-OC3-MM/SMI/SML: 1-port ATM-enhanced OC-3c/STM1 multimode intermediate and long range port adapter	•	•	•	• (Native)
PA-A3-OC12-MM: 1-port ATM-enhanced OC-12/STM4 multimode	–	–	–	–
PA-A3-T3/E3: 1-port ATM-enhanced DS3 port adapter	•	•	–	• (Native)
PA-A6-OC3MM/SMI/SML: 1-port ATM OC-3 multimode, intermediate and long range port adapter	•	•	–	•
PA-A6-T3 or E3: 1-port ATM DS3 (E3) port adapter	•	•	•	•
Ethernet Port Adapters				
PA-2FE-TX/FX: 2-port Fast Ethernet 100Base-TX/FX port adapter	•	•	• (TX)	•
PA-4E: 4-port Ethernet 10Base-T port adapter	•	•	•	–
PA-8E: 8-port Ethernet 10Base-T port adapter	•	•	•	–
PA-GE: Gigabit Ethernet port adapter	•	–	•	–
Serial Port Adapters				
PA-4E1G/75: 4-port E1 G.703 serial port adapter (120 ohm/balanced)	•	•	•	–
PA-4E1G/120: 4-port E1 G.703 serial port adapter (120 ohm/balanced)	•	•	•	•
PA-4T+: 4-port serial port adapter, enhanced	•	•	•	• (Native)
PA-8T-XXX: 8-port serial, 232, V.35, X.21 port adapter	•	•	•	• (Native)
High-speed Serial Port Adapters				
PA-H: 1-port HSSI port adapter	•	•	•	• (Native)
PA-2H: 2-port HSSI port adapter	•	•	•	• (Native)
PA-E3: 1-port E3 serial port adapter with E3 DSU	•	•	•	• (Native)
PA-2E3: 2-port E3 serial port adapter with E3 DSUs	•	•	•	• (Native)
PA-T3+: 1-port T3 serial port adapter, enhanced	•	•	•	• (Native)
PA-2T3+: 2-port T3 serial port adapter, enhanced	•	•	•	• (Native)
Multichannel Serial Port Adapters				
PA-4B-U	•	•	–	–
PA-8B-S/T: 8-port BRI port adapter, S/T interface	•	•	–	–
PA-MC-2T(1): 2-port multichannel T1 port adapter with integrated CSU/DSUs	•	•	•	–
PA-MC-4T(1): 4-port multichannel T1 port adapter with integrated CSU/DSUs	•	•	•	• (Native)
PA-MC-8TE1+: 8-port multichannel T1/E1 8PRI port adapter	•	•	•	–
PA-MC-2E1/120: 2-port multichannel E1 port adapter with G.703 120 ohm interface	•	•	•	–
PA-MC-E3: 1-port multichannel E3 port adapter	•	•	•	• (Native)

Port Adapter	7200VXR	7301	7304 Carrier Card	7600
PA-MC-T3: 1-port multichannel T3 port adapter	•	•	•	• (Native)
PA-MC-2T3+: 2-port multichannel T3 port adapter	•	•	•	• (Native)
PA-MC-STM-1MM: 1-port multichannel STM-1 multimode port adapter	•	•	•	• (Native)
PA-MC-STM-1SMI: 1-port multichannel STM-1 single mode port adapter	•	•	•	• (Native)
PA-MCX-2TE(1): 2-port MIX-enabled multichannel T1/E1 with CSU/DSU	•	—	—	—
PA-MCX-4TE(1): 4-port MIX-enabled multichannel T1/E1 with CSU/DSU	•	—	—	—
PA-MCX-8TE(1): 8-port MIX-enabled multichannel T1/E1 with CSU/DSU	•	—	—	—
SONET Port Adapters				
PA-POS-OC3-SMI: 1-port OC-3/STM1 POS port adapter	•	•	—	—
PA-POS-OC3-SML: 1-port OC-3/STM1 POS port adapter	•	•	•	• (Native)
PA-POS-2OC3: 2-port OC-3/STM1 POS port adapter	•	•	•	• (Native)
PA-POS-1OC3	•	•	—	• (Native)
PA-POS-OC3-MM: 1-port packet/SONET OC-3c/STM1 multimode port adapter	•	•	•	• (Native)
Other Port Adapters and Service Adapters				
PA-4C-E: 1-port-enhanced ESCON channel port adapter	•	—	—	—
SA-VAM2+: VPN acceleration module 2+	•	—	—	—
PA-VXC-2TE1+: 2-port T1/E1 high-capacity enhanced-voice PA	•	•	—	—
PA-VXB-2TE1+: 2-port T1/E1 moderate-capacity enhanced-voice PA	•	•	—	—
PA-VXA-1TE1-24+: 1-port T1/E1 digital voice port adapter with 24 channels	•	—	—	—
PA-VXA-1TE1-30+: 1-port T1/E1 digital voice port adapter with 30 channels	•	—	—	—
PA-4R-DTR: 4-port dedicated Token Ring, 4/16 Mbps, HDX/FDX	•	—	—	—

Cisco SB 100 Series



The Cisco Small Business Series of secure broadband routers addresses the needs of small businesses, providing affordable, easy-to-use, and secure broadband access for data-only applications. They provide the required performance to run basic, secure services in small offices, including firewall and support for MPLS-based VPNs.

When to Sell

Sell This Product

Cisco SB 100 Series

When a Customer Needs These Features

- An affordable Cisco router for data-only applications in small businesses offices with up to five users
- Companies that need the remote management capabilities of Cisco IOS
- Service providers who offer value-added services to small offices
- Managed services for a company with a single location
- VARs who are familiar with Cisco IOS software and want to profitably service small office customers
- Locations that do not require encrypted site-to-site VPN connectivity

Key Features

- Fixed configuration support for several types of 10/100 Ethernet or ADSL WAN connections
- Standard security with ACLs, PAT/NAT, PAP/CHAP, MS-CHAP
- Enhanced security with stateful inspection firewall
- Out of band management via integrated ISDN port on the SB106; Integrated 4-port 10/100 Ethernet Switch
- Cisco Security Device Manager (SDM) allows nontechnical users to quickly set up the router and firewall; Easy-to-use configuration tool; Remote management capabilities in Cisco IOS Software facilitate easy deployment and centralized management for service providers or value-added resellers

Specifications

Feature	SB 100	SB 106	SB 107
Fixed LAN Port Connections	4-port 10/100 Ethernet Switch	4-port 10/100 Ethernet Switch	4-port 10/100 Ethernet Switch
Fixed WAN Port Connections	1-port 10 Mbps Ethernet	1-port ADSL over ISDN	1-port ADSL
Flash Memory	12 MB	12 MB	12 MB
DRAM Memory	64 MB	64 MB	64 MB
Dimensions (H x W x D)	2.0 x 9.7 x 8.5 in. (5.1 x 24.6 x 21.6 cm)	2.0 x 9.7 x 8.5 in. (5.1 x 24.6 x 21.6 cm)	2.0 x 9.7 x 8.5 in. (5.1 x 24.6 x 21.6 cm)

Selected Part Numbers and Ordering Information¹

Cisco Small Business 100 Series Routers

CISCOB101-K9	Cisco Small Business 101 Secure Broadband Router
CISCOB106-K9	Cisco Small Business 106 Secure ADSL over ISDN Router
CISCOB107-K9	Cisco Small Business 107 Secure ADSL Router

1. This is only a small subset of all parts available via URL listed under “For More Information.” Some parts have restricted access or are not available through distribution channels.

For More Information

See the Cisco SB 100 Series Website: <http://www.cisco.com/go/sb100>

Cisco 800 Series

The Cisco 800 series router provides enhanced network security, wireless LAN, and proven reliability through Cisco IOS software, for small offices and telecommuters. It connects users to the Internet or to a corporate LAN via one ADSL, ADSL over ISDN, G.SHDSL, IDSL, ISDN, or serial connection (up to 512 Kbps), or with an Ethernet WAN port connected to an external broadband modem.



When to Sell

Sell This Product When a Customer Needs These Features

Cisco 800 Series

- Companies with Cisco IOS-based networks who want to add telecommuters or very small branch offices
- Service providers who offer value-added services to small offices
- VARs who are familiar with Cisco IOS software and want to profitably service small office customers
- Ethernet LAN ports and variety of WAN connectivity, including: ISDN BRI, Frame Relay, ADSL, G.SHDSL, async dialup (see Specifications for details)
- Locations with advanced security and wireless LAN requirements

Key Features

- Fixed configuration support for several types of WAN connections
- Optional IEEE 802.11 b/g wireless LAN (850 and 870 Series)
- Standard security with ACLs, PAT/NAT, PAP/CHAP, MS-CHAP, Lock and Key, and Generic Routing Encapsulation (GRE) tunneling
- Enhanced security with stateful inspection firewall, IPSec encryption (hardware DES, 3DES and AES encryption on Cisco 830, 850, and 870 Series). The Cisco 870 Series also includes security features like IPS, 802.1x, Dynamic Multipoint VPN (DMVPN), EasyVPN, URL filtering, and NAC
- Dial backup via aux/console port on the 830 and 870 series routers
- Dial backup via integrated ISDN port on the 836 and 876
- X.25 over D-channel support on 836 and 876
- DMZ interface on all 830 and 870 routers. Optional external power injector for Power Over Ethernet (PoE) on 870 routers
- Integrated 4-port 10/100 Ethernet Switch on Cisco 830, 850, and 870 series
- Bandwidth optimization features such as compression, Bandwidth-on-Demand, Dial-on-Demand, Always-On-Dynamic-ISDN (AODI), and X.25 over D channel (Cisco 801, 836, 876)
- Support for CAPI applications in the European market (801)

Specifications

Feature	801	805	831	836	837
Fixed LAN Port Connections	1-port Ethernet (10BASE-T)	1-port Ethernet (10BASE-T)	4-port Ethernet switch (10BASE-T)	1-port Ethernet switch (10BASE-T)	4-port Ethernet switch (10BASE-T)
Fixed WAN Port Connections	1-port ISDN BRI (S/T)	1-port Serial (Up to 512 KBPS)	1-port Ethernet	1-port ADSL-over-ISDN, 1-port ISDN S/T	1-port ADSL over POTS
Flash Memory	8MB (default) 12 MB (max)	8MB (default) 12MB (max)	12MB (default) 24MB (max)	12MB (default) 24MB (max)	12MB (default) 24MB (max)
DRAM Memory	8MB (default) 12MB (max)	8MB (default) 16MB (max)	48MB (default) 48MB (max)	48MB (default) 48MB (max)	48MB (default) 48MB (max)
Dimensions (H x W x D)	2.0 x 9.9 x 8.3 in. (5.1 x 25.2 x 21.1 cm)	2.0 x 9.9 x 8.3 in. (5.1 x 25.2 x 21.1 cm)	2.0 x 9.7 x 8.5 in. (5.1 x 24.7 x 21.1 cm)	2.0 x 9.7 x 8.5 in. (5.1 x 24.7 x 21.1 cm)	2.0 x 9.7 x 8.5 in. (5.1 x 24.7 x 21.1 cm)

Feature	851	857	871	876	877	878
Fixed LAN Port Connections	4-port 10/100 Ethernet switch	4-port 10/100 Ethernet switch	4-port 10/100 Ethernet switch	4-port 10/100 Ethernet switch	4-port 10/100 Ethernet switch	4-port 10/100 Ethernet switch
Fixed WAN Port Connections	1-port 10/100 Ethernet	1-port ADSL, ADSL 2/2+	1-port 10/100 Ethernet	1-port ADSL-over-ISDN, 1-port ISDN S/T (ADSL, ADSL 2/2+)	1-port ADSL over POTS (ADSL, ADSL 2/2+)	1-port 6.SHDSL
Wireless LAN	IEEE 802.11 b/g ("W" model)	IEEE 802.11 b/g ("W" model)	IEEE 802.11 b/g ("W" model)	IEEE 802.11 b/g ("W" model)	IEEE 802.11 b/g ("W" model)	IEEE 802.11 b/g ("W" model)
Wireless Antenna	Single fixed antenna	Single fixed antenna	Dual removable antennas	Dual removable antennas	Dual removable antennas	Dual removable antennas
Maximum VPN Tunnels	5	5	10	10	10	10
NAC	No	No	Yes	Yes	Yes	Yes
URL Filtering	No	No	Yes	Yes	Yes	Yes
Stateful Firewall	Yes	Yes	Yes	Yes	Yes	Yes
Inline IPS	No	No	Yes	Yes	Yes	Yes

Selected Part Numbers and Ordering Information¹

Cisco 800 Series Routers

CISCO801	1-port 10BASE-T, 1-port BRI (S/T), IP s/w
CISCO805	1-port 10BASE-T, 1-port serial, IP s/w
CISCO801-CAPI	ISDN/Ethernet Router with one-user CAPI license
CISCO831-K9 USD 649.00	Cisco 831 Ethernet Router
CISCO836-K9	Cisco 836 ADSL over ISDN Router
CISCO837-K9	Cisco 837 ADSL Router
CISCO851-K9	Cisco 851 Ethernet to Ethernet Router
CISCO851W-G-A-K9	Cisco 851 Ethernet to Ethernet Wireless Router; Americas
CISCO851W-G-E-K9	Cisco 851 Ethernet to Ethernet Wireless Router; Europe
CISCO851W-G-J-K9	Cisco 851 Ethernet to Ethernet Wireless Router; Japan
CISCO857-K9	Cisco 857 ADSL Router
CISCO857W-G-A-K9	Cisco 857 ADSL Wireless Router; U.S. and Americas
CISCO857W-G-E-K9	Cisco 857 ADSL Wireless Router; Europe
CISCO871-K9	Cisco 871 Ethernet to Ethernet Router
CISCO871W-G-A-K9	Cisco 871 Ethernet to Ethernet Wireless Router; U.S./Americas
CISCO871W-G-E-K9	Cisco 871 Ethernet to Ethernet Wireless Router; Europe
CISCO871W-G-J-K9	Cisco 871 Ethernet to Ethernet Wireless Router; Japan
CISCO876-K9	Cisco 876 ADSL over ISDN Router
CISCO876W-G-E-K9	Cisco 876 ADSL over ISDN Wireless Router
CISCO877-K9	Cisco 877 ADSL Router
CISCO877W-G-A-K9	Cisco 877 ADSL Wireless Router: U.S./Americas
CISCO877W-G-E-K9	Cisco 877 ADSL Wireless Router; Europe
CISCO878-K9	Cisco 878 G.SHDSL Router
CISCO878W-G-A-K9	Cisco 878 G.SHDSL Wireless Router; U.S./Americas
CISCO878W-G-E-K9	Cisco 878 G.SHDSL Wireless Router; Europe

Cisco 800 Series CD Feature Packs

CD08-BHL-12.0.7XV=	Cisco 800 Series IP/IPX/FW Plus IPsec 56
CD08-BP-12.07.XV=	Cisco 800 Series IP/IPX/Plus
CD800-5CAPI=	CAPI 5 User CD
CD08-IC-12.0.5T=	Cisco 800 Series Internet DSL
CD08-ICHL-12.0.5T=	Cisco 800 Series Internet DSL FW IPsec56
CD08-IBHL-12.0.5T=	Cisco 800 Series Internet DSL IPX FW IPsec56

Cisco 800 Series Memory Options

MEM800-4F=	Cisco 800 Series, 4 MB Flash Mini-Card
MEM800-8F=	Cisco 800 Series, 8 MB Flash Mini-Card
MEM800-4D=	Cisco 800 Series, 4 MB DRAM DIMM
MEM800-8D=	Cisco 800 Series, 8 MB DRAM DIMM
MEM820-8U16F	Cisco 820 Flash upgrade 8Mbyte-16Mbyte
MEM820-16U20D	Cisco 820 DRAM upgrade 16Mbyte-20Mbyte (16Mbyte-24Mbyte & 16Mbyte-32Mbyte also available)
MEM820-24U32D	Cisco 820 DRAM 24Mbyte upgrade to 32 Mbytes

Cisco 800 Series Accessories

800-ILPM-4	4 port 802.3af capable Inline power module for 800 Routers
PWR-8xx-WW1=	Cisco 8xx Series, AC Power Supply Spare

Cisco 800 Series Basic Maintenance

CON-SNT-PKG1	Cisco 800 Series SMARTnet Maintenance (8x5xNBD)
--------------	---

1. This is only a small subset of all parts available via URL listed under "For More Information." Some parts have restricted access or are not available through distribution channels.

For More Information

See the Cisco 800 Series Website: <http://www.cisco.com/go/800>

Cisco 1800 Series

Cisco 1800 Series integrated services routers are the next evolution of the award-winning Cisco 1700 Series modular access routers. The Cisco 1800 Series is designed for secure data connectivity via frame relay, leased line, or broadband access, and wireless local area networks. It features secure, fast, and high-quality delivery of multiple, concurrent services for small-to-medium-sized businesses and small enterprise branch offices.



When to Sell

Sell This Product

Cisco 1801, 1802, 1803

When a Customer Needs These Features

- Secure data access via broadband DSL
- Primary WAN access via ADSL over POTS (1801), ADSL over ISDN (1802), or G.SHDSL (1803)
- ADSL 2/2+ capability on 1801 and 1802
- Backup WAN interface using ISDN BRI
- Integrated 8-port managed 10/100 Ethernet switch
- Integrated IEEE 802.11 a/b/g wireless LAN ("W" models)

Cisco 1811, 1812

- Secure data access at broadband rates
- Using 10/100 Ethernet as a WAN access connecting to external DSL or cable modem
- Backup WAN interface using V.92 analog modem (1811) or ISDN BRI (1812)
- Integrated 8-port managed 10/100 Ethernet switch
- Integrated IEEE 802.11 a/b/g wireless LAN ("W" models)

Cisco 1841

- Secure data access solution for customer environments up to T1/E1/xDSL WAN rates with services turned on
- Modularity for flexibility in WAN configurations
- Needs support for a broad array of WAN services
- Needs comprehensive security features

Key Features

- Available with IEEE 802.11 a/b/g wireless access point ("W" models of 1801-1812, HWIC-AP for 1841)
- Modular 1841 provides flexibility with internal AIM slot designated for higher speed VPNs and future applications; Provides several slot types to add future connectivity and services on an "integrate-as-you-grow" basis
- Integrated 8-port 10/100 Ethernet switch with PoE on fixed configuration 1801-1812. Optional 4-port switch HWIC on 1841
- Supports the latest Cisco IOS Software-based QoS bandwidth management features
- Advanced device management—using Cisco Router and SDM
- High-performance processor—Supports concurrent deployment of high-performance, secure data services with headroom for future applications
- Integrated hardware-based encryption acceleration—Offers cryptography accelerator as standard integrated hardware that can be enabled with an optional Cisco IOS Software for 3DES and AES encryption support
- Security performance enhanced feature set; Offers intrusion prevention system (IPS), Network Admission Control (NAC), and firewall functions.
- Allows LAN segmentation using Virtual LANs (VLANs)
- Integrated standard power supply—Easier router platform installation and management

Chapter 1

Specifications

Feature	Cisco 1841 Series	Cisco 1800 Series Fixed-Configuration Routers
Form factor	Desktop, 1-rack-unit (1RU) height (4.75 cm high with rubber feet)	Desktop, 1-rack-unit (1-RU) high (4.75-cm high with rubber feet)
Target Applications	Secure data with frame relay or leased line access (T1/E1)	Secure data with broadband access and backup WAN
Chassis	Metal	Metal
Wall-mountable	Yes	Yes
Rack-mountable	No	Yes (optional 19-in. rack-mount kit required)
Dimensions (W x D)	13.5 x 10.8 in. (34.3 x 27.4 cm); Height without rubber feet: 1.73 in. (4.39 cm); Height with rubber feet: 1.87 in. (4.75 cm)	12.5 x 9.5 in. (34.3 x 27.4 cm); Height without rubber feet: 1.73 in. (4.39 cm); Height with rubber feet: 1.87 in. (4.75 cm)
Weight	Maximum: 6.2 lb. (2.8 kg); with interface cards and modules; Minimum: 6.0 lb. (2.7 kg) (no interface cards and modules)	Maximum: 6.1 lb. (2.8 kg)
DRAM	Synchronous dual in-line memory module (DIMM) DRAM	Synchronous dual in-line memory module (DIMM) SDRAM (1 DIMM slot)
DRAM capacity	Default: 128 MB; Maximum: 384 MB	Default: 128 MB; Maximum: 384 MB
Flash memory	External removable compact Flash	External removable Compact Flash
Flash memory capacity	Default: 32 MB; Maximum: 128 MB	Default: 32 MB; Maximum: 128 MB
Modular slots - total	Two	None
Modular slots (WAN)	Two	None
Modular slots (HWICs)	Two	None
Modular slots (voice)	None: The Cisco 1841 does not support voice	None: The Cisco 1800 Series does not support voice
VoIP support	Voice-over-IP (VoIP) pass-through only	Same as 1841
ADSL Port	ADSL over POTS, ADSL over ISDN via WAN Interface Card	One ADSL over POTS port on Cisco 1801. One ADSL over ISDN on Cisco 1802. The Cisco 1801 supports ADSL over POTS standards G.992.1 G.DMT and ANSI T1.413 DMT Issue 2. The Cisco 1802 supports ADSL over ISDN standards ETSI 101-388, U-R2, and G.992.1 G.DMT. The Cisco 1801 is interoperable with the following DSLAMs: Cisco 6130 and Cisco 6260 IP DSL switches; Alcatel (ASAM 1000 and 7300); Lucent Stinger (24- and 72-port line cards); ECI HiFocus (16- and 32-port line cards); The Cisco 1802 is interoperable with the following DSLAMs: Cisco 6260; Alcatel (ASAM 1000 and 7300); Siemens (XpressLink 2.0 and XpressLink 2.1); Lucent Stinger (48-port line cards); ECI HiFocus (16- and 32-port line cards)
G.SHDSL Port	G.SHDSL 2- and 4-wire support via WAN Interface Card	One G.SHDSL port on Cisco 1803 supports either 2-wire mode or 4-wire mode. The Cisco 1803 supports the same standards as the Cisco G.SHDSL WIC and is based on ITU Recommendation G.991.2 (accepted worldwide).
G. SHDSL DSLAM Interoperability	The WIC-1SHDSL-V3 in 2-wire mode is interoperable with the following DSLAMs: Cisco 6000 Series IP DSL switches; Alcatel ASAM 7300 (12- and 24-port line cards); ECI HiFocus SAM 2401 (16-port Metalink-based line cards); Lucent Stinger FS (32- and 48-port line cards); CopperEdge 200 DSLAM (24-port line cards); The WIC-1SHDSL-V3 in 4-wire mode is interoperable with the following DSLAMs: Alcatel ASAM 7300 (12- and 24-port line cards); CopperEdge 200 DSLAM (24-port line cards)	The Cisco 1803 in 2-wire mode is interoperable with the following DSLAMs: Cisco 6000 Series IP DSL switches; Alcatel ASAM 7300 (12- and 24-port line cards); ECI HiFocus SAM 2401 (16-port Metalink-based line cards); Lucent Stinger FS (32- and 48-port line cards); CopperEdge 200 DSLAM (24-port line cards); The Cisco 1803 in 4-wire mode is interoperable with the following DSLAMs: Alcatel ASAM 7300 (12- and 24-port line cards); CopperEdge 200 DSLAM (24-port line cards)
Onboard Ethernet ports	Two 10/100	10/100BASE-T ports for WAN connection supporting DSL and cable modems and Ethernet access services. (One port is available on Cisco 1801, 1802, and 1803. Two ports are available on Cisco 1811 and
Integrated Ethernet Switch Ports	Optional via 4-port Ethernet switch HWIC, up to 15 VLANs	Eight 10/100BASE-T fully managed switch ports with 802.1Q VLAN and 802.3af PoE support. Up to 8 VLANs
Onboard USB ports	One (1.1)	Two (USB 2.0) on Cisco 1811 and 1812 only. The Cisco 1801, 1802, and 1803 do not offer USB support.
ISDN S/T BRI Port	Optional via WAN Interface Card	One ISDN S/T BRI port on Cisco 1801, 1802, 1803, and 1812
V.92 Analog Modem Port	Optional via WAN Interface Card (1 or 2 ports)	One analog modem port on Cisco 1811
Console port	One: up to 115.2 kbps	One—up to 115.2 kbps

Feature	Cisco 1841 Series	Cisco 1800 Series Fixed-Configuration Routers
Auxiliary port	One: up to 115.2 kbps	One—up to 115.2 kbps
Onboard AIM slots	One (internal)	None
Packet-voice-DSP-module (PVDM) slots on motherboard	None: The Cisco 1841 does not support voice	None: The Cisco 1800 Series does not support voice
Integrated H/W-based encryption on motherboard	Yes	Yes
Encryption support in software and hardware by default	DES, 3DES, AES 128, AES 192, AES 256	DES, 3DES, AES 128, AES 192, AES 256
IPSec Tunnels	100 with on-board encryption, 800 with VPN AIM50	
IPSec VPN Performance	40 Mbps 3DES @ 1400 byte packets	40 Mbps 3DES @ 1400 byte packets
Cisco IOS Firewall Performance	100 Mbps @ 1400 byte packets	100 Mbps @ 1400 byte packets
Wireless LAN Hardware	Optional IEEE 802.11 a/b/g or IEEE 802.11 b/g via HWIC	IEEE 802.11 a/b/g on wireless models
Wireless LAN features	IEEE 802.11a/b/g; Automatic rate selection for 802.11a/11b/11g; Field-replaceable antennae; External antenna; Antenna diversity; Wi-Fi Certified for WPA-Personal and WPA-Enterprise; Default antenna gain—2.2 dBi	IEEE 802.11a/b/g; Automatic rate selection for 802.11a/11b/11g; Field-replaceable antennae; External antenna; Antenna diversity; Wi-Fi Certified for WPA-Personal and WPA-Enterprise; Default antenna gain—2.2 dBi
Data Rates Supported	802.11a: 6, 9, 12, 18, 24, 36, 48, and 54 Mbps; 802.11g: 1, 2, 5.5, 6, 9, 11, 12, 18, 24, 36, 48, and 54 Mbps	802.11a: 6, 9, 12, 18, 24, 36, 48, and 54 Mbps; 802.11g: 1, 2, 5.5, 6, 9, 11, 12, 18, 24, 36, 48, and 54 Mbps
Range		Range—Indoor 1 Mbps at 320 ft.
Wireless LAN Software Features		Maximize throughput or maximize range option; Software-configurable transmit power; Support for Wi-Fi Multimedia (WMM); Quality of Service (QoS) for WLANs
Wireless LAN Security Features	IEEE 802.1X per-user, per-session mutual authentication with a variety of extensible authentication protocol (EAP) types including Cisco LEAP, Protected Extensible Authentication Protocol (PEAP), and EAP-Transport Layer Security (EAP-TLS). Preshared Key (PSK) Authentication; MAC authentication/filter encryption; WPA Temporal Key Integrity Protocol (TKIP) with support for per-packet key hashing, message integrity check; Static and dynamic wired equivalent privacy (WEP) keys of 40 bits and 128 bits; Additional security features: IEEE 802.1X local authentication; Configurable limit for the number of wireless clients; Configurable RADIUS accounting for wireless clients	IEEE 802.1X per-user, per-session mutual authentication with a variety of extensible authentication protocol (EAP) types including Cisco LEAP, Protected Extensible Authentication Protocol (PEAP), and EAP-Transport Layer Security (EAP-TLS). Preshared Key (PSK) Authentication; MAC authentication/filter encryption; WPA Temporal Key Integrity Protocol (TKIP) with support for per-packet key hashing, message integrity check; Static and dynamic wired equivalent privacy (WEP) keys of 40 bits and 128 bits; Additional security features: IEEE 802.1X local authentication; Configurable limit for the number of wireless clients; Configurable RADIUS accounting for wireless clients
SSIDs	8	8
Wireless LAN	Supported by CiscoWorks 2000, CiscoView and Router, and Security Device Management (SDM)	Supported by CiscoWorks 2000, CiscoView and Router, and Security Device Management (SDM)
Management Features	GUI-based network management for wireless interface is provided	GUI-based network management for wireless interface is provided
Cisco IOS Software default image	IP BASE (12.3(8)T)	12.3(8)YI
Cisco IOS Software Default Image	IP Base (security and broadband bundles have image upgrades)	Advanced IP services (without voice services) except Cisco 1801 which comes with Cisco IOS IP Broadband
User Support	Up to 50 users (recommended)	Up to 50 users (recommended)
Routing Protocols	BGP, EIGRP, OSPF, RIPv1, RIPv2	BGP, EIGRP, OSPF, RIPv1, RIPv2
Routed Protocols	IPv4, IPv6 unicast only (Internetwork Packet Exchange [IPX], IBM SNA, AppleTalk supported with optional Advanced Enterprise Services Feature Set)	IPv4, IPv6 unicast only (Internetwork Packet Exchange [IPX], IBM SNA, AppleTalk supported with optional Advanced Enterprise Services Feature Set)
QoS Protocols	Weighted Fair Queuing (WFQ), Class-Based WFQ (CBWFQ), Weighted Random Early Detection (WRED), Committed Access Rate (CAR), Resource Reservation Protocol (RSVP), Network-Based Application Recognition	Weighted Fair Queuing (WFQ), Class-Based WFQ (CBWFQ), Weighted Random Early Detection (WRED), Committed Access Rate (CAR), Resource Reservation Protocol (RSVP), Network-Based Application Recognition
Internal system power supply	Yes	Yes
Power over Ethernet (PoE) power supply	None	None
Redundant power supply	No	No
DC power support	No	No
AC input voltage	100 to 240 VAC	100 to 240 VAC
Frequency	50 to 60 Hz	50 to 60 Hz
AC input current	1.5A maximum	1.5A maximum

		Cisco 1800 Series
Feature	Cisco 1841 Series	Fixed-Configuration Routers
Output power	50W (maximum)	50W (maximum)
PoE Support	Not supported	Supported on 10/100 Ethernet switch ports with optional PoE kit
PoE Standards	None	IEEE 802.3af, Cisco Prestandard PoE
External PoE Power Supply	None	80W external power supply
System Power Dissipation	153 BTU/hr.	153 BTU/hr.
Operating temp	32 to 104°F (0 to 40°C)	32° to 104°F (0° to 40°C)
Operating humidity	10 to 85% non condensing operating; 5 to 95% non condensing, non operating	10 to 85 percent non condensing operating; 5 to 95 percent non condensing, non operating
Non operating Temp	-4 to 149°F (-25 to 65°C)	-4° to 149°F (-25 to 65°C)
Operating altitude	10,000 feet (3000 meters) @ 77°F (25°C)	10,000 ft. (3000m) at 77°F (25°C)
Noise level	Normal operating temperature: <78° F/25.6°C: 34 dBA; >78°F/25.6°C through; 104°F/40°C	<80°F (27°C): 34 dBA; >80°F (27°C) through <104°F (40°C): 36 dBA; >104°F (40°C): 42 dBA
Safety	UL60950-1; CAN/CSA 60950-1; AS 3260; EN60950-1	UL 60950; CAN/CSA C22.2 No. 60950; IEC 60950-1; EN 60950-1; AS/NZS 60950
EMI	EN 55022, 1998, class A; CISPR22, 1997, class A; CFR47, Part 15, Subpart B, 1995, class A; EN61000-3-2 Harmonic Current Emission (only for class A; VCCI Class A; EN 300386; EN61000-3-2; equipment >75W but <16A); EN61000-3-3 Voltage Fluctuation and Flicker (only for equipment £16A)	CFR 47 Part 15, Class A; ICES-003 Class A; EN55022 Class A; CISPR22 Class A; AS/NZS 3548; EN300386; EN61000-3-2
Immunity	CISPR24, 1997 ITE-Immunity characteristics, Limits and methods of measurement; EN 55024, 1998 ITE-Immunity characteristics, Limits and methods of measurement; EN50082-1, 1997 Electromagnetic compatibility Generic immunity standard, Part 1 EN 300 386, 1997 Telecommunications network equipment EMC requirements; The requirements are covered by the following standards: IEC 61000-4-2:1995 Immunity to Electrostatic Discharges; IEC 61000-4-3:1995 Immunity to Radio Frequency Electromagnetic Fields; IEC 61000-4-4:1995 Immunity to Electrical Fast Transients; IEC 61000-4-5:1995 Immunity to Power Line Transients (Surges); IEC61000-4-6:1996 Immunity to Radio Frequency Induced Conducted Disturbances; IEC 61000-4-11:1995 Immunity to Voltage Dips, Voltage Variations, and Short Voltage Interruptions	EN300386; EN55024(CISPR24); EN61000-4-2; EN61000-4-3; EN41000-4-4; EN41000-4-5; EN41000-4-6; EN41000-4-8; EN41000-4-11; EN50082-1; EN61000-6-2; ITU-T K.21
Network homologation	USA: TIA-968-A, T1.TRL6-2001; Canada: CS-03; European Union: RTTE Directive 5/99; Argentina: CTR 21; Australia: AS/ACIF S002, S003, S016, S031, 3043; Brazil: 225-540-788, CTR3, 225-100-717 Edition 3, NET 001/92 1990; China: ITU-G.992.1, ITU-G.992.1, ITU-G.991.2, CTR3, ITU I.431 1993; Hong Kong: HKTA 2033, HKTA 2033, HKTA 2014, HKTA 2017 Issue 3 2003, HKTA 2011 Issue 1, HKTA 2011 Issue 2, HKTA 2013 Issue 1; India: I_DCA_18_02_Jun_99-1999, S/ISN-01/02 Issue 1999 S/ISN-02 1 1998, IR/PRI-01/02 Issue 1 1998, S/INT-2W/02 MAY 2001, S/INT-2W/02 MAY 2001; Israel: U.S. approval accepted; Japan: Technical condition (DoC acceptance in process); Korea: U.S. approval accepted; Mexico: U.S. approval accepted; New Zealand: PTC 270/272, CTR 3, ACA 016 Revision 4 1997, PTC 200; Singapore: IDA TS ADSL1 Issue 1, IDA TS ADSL 2, IDA TS HDLSL, IDA TS ISDN 1 Issue 1 1999, IDA TS ISDN 3 Issue 1 1999, IDA TS PSTN 1 Issue 4, IDA TS PSTN 1 Issue 4, IDA TS PSTN 1 Issue 4; South Africa: U.S. approval accepted; Taiwan: U.S. approval accepted	Telecom compliance standards depend upon country and interface type. Interfaces comply with FCC Part 68, CS-03, JATE Technical Conditions, European Directive 99/5/EC, and relevant Technical Basis for Regulation (TBRs). For specific information, refer to the data sheet for the specific interface card. Homologation requirements vary by country and interface type. For specific country information, refer to the online approvals database. Cisco 1801, 1802, 1803, and 1812 ISDN BRI S/T: TIA-968-A; IC CS-03 Part VI; JATE Technical Requirements; TBR3; S031

Selected Part Numbers and Ordering Information¹

Cisco 1800 Series (Modular) Integrated Services Routers

CISCO1841	Modular Router w/2xFE, 2 WAN slots, 32 FL/128 DR
CISCO1841-T1	1841 bundle w/WIC-1DSU-T1-V2, IP Base, 32FL/128DR

Cisco 1800 Series (Fixed) Integrated Services Routers

CISCO1801	ADSL/POTS router w/IOS IP Broadband
CISCO1801/K9	ADSL/POTS Router with Firewall/IPS and IPSEC 3DES
CISCO1802/K9	ADSL/ISDN Router with Firewall/IPS and IPSEC 3DES
CISCO1803/K9	G.SHDSL Router with Firewall/IPS and IPSEC
CISCO1811/K9	Dual Ethernet Security Router with V.92 Modem Backup
CISCO1812/K9	Dual Ethernet Security Router with ISDN S/T Backup

Cisco 1800 Series (Fixed Wireless) Integrated Services Router

CISCO1801W-AG-E/K9	ADSL/POTS Router with 802.11a+g ETSI Compliant and Security
CISCO1802W-AG-E/K9	ADSL/ISDN Router with 802.11a+g ETSI Compliant and Security
CISCO1803W-AG-A/K9	G.SHDSL Router with 802.11a+g FCC Compliant and Security
CISCO1803W-AG-E/K9	G.SHDSL Router with 802.11a+g ETSI Compliant and Security
CISCO1811W-AG-A/K9	Security Router with 802.11a+g FCC Compliant and Analog B/U
CISCO1812W-AG-E/K9	Security Router with 802.11a+g ETSI Compliant and ISDN S/T

Cisco 1800 Series (modular) Security bundles

CISCO1841-SEC/K9	1841 Security Bundle, Adv. Security, 64FL/256DR
CISCO1841-HSEC/K9	1841 Security bundle w/AIM-VPN, Adv. IP Svcs, 64FL/256DR
CISCO1841-T1SEC/K9	1841 Security Bundle w/ WIC-1DSU-T1-V2, Adv. Sec., 64FL/256DR

Cisco 1800 Series (modular) Broadband bundles

CISCO1841-ADSL	1841 ADSLoPOTS Bdle, IP Broadband, 32FL/128DR
CISCO1841-ADSL-DG	1841 ADSLoPOTS w/dying gasp Bundle, IP Broadband, 32FL/128DR
CISCO1841-ADSLI	1841 ADSLoISDN Bundle, IP Broadband, 32FL/128DR
CISCO1841-SHDSL-V3	1841 G.shdsl 4-wire Bundle, includes WIC-1SHDSL-V3, IP Broadband, 32 MB flash/128 MB DRAM

Cisco 1841 WAN Interface Cards

WIC-1T	1-Port Serial WAN Interface Card
WIC-2T	2-Port Serial WAN Interface Card
WIC-2A/S	2-Port Async/Sync Serial WAN Interface Card
WIC-1AM	One-port Analog Modem WAN Interface Card
WIC-2AM	Two-port Analog Modem WAN Interface Card
WIC-1DSU-56K4	1-port 4-WIRE 56/64 KBPS WAN INTERFACE CARD
HWIC-1ADSL	1-port ADSLoPOTS HWIC
HWIC-1ADSLI	1-port ADSLoISDN HWIC
WIC-1ADSL	1-port ADSL WAN Interface Card
WIC-1ADSL-DG	1-port ADSLoPOTS WIC with Dying Gasp
WIC-1ADSL-I-DG	1-port ADSLoISDN Wan Interface Card
WIC-1SHDSL-V3	1-Port G.SHDSL WIC with 2- and 4-wire support
WIC-1B-S/T-V3	1-Port ISDN WAN Interface Card (dial and leased line)
WIC-1B-U-V2	1-Port ISDN BRI NT-1 WIC
WIC-BLANK-PANEL=	Blank WAN Interface Card Panel
WIC-1DSU-T1-V2	Updated 1-Port T1/Fractional T1 DSU/CSU WAN Interface Card

Cisco 1841 High Speed WAN Interface Cards

HWIC-4ESW	Four port 10/100 Ethernet switch interface card
HWIC-4A/S	4-Port Async/Sync Serial HWIC
HWIC-8A/S-232	8-Port Async/Sync Serial HWIC, EIA-232
HWIC-8A	8-Port Async HWIC

Cisco 1841 Wireless HWICs and Accessories

HWIC-AP-G-A	Cisco 802.11 B/G Access Point High Speed Wan Interface Card for the Americas (FCC configuration)
HWIC-AP-G-E	Cisco 802.11 B/G Access Point High Speed Wan Interface Card for Europe (ETSI configuration)
HWIC-AP-G-J	Cisco 802.11 B/G Access Point High Speed Wan Interface Card for Japan (TELEC configuration)
HWIC-AP-AG-A	Cisco 802.11 A/B/G Access Point High Speed Wan Interface Card for the Americas (FCC configuration)
HWIC-AP-AG-E	Cisco 802.11 A/B/G Access Point High Speed Wan Interface Card for Europe (ETSI configuration)
HWIC-AP-AG-J	Cisco 802.11 A/B/G Access Point High Speed Wan Interface Card for Japan (TELEC configuration)
AIR-ANT4941	2.2 dBi Cisco Aironet 2.4 GHz Swivel mount dipole
AIR-ANT5959	2 dBi Cisco Aironet 2.4 GHz Diversity omni-directional ceiling mount patch
AIR-ANT1728	5.2dBi Cisco Aironet 2.4 GHz Omni-directional ceiling mount
AIR-ANTM2050D-R	(2.2 dBi Cisco 2.4 Ghz and 5.0 dBi 5 GHz) Dual band Swivel mount dipole antenna
AIR-ANTM5560P-R	(5.5 dBi Cisco 2.4 Ghz and 6.0 dBi 5 GHz) Dual band Wall-mount patch antenna
AIR-ANTM4050V-R	(4.0 dBi Cisco 2.4 Ghz and 5.0 dBi 5 GHz) Dual band Diversity Ceiling-mount omnidirectional antenna
AIR-CAB020LL-R	20-ft. (6m) low-loss cable with RP-TNC connectors
AIR-CAB050LL-R	50-ft. (15m) low-loss cable with RP-TNC connectors
AIR-CAB100ULL-R	100 ft. (30m) ultra-low-loss cable with RP-TNC connectors
AIR-CAB150ULL-R	150-ft. (46m) ultra-low-loss cable with RP-TNC connector

Cisco 1841 Multiflex Voice/WAN Interface Cards

VVIC-1MFT-E1	1-Port RJ-48 Multiflex Trunk - E1
VVIC-2MFT-E1	2-Port RJ-48 Multiflex Trunk - E1
VVIC-2MFT-E1-DI	2-Port RJ-48 Multiflex Trunk - E1 With Drop and Insert
VVIC-1MFT-T1	1-Port RJ-48 Multiflex Trunk - T1
VVIC-2MFT-T1	2-Port RJ-48 Multiflex Trunk - T1
VVIC-2MFT-T1-DI	2-Port RJ-48 Multiflex Trunk - T1 With Drop and Insert
VVIC-1MFT-G703	1-Port RJ-48 Multiflex Trunk - G.703
VVIC-2MFT-G703	2-Port RJ-48 Multiflex Trunk - G.703
VVIC2-1MFT-T1/E1	1-Port 2nd Gen Multiflex Trunk Voice/WAN Int. Card - T1/E1
VVIC2-2MFT-T1/E1	2-Port 2nd Gen Multiflex Trunk Voice/WAN Int. Card - T1/E1
VVIC2-1MFT-G703	1-Port 2nd Gen Multiflex Trunk Voice/WAN Int. Card - G.703
VVIC2-2MFT-G703	2-Port 2nd Gen Multiflex Trunk Voice/WAN Int. Card - G.703

Cisco 1841 Advanced Integration Modules

AIM-VPN/BPII-PLUS	DES/3DES/AES VPN Encryption/Compression
-------------------	---

Cisco 1800 Series Flash Memory Options

MEM1800-32CF=	32MB Cisco 1800 Compact Flash
MEM1800-64CF=	64MB Cisco 1800 Compact Flash Memory
MEM1800-128CF=	128MB Cisco 1800 Compact Flash Memory
MEM1800-32U64CF	32 to 64MB Cisco 1800 Compact Flash factory upgrade
MEM1800-64U128CF	64 to 128 MB Cisco 1800 Compact Flash factory upgrade
MEM1800-32U128CF	32 to 128 MB Cisco 1800 Compact Flash factory upgrade

Cisco 1800 Series USB Memory Options

MEMUSB-64FT=	64MB USB Flash Token for Cisco 1800/2800/3800 series
MEMUSB-128FT=	128MB USB Flash Token for Cisco 1800/2800/3800 series
MEMUSB-256FT=	256MB USB Flash Token for Cisco 1800/2800/3800 series

Cisco 1800 Series DRAM Memory Options

MEM1841-64D=	64MB SODIMM DRAM for Cisco 1841
MEM1841-128D=	128MB SODIMM DRAM for the Cisco 1841
MEM1841-256D=	256MB SODIMM DRAM for the Cisco 1841
MEM1841-128U192D	128 to 192MB SODIMM DRAM factory upgrade for the Cisco 1841
MEM1841-128U256D	128 to 256MB SODIMM DRAM factory upgrade for the Cisco 1841
MEM1841-128U384D	128 to 384MB SODIMM DRAM factory upgrade for the Cisco 1841
MEM1841-256U384D	256 to 384MB SODIMM DRAM factory upgrade for the Cisco 1841

Cisco 1800 Series Spares and Accessories

PWR-184X-AC=	Cisco 184X AC standard power supply
ACS-184X=	Accessory Kit for Cisco 184X
SW-CONFIG-1800-001	Configuration of software via CCO for 1800 series
CX-CUSTOM-BUILD	Please complete this P.O. via CX Tool

Cisco 1800 Series (modular) Software CD Feature Packs

CD18-AISK9=	CISCO 1841 ADVANCED IP SERVICES Feature Pack
CD18-ASK9=	CISCO 1841 ADVANCED SECURITY Feature Pack
CD18-AESK9=	CISCO 1841 ADVANCED ENTERPRISE SERVICES Feature Pack
CD18-BB=	CISCO 1841 IP Broadband Feature Pack
CD18-EB=	CISCO 1841 ENTERPRISE BASE Feature Pack
CD18-ESK9=	CISCO 1841 ENTERPRISE SERVICES Feature Pack
CD18-IPB=	CISCO 1841 IP BASE Feature Pack
CD18-SPSK9=	CISCO 1841 SP SERVICES Feature Pack
184-SW-SPARECD	Cisco 184X Series Software Spare CD

Cisco 1800 Series IOS Upgrade Licenses

FL18-AISK9-AESK9=	Cisco 1841 Adv IP Ser to Adv Ent Ser Upgrade SW feature lic
FL18-ASK9-AISK9=	Cisco 1841 Adv Sec to Adv IP Ser Upgrade SW feature lic
FL18-EB-ESK9=	Cisco 1841 Ent Base to Ent Ser Upgrade SW feature lic
FL18-ESK9-AESK9=	Cisco 1841 Ent Ser to Adv Ent Ser Upgrade SW feature lic
FL18-SPSK9-AISK9=	Cisco 1841 SP Ser to Adv IP Ser Upgrade SW feature lic
FL18-SPSK9-ESK9=	Cisco 1841 SP Ser to Ent Ser Upgrade SW feature lic
FL18-IPB-ASK9=	Cisco 1800 IP BASE to Adv Sec Upgrade SW feature lic
FL18-IPB-EB=	Cisco 1800 IP BASE to Ent Base Upgrade SW feature lic
FL18-CB=	Corvil Bandwidth Feature License for 1800 Series

Cisco 1800 (Fixed) Series DRAM Memory Options

MEM180X-128U256D	128 to 256MB SODIMM DRAM factory upgrade for the Cisco 180X
MEM181X-128U256D	128 to 256MB SODIMM DRAM factory upgrade for the Cisco 181X
MEM180X-128D=	128MB SODIMM DRAM for the Cisco 1841
MEM181X-128D=	128MB SODIMM DRAM for the Cisco 181X

Cisco 1800 (Fixed) Series PoE Options

POE-180X	802.3af PoE Module, 80W Power Supply and Cable
POE-181X	802.3af PoE Module, 80W Power Supply and Cable
POE-180X=	802.3af PoE Module, 80W Power Supply and Cable
POE-181X=	802.3af PoE Module, 80W Power Supply and Cable

Cisco 1800 (Fixed) Series Rack Mount Kit

ACS-1800-RM-19=	19 inch Rack Mount Kit for Cisco 180X / 181X
-----------------	--

Cisco 1800 (fixed & mod)-802.11 a/g Antennae Options-Spares

AIR-ANTM2050D-R=	2.2dBi/2.4Ghz,5.0dBi/5GHz DualBand Dipole Antenna
AIR-ANTM4050V-R=	4.0dBi/2.4Ghz,5.0 dBi/5GHz Dual Band Ceiling Mount Antenna
AIR-ANTM5560P-R=	5.5 dBi/2.4Ghz,6.0 dBi/5GHz Dual Band Wall Mount Antenna

1. This is only a small subset of all parts available via URL listed under "For More Information." Some parts have restricted access or are not available through distribution channels. Resellers: For latest part number and pricing info, see the *Distribution Product Reference Guide* at: <http://www.cisco.com/dprg> (limited country availability).

For More Information

See the Cisco 1800 Series Website: <http://www.cisco.com/go/ISR>

Cisco 2800 Series

The Cisco 2800 Series Integrated Services Routers offer performance improvements, increased security and voice performance, new embedded service options, and increased slot performance and density. It maintains support for most existing interface cards and modules available for the Cisco 1700 Series and Cisco 2600 Series routers. Comprised of four platforms: the Cisco 2801, the Cisco 2811, the Cisco 2821, and the Cisco 2851 router, the Cisco 2800 Series features the ability to deliver multiple high-quality simultaneous services at wire speed at up to multiple T1/E1/xDSL connections.

When to Sell**Sell This Product****Cisco 2800****When a Customer Needs These Features**

- Performance and densities for concurrent data, security, voice, and advanced services up to multiple T1/E1/xDSL connections
- VPN connections, or plan to migrate to them over time
- Integrated security services which enable network device protection, threat defense, secure connectivity, and endpoint protection and control
- Secure integrated call processing, voice mail, flexible telephony interfaces, redundancy for centralized call processing, or robust DSP support, including local conferencing and transcoding
- Wireless support via integrated IEEE 802.11 a/b/g access point HWICs
- Integrated Layer 2 switching capability in densities from 4 port to 48 port and the ability to utilize Cisco StackWise connectivity.

Key Features

- Modular architecture—A wide variety of LAN and WAN options are available. Network interfaces can be upgraded in the field to accommodate future technologies; Several types of slots are available to add connectivity and services in the future on an “integrate-as-you-grow” basis
- Embedded security hardware acceleration—embedded hardware cryptography accelerators, which when combined with an optional Cisco IOS Software upgrade help enable WAN link security and VPN services
- Integrated dual Fast Ethernet or Gigabit Ethernet ports—Provides two 10/100 Ethernet ports on the Cisco 2801 and Cisco 2811 and two 10/100/1000 Ethernet ports on the Cisco 2821 and Cisco 2851
- HWIC slots with enhanced functions including wireless LAN access points; Dual AIM slots; Packet voice DSP module (PVDM) slots on motherboard
- IP Telephony solutions enable an all-in-one VoIP solution with Cisco Call Manager Express, telephony interfaces, and Cisco Unity Express for voice mail and auto-attendant functions

Chapter 1

- On board hardware-based encryption for DES, 3DES, AES, and onboard slots for PVDMs, and they all include high-speed Ethernet interfaces
- Support for an optional dedicated security AIM
- EzVPN eases administration and management of point-to-point VPNs by pushing new security policies from a single headend to remote sites
- DSP modules deliver support for analog and digital voice, conferencing, transcoding, and secure Real-Time Transport Protocol (RTP) applications
- Network Admission Control (NAC)—A Cisco Self-Defending Network initiative seeks to dramatically improve the ability of networks to identify, prevent, and adapt to threats by allowing network access only to compliant and trusted endpoint devices
- Optional integrated power supply for distribution of PoE
- Real-time clock support

Competitive Products

- Juniper: J Series
- 3Com: SuperStack II NETBuilder SI and Pathbuilder S400, 5000 & 6000 Series
- Intel/Shiva: LanRover Family
- Motorola: Vanguard 645x/643x
- Nortel/Bay: Advanced Remote Node (ARN), Passport 4400 series
- Tasman: 2004, 1400
- Huawei: AR2800

Specifications

Feature	Cisco 2801	Cisco 2811	Cisco 2821	Cisco 2851
Fixed USB 1.1 ports	1	2	Same As Cisco 2811	Same As Cisco 2811
Onboard LAN ports	2 - 10/100	Same As Cisco 2801	2 - 10/100/1000	Same As Cisco 2821
Onboard AIM (internal) slot	2	Same As Cisco 2801	Same As Cisco 2801	Same As Cisco 2801
Interface card slots	4 slots; 2 slots support HWIC, WIC, VIC, or VWIC type modules 1 slot supports WIC, VIC, or VWIC type modules 1 slot supports VIC or VWIC type modules	4 slots, each slot can support HWIC, WIC, VIC, or VWIC type modules		
Network-module slot	No	1 slot, supports NM and NME type modules	1 slot, supports NM, NME and NME-X type modules	1 slot, supports NM, NME, NME-X, and NME-XD type modules
Extension Voice Module Slot	0	Same As Cisco 2801	1	Same As Cisco 2821
PVDM (DSP) slots on motherboard	2	Same As Cisco 2801	3	Same As Cisco 2821
Integrated hardware-based encryption	Yes	Same As Cisco 2801	Same As Cisco 2801	Same As Cisco 2801
Optional PoE	Yes, requires AC-IP system power supply	Same As Cisco 2801	Same As Cisco 2801	Same As Cisco 2801
Console port (up to 115.2 kbps)	1	Same As Cisco 2801	Same As Cisco 2801	Same As Cisco 2801
Auxiliary port (up to 115.2 kbps)	1	Same As Cisco 2801	Same As Cisco 2801	Same As Cisco 2801
Minimum Cisco IOS Software release	12.3(8)T4	Same As Cisco 2801	Same As Cisco 2801	Same As Cisco 2801
Rack mounting	Yes, 19-inch	Yes, 19- and 23-in. options	Same As Cisco 2811	Same As Cisco 2811
Wall mounting	No	Yes	Same As Cisco 2801	Same As Cisco 2801
AC input voltage	100 to 240 VAC	Same As Cisco 2801	Same As Cisco 2801	Same As Cisco 2801
AC input frequency	47-63 Hz	Same As Cisco 2801	Same As Cisco 2801	Same As Cisco 2801
AC input current	2A (110V); 1A (230V)	Same As Cisco 2801	3A (110V); 2A (230V)	Same As Cisco 2821
AC input surge current	50A maximum, one cycle (-48V power included)	Same As Cisco 2801	Same As Cisco 2801	Same As Cisco 2801
AC-IP max in-line power distribution	120W	160W	240W	360W
AC-IP input current	4A (110V); 2A (230V)	Same As Cisco 2801	8A (110V); 4A (230V)	Same As Cisco 2821

Feature	Cisco 2801	Cisco 2811	Cisco 2821	Cisco 2851
AC-IP input surge current	50A maximum, one cycle (–48V power included)	Same As Cisco 2801	Same As Cisco 2801	Same As Cisco 2801
DC input voltage	No DC Power Option available	24 to 60 VDC, autorunning positive or negative	Same As Cisco 2811	Same As Cisco 2811
DC input current	No DC Power Option available	8A (24V) 3A (60V) Startup current 5A<10 ms	12A (24V) 5A (60V) Startup current 50A<10 ms	Same As Cisco 2821
Power dissipation—AC 150W (511 BTU/hr.) without PoE support		170W (580 BTU/hr.)	280W (955 BTU/hr.)	Same As Cisco 2821
Power dissipation—AC 180W (612 BTU/hr.) with PoE-IP phones		160W (546 BTU/hr.)	240W (819 BTU/hr.)	Same As Cisco 2821
Power dissipation—DC	Not applicable	180W (614 BTU/hr.)	300W (1024 BTU/hr.)	Same As Cisco 2821
Redundant Power Support (RPS)	No	External only, connector for RPS provided by default	Same As Cisco 2811	Same As Cisco 2811
Recommended RPS unit	No RPS option	Cisco RPS-675 Redundant Power System	Same As Cisco 2811	Same As Cisco 2811
Operating temp	32 to 104°F; (0 to 40°C)	Same As Cisco 2801	Same As Cisco 2801	Same As Cisco 2801
Operating humidity	10 to 85% non condensing	5 to 95%, non condensing	Same As Cisco 2811	Same As Cisco 2811
Non operating temp	N/A	–4 to 149°F (–20 to 65°C)	Same As Cisco 2811	Same As Cisco 2811
Dimensions (H x W x D)	1.72 x 17.5 x 16.5 in. (43.7 x 445 x 419 MM.)	1.75 x 17.25 x 16.4 in. (44.5 x 438.2 x 416.6 MM.)	3.5 x 17.25 x 16.4 in. (88.9 x 438.2 x 416.6 MM.)	Same As Cisco 2821
Rack height	1 rack unit (1RU)	1 rack unit (1RU)	2RU	Same As Cisco 2821
Weight (configured)	13.7 lb. (6.2 kg)	14 lb. (6.4 kg)	25 lb. (11.4 kg)	Same As Cisco 2821
Noise level (min/max)	39 dBA for normal operating temperature (<90°F/32.2°C) 53.5 dBA (@ maximum fan speed)	47 dBA for normal operating temperature (<90°F/32.2°C) 57 dBA (@ maximum fan speed)	44 dBA for normal operating temperature (<90°F/32.2°C) 53 dBA (@ maximum fan speed)	
Safety	UL 60950 CAN/CSA C22.2 No. 60950 IEC 60950 EN 60950-1 AS/NZS 60950	Same As Cisco 2801	Same As Cisco 2801	Same As Cisco 2801
Immunity	EN300386 EN55024/CISPR24 EN50082-1 EN61000-6-2	Same As Cisco 2801	Same As Cisco 2801	Same As Cisco 2801
EMC	FCC Part 15; ICES-003 Class A; EN55022 Class A; CISPR22 Class A; AS/NZS 3548 Class A; VCCI Class A EN 300386; EN61000-3-3; EN61000-3-2			
TELCOM	Telecom compliance standards depend upon country and interface type. Interfaces comply with FCC Part 68, CS-03, JATE Technical Conditions, European Directive 99/5/EC and relevant TBRs. See the datasheet for the specific interface card.			

Selected Part Numbers and Ordering Information¹

Cisco 2800 Series Router

CISCO2801	Integrated services router with AC power, 2FE, 4 Interface Card Slots, 2 PVDM slots, 2 AImS, and Cisco IOS IP Base Software
CISCO2801-AC-IP	Integrated services router with AC power including Inline power distribution capability, 2FE, 4 Interface Card Slots, 2 PVDM slots, 2 AImS, and Cisco IOS IP Base Software
CISCO2811	Integrated services router with AC power, 2FE, 1 NME, 4 HWICs, 2 PVDM slots, 2 AImS, and Cisco IOS IP Base Software
CISCO2811-AC-IP	Integrated services router with AC power including Inline power distribution capability, 2FE, 1 NME, 4 HWICs, 2 PVDM slots, 2 AImS, and Cisco IOS IP Base Software
CISCO2811-DC	Integrated services router with DC power, 2FE, 1 NME, 4 HWICs, 2 PVDM slots, 2 AImS, and Cisco IOS IP Base Software
CISCO2821	Integrated services router with AC power, 2GE, 1 NME-X, 1 EVM, 4 HWICs, 2 PVDM slots, 2 AImS, and Cisco IOS IP Base Software
CISCO2821-AC-IP	Integrated services router with AC power including inline power distribution capability, 2GE, 1 NME-X, 1 EVM, 4 HWICs, 3 PVDM slots, 2 AImS, and Cisco IOS IP Base Software
CISCO2821-DC	Integrated services router with DC power, 2GE, 1 NME-X, 1 EVM, 4 HWICs, 3 PVDM slots, 2 AImS, and Cisco IOS IP Base Software
CISCO2851	Dual Gigabit Ethernet integrated services router with AC power, 2GE, 1 NME-XD, 1 EVM, 4 HWICs, 3 PVDM slots, 2 AImS, and Cisco IOS IP Base Software
CISCO2851-AC-IP	Integrated services router with AC power including inline power distribution capability, 2GE, 1 NME-XD, 1 EVM, 4 HWICs, 3 PVDM slots, 2 AImS, and Cisco IOS IP Base Software
CISCO2851-DC	Integrated services router with DC power, 2GE, 1 NME-XD, 1 EVM, 4 HWICs, 3 PVDM slots, 2 AImS, and Cisco IOS IP Base Software

Cisco 2800 Series Security Bundles

CISCO2801-SEC/K9	2801 Security Bundle, Adv Security, 64F/256D
CISCO2801-HSEC/K9	2801 Security Bundle, AIM-VPN/EPII-PLUS, Adv. IP Serv, 64F/256D
CISCO2811-SEC/K9	2811 Security Bundle, Adv Security, 64F/256D
CISCO2811-HSEC/K9	2811 Security Bundle, AIM-VPN-EPII-PLUS, Adv. IP Serv, 64F/256D
CISCO2821-SEC/K9	2821 Security Bundle, Adv Security, 64F/256D
CISCO2821-HSEC/K9	2821 Security Bundle, AIM-VPN-EPII-PLUS, Adv. IP Serv, 64F/256D
CISCO2851-SEC/K9	2851 Security Bundle, Adv Security, 64F/256D
CISCO2851-HSEC/K9	2851 Security Bundle, AIM-VPN-EPII-PLUS, Adv. IP Serv, 64F/256D

Cisco 2800 Series Voice Bundles

CISCO2801-V/K9	2801 Voice Bundle, PVDM2-8, SP Serv, 64F/256D
CISCO2801-CCME/K9	2801 Voice Bundle w/ PVDM2-8, FL-CCME-24, SP Serv, 64F/256D
CISCO2801-SRST/K9	2801 Voice Bundle w/ PVDM2-8, FL-SRST-24, SP Serv, 64F/256D
CISCO2811-V/K9	2811 Voice Bundle, PVDM2-16, SP Serv, 64F/256D
CISCO2811-CCME/K9	2811 Voice Bundle w/ PVDM2-16, FL-CCME-36, SP Serv, 64F/256D
CISCO2811-SRST/K9	2811 Voice Bundle w/ PVDM2-16, FL-SRST-36, SP Serv, 64F/256D
CISCO2821-V/K9	2821 Voice Bundle, PVDM2-32, SP Serv, 64F/256D
CISCO2821-CCME/K9	2821 Voice Bundle w/ PVDM2-32, FL-CCME-48, SP Serv, 64F/256D
CISCO2821-SRST/K9	2821 Voice Bundle w/ PVDM2-32, FL-SRST-48, SP Serv, 64F/256D
CISCO2851-V/K9	2851 Voice Bundle, PVDM2-48, SP Serv, 64F/256D
CISCO2851-CCME/K9	2851 Voice Bundle w/ PVDM2-48, FL-CCME-96, SP Serv, 64F/256D
CISCO2851-SRST/K9	2851 Voice Bundle w/ PVDM2-48, FL-SRST-96, SP Serv, 64F/256D

Cisco 2800 Series Secure Voice Bundles

CISCO2801-V3PN/K9	2801 V3PN bdl, AIM-VPN, PVDM2-8, FL-CCME-24, Adv IPServ, 64F/256D
CISCO2811-V3PN/K9	2811 V3PN bdl w/ AIM-VPN, PVDM2-16, CCME-36, Adv IPServ, 64F/256D
CISCO2821-V3PN/K9	2821 V3PN bdl w/ AIM-VPN, PVDM2-32, CCME-48, Adv IPServ, 64F/256D
CISCO2851-V3PN/K9	2851 V3PN bdl w/ AIM-VPN, PVDM2-48, CCME-72, Adv IPServ, 64F/256D

Cisco 2800 Series Broadband Bundles

CISCO2801-ADSL/K9	2801 DSL Bundle, WIC-1ADSL(ADSLoPOTS), SP Serv, 64F/192D
CISCO2801C2801-SHDSL-V3/K9	2801 DSL Bdl Bundle, WIC-1SHDSL-V3 (2- or 4 Wire only), SP Serv, 64F/192D), IP BASE, 64FL/192DR
CISCO2811-ADSL/K9	2811 with WIC-1ADSL (ADSLoPOTS), SP Ser IOS, 64F/256D
CISCO2811C2811-SHDSL-V3/K9	2811 DSL Bundle, WIC-1SHDSL-V2V3 (2 or 4 Wire), SP Serv, 64F/256D

Cisco 2851/2800 WAN Optimization Bundles

CISCO2821-AA/K9	Cisco 2821 Basic Wan Optimization Bundle
CISCO2821-SAA/K9	Cisco 2821 Secure Wan Optimization Bundle
CISCO2851-AA/K9	Cisco 2851 Basic Wan Optimization Bundle
CISCO2851-SAA/K9	Cisco 2851 Secure Wan Optimization Bundle

Ethernet Switching Network Modules

NME-16ES-1G	EtherSwitch Service Mod 16 10/100T + 1 GE, IP Base
NME-16ES-1G-P	EtherSwitch Service Mod 16 10/100T POE + 1 GE, IP Base
NME-X-23ES-1G	EtherSwitch Service Mod 23 10/100T + 1 GE POE, IP Base
NME-X-23ES-1G-P	EtherSwitch Service Mod 23 10/100T POE + 1 GE POE, IP Base
NM-16ESW	16-port 10/100 Cisco EtherSwitchÆ Network Module
NM-16ESW-1GIG	16-port 10/100 Cisco EtherSwitch Network Module with 1 Gigabit Ethernet (1000BASE-T) port
NM-16ESW-PWR	16-port 10/100 Cisco EtherSwitch Network Module with in-line power support
NM-16ESW-PWR-1GIG	16-port 10/100 Cisco EtherSwitch Network Module with in-line power and Gigabit Ethernet
NMD-36ESW	36-port 10/100 Cisco EtherSwitch High-Density Services Module (HDSM)
NMD-36ESW-2GIG	36-port 10/100 Cisco EtherSwitch HDSM with 1 Gigabit Ethernet (1000BASE-T) port
NMD-36ESW-PWR	36-port 10/100 Cisco EtherSwitch HDSM with in-line power support
NMD-36ESW-PWR-2G	36-port 10/100 Cisco EtherSwitch HDSM with in-line power and Gigabit Ethernet
NME-XD-24ES-1S-P	24 10/100 w/ POE + 1 SFP + Stackwise interfaces
NME-XD-48ES-2S-P	48 10/100 w/ POE + 2 SFP

Serial Connectivity Network Modules

NM-1T3/E3	1-port clear-channel T3/E3 network module
NM-1HSSI	1-port High-Speed Serial Interface (HSSI) network module
NM-4A/S	4-port asynchronous/synchronous serial network module
NM-8A/S	8-port asynchronous/synchronous serial network module
NM-16A/S	16-port asynchronous/synchronous serial network module
NM-16A	16-port asynchronous serial network module
NM-32A	32-port asynchronous serial network module

Channelized T1/E1 and ISDN Network Modules

NM-1CE1T1-PRI	1-port Channelized E1/T1/ISDN PRI network module
NM-2CE1T1-PRI	2-port Channelized E1/T1/ISDN PRI network module
NM-4B-S/T	4-port ISDN BRI network module (S/T interface)
NM-4B-U	4-port ISDN BRI network module with integrated Network Termination 1 (NT1) (U interface)
NM-8B-S/T	8-port ISDN BRI network module (S/T interface)
NM-8B-U	8-port ISDN BRI network module with integrated NT1 (U interface)

ATM Network Modules

NM-1A-T3	1-port DS-3 ATM network module
NM-1A-E3	1-port E3 ATM network module

Analog Dialup and Remote Access Network Modules

NM-8AM-V2	8-port analog modem network module with v.92
NM-16AM-V2	16-port analog modem network module with v.92

Voice Network Modules and Accessories

NM-HD-1V	1-slot IP Communications voice and fax network module
NM-HD-2V	2-slot IP Communications voice and fax network module
NM-HD-2VE	2-slot IP Communications enhanced voice and fax network module
NM-HDA-4FXS	High-density analog voice and fax network module with 4 FXS slots
NM-HDV2	IP Communications high-density voice and fax network module
NM-HDV2-1T1/E1	1-port T1/E1 IP Communications high-density voice and fax network module
NM-HDV2-2T1/E1	2-port T1/E1 IP Communications high-density voice and fax network module
NM-HDV=	High-density voice and fax network module (single VIC slot)
NM-HDV-1T1-12	1-port 12-channel T1 voice and fax network module
NM-HDV-1T1-24	1-port 24-channel T1 voice and fax network module
NM-HDV-1T1-24E	Single-port 24-enhanced-channel T1 voice and fax network module
NM-HDV-2T1-48	2-port 48-channel T1 voice and fax network module
NM-HDV-1E1-12	1-port 12-channel E1 voice and fax network module
NM-HDV-1E1-30	1-port 30-channel E1 voice and fax network module
NM-HDV-1E1-30E	1-port 30-enhanced-channel E1 voice and fax network module
NM-HDV-2E1-60	2-port 60-channel E1 voice and fax network module
NM-HDV-1J1-30	1-port 30-channel J1 high-density voice network module
NM-HDV-1J1-30E	1-port 30-enhanced-channel J1 high-density voice network module
NM-HDV-FARM-C36	36-port transcoding and conferencing DSP farm
NM-HDV-FARM-C54	54-port transcoding and conferencing DSP farm
NM-HDV-FARM-C90	90-port transcoding and conferencing DSP farm

Application Network Modules

NM-CE-BP-40G-K9	Cisco Content Engine Network Module, basic performance, 40-GB IDE hard disk
NM-CE-BP-80G-K9	Cisco Content Engine Network Module, basic performance, 80-GB IDE hard disk
NM-CIDS-K9	Cisco IDS Network Module
NM-CUE	Cisco Unity Express Voice-Mail Network Module; price includes 12-mailbox license
NM-CUE-EC	Cisco Unity Express Network Module Enhanced Capacity; price includes 12-mailbox license
NM-NAM	Cisco series Network Analysis Module Network Module
NM-AON-K9	Cisco 2600/2800/3700/3800 Series AON Network Module
NM-AIR-WLC6-K9	WLAN controller Network Module for 28/38xx ISR

Circuit Emulation Service over IP (CESoIP) Network Modules

NM-CEM-4SER	4-port serial CESoIP network module
NM-CEM-4T1E1	4-port T1/E1 CESoIP network module

Extension Voice Modules

EVM-HD-8FXS/DID	High-density voice and fax extension module - 8 FXS or DID
-----------------	--

Ethernet Switching HWICs

HWIC-4ESW	4-port single-wide 10/100BASE-T Ethernet switch HWIC
HWIC-D-9ESW	9-port double-wide 10/100BASE-T Ethernet switch HWIC
HWIC-4ESW-POE	4-port Ethernet switch HWIC, PoE capable
HWIC-D-9-ESW-POE	9-port Ethernet switch HWIC, PoE capable

Gigabit Ethernet HWICs

HWIC-1GE-SFP	GigE High Speed WIC With One SFP Slot
--------------	---------------------------------------

Wireless HWICs and Accessories

HWIC-AP-G-A	Cisco 802.11 B/G Access Point High Speed Wan Interface Card for the Americas (FCC configuration)
HWIC-AP-G-E	Cisco 802.11 B/G Access Point High Speed Wan Interface Card for Europe (ETSI configuration)
HWIC-AP-G-J	Cisco 802.11 B/G Access Point High Speed Wan Interface Card for Japan (TELEC configuration)
HWIC-AP-AG-A	Cisco 802.11 A/B/G Access Point High Speed Wan Interface Card for the Americas (FCC configuration)
HWIC-AP-AG-E	Cisco 802.11 A/B/G Access Point High Speed Wan Interface Card for Europe (ETSI configuration)
HWIC-AP-AG-J	Cisco 802.11 A/B/G Access Point High Speed Wan Interface Card for Japan (TELEC configuration)
AIR-ANT4941	2.2 dBi Cisco Aironet 2.4 GHz Swivel mount dipole
AIR-ANT5959	2 dBi Cisco Aironet 2.4 GHz Diversity omni-directional ceiling mount patch
AIR-ANT1728	5.2dBi Cisco Aironet 2.4 GHz Omni-directional ceiling mount
AIR-ANTM2050D-R	(2.2 dBi Cisco 2.4 Ghz and 5.0 dBi 5 GHz) Dual band Swivel mount dipole antenna
AIR-ANTM5560P-R	(5.5 dBi Cisco 2.4 Ghz and 6.0 dBi 5 GHz) Dual band Wall-mount patch antenna
AIR-ANTM4050V-R	(4.0 dBi Cisco 2.4 Ghz and 5.0 dBi 5 GHz) Dual band Diversity Ceiling-mount omnidirectional antenna
AIR-CAB020LL-R	20-ft (6m) low-loss cable with RP-TNC connectors
AIR-CAB050LL-R	50-ft (15m) low-loss cable with RP-TNC connectors
AIR-CAB100ULL-R	100 ft (30m) ultra-low-loss cable with RP-TNC connectors
AIR-CAB150ULL-R	150-ft (46m) ultra-low-loss cable with RP-TNC connector

Serial WICs and HWICs

HWIC-4T	4-Port Serial HWIC
HWIC-4A/S	4-Port Async/Sync Serial HWIC
HWIC-8A/S-232	8-Port Async/Sync Serial HWIC, EIA-232
HWIC-8A	8-Port Async HWIC
HWIC-16A	16-Port Async HWIC
WIC-1T	1-port high-speed serial WIC
WIC-2T	2-port high-speed serial WIC
WIC-2A/S	2-port asynchronous/synchronous serial WIC

CSU/DSU WICs

WIC-1DSU-T1-V2	1-port T1/Fractional-T1 DSU/CSU WIC
WIC-1DSU-56K4	1-port 4-wire 56-/64-kbps CSU/DSU WIC

ISDN BRI WICs and HWICs

WIC-1B-U-V2	1-port ISDN BRI with integrated NT1 (U interface)
WIC-1B-S/T-V3	1-port ISDN BRI with S/T interface
HWIC-ADSL-B/ST	HWIC w/ADSLoPOTS and ISDN BRI ports
HWIC-ADSLI-B/ST	HWIC w/ADSLoISDN and ISDN BRI ports

DSL WICs and HWICs

WIC-1ADSL	1-port asymmetric DSL (ADSL) over basic-telephone-service WIC
WIC-1ADSL-DG	1-port ADSL over basic telephone service with dying-gasp WIC
WIC-1ADSL-I-DG	1-port ADSL over ISDN with dying-gasp WIC
HWIC-1ADSL	1-port ADSLoPOTS HWIC
HWIC-1ADSLI	1-port ADSLoISDN HWIC
HWIC-ADSL-B/ST	HWIC w/ADSLoPOTS and ISDN BRI ports
HWIC-ADSLI-B/ST	HWIC w/ADSLoISDN and ISDN BRI ports
WIC-1SHDSL-V3	1-port G.shdsl WIC (two or four wire)

Analog Modem WICs

WIC-1AM	1-port analog modem WIC
WIC-2AM	2-port analog modem WIC

T1, E1, and G.703 Multiflex Trunk Voice Cards and WICs

VVIC2-1MFT-T1/E1=	1-Port 2nd Gen Multiflex Trunk Voice/WAN Int. Card - T1/E1
VVIC2-2MFT-T1/E1=	2-Port 2nd Gen Multiflex Trunk Voice/WAN Int. Card - T1/E1
VVIC2-1MFT-G703=	1-Port 2nd Gen Multiflex Trunk Voice/WAN Int. Card - G.703
VVIC2-2MFT-G703=	2-Port 2nd Gen Multiflex Trunk Voice/WAN Int. Card - G.703
EC-MFT-32=	32-Channel Multiflex Trunk Dedicated ECAN Module
EC-MFT-64=	64-Channel Multiflex Trunk Dedicated ECAN Module
VVIC-1MFT-T1	1-port RJ-48 multiflex trunk - T1
VVIC-2MFT-T1	2-port RJ-48 multiflex trunk - T1
VVIC-2MFT-T1-DI	2-port RJ-48 multiflex trunk - T1 with drop and insert
VVIC-1MFT-E1	1-port RJ-48 multiflex trunk - E1
VVIC-1MFT-G703	1-port RJ-48 multiflex trunk - G.703
VVIC-2MFT-E1	2-port RJ-48 multiflex trunk - E1
VVIC-2MFT-E1-DI	2-port RJ-48 multiflex trunk - E1 with drop and insert
VVIC-2MFT-G703	2-port RJ-48 multiflex trunk - G.703

VICs

VIC-2DID	2-port DID voice and fax interface card
VIC-1J1	1-port digital VIC (J1) for Japan
VIC-4FXS/DID	4-port FXS or DID VIC
VIC2-2FXS	2-port VIC - FXS
VIC2-2FXO	2-port VIC - FXO (universal)
VIC2-4FXO	4-port VIC - FXO (universal)
VIC2-2E/M	2-port VIC - E&M
VIC2-2BRI-NT/TE	2-port VIC card - BRI (NT and TE)

AIMs

AIM-ATM	High-performance ATM SAR AIM
AIM-ATM-1T1=	High Performance ATM AIM/T1 Bundle AIM-ATM
AIM-ATM-1E1=	High Performance ATM AIM/E1 Bundle AIM-ATM
AIM-ATM-4T1=	AIM-ATM with 2 VWIC-2MFT-T1
AIM-ATM-4E1	AIM-ATM with 2 VWIC-2MFT-E1
AIM-COMPR2-V2	Data-compression AIM
AIM-CUE	Cisco Unity Express Voice-Mail AIM
AIM-VPN/EPII-PLUS	Enhanced-performance DES, 3DES, AES, and compression VPN encryption AIM

PVDM Support on Motherboard Slots

PVDM2-8	8-channel fax and voice DSP module
PVDM2-16	16-channel fax and voice DSP module
PVDM2-32	32-channel fax and voice DSP module
PVDM2-48	48-channel fax and voice DSP module
PVDM2-64	64-channel fax and voice DSP module

1. This is only a small subset of all parts available via URL listed under "For More Information". Some parts have restricted access or are not available through distribution channels. Resellers: For latest part number and pricing info, see the *Distribution Product Reference Guide* at: <http://www.cisco.com/dprg> (limited country availability).

For More Information

See the Cisco 2800 Series Website: <http://www.cisco.com/go/2800>

Cisco 3800 Series



The Cisco 3800 Series is the flagship platform in a portfolio of next-generation routers that integrate advanced technologies, adaptive services, and secure enterprise communications.

These new routers offer the performance and reliable packet delivery necessary to efficiently deliver mission-critical network capabilities, including real-time applications such as VoIP, business video, and collaborative communications. Architectural enhancements include embedded security processing, significant platform performance and memory improvements, and new high-density interface types.

When to Sell

When a Customer Needs These Features

Cisco 3825

- Medium- to large-sized branch offices and businesses with the ability to support concurrent data, security, voice, and advanced services at wire speed up to ½ T3/E3 rates
- Two onboard 10/100/1000, 4 HWIC slots and one SFP port
- Low density (up to 88 ports), integrated 10/100 switching; up to 360W Cisco Inline Power or PoE
- Integrated onboard security acceleration for IPSec for improved IPSec performance and an integral part of Cisco Self Defending Network, which enable network device protection, threat defense, secure connectivity, and endpoint protection and control
- Up to four Integrated PVDMs slots, industry-leading call processing and autoattendant solutions, and high-density voice cards and modules that speed IP Communications and give customers a choice of telephony interface devices

Cisco 3845

- Same features as above plus:
- Medium- to large-sized branch offices and businesses providing the highest performance and densities for concurrent data, security, voice, and advanced services with the ability to run at wire-speed up to T3/E3
 - 4 Enhanced Network Module slots
 - Up to 112 ports integrated 10/100 switching; up to 360W redundant Cisco in-line power or PoE
 - Higher availability and resiliency, such as redundant system and inline power, online insertion and removable (OIR) components, and field replaceable components such as the cpu motherboard and fan assembly

Key Features

- Cisco IOS Software Firewall—Stateful, application-based filtering (context-based access control); Per-user authentication and authorization; Real-time alerts; Transparent firewall; IPv6 firewall
- VPN—Data Encryption Standard (DES), Triple DES (3DES), and Advanced Encryption Standard (AES) 128, 192, and 256 cryptology support; Embedded hardware-based VPN acceleration on the motherboard; Support for optional higher-performance AIM-based security acceleration with Layer 3 compression; Support for up to 1800 tunnels with VPN Module; Cisco Easy VPN remote and server support; DMVPN
- Multiprotocol Label Switching (MPLS) VPN support—Specific provider edge capabilities; Virtual routing and forwarding (VRF) firewall and VRF IPsec
- Onboard USB 1.1 port(s)—Future support for secure token and Flash memory
- IPS—More than 700 IPS signatures supported in Cisco IOS Software, with the ability to load and enable selected IPS signatures; More than 1000 IPS signatures with optional high-performance IDS Network Module
- URL filtering—Onboard with an optional content-engine network module; Local URL filtering in Cisco IOS Software based on external server
- Cisco Router and SDM—Comes standard on all Cisco 3800 Series routers
- IP phone support—Optional integrated power supply with inline power; 802.3af support—360W of inline power
- Analog voice support—Up to 88 FXS and 56 FXO ports; Digital voice support—Up to 720 calls; Packet voice digital signal processor (DSP) module (PVDM) slots on motherboard—4 PVDM slots on motherboard; Local conferencing and transcoding;
- Cisco CME—Up to 240 phones; SRST—Up to 720 phones
- Voice mail—Up to a 120 mailboxes using Cisco Unity Express network module
- Voice interfaces—FXS, FXO, Direct Inward Dial (DID), E&M, Centralized Automated Message Accounting (CAMA), BRI, T1, E1, J1, Primary Rate Interface (PRI), Q.SIG, channel associated signaling (CAS)

Specifications

Feature	Cisco 3825	Cisco 3845
Network Module Slots	2	4
Advanced Integration Module (AIM) Slots	2	Same As Cisco 3825
High speed WAN Interface Card (HWIC) Slots	4	Same As Cisco 3825
10/100/1000 GE Ports	2	Same As Cisco 3825
Small Form Pluggable (SFP) ports	1	Same As Cisco 3825
Onboard PVDM slots	4	Same As Cisco 3825
WAN Network Modules	Yes	Same As Cisco 3825
ATM AIM Modules	Yes	Same As Cisco 3825
Voice/Fax Network Modules	Yes	Same As Cisco 3825
WAN Interface Card (WIC) Modules	Yes	Same As Cisco 3825
Multiflex Voice/WAN Interface Cards	Yes	Same As Cisco 3825
Voice Interface Card (VIC) Modules	Yes	Same As Cisco 3825
Modem Modules	Yes	Same As Cisco 3825
EtherSwitch Modules	Yes, HWIC and Network Modules	Same As Cisco 3825
Performance with Services	Up to 14 T1/E1s	Up to T3
VPN/Security Advanced Integration Modules (AIM)	Yes, AIM-VPN/EPII-PLUS	Yes, AIM-VPN/EPII-PLUS
Content Engine Network Modules	Yes	Same As Cisco 3825
Flash Memory (External)	64 MB (default) -256 MB (optional)	Same As Cisco 3825
DRAM Memory	256 MB (default)	Same As Cisco 3825
	1024 MB (max)	Same As Cisco 3825

Feature	Cisco 3825	Cisco 3845
Power Supply	AC, AC +POE, DC, external redundant AC/AC, DC, internal redundant AC + POE	
Dimensions (H x W x D)	3.5 x 17.1 x 14.7 in.	5.25 x 17.25 x 16 in.

Selected Part Numbers and Ordering Information¹

Cisco 3800 Series Integrated Services Routers

CISCO3825	Cisco 3825 Integrated Services Router with 2 Gigabit Ethernet, 1 SFP, 2 NME, 4 HWIC, 2 AIM, Cisco IOS IP Base software, and AC power
CISCO3825-AC-IP	Cisco 3825 Integrated Services Router with 2 Gigabit Ethernet, 1 SFP, 2 NME, 4 HWIC, 2 AIM, Cisco IOS IP Base software, AC Power, and PoE
CISCO3825-DC	Cisco 3825 Integrated Services Router with 2 Gigabit Ethernet, 1 SFP, 2 NME, 4 HWIC, 2 AIM, Cisco IOS IP Base software, and DC power
CISCO3845	Cisco 3845 Integrated Services Router with 2 Gigabit Ethernet, 1 SFP, 4 NME, 4 HWIC, 2 AIM, Cisco IOS IP Base software, and AC power
CISCO3845-AC-IP	Cisco 3845 Integrated Services Router with 2 Gigabit Ethernet, 1 SFP, 4 NME, 4 HWIC, 2 AIM, Cisco IOS IP Base software, AC Power, and PoE

Cisco 3800 Series Secure Voice Bundles

CISCO3845-V3PN/K9	Cisco 3845 V3PN Bundle with IOS Advanced IP Services, PVDM2-64, AIM-VPN/HPII-PLUS, FL-CCME (240 users), 64 MB Flash/256 MB DRAM
CISCO3825-V3PN/K9	Cisco 3825 V3PN Bundle with IOS Advanced IP Services, PVDM2-64, AIM-VPN/EPII-PLUS, FL-CCME (168 users), 64 MB Flash/256 MB DRAM

Cisco 3800 Series Security Bundles

CISCO3845-SEC/K9	Cisco 3845 Security Bundle with IOS Advanced Security, 64MB Flash/256 MB DRAM
CISCO3845-HSEC/K9	Cisco 3845 Security Bundle with IOS Advanced IP Services, AIM-VPN/HPII Plus, 64MB Flash/256 MB DRAM
CISCO3825-SEC/K9	Cisco 3825 Security Bundle with IOS Advanced Security, 64MB Flash/256MB DRAM
CISCO3825-HSEC/K9	Cisco 3825 Security Bundle with IOS Advanced IP Services, AIM-VPN/EPII Plus, 64MB Flash/256 MB DRAM

Cisco 3800 Series Voice Bundles

CISCO3845-V/K9	Cisco 3845 Voice Bundle with IOS SP Services, PVDM2-64, 64 MB Flash/256 MB DRAM
CISCO3845-SRST/K9	Cisco 3845 Voice Bundle with IOS SP Services, PVDM2-64, FL-SRST (240 users), 64 MB Flash/256 MB DRAM
CISCO3845-CCME/K9	Cisco 3845 Voice Bundle with IOS SP Services, PVDM2-64, FL-CCME (240 users), 64 MB Flash/256 MB DRAM
CISCO3825-V/K9	Cisco 3825 Voice Bundle with IOS SP Services, PVDM2-64, 64 MB Flash/256 MB DRAM
CISCO3825-SRST/K9	Cisco 3825 Voice Bundle with IOS SP Services, PVDM2-64, FL-SRST (168 users), 64 MB Flash/256 MB DRAM
CISCO3825-CCME/K9	Cisco 3825 Voice Bundle with IOS SP Services, PVDM2-64, FL-CCME (168 users), 64 MB Flash/256 MB DRAM

Cisco 3800 Series WAN Optimization Bundles

CISCO3825-AA/K9	Cisco 3825 Basic Wan Optimization Bundle
CISCO3825-SAA/K9	Cisco 3825 Secure Wan Optimization Bundle
CISCO3845-AA/K9	Cisco 3845 Basic Wan Optimization Bundle
CISCO3845-SAA/K9	Cisco 3845 Secure Wan Optimization Bundle

Ethernet Switching Network Modules

NME-16ES-1G-P=	EtherSwitch Service Mod 16 10/100T POE + 1 GE,IP Base
NME-X-23ES-1G-P=	EtherSwitch Service Mod 23 10/100T POE + 1 GE POE, IP Base
NM-16ESW	16-port 10/100 Cisco EtherSwitch Network Module
NM-16ESW-1GIG	16-port 10/100 Cisco EtherSwitch Network Module with 1 Gigabit Ethernet (1000BASE-T) port
NM-16ESW-PWR	16-port 10/100 Cisco EtherSwitch Network Module with in-line power support
NM-16ESW-PWR-1GIG	16-port 10/100 Cisco EtherSwitch Network Module with in-line power and Gigabit Ethernet
NMD-36ESW	36-port 10/100 Cisco EtherSwitch High-Density Services Module (HDSM)
NMD-36ESW-2GIG	36-port 10/100 Cisco EtherSwitch HDSM with 1 Gigabit Ethernet (1000BASE-T) port
NMD-36ESW-PWR	36-port 10/100 Cisco EtherSwitch HDSM with in-line power support
NMD-36ESW-PWR-2G	36-port 10/100 Cisco EtherSwitch HDSM with in-line power and Gigabit Ethernet
NME-XD-24ES-1S-P	24 10/100 w/ POE + 1 SFP + Stackwise interfaces
NME-XD-48ES-2S-P	48 10/100 w/ POE + 2 SFP

Serial Connectivity Network Modules

NM-1T3/E3	1-port clear-channel T3/E3 network module
NM-1HSSI	1-port High-Speed Serial Interface (HSSI) network module
NM-4A/S	4-port asynchronous/synchronous serial network module
NM-8A/S	8-port asynchronous/synchronous serial network module
NM-16A/S	16-port asynchronous/synchronous serial network module
NM-16A	16-port asynchronous serial network module
NM-32A	32-port asynchronous serial network module
NM-4T	4-Port Serial Network Module

Channelized T1/E1 and ISDN Network Modules

NM-1CE1T1-PRI	1-port Channelized E1/T1/ISDN PRI network module
NM-2CE1T1-PRI	2-port Channelized E1/T1/ISDN PRI network module
NM-4B-S/T	4-port ISDN BRI network module (S/T interface)
NM-4B-U	4-port ISDN BRI network module with integrated Network Termination 1 (NT1) (U interface)
NM-8B-S/T	8-port ISDN BRI network module (S/T interface)
NM-8B-U	8-port ISDN BRI network module with integrated NT1 (U interface)

ATM Network Modules and Transceiver Modules

NM-1A-T3	1-port DS-3 ATM network module
NM-1A-E3	1-port E3 ATM network module
NM-1A-OC3-POM	ATM OC3 module with single POM (SFP) slot
SFP-OC3-MM	OC3/STM1 SFP, Multi-mode fiber
SFP-OC3-IR1	OC3/STM1 SFP, Single-mode fiber, Intermediate Reach
SFP-OC3-LR1	OC3/STM1 SFP, Single-mode fiber, Long Reach (40km)

Analog Dialup and Remote Access Network Modules

NM-8AM-V2	8-port analog modem network module with v.92
NM-16AM-V2	16-port analog modem network module with v.92

Digital Modem and Remote Access Network Modules

NM-6DM	6 Port Digital Modem Network Module
NM-12DM	12 Port Digital Modem Network Module
NM-18DM	18 Port Digital Modem Network Module
NM-24DM	24 Port Digital Modem Network Module
NM-30DM	30 Port Digital Modem Network Module
MICA-6MOD=	6 Port Digital Modem Module, Spare

LAN/WAN Mixed Media Network Modules

NM-1FE1R2W	1 10/100 Ethernet 1 4/16 Token-Ring 2 WAN Card Slot NM
NM-1FE2W-V2	1 10/100 Ethernet with 2 WAN Card Slot Network Module
NM-1FE2W-V2	2 10/100 Ethernet with 2 WAN Card Slot Network Module
NM-1GE	1 Port Gigabit Ethernet Network Module

Voice Network Modules and Accessories

NM-HD-1V	1-slot IP Communications voice and fax network module
NM-HD-2V	2-slot IP Communications voice and fax network module
NM-HD-2VE	2-slot IP Communications enhanced voice and fax network module
NM-HDA-4FXS	High-density analog voice and fax network module with 4 FXS slots
NM-HDV2	IP Communications high-density voice and fax network module
NM-HDV2-1T1/E1	1-port T1/E1 IP Communications high-density voice and fax network module
NM-HDV2-2T1/E1	2-port T1/E1 IP Communications high-density voice and fax network module
NM-HDV=	High-density voice and fax network module (single VIC slot)
NM-HDV-1T1-12	1-port 12-channel T1 voice and fax network module
NM-HDV-1T1-24	1-port 24-channel T1 voice and fax network module
NM-HDV-1T1-24E	Single-port 24-enhanced-channel T1 voice and fax network module
NM-HDV-2T1-48	2-port 48-channel T1 voice and fax network module
NM-HDV-1E1-12	1-port 12-channel E1 voice and fax network module
NM-HDV-1E1-30	1-port 30-channel E1 voice and fax network module
NM-HDV-1E1-30E	1-port 30-enhanced-channel E1 voice and fax network module
NM-HDV-2E1-60	2-port 60-channel E1 voice and fax network module
NM-HDV-1J1-30	1-port 30-channel J1 high-density voice network module
NM-HDV-1J1-30E	1-port 30-enhanced-channel J1 high-density voice network module
NM-HDV-FARM-C36	36-port transcoding and conferencing DSP farm
NM-HDV-FARM-C54	54-port transcoding and conferencing DSP farm
NM-HDV-FARM-C90	90-port transcoding and conferencing DSP farm

Application Network Modules

NM-CE-BP-40G-K9	Cisco Content Engine Network Module, basic performance, 40-GB IDE hard disk
NM-CE-BP-80G-K9	Cisco Content Engine Network Module, basic performance, 80-GB IDE hard disk
NM-CIDS-K9	Cisco IDS Network Module
NM-CUE	Cisco Unity Express Voice-Mail Network Module; price includes 12-mailbox license
NM-CUE-EC	Cisco Unity Express Network Module Enhanced Capacity; price includes 12-mailbox license
NM-NAM	Cisco series Network Analysis Module Network Module
NM-AON-K9	Cisco 2600/2800/3700/3800 Series AON Network Module
NM-AIR-WLC6-K9	WLAN controller Network Module for 28/38xx ISR

Circuit Emulation Service over IP (CESoIP) Network Modules

NM-CEM-4SER	4-port serial CESoIP network module
NM-CEM-4T1E1	4-port T1/E1 CESoIP network module

Extension Voice Modules

EVM-HD-8FXS/DID	High-density voice and fax extension module - 8 FXS or DID
-----------------	--

Ethernet Switching HWICs

HWIC-4ESW	4-port single-wide 10/100BASE-T Ethernet switch HWIC
HWIC-D-9ESW	9-port double-wide 10/100BASE-T Ethernet switch HWIC
HWIC-4ESW-POE	4-port Ethernet switch HWIC, PoE capable
HWIC-D-9-ESW-POE	9-port Ethernet switch HWIC, PoE capable

Gigabit Ethernet HWICs

HWIC-1GE-SFP	GigE High Speed WIC With One SFP Slot
--------------	---------------------------------------

Wireless HWICs and Accessories

HWIC-AP-G-A	Cisco 802.11 B/G Access Point High Speed Wan Interface Card for the Americas (FCC configuration)
HWIC-AP-G-E	Cisco 802.11 B/G Access Point High Speed Wan Interface Card for Europe (ETSI configuration)
HWIC-AP-G-J	Cisco 802.11 B/G Access Point High Speed Wan Interface Card for Japan (TELEC configuration)
HWIC-AP-AG-A	Cisco 802.11 A/B/G Access Point High Speed Wan Interface Card for the Americas (FCC configuration)
HWIC-AP-AG-E	Cisco 802.11 A/B/G Access Point High Speed Wan Interface Card for Europe (ETSI configuration)
HWIC-AP-AG-J	Cisco 802.11 A/B/G Access Point High Speed Wan Interface Card for Japan (TELEC configuration)
AIR-ANT4941	2.2 dBi Cisco Aironet 2.4 GHz Swivel mount dipole
AIR-ANT5959	2 dBi Cisco Aironet 2.4 GHz Diversity omni-directional ceiling mount patch
AIR-ANT1728	5.2dBi Cisco Aironet 2.4 GHz Omni-directional ceiling mount
AIR-ANTM2050D-R	(2.2 dBi Cisco 2.4 Ghz and 5.0 dBi 5 GHz) Dual band Swivel mount dipole antenna
AIR-ANTM5560P-R	(5.5 dBi Cisco 2.4 Ghz and 6.0 dBi 5 GHz) Dual band Wall-mount patch antenna
AIR-ANTM4050V-R	(4.0 dBi Cisco 2.4 Ghz and 5.0 dBi 5 GHz) Dual band Diversity Ceiling-mount omnidirectional antenna
AIR-CAB020LL-R	20-ft (6m) low-loss cable with RP-TNC connectors
AIR-CAB050LL-R	50-ft (15m) low-loss cable with RP-TNC connectors
AIR-CAB100ULL-R	100 ft (30m) ultra-low-loss cable with RP-TNC connectors
AIR-CAB150ULL-R	150-ft (46m) ultra-low-loss cable with RP-TNC connector

Serial WICs and HWICs

HWIC-4T	4-Port Serial HWIC
HWIC-4A/S	4-Port Async/Sync Serial HWIC
HWIC-8A/S-232	8-Port Async/Sync Serial HWIC, EIA-232
HWIC-8A	8-Port Async HWIC
HWIC-16A	16-Port Async HWIC
WIC-1T	1-port high-speed serial WIC
WIC-2T	2-port high-speed serial WIC
WIC-2A/S	2-port asynchronous/synchronous serial WIC

CSU/DSU WICs

WIC-1DSU-T1-V2	1-port T1/Fractional-T1 DSU/CSU WIC
WIC-1DSU-56K4	1-port 4-wire 56-/64-kbps CSU/DSU WIC

ISDN BRI WICs

WIC-1B-U-V2	1-port ISDN BRI with integrated NT1 (U interface)
WIC-1B-S/T-V3	1-port ISDN BRI with S/T interface

DSL WICs and HWICs

WIC-1ADSL	1-port asymmetric DSL (ADSL) over basic-telephone-service WIC
WIC-1ADSL-DG	1-port ADSL over basic telephone service with dying-gasp WIC
WIC-1ADSL-I-DG	1-port ADSL over ISDN with dying-gasp WIC
HWIC-1ADSL	1-port ADSLoPOTS HWIC
HWIC-1ADSLI	1-port ADSLolSDN HWIC
WIC-1SHDSL-V3	1-port G.shdsl WIC (two or four wire)

Analog Modem WICs

WIC-1AM	1-port analog modem WIC
WIC-2AM	2-port analog modem WIC

T1, E1, and G.703 Multiflex Trunk Voice Cards and WICs

VVIC2-1MFT-T1/E1=	1-Port 2nd Gen Multiflex Trunk Voice/WAN Int. Card - T1/E1
VVIC2-2MFT-T1/E1=	2-Port 2nd Gen Multiflex Trunk Voice/WAN Int. Card - T1/E1
VVIC2-1MFT-G703=	1-Port 2nd Gen Multiflex Trunk Voice/WAN Int. Card - G.703
VVIC2-2MFT-G703=	2-Port 2nd Gen Multiflex Trunk Voice/WAN Int. Card - G.703
EC-MFT-32=	32-Channel Multiflex Trunk Dedicated ECAN Module
EC-MFT-64=	64-Channel Multiflex Trunk Dedicated ECAN Module
VVIC-1MFT-T1	1-port RJ-48 multiflex trunk - T1
VVIC-2MFT-T1	2-port RJ-48 multiflex trunk - T1
VVIC-2MFT-T1-DI	2-port RJ-48 multiflex trunk - T1 with drop and insert
VVIC-1MFT-E1	1-port RJ-48 multiflex trunk - E1
VVIC-1MFT-G703	1-port RJ-48 multiflex trunk - G.703
VVIC-2MFT-E1	2-port RJ-48 multiflex trunk - E1
VVIC-2MFT-E1-DI	2-port RJ-48 multiflex trunk - E1 with drop and insert
VVIC-2MFT-G703	2-port RJ-48 multiflex trunk - G.703

VICs

VIC-2DID	2-port DID voice and fax interface card
VIC-1J1	1-port digital VIC (J1) for Japan
VIC-4FXS/DID	4-port FXS or DID VIC
VIC-2FXS	2-port VIC - FXS
VIC-2FXO	2-port VIC - FXO (universal)
VIC-4FXO	4-port VIC - FXO (universal)
VIC-2E/M	2-port VIC - E&M
VIC-2BRI-NT/TE	2-port VIC card - BRI (NT and TE)

AIMs

AIM-ATM	High-performance ATM SAR AIM
AIM-ATM-1T1=	High Performance ATM AIM/T1 Bundle AIM-ATM
AIM-ATM-1E1=	High Performance ATM AIM/E1 Bundle AIM-ATM
AIM-ATM-4T1=	AIM-ATM with 2 VVIC-2MFT-T1
AIM-ATM-4E1	AIM-ATM with 2 VVIC-2MFT-E1
AIM-COMPR4	Data-compression AIM
AIM-CUE	Cisco Unity Express Voice-Mail AIM
AIM-VPN/EPII-PLUS	Enhanced-performance DES, 3DES, AES, and compression VPN encryption AIM

PVDM Support on Motherboard Slots

PVDM2-8	8-channel fax and voice DSP module
PVDM2-16	16-channel fax and voice DSP module
PVDM2-32	32-channel fax and voice DSP module
PVDM2-48	48-channel fax and voice DSP module
PVDM2-64	64-channel fax and voice DSP module

1. This is only a small subset of all parts available via URL listed under "For More Information." Some parts have restricted access or are not available through distribution channels. Resellers: For latest part number and pricing info, see the Distribution Product Reference Guide at: <http://www.cisco.com/dprg> (limited country availability).

For More Information

See the Cisco 3800 Series Website: <http://www.cisco.com/go/3800>

Cisco 7200 VXR Series

The Cisco 7200 VXR Series routers deliver an exceptional price to performance ratio, versatility, and feature-richness in a compact form factor. The Cisco 7200 VXR series is an optimized multi-service OC3/GE edge router ideal as a WAN aggregator for the Service Provider (small POP) or enterprise edge, an enterprise WAN gateway, a high-end managed CPE, for IBM data center connectivity or as a small core router. With the hardware supported IPsec encryption module as well as robust firewall and VRF aware IPsec/NAT support, the Cisco 7200 is ideal for integrated security service. The Cisco 7200 VXR series also supports Gatekeeper and IP-to-IP Gateway functionality. Modularity combined with a low initial price point guarantees both investment protection and maximum return on investment, allowing the customer to upgrade and/or redeploy their Cisco 7200 as their network needs change.



When to Sell

Sell This Product

Cisco 7204VXR

When a Customer Needs These Features

- 4-slot chassis
- Modular processor: 225, 400, or 1 Mpps (NPE-225, NPE-400, NPE-G1)
- 1.8 Gbps backplane (with NPE-G1)
- WAN Services aggregation (e.g. MPLS PE traffic segmentation)
- Integrated Edge Services (e.g. Integrated Security)
- IP-to-IP Gateway - highest capacity of call support
- MIX-enabled bus for data/voice/video applications

Cisco 7206VXR

- 6-slot chassis
- Modular processor: 225, 400, or 1 Mpps (NPE-225, NPE-400, NPE-G1)
- 1.8 Gbps backplane (with NPE-G1)
- WAN Services aggregation (e.g. MPLS PE traffic segmentation)
- IP-to-IP Gateway - highest capacity of call support
- MIX-enabled bus for data/voice/video applications

Key Features

- Compact Form Factor—Up to six port adapters in a fully modular 3RU form factor
- Modularity—A choice of 4- and 6-slot chassis, a selection of processors providing up to 1 Mpps, an extensive range of LAN and WAN interfaces with up to 48 ports per chassis, and single or dual power supplies
- Exceptional Value—Offers superior price to performance ratio supporting high-speed media and high-density configurations with up to 1 million packets per second processing at a competitive price point
- Feature Rich—Full support for Cisco IOS software and enhancements for high-performance network services; offers industry-leading network services, including: MPLS, broadband aggregation, QoS, Service Management router, IBM data center, Storage Area Network application, security, and voice/video/data support, Gatekeeper and IP-to-IP Gateway support
- Connectivity/Flexibility—Provides high port density and an extensive range of LAN and WAN media
- Common port adapters—Port adapters are shared with the Cisco 7300 and 7600 (w/FlexWAN Module), which simplifies sparing and protects customer investment in interfaces

Competitive Products

- Redback: SMS-500, SMS-1800
- Juniper: M7i, M10i
- Juniper: ERX700, ERX1400

Specifications

Feature	Cisco 7204VXR	Cisco 7206VXR
Fixed Ports	None	Same as 7204VXR
Expansion Slots	4	6
WAN Port Adapters	DS0 to OC-3	Same as 7204VXR
Processor	RM7K RISC Processor	Same as 7204VXR
Forwarding Rate	Up to 1 Mpps	Same as 7204VXR
Backplane Capacity	1.8 Gbps (with NPE-G1)	Same as 7204VXR
Flash (PCMCIA) Memory	For NPE-G1: 64 MB (expandable to 256 MB)	Same as 7204VXR
Flash (Compact) Memory	For NPE-225: 64 MB (expandable to 256 MB)	Same as 7204VXR
System DRAM Memory	NPE-225: 128 MB (default); 256 MB (max.) NPE-400: 256 MB (default); 512 MB (max.) NPE-G1: 256 MB (default); 1 GB (max.)	Same as 7204VXR
Minimum Cisco IOS Release	NPE-G1: 12.2(4)BW, 12.2(15)B, 12.2(14)S, 12.2(14)SU, 12.2(15)T, 12.1(14)E, 12.3(1), 12.3(2)T, 12.0(28)S, 12.3(1a)B (and later) NPE-400: 12.0(14)S, 12.1(3)E, 12.1(5)T, 12.2(1)T, 12.2(1) (and later) NPE-225: 12.0(5)XE6, 12.0(7)XE1, 12.0(9)S, 12.1(1) (and later)	Same as 7204VXR
Internal Power Supply	AC or DC, dual option	Same as 7204VXR
Redundant Power Supply	Yes, for AC or DC	Same as 7204VXR
Chassis Height	3 RU	Same as 7204VXR
Rack Mountable	Yes, up to 16 per rack	Same as 7204VXR
Dimensions (H x W x D)	5.25 x 16.8 x 17 in.	Same as 7204VXR

Selected Part Numbers and Ordering Information¹

Cisco 7204 Chassis

CISCO7204VXR

Cisco 7204VXR, 4-slot chassis, 1 AC Supply w/IP Software

CISCO7206VXR

Cisco 7206VXR, 6-slot chassis, 1 AC Supply w/IP Software

Cisco 7200 Series Processors

NPE-G1=

Cisco 7200 Network Processing Engine NPE-G1 including 256MB default DRAM and 64MB default flash memory.

NPE-400=

7200VXR NPE-400 (128MB default memory), SPARE

NPE-225=

Network Processing Engine 225 (128MB default memory)-spare

Cisco 7200 Series Input/Output Controller

C7200-I/O=

Cisco 7200 Input/Output Controller, Spare

C7200-I/O-2FE/E=

Cisco 7200 Input/Output Controller with Dual 10/100 Ethernet

C7200-I/O-GE+E=

Cisco 7200 Input/Output Controller with GE and Ethernet

Cisco 7200 Processor Memory: NPE-G1

MEM-NPE-G1-256MB=

Two 128MB memory modules (256MB total) for the Cisco 7200 Network Processing Engine NPE-G1

MEM-NPE-G1-512MB=

Two 256MB memory modules (512MB total) for the Cisco 7200 Network Processing Engine NPE-G1

MEM-NPE-G1-1GB=

Two 512MB memory modules (1GB total) for the Cisco 7200 Network Processing Engine NPE-G1

MEM-NPE-G1-FLD64=

64MB Compact Flash Disk for the Cisco 7200 Network Processing Engine NPE-G1

MEM-NPE-G1-FLD128=

128MB Compact Flash Disk for the Cisco 7200 Network Processing Engine NPE-G1

MEM-NPE-G1-FLD256=

256MB Compact Flash Disk for the Cisco 7200 Network Processing Engine NPE-G1

Cisco 7200 Processor Memory: NPE-400

MEM-NPE-400-256MB=

256MB Memory for NPE-400 in 7200 Series

MEM-NPE-400-512MB=

512MB Memory for NPE-400 in 7200 Series

Cisco 7200 Processor Memory: NPE-225

MEM-SD-NPE-128MB=

128MB Memory Upgrade Kit for NPE-300/NPE-225/NPE-175

Cisco 7200 NPE Bundles

CISCO7204VXR/225

7204VXR Bundle with NPE-225 and I/O Controller with 2 FE/E

C7206VXR/400/2FE

7206VXR with NPE-400 and I/O Controller with 2 FE/E Ports

C7206VXR/400/GE

7206VXR with NPE-400 and GE+E I/O controller

7206VXR/NPE-G1

7206VXR with NPE-G1 includes 3GigE/FE/E Ports and IP SW

Cisco 7200 Security Bundles

7206VXR400/VPNK9

7206VXR NPE400, I/O 2FE, VAM, 256MB, IP FW/IDS IPSec IOS

7206VXRG1/VPNK9

7206VXR NPE-G1, 3 FE/GE, 256MB, VAM, IP FW/IDS IPSec IOS

7206VXRG1/2VPNK9

7206VXR NPE-G1, 3 FE/GE, 256MB, VAM2, IP FW/IDS IPSec IOS

7206VXRG1/2+VPNK9

7206VXR, NPE-G1, VAM2+, AC pwr, 512 sys mem, SDM

7206VXR400/2VPNK9

7206VXR NPE400, I/O 2FE, 256MB, VAM2, IP FW/IDS IPSec IOS

7206VXR400/2+VPNK9

7206VXR, NPE-400, VAM2+, AC pwr, 512 sys mem, SDM

Cisco 7200 Voice Bundles

C7206VXR/VOICE/400

7206VXR w/ NPE-400, Voice PA PA-VXC-2TE1+, I/O contrlr w/ 2FE

Cisco 7200 Broadband Bundles

CISCO7206-BB

Cisco 7206 Broadband Bundle NPE-G1 includes 3GigE/FE/E Ports

Cisco 7200 CPE Bundle

7204VXR/CPE

7204VXR w/ NPE-225, 2 FE I/O, choice of specified WAN PA

Cisco 7200 Channel Bundles

CISCO7204VXR-CH

Cisco 7204VXR, 4-slot chassis, 1 AC Supply w/ IP Software

CISCO7206VXR-CH

Cisco 7206VXR, 6-slot chassis, 1 AC Supply w/ IP Software

1. This is only a small subset of all parts available via URL listed under "For More Information." Some parts have restricted access or are not available through distribution channels.

For More Information

See the Cisco 7200 Series Website: <http://www.cisco.com/go/7200>

Cisco 7300 Series

The Cisco 7300 Series Routers are optimized for flexible, high performance IP/MPLS services at the network edge, where service providers and enterprises link together.



The Cisco 7304 Series Router is ideally applied as a high-end CPE or as an Internet Gateway router. Architected for network High Availability and multi-protocol support, the 7304 supports the broad set of existing Cisco 7000 Series Port Adapters with the Cisco 7304 Port Adapter Carrier Card. The Cisco 7304 also supports the new Shared Port Adapters with the Cisco 7304 Multiservice Carrier Card (MSC).

The Cisco 7301 Series Router is a compact single rack unit router coupled with a broad set of interfaces and Cisco IOS software features. It packs high performance in a space and power efficient form factor that includes a single 7000 Series port adapter slot, 3 on-board Gigabit Ethernet (copper or optical)/Fast Ethernet ports and a new high-speed bus technologies.

When to Sell

Sell This Product

Cisco 7301

When a Customer Needs These Features

- Compact, power efficient 1RU form factor
- Three times the performance increase over the Cisco 7401
- Single 7000 Series Port Adapter Slot

Cisco 7304

- Highly modular price and performance optimized platform, rich in IP services
- High performance connectivity—DS-1 through OC48/STM16 with 3.5 Mpps performance
- Built-in Gigabit Ethernet connectivity
- Support for Shared Port Adapters
- Multiprotocol routing: IP, IPX, AppleTalk, DLSw
- Compact size, high availability and optimal cooling

Key Features

- Cisco 7301—With nearly 1 Mpps processing performance, the fastest Cisco 1RU general-purpose processor; 3 fixed 10/100/1000-Mbps ports (RJ-45 or SFP optics) directly on the processor; Full Cisco IOS feature support; Pluggable Gigabit Ethernet optics (SFPs); Up to 1GB of available DRAM; Up to 256MB of removable compact flash memory; Front-back airflow and single sided management
- Cisco 7304—Compact modular form factor with four RU with four port adapter slots per chassis; Comes with a choice of 2 route processors: NSE-100 and NPE-G100. NSE-100 offers PXF-based; Hardware-accelerated services such as Cisco Express Forwarding (CEF), NetFlow v8, and Turbo ACL; Offers up to 3.5 Mpps performance for PXF-accelerated services with the NSE-100 Network Services Forwarding Engine; Two Gigabit Ethernet ports per NSE-100; NPE-G100 offers up to 1Mpps performance; System redundancy: optional dual processors and dual AC or DC power supplies increases network availability

Competitive Products

- Cisco 7301—Redback: SMS-500, SMS-1800
- Cisco 7304—Juniper: M5, M10, M7i, M10i, Huawei N20-2/4/8
- Juniper: ERX700, ERX1400

Specifications

Feature	Cisco 7301	Cisco 7304
Fixed Ports	Three Gigabit Ethernet ports	NSE-100: 2 Gigabit Ethernet Ports NPE-G100: 3 Gigabit Ethernet Ports
Expansion Slots	1	4
WAN Interface Range	DS-1 to OC-3	DS-1 to OC-48
Processor	RM 7000 MIPS Processor + PXF Processor	RM 7000 MIPS Processor + PXF Processor
Forwarding Rate	Up to 1 Mpps	NSE-100: Up to 3.5 Mpps NPE-G100: Up to 1 Mpps
Backplane Capacity	1.2 Gbps	16 Gbps
Flash PCMCIA Memory	64 MB (expandable to 128 MB)	NSE-100: 128 MB NPE-G100: 256 MB
System DRAM Memory	128 MB (expandable to 512 MB)	NSE-100: 512 MB NPE-G100: 1024 MB
Min Cisco IOS Release	12.2(11)YZ	12.1(9)EX
Internal Power Supply	AC or DC	Same as 7301
RPS Support	Yes, for AC or DC	Same as 7301
Chassis Height	1 RU	4 RU
Rack Mountable	Yes, up to 40 per rack	Yes, up to 11 per rack
Dimensions (H x W x D)	1.73 x 17.3 x 13.87 in.	7 x 17.2 x 20.5 in.

Selected Part Numbers and Ordering Information¹

Cisco 7300 System

PWR-7301/2-AC	Cisco 7301 Dual AC Power Supply Option
PWR-7301/2-DC48	Cisco 7301 Dual DC48 Power Supply Option
CISCO7301	Cisco 7301 chassis, 256MB memory, A/C power, 64MB Flash
CISCO7304=	Cisco 7300, 4-slot chassis, NSE100, Power, IP Software
CISCO7304-CH	Cisco7304 channel bundle
7300-NSE-100=	Cisco 7304 Network Services Engine 100
7300-NPE-G100=	Cisco 7304 NPE-G100 w/1GB SDRAM, 256MB Flash, 3 GE/FE/E Ports
7300-NSE-100/2	Redundant Cisco 7304 NSE-100 w/Redundancy Feature License
7304-NPE-G100/2	Redundant 7304 NPE-G100 w/1GB SDRAM, 256MB Flash, 3 GE/FE/E Ports
7300-PWR-DC=	Cisco 7304 DC Power Supply Spare
7300-PWR-AC=	Cisco 7304 AC Power Supply Spare
7300-PWR/2-DC	Cisco 7304 Redundant DC Power Supply Option
7300-PWR/2-AC	Cisco 7304 Redundant AC Power Supply Option

Cisco 7300 Memory Options

MEM-7301-1GB=	1GB memory upgrade for 7301
MEM-7301-512MB=	512MB memory upgrade for 7301
MEM-7301-256MB=	256MB memory upgrade for Cisco 7301
7300-MEM-128=	128MB default SDRAM for 7304 NSE-100, spare
7300-MEM-256=	256MB SDRAM for 7304 NSE-100, spare
7300-MEM-512=	512MB SDRAM for 7304 NSE-100, spare
7300-I/O-CFM-64M=	Cisco 7304 Compact Flash Memory, 64 MB
7300-I/O-CFM-128M=	Cisco 7304 Compact Flash Memory, 128 MB

Cisco 7300 Series Compact Flash Disk Options

MEM-7301-FLD64=	Compact Disk Flash for 7301, 64MB option
MEM-7301-FLD128=	Compact Disk Flash for 7301, 128MB option
MEM-7301-FLD256	Compact Disk Flash for 7301, 256MB Option

Cisco 7300 Line Cards

7300-10C12POS-SMI=	1-port OC12 POS line card for Cisco 7304 w/ Single-mode IR
7300-10C48POS-SMI=	1-port OC48 POS line card for Cisco 7304 w/ Single-mode IR
7300-10C48POS-SMS=	1-port OC48 POS line card for Cisco 7304 w/ Single-mode SR
7300-20C12POS-SMI=	2-port OC12 POS line card for Cisco 7304 w/ Single-mode IR
7300-20C3ATM-MM=	2-port OC3 ATM line card for Cisco 7304 w/ Multi-mode
7300-20C3ATM-SMI=	2-port OC3 ATM line card for Cisco 7304 w/ Single-mode IR
7300-20C3POS-MM=	2-port OC3 POS line card for Cisco 7304 w/ Multi-mode
7300-20C3POS-SMI=	2-port OC3 POS line card for Cisco 7304 w/ Single-mode IR
7300-40C3POS-SMI=	4-port OC3 POS line card for Cisco 7304 w/ Single-mode IR
7300-6T3=	6-port T3 line card for Cisco 7304 w/ DSU

Cisco 7300 Carrier Cards
7300-CC-PA=

7304 Carrier Card for 7200 Series Port Adapters

1. This is only a small subset of all parts available via URL listed under “For More Information.” Some parts have restricted access or are not available through distribution channels.

For More Information

See the Cisco 7300 Series Website: <http://www.cisco.com/go/7300>

Cisco 7600 Series



The Cisco 7600 Series combines optical WAN/MAN networking and high-volume Ethernet aggregation with a focus on the delivery of high-touch services for the IP and MPLS edge. It combines Layer 2 and Layer 3 networking capabilities with a high-bandwidth, high-performance architecture including hardware-based forwarding of MPLS, IPv4, & IPv6. Cisco 7600 series form factors include the Cisco 7604, 7606, 7609, and 7613. Each router can deliver DS0 to OC-48 WAN and nx10-Mbps Ethernet to nx10-Gigabit Ethernet connectivity into service provider edge, metropolitan-area and enterprise networks for a variety of triple-play and aggregation solutions.

When to Sell

Sell This Product

- Cisco 7604**
- Cisco 7606**
- Cisco 7609**
- Cisco 7613**

When a Customer Needs These Features

- 4 slot (horizontal) chassis; 320 Gbps backplane bandwidth¹; 30 Mpps forwarding rate¹; NEBs Compliant
- 6 slot (horizontal) chassis; 480 Gbps backplane bandwidth¹; 30 Mpps forwarding rate¹; NEBs Compliant
- 9 slot (vertical) chassis; 720 Gbps backplane bandwidth¹; 30 Mpps forwarding rate¹; NEBs Compliant
- 13 slot (horizontal) chassis; 720 Gbps backplane bandwidth¹; 30 Mpps forwarding rate¹; NEBs Compliant

1. Bandwidth & forwarding rate numbers assume Sup720 Engine

Key Features

- Up to 30 Mpps forwarding processor with hardware accelarated IPv4, IPv6, & MPLS
- Hardware accelerated IP services on each Optical Services Module (OSM), delivering up to 6 Mpps per slot
- Modular and scalable from 32 Gbps to 720 Gbps switch fabric
- One of the widest, most complete ranges of WAN interfaces in the industry, with DS0 to OC-48 connectivity
- Leveraging the FlexWAN Module, 7x00 port adapters are shared with the Cisco 7200, 7300, 7400, and 7500 which simplifies sparing and protects customer investment in interfaces
- Support for the Cisco SPA/SIP portfolio
- Compatible with Catalyst 6500 LAN interfaces, offering nx10 Mbps Ethernet to 10 Gbps

Competitive Products

- Alcatel: 7450, 7750
- Juniper: M10i, M20, M40e, M320
- Juniper: ERX700, ERX1400
- Extreme: Black Diamond 6808

Specifications

Feature	Cisco 7604	Cisco 7606	Cisco 7609	Cisco 7613
Fixed Ports	SFP & 10/100/1000 (Sup720)	Same as Cisco 7604	Same as Cisco 7604	Same as Cisco 7604
Expansion Slots	4 (horizontal)	6 (horizontal)	9 (vertical)	13 (horizontal)
WAN Interface Range	DS0 to OC-48	Same as Cisco 7604	Same as Cisco 7604	Same as Cisco 7604

Feature	Cisco 7604	Cisco 7606	Cisco 7609	Cisco 7613
Processor	Supervisor720-3B Supervisor720-3BXL Supervisor 32	Same as Cisco 7604	Same as Cisco 7604	Same as Cisco 7604
Forwarding Rate	Up to 30 Mpps	Same as Cisco 7604	Same as Cisco 7604	Same as Cisco 7604
Backplane Capacity	320 Gbps	480 Gbps	720 Gbps	720 Gbps
Flash PCMCIA Memory	up to 512MB	Same as Cisco 7603	Same as Cisco 7603	Same as Cisco 7603
System DRAM Memory	512MB on Sup720-3B 1G on Sup720-3BXL	Same as Cisco 7603	Same as Cisco 7603	Same as Cisco 7603
Internal Power Supply	AC or DC	Same as Cisco 7603	Same as Cisco 7603	Same as Cisco 7603
RPS Support	Yes	Same as Cisco 7603	Same as Cisco 7603	Same as Cisco 7603
Chassis Height	5 RU	7 RU	20 RU	18 RU
Rack Mountable	Yes, up to 10 per rack	Yes, up to 6 per rack	Yes, up to 2 per rack	Yes, up to 2 per rack
Dimensions (H x W x D)	7 x 17.37 x 21.75 in.	12.25 x 17.37 x 21.75 in.	36.75 x 17.2 x 20.7 in.	33.3 x 17.2 x 18.1 in.

Selected Part Numbers and Ordering Information¹

Cisco 7613 Systems

CISCO7613	7613 Chassis Bundles
CISCO7613=	Spare CISCO7613 Chassis, equipped with High-speed FAN2
7613-S323B-8G-P	Cisco 7613 Chassis, 13-slot, SUP32-8GE-3B, PS
7613-S323B-8G-R	Cisco 7613 Chassis, 13-slot, Redundant SUP32-8GE-3B and PS
7613-S323B-10G-P	Cisco 7613 Chassis, 13-slot, SUP32-2X10GE-3B, PS
7613-S323B-10G-R	Cisco 7613 Chassis, 13-slot, Redundant SUP32-2X10GE-3B and PS
7613-SUP720XL-PS	Cisco 7613 13-slot, SUP720-3BXL and PS
7613-2SUP720XL-2PS	Cisco 7613 13-slot, Redundant System, 2 SUP720-3BXL and 2 PS
7613-SUP7203B-PS	Cisco 7613 Chassis, 13-slot, SUP7203B, Power Supply
7613-2SUP7203B-2PS	Cisco 7613 Chassis, 13-slot, 2 SUP7203B, 2 Power Supply

Cisco 7609 Systems

CISCO7609	7609 Chassis Bundles
CISCO7609=	Cisco 7609 Chassis Spare
7609-S323B-8G-P	Cisco 7609 Chassis, 9-slot, SUP32-8GE-3B, PS
7609-S323B-8G-R	Cisco 7609 Chassis, 9-slot, Redundant SUP32-8GE-3B and PS
7609-S323B-10G-P	Cisco 7609 Chassis, 9-slot, SUP32-2X10GE-3BB, PS
7609-S323B-10G-R	Cisco 7609 Chassis, 9-slot, Redundant SUP32-2X10GE-3B and PS
7609-SUP720XL-PS	Cisco 7609 9-slot, SUP720-3BXL and PS
7609-2SUP720XL-2PS	Cisco 7609 9-slot, Redundant System, 2 SUP720-3BXL and 2 PS
7609-SUP7203B-PS	Cisco 7609 Chassis, 9-slot, SUP7203B, Power Supply
7609-2SUP7203B-2PS	Cisco 7609 Chassis, 9-slot, 2 SUP7203B, 2 Power Supply

Cisco 7606 Systems

CISCO7606	Cisco 7606 Chassis Bundle
7606-S323B-8G-P	Cisco 7606 Chassis, 6-slot, SUP32-8GE-3B, PS
7606-S323B-8G-R	Cisco 7606 Chassis, 6-slot, Redundant SUP32-8GE-3B and PS
7606-S323B-10G-P	Cisco 7606 Chassis, 6-slot, SUP32-2X10GE-3B, PS
7606-S323B-10G-R	Cisco 7606 Chassis, 6-slot, Redundant SUP32-2X10GE-3B and PS
7606-SUP720XL-PS	Cisco 7606 6-slot, SUP720-3BXL and PS
7606-2SUP720XL-2PS	Cisco 7606 6-slot, Redundant System, 2 SUP720-3BXL and 2 PS
7606-SUP7203B-PS	Cisco 7606 Chassis, 6-slot, SUP7203B, Power Supply
7606-2SUP7203B-2PS	Cisco 7606 Chassis, 6-slot, 2 SUP7203B, 2 Power Supply

Cisco 7604 Systems

CISCO7604	Cisco 7604 Chassis Bundle
7604-S323B-8G-P	Cisco 7604 Chassis, 4-slot, SUP32-8GE-3B, PS
7604-S323B-8G-R	Cisco 7604 Chassis, 4-slot, Redundant SUP32-8GE-3B and PS
7604-S323B-10G-P	Cisco 7604 Chassis, 4-slot, SUP32-2X10GE-3B, PS
7604-S323B-10G-R	Cisco 7604 Chassis, 4-slot, Redundant SUP32-2X10GE-3B and PS
7604-SUP7203B-PS	Cisco 7604 Chassis, 4-slot, SUP720-3B, PS
7604-2SUP7203B-2PS	Cisco 7604 Chassis, 4-slot, 2 SUP720-3B, 2 PS
7604-SUP720XL-PS	Cisco 7604 chassis, 4-slot, SUP720-3BXL, PS
7604-2SUP720XL-2PS	Cisco 7604 Chassis, 4-slot, 2SUP720-3BXL, 2 PS

Cisco 7600 FlexWAN Modules

WS-X6582-2PA=	Enhanced FlexWAN Module for Cisco 7600 / Catalyst 6000
WS-X6182-2PA=	FlexWAN Module for Cisco 7600 / Catalyst 6000

Cisco 7600 Optical Services Modules (OSMs)

OSM-1CHOC12/T1-SI=	1-port CHOC-12/CHSTM-4 OSM IR, to DS0 and T1/E1, w/4GE
OSM-12CT3/T1=	12-port Channelized DS-3 to DS-1/DS-0
OSM-1CHOC12/T3-SI=	1-port CHOC-12/CHSTM-4 OSM, to T3/E3, SM-IR, with 4 GE
OSM-10C48-POS-SI+=	Enhanced 1-port OC-48/STM-16 SONET/SDH OSM, SM-IR, with 4 GE
OSM-10C48-POS-SL+=	Enhanced 1-port OC-48/STM-16 SONET/SDH OSM, SM-LR, with 4 GE
OSM-10C48-POS-SS+=	Enhanced 1-port OC-48/STM-16 SONET/SDH OSM, SM-SR, with 4 GE
OSM-20C12-ATM-MM+=	Enhanced 2-port OC12/STM4 ATM OSM+, MM, with 4 GE
OSM-20C12-ATM-SI+=	Enhanced 2-port OC12/STM4 ATM OSM+, SI, with 4 GE
OSM-20C12-POS-MM+=	Enhanced 2-port OC-12/STM-4 SONET/SDH OSM, MM, with 4 GE
OSM-20C12-POS-SI+=	Enhanced 2-port OC-12/STM-4 SONET/SDH OSM, SM-IR, with 4 GE
OSM-2+4GE-WAN+=	Enhanced OSM with 4 GE WAN Ports & 2GE LAN Ports
OSM-40C3-POS-SI+=	Enhanced 4-port OC-3/STM-1 SONET/SDH OSM, with 4 GE
OSM-40C12-POS-MM+=	Enhanced 4-port OC-12/STM-4 SONET/SDH OSM, MM, with 4 GE
OSM-40C12-POS-SI+=	Enhanced 4-port OC-12/STM-4 SONET/SDH OSM, SM-IR, with 4 GE
OSM-80C3-POS-SI+=	Enhanced 8-port OC-3/STM-1 SONET/SDH OSM, SM-IR, with 4 GE
OSM-80C3-POS-SL+=	Enhanced 8-port OC-3/STM-1 SONET/SDH OSM, SM-LR, with 4 GE
OSM-20C48/1DPT-SS=	2-port OC-48/STM-16 POS/DPT OSM, SM-SR, with 4 GE
OSM-20C48/1DPT-SI=	2-port OC-48/STM-16 POS/DPT OSM, SM-IR, with 4 GE
OSM-20C48/1DPT-SL=	2-port OC-48/STM-16 POS/DPT OSM, SM-LR, with 4 GE

Cisco 7600/Catalyst 6500 Ethernet Modules

WS-F6K-DFC=	Distributed Forwarding Card
WS-F6700-DFC3BXL	Catalyst 6500 Dist Fwd Card- 3BXL, for WS-X67xx
WS-F6700-DFC3B=	Catalyst 6500 Dist Fwd Card, 256K+ Routes for WS-X67xx
WS-X6348-RJ-45=	Catalyst 6000 48-port 10/100, Upgradable to Voice, RJ-45
WS-X6516-GBIC=	Catalyst 6500 16-port GigE Mod: fabric-enabled (Req. GBICs)
WS-X6524-100FX-MM=	Catalyst 6500 24-port 100FX, MT-RJ, fabric-enabled
WS-X6502-10GE=	Catalyst 6500 10 Gigabit Ethernet Base Module(Req OIM),Spare
WS-X6816-GBIC=	Catalyst 6500 16-port GigE mod, 2 fab I/F w/DF, (Req GBICs)
WS-X6548-RJ-21=	Catalyst 6500 48-port 10/100, RJ-21, fabric-enabled
WS-X6548-RJ-45=	Catalyst 6500 48-port 10/100, RJ-45, x-bar
WS-X6516-GE-TX=	Catalyst 6500 16-port Gig/Copper Module, x-bar
WS-X6748-GE-TX=	Cat6500 48-port 10/100/1000 GE Mod: fabric enabled, RJ-45
WS-X6724-SFP=	Catalyst 6500 24-port GigE Mod: fabric-enabled (Req. SFPs)
WS-X6748-SFP=	Catalyst 6500 48-port CEF720 GigE Module (Req. SFPs)
WS-X6704-10GE=	Cat6500 4-port 10 Gigabit Ethernet Module (req. XENPAKs)

Cisco 7600 Services Modules

WS-SVC-IPSEC-1=	IPSec VPN Security Module
WS-SVC-FWM-1-K9=	Firewall blade
WS-SVC-NAM-1=	Network Analysis Module-1
WS-SVC-NAM-2=	Network Analysis Module-2
WS-X6066-SLB-APC=	Content Switching Module
WS-SVC-SSL-1-K9=	SSL Module
WS-SVC-MWAM-1=	Multi-Processor WAN Application Module

1. This is only a small subset of all parts available via URL listed under "For More Information." Some parts have restricted access or are not available through distribution channels.

For More Information

See the Cisco 7600 Series Website: <http://www.cisco.com/go/7600>

Cisco 10700 Series

The Cisco 10700 series includes the Cisco 10720 Internet Router is a high-performance router and a principle building block in the metro IP network. It enables service providers to offer innovative and differentiated IP services to their customers at optical speeds.

When to Sell

Sell This Product

Cisco 10700 Series

When a Customer Needs These Features

- High-performance IP services as part of their business strategy by extending IP further out into the network
- Simple, scalable, reliable features of DPT technology while maximizing fiber usage
- Any customer already using DPT technology in their network, most likely with DPT cards on the 12000 Internet Router
- Metro Ethernet Services such as L2 and L3 VPN with FE/GE hand off to the Customer and 50ms restoration over dark fiber using DPT
- IEEE 802.17-standard-compliant RPR technology

Key Features

- Support for IP, MPLS and L2TPv3 features at 2MPPS
- L2 VPN—L2TPv3 and EoMPLS; L3 VPN MPLS VPN and MPLS VPN over IP
- Security—ACLs, uRPF, Control Plane Policing and BFD
- SRP or 802.17 RPR with <50 ms restoration time
- Multicast support including PIM SM, PIM DM, MBGP
- QoS—Modular QoS CLI, 8 queues per port
- Ethernet—MDI-MDI-X support, 10/100 speed auto-negotiation, HDX-FDX negotiation and time delay reflectometry (TDR) for 10/100BaseTX
- Hot Standby Routing Protocol (HSRP)/Multiple Hot Standby Routing Protocol (MHSRP)
- Optical receive power monitoring support on OC-48/STM-16 Interface and GE
- Management information bases (MIBs)—SNMP, SRP, SONET, Etherlike, OSPF
- Suitable for other applications—Internet data center applications, intra-POP aggregation, cable multisystem operator (MSO) internetworking, and VoIP aggregation

Specifications

Feature	Cisco 10700 Series
Security Features	Including AAA, RADIUS authentication, TACACS+, and encrypted passwords
Management	Cisco IOS CLI; TACACS+ and RADIUS; Configuration and administration features including Telnet and Cisco Discovery Protocol (CDP); Serial (aux) and console ports for local and remote administration; Remote software download via TFTP and RCP; IP over DCC for remote management of the Cisco ONS 15104 OC-48/STM-16 Optical Regenerator, where applicable
Physical Interfaces	Uplink Modules: 2-port single-mode OC-48c/STM16c DPT (SR 2 km (1.2 miles), IR 15 km (9.3 miles), LR1 40km (24 miles) and LR2 80km (50miles) Interface Modules—The Cisco 10720 Internet Router has two dedicated slots for interface modules—modules are not interchangeable or hot swappable: • Upper slot is dedicated for DPT or POS Uplink module equipped with two physical ports of OC-48c/STM16c that provide an aggregate bandwidth of approximately 5 Gbps. The cards are available in two four versions of optics, short reach (SR) and intermediate reach (IR), Long Reach1 (LR1) and Long Reach2 (LR2) with two small form-factor OC-48 ports with LC connectors. • A third option for the upper slot is the CON-AUX module, which is a depopulated uplink card equipped with Console and Auxiliary ports only; this allows the configuration of the 10720 as an "Ethernet Router" allowing the use of one or more of the Ethernet ports in the lower slot for network connectivity • New Uplink module that supports 2XOC48/STM16 RPR/DPT with pluggable optics. This is Cisco's first IEEE 802.17-compliant RPR module. This module can be optionally configured in SRP mode, thus making it backward compatible with existing DPT deployments • Lower slot is dedicated for 24-port Fast Ethernet module—available in TX (100 m reach), FX-MM (2 km reach) or FX-SM (15 km reach). The TX module is equipped with RJ-45 connectors while the FX-SM and FX-MM modules are equipped with MT-RJ connectors. • Also available is a combination 4 Gigabit Ethernet with Small Form Factor Plug-able (SFP) Optics available in SX 550m, LH 10km, ZH 70km and Copper plus an additional 8 Ports of Fast Ethernet 10/100 TX Copper ports.
Dimensions (H x W x D)	3.5 x 17.25 x 18.25 in. (8.9 x 43.81 x 46.35 cm)

Selected Part Numbers and Ordering Information¹

Cisco 10700 Series

CISCO10720-AC-A	Cisco 10720 Internet Router with dual AC power supply
CISCO10720-DC-A	Cisco 10720 Internet Router with dual DC Power Supply
10720-FE-TX	24-port 10/100 Ethernet Access Module RJ45 connectors
10720-GE-FE-TX-B	4-port 100Mbps SFP GE with 8-ports of 10/100 Ethernet TX-RJ45
SFP-GE-S	GE SFP - Short Reach 550M LC connectors
SFP-GE-L	GE SFP - Intermediate Reach 10KM LC connectors
CWDM-SFP-1470	Longwave 1470 nm laser, single mode - Gray
CWDM-SFP-1490	Longwave 1490 nm laser, single mode - Violet
CWDM-SFP-1510	Longwave 1510 nm laser, single mode - Blue
CWDM-SFP-1530	Longwave 1530 nm laser, single mode - Green
CWDM-SFP-1550	Longwave 1550 nm laser, single mode - Yellow
CWDM-SFP-1570	Longwave 1570 nm laser, single mode - Orange
CWDM-SFP-1590	Longwave 1590 nm laser, single mode - Red
CWDM-SFP-1610	Longwave 1610 nm laser, single mode - Brown
SFP-GE-T	GE SFP - 1000BaseT
10720-LR2-LC-POS	OC-48c/STM-16c SRP Long Reach 2 (80km) Uplink Module-LC connectors
10720-MEM-512=	512MB RP Memory
10720-RPR-SFP	OC-48c/STM-16c RPR/SRP Uplink Module supporting SFPs
SFP-OC48-SR	OC-48c/STM-16c Short Reach (2KM) pluggable SFP
SFP-OC48-IR1	OC-48c/STM-16c Intermediate Reach1 (15KM) pluggable SFP
SFP-OC48-LR2	OC-48c/STM-16c Long Reach2 (80KM) pluggable SFP

1. This is only a small subset of all parts available via URL listed under "For More Information." Some parts have restricted access or are not available through distribution channels.

For More Information

See the Cisco 10720 Internet Router Website: <http://www.cisco.com/go/10700>

Cisco XR 12000 and 12000 Series

The Cisco XR 12000 Series and Cisco 12000 Series routers compose a portfolio of intelligent routing solutions that scale from 2.5G to n x 10 G capacity per slot, enabling carrier-class IP/MPLS networks and accelerating the evolution to IP Next-Generation Networks.



Key Features

- Delivers up to 1.28 Tbps switching capacity with wire-speed feature performance, scalability, and graceful hardware and software upgrade paths
- Offers full forward compatibility for all line cards and portfolio of SPAs and SIPs.
- Scales to the edge, supporting backbone- or edge-optimized line cards in the same chassis
- Maximizes the value of line-rate edge applications with 10G uplinks.
- IP QoS and congestion control implementation that enables real-time services such as VoIP and video. Its distributed architecture and class of service features such as priority based congestion control (WRED) and dedicated low latency queuing (MDRR), along with virtual output queuing (VoQ), eliminate head of line blocking (HOL) and maintain packet sequence integrity under all conditions
- Non-service impacting online insertion and removal (OIR) of components (including switch fabric cards) and front accessibility reduce downtime and simplify maintenance
- Offers Cisco NSF and Cisco Stateful Switchover (SSO) eliminate single points of failure, help maintain system performance, and prevent service interruption; packet forwarding remains uninterrupted before, during and after a route processor switchover.

Competitive Products

• Juniper: T640, T320, M320

• Avici: Stackable Switch Router (SSR)

Specifications

Feature	Cisco XR 12000/ 12000	Cisco XR 12000/ 12000 Series 10-Slot Chassis	Cisco XR 12000/ 12000 Series 6-Slot Chassis	Cisco XR 12000/ 12000 Series 4-Slot Chassis
Slot Capacity	16 slots	10 slots	6 slots	4 slots
Aggregate Switching Capacity	12016: 80 Gbps; 12416: 320 Gbps; 12816: 1280 Gbps	12010: 50 Gbps; 12410: 200 Gbps; 12810: 800 Gbps	12006: 30 Gbps; 12406: 120 Gbps	12404: 80 Gbps
Full-Duplex Throughput Per	12016: 2.5 Gbps/slot 12416: 10 Gbps/slot 12816: 40 Gbps/slot	12010: 2.5 Gbps/slot 12410: 10 Gbps/slot 12810: 40 Gbps/slot	12006: 2.5 Gbps/slot 12406: 10 Gbps/slot	12404: 10 Gbps/slot
Dimensions (H x W x D)	71.5 x 17.25 x 22.0 in. (181.6 x 184.2 x 55.9 cm) 72.5 x 18.75 x 24.0 in. ² (43.8 x 47.6 x 61.0 cm) ³	37.5 x 19 x 22.0 in. (95.25 x 48.26 x 55.9 cm); 24.0 in. (61.0 cm) ¹	18.5 in. (47.0 cm) Chassis width 17.3 in. (43.9 cm) 18.9 in. (48.0 cm) ² Chassis depth 28.0 in. (71.1 cm)	8.75 in. (22.23 cm) Chassis width 17.38 in. (44.15 cm) 18.9 in. (48.01 cm) ² Chassis depth 27.5 in. (69.85 cm)
Weight	140 lb. (64 kg) ⁴ ; 390 lb. (177 kg) ⁵	125 lb. (57 kg) ⁴ ; 275 lb. (125 kg) ⁵	140 lb. (64 kg) ⁴ ; 205 lb. (94 kg) ⁵	73 lb. (33.18 kg) ⁴ ; 103 lb. (46.82 kg) ⁵
Chassis Per Rack	One	Two	Four	Eight
Software Components (Per Base System)	Cisco IOS XR or Cisco IOS Software Operating System; Cisco Express Forwarding for distributed packet forwarding			
Compatibility	12800: Line cards that support 2.5-, 10-, or 20-Gbps capability; 12400: Line cards that support 2.5- or 10-Gbps capability; 12000: Line cards that support 2.5-Gbps capability			
Protocols	IPv4, MPLS, BGPv4, IS-IS, OSPFv2, RIPv2, IGMP, DVMRP, and PIM DX/SX			
Connectivity	Packet over SONET/SDH (POS), Ethernet, ATM, copper (DS-3/E3), Channelized (CT3, ChOC-3/CHSTM1, ChOC-12/CHSTM4, ChOC-48/CHSTM16); see Cisco IOS XR Software release notes for specific connectivity support on the Cisco XR 12000 Series			

1. With AC input power shelf or DC input power shelf, front covers installed
2. Including chassis rack-mount flanges
3. Including cable-management system and front cover
4. Chassis only, including power shelf for 16-slot chassis
5. Chassis fully configured, using all card slots, AC or DC power shelf for 16-slot chassis, and AC or DC input power supplies

Selected Part Numbers and Ordering Information¹

Cisco XR 12000 16-Slot Systems

XR-12416/320-AC	Cisco XR 12000 16-slot Chassis with 3 AC power supplies, 320-Gbps fabric (2 CSC and 3 SFC cards), 2
XR-12416/320-AC4	Cisco XR 12000 16-slot Chassis with 4 AC power supplies, 320-Gbps fabric (2 CSC and 3 SFC cards), 2
XR-12416/320-DC	Cisco XR 12000 16-slot Chassis with 4 DC power supplies, 320-Gbps fabric (2 CSC and 3 SFC cards), 2

Cisco 12000 16-Slot Systems

GSR16/80-AC-8R	Cisco 12000 16-slot Chassis with 3 AC power supplies, 80-Gbps fabric (2 CSC and 3 SFC cards), 2 blowers, 2
GSR16/320-AC	Cisco 12000 16-slot Chassis with 3 AC power supplies, 320-Gbps fabric (2 CSC and 3 SFC cards), 2 blowers, 2
12816/1280-AC3	Cisco 12000 16-slot Chassis with 3 AC power supplies, 1280-Gbps fabric (2 CSC and 3 SFC cards), 2 blowers, 2 alarms, and 1 PRP-1
GSR16/80-AC4-8R	Cisco 12000 16-slot Chassis with 4 AC power supplies, 80-Gbps fabric (2 CSC and 3 SFC cards), 2 blowers, 2
GSR16/320-AC4	Cisco 12000 16-slot Chassis with 4 AC power supplies, 320-Gbps fabric (2 CSC and 3 SFC cards), 2 blowers, 2
12816/1280-AC4	Cisco 12000 16-slot Chassis with 4 AC power supplies, 1280-Gbps fabric (2 CSC and 3 SFC cards), 2 blowers, 2 alarms, and 1 PRP-1
GSR16/80-DC-8R	Cisco 12000 16-slot Chassis with 4 DC power supplies, 80-Gbps fabric (2 CSC and 3 SFC cards), 2 blowers, 2
GSR16/320-DC	Cisco 12000 16-slot Chassis with 4 DC power supplies, 320-Gbps fabric (2 CSC and 3 SFC cards), 2 blowers, 2
12816/1280-DC	Cisco 12000 16-slot Chassis with 4 DC power supplies, 1280-Gbps fabric (2 CSC and 3 SFC cards), 2 blowers, 2 alarms, and 1 PRP-1

Cisco XR 12000 10-Slot Systems

XR-12410/200-AC	Cisco XR 12000 10-slot Chassis with 2 AC power supplies, 200-Gbps fabric (2 CSC and 5 SFC cards), 1
XR-12410/200-DC	Cisco XR 12000 10-slot Chassis with 2 DC power supplies, 200-Gbps fabric (2 CSC and 5 SFC cards), 1

Cisco 12000 10-Slot Systems

12010-AC	Cisco 12000 10-slot Chassis with 2 AC power supplies, 50-Gbps fabric (2 CSC and 5 SFC cards), 1 blower, 2
12010-DC	Cisco 12000 10-slot Chassis with 2 DC power supplies, 50-Gbps fabric (2 CSC and 5 SFC cards), 1 blower, 2
GSR10/200-AC	Cisco 12000 10-slot Chassis with 2 AC power supplies, 200-Gbps fabric (2 CSC and 5 SFC cards), 1 blower, 2
GSR10/200-DC	Cisco 12000 10-slot Chassis with 2 DC power supplies, 200-Gbps fabric (2 CSC and 5 SFC cards), 1 blower, 2
12810/800-AC	Cisco 12000 10-slot Chassis with 2 AC power supplies, 800-Gbps fabric (2 CSC and 5 SFC cards), 1 blower, 2
12810/800-DC	Cisco 12000 10-slot Chassis with 2 DC power supplies, 800-Gbps fabric (2 CSC and 5 SFC cards), 1 blower, 2

Cisco XR 12000 6-Slot Systems

XR-12406/120-AC	Cisco XR 12000 6-slot Chassis with 1 AC power supply, 120-Gbps fabric (1 CSC and 3 SFC cards), 1 blower, 2
XR-12406/120-DC	Cisco XR 12000 6-slot Chassis with 1 DC power supply, 120-Gbps fabric (1 CSC and 3 SFC cards), 1 blower, 2

Cisco 12000 6-Slot Systems

12006-AC	Cisco 12000 6-slot Chassis with 2 AC power supplies, 30-Gbps fabric (2 CSC and 3 SFC cards), 1 blower, 2
12006-DC	Cisco 12000 6-slot Chassis with 2 DC power supplies, 30-Gbps fabric (2 CSC and 3 SFC cards), 1 blower, 2
GSR6/120-AC	Cisco 12000 6-slot Chassis with 1 AC power supply, 120-Gbps fabric (1 CSC and 3 SFC cards), 1 blower, 2

GSR6/120-DC	Cisco 12000 6-slot Chassis with 1 DC power supply, 120-Gbps fabric (1 CSC and 3 SFC cards), 1 blower, 2
Cisco XR 12000 4-Slot Systems	
XR-12404/80-AC	Cisco XR 12000 4-slot Chassis with 2 AC power supply, 80-Gbps fabric (consolidated switch fabric, clock scheduler, and alarm card), 1 blower, and 1 PRP-2
XR-12404/80-DC	Cisco XR 12000 4-slot Chassis with 2 DC power supply, 80-Gbps fabric (consolidated switch fabric, clock scheduler, and alarm card), 1 blower, and 1 PRP-2
Cisco 12000 4-Slot Systems	
GSR4/80-AC	Cisco 12000 4-slot Chassis with 2 AC power supply, 80-Gbps fabric (consolidated switch fabric, clock scheduler, and alarm card), 1 blower, and 1 PRP-1
GSR4/80-DC	Cisco 12000 4-slot Chassis with 2 DC power supply, 80-Gbps fabric (consolidated switch fabric, clock scheduler, and alarm card), 1 blower, and 1 PRP-1
Cisco 12000 Series Line Cards	
12DS3-SMB	DS3 line card, 12 ports
12E3-SMB	E3 line card, 12 ports
16OC3X/POS-I-LC-B	16 PORT OC3 WITH EXTENDED FEATURES RELEASE B
16OC3X/POS-M-MJ-B	GSR 16-port OC3/POS MM Eng3 release B
1X10GE-ER-SC	Cisco 12000 1-Port 10GE Card, 1550nm serial, 40km, SC
1X10GE-LR-SC	Cisco 12000 1-Port 10GE Card, 1310nm serial, 10km, SC
2CHOC3/STM1-IR-SC	Channelized OC3/STM1 -> DS1/E1, 2 ports Intermediate Reach
20C192/POS-IR-SC	Cisco Two-port OC192c/STM64c POS Line Card 1550nm IR, SC
20C192/POS-SR-SC	Cisco Two-port OC192c/STM64c POS Line Card 1310 nm SR, SC
20C192/POS-VSR	Cisco Two-port OC192c/STM64c POS Line Card 850nm VSR, MTP
4CHOC12/DS3-I-SCB	4 PORT CHANNELIZED OC12 B
4GE-SFP-LC	4 port-GE line card for Cisco 12000
40C12X/ATM-IR-SC	4-port OC12/STM4 ATM SM-IR ISE LC with SC connector
40C12X/ATM-MM-SC	4-port OC12/STM4 ATM MM ISE LC with SC connector
40C12X/POS-I-SC-B	4 PORT OC12 POS B
40C12X/POS-M-SC-B	4-port OC12/POS Eng3 Multi-mode
40C12X/SRP-IR-LC	4 port OC-12c/STM-4c SRP ISE Line Card, 1310nm IR, LC
40C12X/SRP-XR-LC	4 port OC-12c/STM-4c SRP ISE Line Card, 1550nm XR, LC
40C3X/ATM-IR-SC	4-port OC3/STM1 ATM SM-IR ISE LC with SC connector
40C3X/ATM-MM-SC	4-port OC3/STM1 ATM MM ISE LC with SC connector
40C3X/POS-IR-LC-B	GSR 4-port OC3/POS IR Eng3 release B
40C3X/POS-LR-LC-B	GSR 4-port OC3/POS LR Eng3 release B
40C3X/POS-MM-MJ-B	GSR 4-port OC3/POS MM Eng3 release B
40C48E/POS-LR-SC	Edge 4 Port OC-48c/STM-16c SONET/SDH LR with SC
40C48E/POS-SR-SC	Edge 4 Port OC-48c/STM-16c SONET/SDH SR with SC
40C48/SRP-SFP	4 Port OC48c/STM16c SRP Linecard, SFP Optics
6CT3-SMB	Channelized T3 for the GSR
6DS3-SMB-B	6DS3-SMB-B w/ ECC
6E3-SMB	E3 line card, 6 ports
8FE-FX-SC-B	GSR 8-port 100baseFX, SC connector, version B
8FE-TX-RJ45-B	8-port 100baseTX, RJ45 connector type, version B
8OC3X/POS-IR-LC-B	GSR 8-port OC3/POS IR Eng3 release B
8OC3X/POS-MM-MJ-B	GSR 8-port OC3/POS MM Eng3 release B
CHOC12/DS1-IR-SC	GSR12000 Channelized OC12/STM4 to DS1 (Engine3 based)
CHOC48/DS3-SR-SC	1 port Channelized OC-48 to DS3
EPA-3GE-SX/LH-LC	Cisco 12000 3-Port GE Port Adapter for EPA-GE/FE-BBRD
EPA-GE/FE-BBRD	Cisco 12000 Modular GE Baseboard w/ 1GE and 3 EPA Slots
LC-10C12/ATM-MM	1 port OC12/STM4 ATM Line Card, Multi-Mode
LC-10C12/ATM-SM	1 port OC12/STM4 ATM Line Card, Single-Mode
LC-10C12/POS-MM	1 port OC12/STM4 Packet Over SONET/SDH Line Card, Multi-Mode
LC-10C12/POS-SM	1port OC12/STM4 Packet Over SONET/SDH Line Card, Single-Mode
OC192E/POS-IR-SC	1 Port OC192c/STM64c POS Edge Card, 1550nm IR, SC
OC192E/POS-LR-SC	OC192/STM64 Packet over Sonet Long Reach with SC
OC192E/POS-SR-SC	1 Port OC192c/STM64c POS Edge Card, 1310nm SR, SC
OC192E/POS-VSR	1 Port OC192c/STM64c POS Edge Card, VSR Optics
OC192/SRP-IR-PR	Two OC192/SRP-IR-SC Linecards With One CBL-SRP-OC192 Cable
OC192/SRP-IR-SC	1 Port OC192c/STM64c SRP Linecard, 1550nm IR, SC
OC192/SRP-SR-PR	Two OC192/SRP-SR-SC Linecards With One CBL-SRP-OC192 Cable
OC192/SRP-SR-SC	1 Port OC192c/STM64c SRP Linecard, 1310nm SR, SC
OC192/SRP-VSR	1 Port OC192c/STM64c SRP Linecard, 850nm VSR, MTP
OC192/SRP-VSR-PR	Two OC192/SRP-VSR Linecards With One CBL-SRP-OC192 Cable
OC48/SRP-LR-B-PR	Two OC48/SRP-LR-SC-B Line Cards with MATE Cable
OC48/SRP-LR-SC-B=	OC48 SRP Rev-B Line Card, Single Mode, Long Reach
OC48/SRP-SR-B-PR	Two OC48/SRP-SR-SC-B Line Cards with MATE Cable, GSR
OC48/SRP-SR-SC-B=	OC48 SRP Rev-B Line Card, Single Mode, Short Reach, GSR
OC48X/POS-LR-SC	CONCATENATED OC48 WITH EXTENDED FEATURES LONG REACH
OC48X/POS-SR-SC	1 port OC48 POS Extended features
12000-SIP-400	Cisco 12000 Series SPA Interface Processor-400
12000-SIP-400=	Cisco 12000 Series SPA Interface Processor-400, spare

1. Some parts have restricted access or are not available through distribution channels.

For More Information

See the Cisco XR 12000 and 12000 Series Website: <http://www.cisco.com/go/12000>



LAN Switching

LAN Switching Products at a Glance

Product	Features	Page
Fixed Configuration Products		
Catalyst Express 500 Series	• Standalone fixed-configuration Layer 2 switches • Fast Ethernet and Gigabit Ethernet connectivity • Up to 24 10/100 ports with optional PoE or 12 10/100/1000 ports	2-3
Catalyst 2940 Series	• Fixed-configuration managed Ethernet switches • 8 10/100 ports + 1 10/100/1000BASE-T port (WS-C2940-8TT-S) • 8 10/100 ports + 1 100BASE-FX or SFP port (WS-C2940-8TF-S) • Small form factor (10.6 in. long and 6.4 in. deep) and all metal shell • Silent operation with no fans • Flexible mounting capabilities • Simplified network management through Cisco Network Assistant (CNA)	2-4
Catalyst 2960 Series	• Standalone fixed-configuration switches • Layer 2 switching with intelligent Layer 2-4 services • Fast Ethernet and Gigabit Ethernet connectivity • Up to 48 10/100 ports or 10/100/1000 ports • AC power supply failure protection with external power supply	2-6
Catalyst 3560 Series	• Fast-Ethernet and Gigabit-Ethernet configurations • Extensive network security capability • Granular network control and bandwidth optimization • Network scalability • Lower Total Cost of Ownership (TCO)	2-7
Catalyst 3750 Series	• Provides the highest levels of resilient stacking via Cisco StackWise™ technology, intelligent network services, and Gigabit Ethernet optimization • Provides configurations that can be interconnected and stackable up to 9 switches	2-10
Catalyst 4948 Series	• High performance fixed Gigabit Ethernet switch with intelligent enterprise Cisco IOS services	2-14
Modular Switching Products		
Catalyst 4500 Series	• Modular switch with integrated intelligent L2-L4 services for converged networks in enterprise LAN Access, Layer2/Layer3 distribution, SMB and branch office. • Scalable, evolutionary modular architecture for investment protection • Up to 384 ports of Fast Ethernet or Gigabit Ethernet over Fiber or Copper with wire-speed 10 Gigabit Ethernet Uplinks • High performance, Layer 2/3/4 switching up to 136 Gbps and 102 Mpps • Advanced network control with predictable performance, granular QoS, advanced security and web-based Network Management	2-15
Catalyst 6500 Series	• High-performance, multilayer switch with integrated intelligent services for enterprise campus backbones, wiring closets, server aggregation, or internet data centers • Up to 1152 10/100 ports and 57710/100/1000 ports, up to 410 high performance Gigabit Ethernet ports, up to 32 10GE ports, multigigabit L4-7 and Security Services such as Firewall, Intrusion Detection and Load Balance • Layer 4-7 services • Up to 720 Gbps of switching capacity and Packet throughput scalable to 425 Mpps IPv4 (200 Mpps IPv6)	2-19
Product Ordering Website	To place an order, visit the Cisco Ordering Website: http://www.cisco.com/en/US/ordering/index.shtml	

Cisco LAN and MAN Products Port Matrix

	Fixed Switches							Modular Switches	
	Catalyst Express 500	Catalyst 2900	Catalyst 2940	Catalyst 2960	Catalyst 3560	Catalyst 3750	Catalyst 4948	Catalyst 4500	Catalyst 6500
Fixed Ports Only	X								
Fixed and Modular Ports		X	X	X	X	X		X	
Modular Ports Only									X
10BASE-T Switched	X	X	X	X	X	X	X	X	X
10BASE-FL Switched									X
100BASE-T Switched	X	X	X	X	X	X	X	X	X
100BASE-FX Switched		X	X	X	X	X		X	X
10/100 Autosensing Switched	X	X	X	X	X	X	X	X	X
10/100/1000BaseT		X	X	X	X	X	X	X	X
Gigabit Ethernet	X	X	X	X	X	X	X	X	X
10 Gigabit Ethernet						X	X	X	X
Integrated PoE					X	X		X	X
Integrated Service Modules: Firewall, IDS, Network Analysis (NAM), Wireless (WiSM), Voice Gateway (CMM), Content Switching/SSL, Anomaly Detection, IPSec VPN, SSL VPN, AON)									X
WAN Modules: SIP/SPA, OSM, Enhanced FlexWAN									X

Cisco Catalyst Express 500 Series

Cisco Catalyst Express 500 Series switches deliver best-in-class networking that is designed to meet the needs of growing businesses with up to 250 employees. This family of Layer 2-managed Fast Ethernet and Gigabit Ethernet switches offers non-blocking, wire-speed performance and provides a secure network foundation optimized for data, wireless, and IP Communications. The Cisco Catalyst Express 500 also offers options for Power over Ethernet (PoE) to help reduce the cost and complexity of IP Communications and enable new uses for the Ethernet network.



When to Sell

Sell This Product

Catalyst Express 500 Series

When a Customer Needs These Features

- Standalone fixed-configuration Layer 2 switches
- Fast Ethernet and Gigabit Ethernet connectivity
- Up to 24 10/100 ports with optional PoE or 12 10/100/1000 ports

Key Features

- Standards-based, high-performance LAN switching—Offers wire-speed switching with standard features such as 802.1d Spanning Tree, 802.1x authentication, and 802.3ad link aggregation
- Power over Ethernet—supports the IEEE 802.3af PoE standard, facilitates new network services by delivering power to IP phones, wireless access points, video surveillance cameras, and other new devices
- Smartports Advisor—Automatically detects connected Cisco devices and recommends preset configurations for the switch port connected to the device
- Security—three security levels to choose from; allows for quick and easy deployment of integrated security features protecting the network from unauthorized access
- Cisco Network Assistant—no-cost, GUI-based management tool for configuration, management, and troubleshooting

Specifications

Feature	CE500-24TT	CE500-24LC	CE500-24PC	CE500G-12TC
Forwarding bandwidth (Gbps)	8.8	8.8	8.8	24
Packets per second (Mpps)	6.6	6.6	6.6	18
MAC addresses supported	8,000	8,000	8,000	8,000
Onboard memory (DRAM MB)	32	32	32	32
Gigabit Ethernet GBIC/SFP density	0	2	2	4
10/100/1000 density	2	2	2	12
10/100 density	24	24	24	0
Max. watt power consumption	30	45	90	45
PoE: Max. 802.3af Class 3 devices (15.4W)	0	4	24	0
PoE: Max. 802.3af Class 2 devices (7.3W)	0	4	24	0
AC/DC support	AC only	AC only	AC only	AC only
Dimensions(H x W x D)	1.73 x 17.5 x 9.9 in. (4.39 x 44.45 x 25.15 cm.)	1.73 x 17.5 x 9.9 in. (4.39 x 44.45 x 25.15 cm.)	1.73 x 17.5 x 14.4 in. (4.39 x 44.45 x 36.58 cm.)	1.73 x 17.5 x 9.9 in. (4.39 x 44.45 x 25.15 cm.)
Unit weight	8 lbs. (3.7 kgs.)	8 lbs. (3.7 kgs.)	12 lbs. (5.5 kgs.)	8 lbs (3.7 kgs.)

Selected Part Numbers and Ordering Information¹

Catalyst Express 500 Series

WS-CE500-24TT	24 10/100 ports + 2 10/100/1000BASE-T ports
WS-CE500-24LC	20 10/100 ports + 4 10/100 ports with PoE + 2 10/100/1000BASE-T or SFP ports
WS-CE500-24PC	24 10/100 ports with PoE + 2 10/100/1000BASE-T or SFP ports
WS-CE500G-12TC	8 10/100/1000BASE-T ports + 4 10/100/1000BASE-T or SFP ports

SFPs

GLC-GE-100FX=	100FX SFP on GE SFP ports for DSBUS switches
GLC-FE-100FX	100BASE-FX SFP for FE port
GLC-LH-SM=	GE SFP, LC connector LX/LH transceiver
GLC-SX-MM=	GE SFP, LC connector SX transceiver
GLC-FE-100LX	100BASE-LX SFP for FE port
GLC-FE-100BX-U	100BASE-BX10-U SFP
GLC-FE-100BX-D	100BASE-BX10-D SFP

Right Angle Power Cords

CAB-AC-RA=	Power Cord, Right Angle
CAB-AC-RA	Power Cord, 110V, Right Angle
CAB-ACR-RA=	Power Cord, Argentina, Right Angle
CAB-ACA-RA=	Power Cord, Australia, Right Angle
CAB-ACC-RA=	Power Cord, China, Right Angle
CAB-ACE-RA=	Power Cord, Europe, Right Angle
CAB-ACI-RA=	Power Cord, Italy, Right Angle
CAB-JPN-RA=	Power Cord, Japan, Right Angle
CAB-JPN-RA	Power Cord, Japan, Right Angle
CAB-ACS-RA=	Power Cord, Switzerland, Right Angle
CAB-ACU-RA=	Power Cord, United Kingdom, Right Angle

RPS

PWR675-AC-RPS-N1=	675W Redundant power supply with 1 connector cable
CAB-RPS-1614=	1 RPS 675 connector cable 16/14

1. This is only a small subset of all parts available via URL listed under "For More Information." Some parts have restricted access or are not available through distribution channels. Resellers: For latest part number and pricing info, see the *Distribution Product Reference Guide* at: <http://www.cisco.com/dprg> (limited country availability).

For More Information

See the Catalyst Express 500 Website: <http://www.cisco.com/go/catalystexpress500>

Cisco Catalyst 2940 Series

The Cisco Catalyst 2940 series switches are small, standalone, managed switches with eight Fast Ethernet ports and a single integrated Fast Ethernet or Gigabit Ethernet uplink. The switches are designed to be used outside the wiring closet in the end-user workspace, and feature a durable metal shell, no fan for silent operation, easy wall or under-the-desk mounting, a security lock slot to prevent theft, and an available cable guard to secure the Ethernet cables and switch.



When to Sell

Sell This Product

Catalyst 2940 Series

When a Customer Needs These Features

- Low port density and price with high performance 10/100 Mbps connectivity
- Small size with quiet operation
- Fiber or 10/100/1000BaseT uplink
- Flexible mounting capabilities

Key Features

- Network Management—CNA offers centralized management and configuration to simplify deployment and ongoing maintenance by leveraging Cisco Smartports technology; PC-based; optimized for networks with 20 devices or less.

Chapter 2

- Express Setup is a Web browser utility that allows simple switch setup so that novices can even perform a basic configuration
- Wire-speed performance across all ports
- Deployed in small workgroups environments outside of the wiring closet
- QoS and security based on Layer 2 information

Specifications

Feature	Catalyst 2940-8TT	Catalyst 2940-8TF
Fixed Ports	8 port 10/100 autosensing & 1 port 10/100/1000	8 port 10/100 autosensing & 1 port 100BASE-FX or 1000BASE-X SFP
Forwarding Bandwidth	3.6 Gbps	Same as Catalyst 2940-8TT
Forwarding Rate	2.7 Mpps	Same as Catalyst 2940-8TT
Full Duplex Capabilities	All Ports	Same as Catalyst 2940-8TT
VLAN Maximum	124-port-based VLANs	Same as Catalyst 2940-8TT
FEC	Yes	Same as Catalyst 2940-8TT
802.1Q	Yes	Same as Catalyst 2940-8TT
Security	Port Security with MAC aging, Private VLAN Edge, 802.1x, TACACS+, RADIUS	Same as Catalyst 2940-8TT
Multicast	IGMP Snooping	Same as Catalyst 2940-8TT
QoS	802.1p, 4 egress queues, WRR, SPS	Same as Catalyst 2940-8TT
Management Capabilities	SNMP, Telnet, RMON, CiscoWorks, CNA	Same as Catalyst 2940-8TT
Flash Memory	8 MB	Same as Catalyst 2940-8TT
CPU DRAM	16 MB	Same as Catalyst 2940-8TT
Embedded RMON	History, Events, Alarms, Statistics	Same as Catalyst 2940-8TT
Dimensions (H x W x D)	1.55 x 10.6 x 6.42 in. (3.94 x 26.92 x 16.3 cm)	Same as Catalyst 2940-8TT
Weight	3 lb (1.36 kg)	Same as Catalyst 2940-8TT

Selected Part Numbers and Ordering Information¹

Catalyst 2940 Series

WS-C2940-8TF-S	8 10/100 ports and 1 100BASE-FX or SFP port
WS-C2940-8TT-S	8 10/100 ports and 1 10/100/1000 port
CABLEGUARD-C2940=	Cable Guard secures switch; prevents tampering w/ Ethernet jacks
RACKMOUNT-C2940	Rack mount for the Catalyst 2940

SFP Transceivers

GLC-LH-SM=	1000BASE-LX/LH Gigabit Ethernet SFP, LC connector, LH transceiver
GLC-SX-MM=	1000BASE-SX Gigabit Ethernet SFP, LC connector, SX transceiver
GLC-ZX-SM=	1000BASE-ZX Gigabit Ethernet SFP, LC connector, ZX transceiver

Fiber Patch Cables

CAB-MTRJ-SC-MM-1M=	1-meter, MT-RJ-to-SC multimode cable
CAB-MTRJ-ST-MM-1M=	1-meter, MT-RJ-to-ST multimode cable
CAB-MTRJ-SC-MM-3M=	3-meter, MT-RJ-to-SC multimode cable
CAB-MTRJ-ST-MM-3M=	3-meter, MT-RJ-to-ST multimode cable
CAB-MTRJ-SC-MM-5M=	5-meter, MT-RJ-to-SC multimode cable
CAB-MTRJ-ST-MM-5M=	5-meter, MT-RJ-to-ST multimode cable

Catalyst 2940 Series Packaged SMARTnet Maintenance 8x5xNBD

CON-SNT-29408TF	Packaged SMARTnet 8x5xNBD Maintenance for the Catalyst 2940-8TF
CON-SNT-29408TT	Packaged SMARTnet 8x5xNBD Maintenance for the Catalyst 2940-8TT

1. This is only a small subset of all parts available via URL listed under "For More Information." Some parts have restricted access or are not available through distribution channels. Resellers: For latest part number and pricing info, see the *Distribution Product Reference Guide* at: <http://www.cisco.com/dprg> (limited country availability).

For More Information

See the Catalyst 2940 Website: <http://www.cisco.com/go/catalyst2940>

Cisco Catalyst 2960 Series



Cisco Catalyst 2960 Series Intelligent Ethernet Switches are a new family of fixed-configuration standalone devices that provide desktop 10/100 Fast Ethernet and 10/100/1000 Gigabit Ethernet connectivity for entry-level enterprise, mid-market, and branch office networks to enable enhanced LAN services.

When to Sell

Sell This Product

Catalyst 2960 Series

When a Customer Needs These Features

- Layer 2 switching with intelligent Layer 2-4 services
- Fast Ethernet and Gigabit Ethernet connectivity
- Up to 48 10/100 ports or 10/100/1000 ports

Key Features

- Network control and bandwidth optimization through advanced QoS, granular rate-limiting, ACLs, and multicast services
- Network security through a wide range of authentication methods, data encryption technologies, and NAC based on users, ports, and MAC addresses
- Cisco Network Assistant is a GUI-based management tool for configuration management, and troubleshooting..
- Smartports automatically detects connected Cisco devices and recommends preset configurations for the switch port connected to the device

Specifications

Features	WS-C2960-24TC-L	WS-C2960-24TT-L	WS-C2960-48TC-L	WS-C2960 48TT-L
Forwarding bandwidth (Gbps)	8.8	8.8	13.6	13.6
Packets per second (Mpps)	6.6	6.6	10.1	10.1
MAC addresses supported	8,000	8,000	8,000	8,000
Onboard memory (DRAM MB)	64	64	64	64
Gigabit Ethernet GBIC/SFP density	2	0	2	0
10/100/1000 density	2*	2	2*	2
10/100 density	24	24	48	48
100BASE-FX density	0	0	0	0
Max. watt power consumption	30	30	45	45
AC/DC support	AC only	AC only	AC only	AC only
Dimensions (H x W x D)	1.73 x 17.5 x 9.3 in. (4.4 x 44.5 x 23.6 cm.)	1.73 x 17.5 x 9.3 in. (4.4 x 44.5 x 23.6 cm.)	1.73 x 17.5 x 9.3 in. (4.4 x 44.5 x 23.6 cm.)	1.73 x 17.5 x 9.3 in. (4.4 x 44.5 x 23.6 cm.)
Unit weight	8 lbs. (3.6 kgs.)	8 lbs. (3.6 kgs.)	8 lbs. (3.6 kgs.)	8 lbs. (3.6 kgs.)

Selected Part Numbers and Ordering Information¹

Catalyst 2960 Series Workgroup Switches

WS-C2960-24TT-L	24 10/100 ports + 2 10/100/1000 uplinks; LAN Base Image
WS-C2960-48TT-L	48 10/100 ports + 2 10/100/1000 uplinks; LAN Base Image
WS-C2960-24TC-L	24 10/100 ports + 2 dual-purpose uplinks; LAN Base Image
WS-C2960-48TC-L	48 10/100 ports + 2 dual-purpose uplinks; LAN Base Image
WS-C2960G-24TC-L	20 10/100/1000 ports + 4 dual-purpose uplinks; LAN Base Image

SFP's

GLC-GE-100FX=	100FX SFP on GE SFP ports for DSBU switches
GLC-FE-100FX	100BASE-FX SFP for FE port
GLC-LH-SM=	GE SFP,LC connector LX/LH transceiver
GLC-SX-MM=	GE SFP, LC connector SX transceiver
GLC-FE-100LX	100BASE-LX SFP for FE port
GLC-FE-100BX-U	100BASE-BX10-U SFP
GLC-FE-100BX-D	100BASE-BX10-D SFP
GLC-ZX-SM=	1000BASE-ZX SFP

Right Angle Power Cords

CAB-AC-RA=	Power Cord, Right Angle
CAB-AC-RA=	Power Cord, 110V, Right Angle
CAB-ACR-RA=	Power Cord, Argentina, Right Angle
CAB-ACA-RA=	Power Cord, Australia, Right Angle
CAB-ACC-RA=	Power Cord, China, Right Angle
CAB-ACE-RA=	Power Cord, Europe, Right Angle
CAB-ACI-RA=	Power Cord, Italy, Right Angle
CAB-JPN-RA=	Power Cord, Japan, Right Angle
CAB-JPN-RA=	Power Cord, Japan, Right Angle
CAB-ACS-RA=	Power Cord, Switzerland, Right Angle
CAB-ACU-RA=	Power Cord, United Kingdom, Right Angle

RPS

PWR675-AC-RPS-N1=	675W redundant power supply with 1 connector cable
CAB-RPS-1614=	1 RPS 675 connector cable 16/14

1. This is only a small subset of all parts available via URL listed under "For More Information." Some parts have restricted access or are not available through distribution channels. Resellers: For latest part number and pricing info, see the *Distribution Product Reference Guide* at: <http://www.cisco.com/dprg> (limited country availability).

For More Information

See the Catalyst 2960 Series Website: <http://www.cisco.com/go/catalyst2960>

Cisco Catalyst 3560 Series



The Cisco Catalyst 3560 Series is a line of fixed-configuration, enterprise-class switches that include PoE functionality in Fast Ethernet and Gigabit Ethernet configurations. It is an ideal access layer switch for small enterprise LAN access or branch-office environments, enabling the deployment of new applications such as IP telephony, wireless access, video surveillance, building management systems, and remote video kiosks.

When to Sell

Sell This Product

Catalyst 3560-24TS

Catalyst 3560-48TS

Catalyst 3560-24PS

Catalyst 3560-48PS

Catalyst 3560G-24TS

Catalyst 3560G-24PS

Catalyst 3560G-48TS

Catalyst 3560G-48PS

When a Customer Needs These Features

- For networks requiring low-density access, Layer 2+ or L3 features, and one or more fiber uplinks
- For networks requiring medium-density access, Layer 2+ or L3 features, and one or more fiber uplinks
- For networks requiring low-density access, PoE, Layer 2+ or L3 features, and one or more fiber uplinks
- For networks requiring medium-density access, PoE, Layer 2+ or L3 features, and one or more fiber uplinks
- For networks requiring low-density 10/100/1000 access, Layer 2+ or L3 features, and one or more fiber uplinks
- For networks requiring low-density 10/100/1000 access, PoE, Layer 2+ or L3 features, and one or more fiber uplinks
- For networks requiring medium-density 10/100/1000 access, Layer 2+ or L3 features, and one or more fiber uplinks
- For networks requiring medium-density 10/100/1000 access, PoE, Layer 2+ or L3 features, and one or more fiber uplinks

Key Features

- Availability-802.1S/W enables standards-based fault tolerance, load balancing, and rapid recovery; the Flexlink feature provides sub-100-millisecond convergence; Per VLAN Spanning Tree Plus (PVST+) increases available bandwidth by allowing traffic on redundant link.
- Power over Ethernet (PoE)-370W PoE simplifies IP telephony, wireless, and video surveillance deployments; intelligent power-management features provide greater control and help extend the power budget

- Layer 3—Advanced routing protocols such as Open Shortest Path First (OSPF), Enhanced Interior Gateway Routing Protocol (EIGRP), Border Gateway Protocol (BGP), static routing, and Policy Based Routing (PBR) increase network scale; equal cost routing as well as multicast routing such as Protocol Independent Multicast (PIM) maximize network resources; Virtual Route Forwarding Lite (VRF Lite) secures traffic; IPv6 simplifies network addressing and mobile IP while increasing security
- QoS—Traffic Shaping smoothes bursty traffic flows without dropping packets; shaped Round Robin guarantees bandwidth to mission critical applications; Scavenger Queueing protects against worms overloading resources.
- Management—Cisco Smartports quicken and simplify configuration of advanced Cisco Catalyst intelligent capabilities; express setup enables quick and easy setup through a Web interface; resource templates help tailor switch resources for the application.
- Security—DHCP snooping allows only trusted ports to relay DHCP messages, eliminating rogue DHCP servers; Network Access Control (NAC) prevents the propagation of costly worms and viruses; Dynamic ARP inspection and IP Source Guard prevent against man-in-the-middle attacks; 802.1x and Identity-based Network Services allow only authorized persons on the network; port security prevents MAC address flooding attacks

Specifications

Features	WS-C3560-24TS	WS-C3560-48TS	WS-C3560-24PS	WS-C3560-48PS
Fixed Ports	24 10/100	48 10/100	24 10/100	48 10/100
VLAN Maximum	1005	1005	1005	1005
Forwarding bandwidth (Gbps)	8.8	17.6	8.8	17.6
Packets per second (Mpps)	6.5	13.1	6.5	13.1
MAC addresses supported	12,000	12,000	12,000	12,000
Routes supported	11,000	11,000	11,000	11,000
Onboard memory (DRAM/Flash)	128/32 MB	128/32 MB	128/16 MB	128/16 MB
Gigabit Ethernet GBIC/SFP density	2	4	2	4
10/100/1000 density	0	0	0	0
Max. watt power consumption	45	65	485	530
PoE: Max. 802.3af Class 3 devices (15.4W)	0	0	24	24
PoE: Max. 802.3af Class 2 devices (7.3W)	0	0	24	48
AC/DC support	AC only	AC only	AC only	AC only
Dimensions (H x W x D)	1.73 x 17.5 x 11.8 lbs. (4.4 x 44.5 x 30.1 cm.)	1.73 x 17.5 x 11.8 lbs. (4.4 x 44.5 x 30.1 cm.)	1.73 x 17.5 x 11.8 lbs. (4.4 x 44.5 x 30.1 cm.)	1.73 x 17.5 x 11.8 lbs. (4.4 x 44.5 x 30.1 cm.)
Unit weight	8.5 lbs. (3.9 kgs.)	9.1 lbs. (4.1 kgs.)	11.3 lbs. (5.1 kgs.)	13.2 lbs. (6.0 kgs.)
FEC/GEC	Yes	Yes	Yes	Yes

Features	WS-C3560G-24TS	WS-C3560G-48TS	WS-C3560G-24PS	WS-C3560G-48PS
Fixed Ports	24 10/100/1000	48 10/100/1000	24 10/100/1000	48 10/100/1000
VLAN Maximum	1005	1005	1005	1005
Forwarding bandwidth (Gbps)	32	32	32	32
Packets per second (Mpps)	38.7	38.7	38.7	38.7
MAC addresses supported	12,000	12,000	12,000	12,000
Routes supported	11,000	11,000	11,000	11,000
Onboard memory (DRAM/Flash)	128/32 MB	128/32 MB	128/32 MB	128/32 MB
Gigabit Ethernet GBIC/SFP density	4	4	4	4
10/100/1000 density	24	48	24	48
Max. watt power consumption	100	160	540	590

Features	WS-C3560G-24TS	WS-C3560G-48TS	WS-C3560G-24PS	WS-C3560G-48PS
PoE: Max. 802.3af Class 3 devices (15.4W)	0	0	24	24
PoE: Max. 802.3af Class 2 devices (7.3W)	0	0	24	48
AC/DC support	AC only	AC only	AC only	AC only
Dimensions (H x W x D)	1.73 x 17.5 x 14.9 lbs. (4.4 x 44.5 x 37.8 cm.)	1.73 x 17.5 x 16.1 lbs. (4.4 x 44.5 x 40.9 cm.)	1.73 x 17.5 x 14.9 lbs. (4.4 x 44.5 x 37.8 cm.)	1.73 x 17.5 x 16.1 lbs. (4.4 x 44.5 x 40.9 cm.)
Unit weight	12 lbs. (5.4 kgs.)	13.5 lbs. (6.1 kgs.)	14 lbs. (6.4 kgs.)	15.5 lbs. (7.0 kgs.)
FEC/GEC	Yes	Yes	Yes	Yes

Selected Part Numbers and Ordering Information¹

Catalyst 3560 Series 10/100/1000 Workgroup Switches²

WS-C3560G-48PS-S	Catalyst 3560 48 10/100/1000T PoE + 4 SFP IP Base Image
WS-C3560G-48PS-E	Catalyst 3560 48 10/100/1000T PoE + 4 SFP IP Services Image
WS-C3560G-24PS-S	Catalyst 3560 24 10/100/1000T PoE + 4 SFP IP Base Image
WS-C3560G-24PS-E	Catalyst 3560 24 10/100/1000T PoE + 4 SFP IP Services Image
WS-C3560G-48TS-S	Catalyst 3560 48 10/100/1000T + 4 SFP IP Base Image
WS-C3560G-48TS-E	Catalyst 3560 48 10/100/1000T + 4 SFP IP Services Image
WS-C3560G-24TS-S	Catalyst 3560 24 10/100/1000T + 4 SFP IP Base Image
WS-C3560G-24TS-E	Catalyst 3560 24 10/100/1000T + 4 SFP IP Services Image

Catalyst 3560 Series 10/100 Workgroup Switches

WS-C3560-48PS-S	Catalyst 3560 48 10/100 PoE + 4 SFP IP Base Image
WS-C3560-48PS-E	Catalyst 3560 48 10/100 PoE + 4 SFP IP Services Image
WS-C3560-24PS-S	Catalyst 3560 24 10/100 PoE + 2 SFP IP Base Image
WS-C3560-24PS-E	Catalyst 3560 24 10/100 PoE + 2 SFP IP Services Image
WS-C3560-48TS-S	Catalyst 3560 48 10/100 + 4 SFP IP Base Image
WS-C3560-48TS-E	Catalyst 3560 48 10/100 + 4 SFP IP Services Image
WS-C3560-24TS-S	Catalyst 3560 24 10/100 + 2 SFP IP Base Image
WS-C3560-24TS-E	Catalyst 3560 24 10/100 + 2 SFP IP Services Image

IOS Upgrades

CD-3560-EMI=	Enhanced Multilayer Image upgrade for 3560 10/100 models
CD-3560G-EMI=	Enhanced Multilayer Image upgrade for 3560 GE models
3560-AISK9-LIC-B=	Advanced IP Services for 3560 FE models running IP Base
3560-AISK9-LIC-S=	Advanced IP Services upgrade for 3560 FE models running IP Services
3560G-AISK9-LIC-B=	Advanced IP Services upgrade for 3560 GE models running IP Base
3560G-AISK9-LIC-S=	Advanced IP Services upgrade for 3560 GE models running IP Services

SFPs for the Catalyst 3560

GLC-GE-100FX=	100FX SFP on GE SFP ports for DSBu switches
GLC-LH-SM=	GE SFP/LC connector LX/LH transceiver
GLC-SX-MM=	GE SFP, LC connector SX transceiver
GLC-T=	1000BASE-T SFP
GLC-ZX-SM=	1000BASE-ZX SFP
CWDM-SFP-1470=	CWDM 1470 NM SFP Gigabit Ethernet and 1G/2G FC
CWDM-SFP-1490=	CWDM 1490 NM SFP Gigabit Ethernet and 1G/2G FC
CWDM-SFP-1510=	CWDM 1510 NM SFP Gigabit Ethernet and 1G/2G FC
CWDM-SFP-1530=	CWDM 1530 NM SFP Gigabit Ethernet and 1G/2G FC
CWDM-SFP-1550=	CWDM 1550 NM SFP Gigabit Ethernet and 1G/2G FC
CWDM-SFP-1570=	CWDM 1570 NM SFP Gigabit Ethernet and 1G/2G FC
CWDM-SFP-1590=	CWDM 1590 NM SFP Gigabit Ethernet and 1G/2G FC
CWDM-SFP-1610=	CWDM 1610 NM SFP Gigabit Ethernet and 1G/2G FC
CAB-SFP-50CM=	Catalyst 3560 SFP Interconnect Cable, 50cm

LC to SC Cables

CSS5-CABLX-LCSC=	CSS11500 10-Meter Fiber Single Mode LX LC-to-SC Connectors
CSS5-CABSX-LC=	CSS11500 10-Meter Fiber Multimode SX LC Connectors
CSS5-CABSX-LCSC=	CSS11500 10-Meter Fiber Multimode SX LC-to-SC Connectors

Right Angle Power Cords

CAB-AC-RA=	Power Cord, Right Angle
CAB-AC-RA	Power Cord, 110V, Right Angle
CAB-ACA-RA=	Power Cord, Australian, Right Angle
CAB-ACC-RA=	Power Cord China, Right Angle
CAB-ACE-RA=	Power Cord Europe, Right Angle
CAB-ACI-RA=	Power Cord-Italian, Right Angle
CAB-ACR-RA=	Power Cord, Argentina, Right Angle
CAB-ACS-RA=	Power Cord for Switzerland, Right Angle
CAB-ACU-RA=	Power Cord UK, Right Angle
CAB-JPN-RA=	Power Cord, Japan, Right Angle
CAB-JPN-RA	Power Cord-Japan, Right Angle

RPS

PWR675-AC-RPS-N1= 675W Redundant Power Supply with 1 connector cable

CAB-RPS-1614= 1 RPS 675 connector cable 16/14

Spare Rack Mount Kits

RCKMNT-1RU= Rack Mount Kit for 1RU for 3750, 3560, 3550, 2900-LRE-XL

RCKMNT-REC-1RU= RECESSED 1RU RACK MOUNT FOR 3550, 3560, and 3750

1. This is only a small subset of all parts available via URL listed under “For More Information.” Some parts have restricted access or are not available through distribution channels. Resellers: For latest part number and pricing info, see the *Distribution Product Reference Guide* at: <http://www.cisco.com/dprg> (limited country availability).
2. S=IP Base; E=IP Services

For More InformationSee the Catalyst 3560 Series Website: <http://www.cisco.com/go/cat3560>**Cisco Catalyst 3750 Series**

The Cisco Catalyst 3750 Series Switch is an innovative product for midsize organizations and enterprise branch offices. Featuring Cisco StackWise technology, the switch improves LAN operating efficiency by combining ease of use and the highest resiliency available for stackable switches.

**When to Sell****Sell This Product****Catalyst 3750-24TS**

For networks requiring low-density access with switch stacking capability, Layer 2+ or L3 features, and 1 or more fiber uplinks.

Catalyst 3750-24PS

For networks requiring low-density access with switch stacking capability, Layer 2+ or L3 features, Power over Ethernet (PoE), and 1 or more fiber uplinks.

Catalyst 3750-48TS

For networks requiring medium-density access with switch stacking, Layer 2+ or L3 features, and 1 or more fiber uplinks.

Catalyst 3750-48PS

For networks requiring medium-density access with switch stacking capability, Layer 2+ or L3 features, Power over Ethernet (PoE), and 1 or more fiber uplinks.

Catalyst 3750G-24T

For networks requiring low-density Layer 2+ or L3 Gigabit Ethernet to the desktop (GTDD) or Ethernet aggregation with stacking capability without any uplinks.

Catalyst 3750G-24TS-1U

For networks requiring low-density Layer 2+ or L3 GTDD or Ethernet aggregation with stacking capability and fiber uplinks in a 1RU form factor

Catalyst 3750G-24TS

For networks requiring low-density Layer 2+ or L3 GTDD or Ethernet aggregation with stacking capability and fiber uplinks in a 1.5RU form factor.

Catalyst 3750G-24PS

For networks requiring low-density Layer 2+ or L3 GTDD or Ethernet aggregation with stacking capability, PoE, and fiber uplinks.

Catalyst 3750G-48TS

For networks requiring medium-density Layer 2+ or L3 GTDD or Ethernet aggregation with stacking capability and fiber uplinks.

Catalyst 3750G-48PS

For networks requiring medium-density Layer 2+ or L3 GTDD or Ethernet aggregation with stacking capability, PoE, and fiber uplinks.

Catalyst 3750G-16TD

For networks requiring low-density L2+ or L3 GTDD or Ethernet aggregation with stacking capability and a 10 GE uplink

Catalyst 3750G-12S

For aggregation of wiring closet switches with optical connectivity and stacking

Key Features

- Availability—802.1S/W enables standards-based fault tolerance, load balancing, and rapid recovery; the Flexlink feature provides sub-100-millisecond convergence; Per VLAN Spanning Tree Plus (PVST+) increases available bandwidth by allowing traffic on redundant link
- Cisco StackWise Technology—One IP address and one command-line interface (CLI) simplify management; a 32-Gbps resilient architecture speeds convergence; 1:N stack master redundancy and Layer 3uplink resilience as well as cross-stack Cisco EtherChannel technology and QoS increase availability; autoconfiguration and Cisco IOS Software version check and update accelerate deployment; hot add and delete of switches keep the stack running

- 370W PoE simplifies IP telephony, wireless, and video surveillance deployments; intelligent power-management features provide greater control and help extend the power budget; PoE combined with Fast Ethernet or Gigabit Ethernet models maximizes existing infrastructure investment
- Layer 3—Advanced routing protocols such as OPSF, EIGRP, BGP, static routing, and PBR increase network scale; equal cost routing as well as multicast routing such as PIM maximize network resources; VRFLite secures traffic; IPv6 simplifies network addressing and mobile IP while increasing security
- QoS—Traffic Shaping smoothes bursty traffic flows without dropping packets; shaped Round Robin guarantees bandwidth to missioncritical applications; Scavenger Queueing protects against worms overloading resources
- Management—Cisco Smartports quicken and simplify configuration of advanced capabilities; express setup enables quick and easy setup through a Web interface; resource templates help tailor switch resources for the application
- Security—DHCP snooping allows only trusted ports to relay DHCP messages, eliminating rogue DHCP servers; NAC prevents the propagation of costly worms and viruses; Dynamic ARP inspection and IP Source Guard prevent against man-in-the-middle attacks; 802.1x and Identity-based Network Services allow only authorized persons on the network; port security prevents MAC address flooding attacks

Competitive Products

- Extreme Networks: Summit5i, Summit 24/48, Summit 48i
- Foundry: FastIron 4802

- Nortel: 5510/5520

Specifications

Features	C3750-24TS	C3750-48TS	C3750-24PS	C3750-48PS	C3750-24FS
Forwarding bandwidth (Gbps)	32	32	32	32	32
Maximum stack members	9	9	9	9	9
Total bandwidth of stack (Gbps)	32	32	32	32	32
Packets per second (Mpps)	6.5	13.1	6.5	13.1	6.5
MAC addresses supported	12,000	12,000	12,000	12,000	12,000
Routes supported	11,000	11,000	11,000	11,000	11,000
Onboard memory (DRAM MB)	128	128	128	128	128
10 GbE density	0	0	0	0	0
Gigabit EthernetGBIC/SFP density	2	4	2	4	2
10 GbE XENPAK/X2 port density	0	0	0	0	0
10/100/1000 density	0	0	0	0	0
10/100 density	24	48	24	48	0
100BASE-FX density	0	0	0	0	24
Max. watt power consumption	50	75	495	540	125
PoE: Max. 802.3af Class 3 devices (15.4W)	0	0	24	24	0
PoE: Max. 802.3af Class 2 devices (7.3W)	0	0	24	48	0
AC/DC support	AC only	AC only	AC only	AC only	AC only
Dimensions(H x W x D)	1.73 x 17.5 x 11.8 in. (4.4 x 44.5 x 30.1 cm.)	1.73 x 17.5 x 11.8 in. (4.4 x 44.5 x 30.1 cm.)	1.73 x 17.5 x 11.8 in. (4.4 x 44.5 x 30.1 cm.)	1.73 x 17.5 x 14.9 in. (4.4 x 44.5 x 37.8 cm.)	1.73 x 17.5 x 11.8 in. (4.4 x 44.5 x 30.1 cm.)
Unit weight	8 lbs. (3.6 kgs.)	9.1 lbs. (4.1 kgs.)	11.3 lbs. (5.1 kgs.)	13.2 lbs. (6.0 kgs.)	9.15 lbs. (4.15 kgs.)

Features	C3750G-24T	C3750G-24TS-1U	C3750G-48TS	C3750G-24PS	C3750G-48PS
Forwarding bandwidth (Gbps)	32	32	32	32	32
Maximum stack members	9	9	9	9	9
Total bandwidth of stack (Gbps)	32	32	32	32	32
Packets per second (Mpps)	35.7	38.7	38.7	38.7	38.7
MAC addresses supported	12,000	12,000	12,000	12,000	12,000
Routes supported	11,000	11,000	11,000	11,000	11,000
Onboard memory (DRAM MB)	128	128	128	128	128
10 GbE density	0	0	0	0	0
Gigabit EthernetGBIC/SFP density	0	4	4	4	4
10 GbE XENPAK/X2 port density	0	0	0	0	0
10/100/1000 density	24	24	48	24	48
10/100 density	0	0	0	0	0
100BASE-FX density	0	0	0	0	0
Max. watt power consumption	165	100	160	540	590
PoE: Max. 802.3af Class 0 3 devices (15.4W)	0	0	0	24	24
PoE: Max. 802.3af Class 0 2 devices (7.3W)	0	0	0	24	48
AC/DC support	AC only	AC only	AC only	AC only	AC only
Dimensions(H x W x D)	1.73 x 17.5 x 12.8 in. (4.4 x 44.5 x 32.6 cm.)	1.73 x 17.5 x 14.9 in. (4.4 x 44.5 x 37.8 cm.)	1.73 x 17.5 x 16.1 in. (4.4 x 44.5 x 40.9 cm.)	1.73 x 17.5 x 14.9 in. (4.4 x 44.5 x 37.8 cm.)	1.73 x 17.5 x 16.1 in. (4.4 x 44.5 x 40.9 cm.)
Unit weight	10 lbs. (4.6 kgs.)	12 lbs. (5.5 kgs.)	14 lbs. (6.4 kgs.)	13.5 lbs. (6.1 kgs.)	15.5 lbs. (7.0 kgs.)

Features	C3750G-12S	C3750G-12S-SD	C3750G-16TD
Forwarding bandwidth (Gbps)	32	32	32
Maximum stack members	9	9	9
Total bandwidth of stack (Gbps)	32	32	32
Packets per second (Mpps)	17.8	17.8	35.7
MAC addresses supported	12,000	12,000	12,000
Routes supported	20,000	20,000	11,000
Onboard memory (DRAM MB)	128	128	128
10 GbE density	0	0	1
Gigabit EthernetGBIC/SFP density	12	12	0
10 GbE XENPAK/X2 port density	0	0	1
10/100/1000 density	0	0	16
Max. watt power consumption	120	72	180
AC/DC support	AC only	DC only	AC only
Dimensions(H x W x D)	1.73 x 17.5 x 12.8 in. (4.4 x 44.5 x 32.6 cm.)	1.73 x 17.5 x 12.8 in. (4.4 x 44.5 x 32.6 cm.)	1.73 x 17.5 x 16.1 in. (4.4 x 44.5 x 40.9 cm.)
Unit weight	10 lbs. (4.6 kgs.)	9 lbs. (4.08 kgs.)	12.5 lbs. (5.7 kgs.)

Selected Part Numbers and Ordering Information¹

Catalyst 3750 Series Ethernet Switches

WS-C3750G-24T-S	Catalyst 3750 24 10/100/1000T Standard Multilayer Image
WS-C3750G-24T-E	Catalyst 3750 24 10/100/1000T Enhanced Multilayer Image
WS-C3750G-24TS-S	Catalyst 3750 24 10/100/1000 + 4 SFP Std Multilayer; 1.5RU
WS-C3750G-24TS-E	Catalyst 3750 24 10/100/1000 + 4 SFP Enhcd Multilayer;1.5RU
WS-C3750G-24TS-S1U	Catalyst 3750 24 10/100/1000 + 4 SFP Std Multilayer;1RU
WS-C3750G-24TS-E1U	Catalyst 3750 24 10/100/1000 + 4 SFP Enh Multilayer;1RU
WS-C3750G-24PS-S	Catalyst 3750 24 10/100/1000T PoE + 4 SFP Standard Image
WS-C3750G-24PS-E	Catalyst 3750 24 10/100/1000T PoE + 4 SFP Enhanced Image
WS-C3750G-48TS-S	Catalyst 3750 48 10/100/1000T + 4 SFP Standard Multilayer
WS-C3750G-48TS-E	Catalyst 3750 48 10/100/1000T + 4 SFP Enhanced Multilayer
WS-C3750G-48PS-S	Catalyst 3750 48 10/100/1000T PoE + 4 SFP Standard Image
WS-C3750G-48PS-E	Catalyst 3750 48 10/100/1000T PoE + 4 SFP Enhanced Image

WS-C3750G-16TD-S	Catalyst 3750 16 10/100/1000BT+ 10GbE (req XENPAK) Std Image
WS-C3750G-16TD-E	Catalyst 3750 16 10/100/1000BT+ 10GbE (req XENPAK) Enh Image
WS-C3750G-12S-S	Catalyst 3750 12 SFP Standard Multilayer Image
WS-C3750G-12S-SD	Catalyst 3750 12 SFP DC powered Standard Multilayer Image
WS-C3750G-12S-E	Catalyst 3750 12 SFP Enhanced Multilayer Image
WS-C3750-24FS-S	Catalyst 3750 24 100BaseFX + 2 SFP Standard Multilayer Image

Catalyst 3750 Series 10/100 Workgroup Switches

WS-C3750-24FS-S	Catalyst 3750 24 100BaseFX + 2 SFP Standard Multilayer Image
WS-C3750-24PS-S	Catalyst 3750 24 10/100 PoE + 2 SFP Standard Image
WS-C3750-24PS-E	Catalyst 3750 24 10/100 PoE + 2 SFP Enhanced Image
WS-C3750-24TS-S	Catalyst 3750 24 10/100 + 2 SFP Standard Multilayer Image
WS-C3750-24TS-E	Catalyst 3750 24 10/100 + 2 SFP Enhanced Multilayer Image
WS-C3750-48PS-S	Catalyst 3750 48 10/100 PoE + 4 SFP Standard Image
WS-C3750-48PS-E	Catalyst 3750 48 10/100 PoE + 4 SFP Enhanced Image
WS-C3750-48TS-S	Catalyst 3750 48 10/100 + 4 SFP Standard Multilayer Image
WS-C3750-48TS-E	Catalyst 3750 48 10/100 + 4 SFP Enhanced Multilayer Image

Catalyst 3750 Series OADM Modules

CWDM-OADM1-1470=	Dual single channel OADM Module (1470nm)
CWDM-OADM1-1490=	Dual single channel OADM Module (1490nm)
CWDM-OADM1-1510=	Dual single channel OADM Module (1510nm)
CWDM-OADM1-1530=	Dual single channel OADM Module (1530nm)
CWDM-OADM1-1550=	Dual single channel OADM Module (1550nm)
CWDM-OADM1-1570=	Dual single channel OADM Module (1570nm)
CWDM-OADM1-1590=	Dual single channel OADM Module (1590nm)
CWDM-OADM1-1610=	Dual single channel OADM Module (1610nm)
CWDM-OADM4-1=	4-channels CWDM OADM Module (1470, 1490, 1510, 1530)
CWDM-OADM4-2=	4-channels CWDM OADM Module (1550, 1570, 1590, 16100)
WDM-1300-1550-S=	1300nm/1550nm WDM splitter cable

IOS Upgrades for the Catalyst 3750

CD-3750-EMI=	Enhanced Multilayer Image upgrade for 3750 FE models
CD-3750G-EMI=	Enhanced Multilayer Image upgrade for 24-port 3750 GE models
CD-3750G-48EMI=	Enhanced Multilayer Image upgrade for 48-port 3750 GE models
3750-AISK9-LIC-B=	Advanced IP Services upgrade for 3750 FE models running SMI
3750-AISK9-LIC-S=	Advanced IP Services upgrade for 3750 FE models running EMI
3750G-AISK9-LIC-B=	Advanced IP Services upgrade for 3750 GE models running SMI
3750G-AISK9-LIC-S=	Advanced IP Services upgrade for 3750 GE models running EMI
3750G48-AISK9LC-B=	Advanced IP Services upgrade for 3750G-48 running SMI
3750G48-AISK9LC-S=	Advanced IP Services upgrade for 3750G-48 running EMI

Cisco StackWise Cables for the Catalyst 3750

CAB-STACK-50CM=	Cisco StackWise 50CM Stacking Cable
CAB-STACK-1M	Cisco StackWise 1M Stacking Cable
CAB-STACK-1M=	Cisco StackWise 1M Stacking Cable
CAB-STACK-3M	Cisco StackWise 3M Stacking Cable
CAB-STACK-3M=	Cisco StackWise 3M Stacking Cable
CAB-STACK-50CM-NH	Cisco StackWise 50CM Non-Halogen Lead Free Stacking Cable
CAB-STACK-50CM-NH=	Cisco StackWise 50CM Non-Halogen Lead Free Stacking Cable
CAB-STACK-1M-NH	Cisco StackWise 1M Non-Halogen Lead Free Stacking Cable
CAB-STACK-1M-NH=	Cisco StackWise 1M Non-Halogen Lead Free Stacking Cable
CAB-STACK-3M-NH	Cisco StackWise 3M Non-Halogen Lead Free Stacking Cable
CAB-STACK-3M-NH=	Cisco StackWise 3M Non-Halogen Lead Free Stacking Cable

SFPs for the Catalyst 3750

GLC-GE-100FX=	100FX SFP on GE SFP ports for DSBU switches
GLC-LH-SM=	GE SFP, LC connector LX/LH transceiver
GLC-SX-MM=	GE SFP, LC connector SX transceiver
GLC-T=	1000BASE-T SFP
GLC-ZX-SM=	1000BASE-ZX SFP
CWDM-SFP-1470=	CWDM 1470 NM SFP Gigabit Ethernet and 1G/2G FC
CWDM-SFP-1490=	CWDM 1490 NM SFP Gigabit Ethernet and 1G/2G FC
CWDM-SFP-1510=	CWDM 1510 NM SFP Gigabit Ethernet and 1G/2G FC
CWDM-SFP-1530=	CWDM 1530 NM SFP Gigabit Ethernet and 1G/2G FC
CWDM-SFP-1550=	CWDM 1550 NM SFP Gigabit Ethernet and 1G/2G FC
CWDM-SFP-1570=	CWDM 1570 NM SFP Gigabit Ethernet and 1G/2G FC
CWDM-SFP-1590=	CWDM 1590 NM SFP Gigabit Ethernet and 1G/2G FC
CWDM-SFP-1610=	CWDM 1610 NM SFP Gigabit Ethernet and 1G/2G FC

XENPAKs for the Catalyst 3750

XENPAK-10GB-ER	10GBASE-ER XENPAK Module
XENPAK-10GB-ER=	10GBASE-ER XENPAK Module
C3-XENPAK10GB-LR=	10GBASE-LR XENPAK Module for Catalyst 3750

LC to SC Cables for the Catalyst 3750

CSS5-CABLX-LCSC=	CSS11500 10-Meter Fiber Single Mode LX LC-to-SC Connectors
CSS5-CABSX-LC=	CSS11500 10-Meter Fiber Multimode SX LC Connectors
CSS5-CABSX-LCSC=	CSS11500 10-Meter Fiber Multimode SX LC-to-SC Connectors

Right Angle Power Cords for the Catalyst 3750

CAB-AC-RA=	Power Cord, Right Angle
CAB-AC-RA	Power Cord, 110V, Right Angle
CAB-ACA-RA=	Power Cord, Australian, Right Angle
CAB-ACC-RA=	Power Cord China, Right Angle
CAB-ACE-RA=	Power Cord Europe, Right Angle
CAB-ACI-RA=	Power Cord-Italian, Right Angle
CAB-ACR-RA=	Power Cord, Argentina, Right Angle
CAB-ACS-RA=	Power Cord for Switzerland, Right Angle
CAB-ACU-RA=	Power Cord UK, Right Angle
CAB-JPN-RA=	Power Cord, Japan, Right Angle
CAB-JPN-RA	Power Cord-Japan, Right Angle

RPS for the Catalyst 3750

PWR675-AC-RPS-N1=	675W Redundant Power Supply with 1 connector cable
CAB-RPS-1614=	1 RPS 675 connector cable 16/14
CAB-16AWG-AC	AC Power cord, 16AWG
CAB-16AWG-AC=	AC Power cord, 16AWG

Spare Rack Mount Kits for the Catalyst 3750

RCKMNT-1RU=	Rack Mount Kit for 1RU for 3750,3560,3550,2900-LRE-XL
RCKMNT-3550-1.5RU=	Rack Mount Kit for 1.5RU Catalyst 3550s
RCKMNT-REC-1.5RU=	RECESSED 1.5RU RACK MOUNT FOR 3550,3750
RCKMNT-REC-1RU=	RECESSED 1RU RACK MOUNT FOR 3550, 3560, and 3750

1. This is only a small subset of all parts available via URL listed under "For More Information." Some parts have restricted access or are not available through distribution channels. Resellers: For latest part number and pricing info, see the *Distribution Product Reference Guide* at: <http://www.cisco.com/dprg> (limited country availability).

For More Information

See the Catalyst 3750 Series Website: www.cisco.com/go/catalyst3750

Cisco Catalyst 4948 Series

The Cisco Catalyst 4948 Series is a family of wire-speed, low-latency, 1 RU fixed configuration switches for rack optimized server switching and DSLAM aggregation. Based on the proven Catalyst 4500 Series hardware and software architecture. The Catalyst 4948 series offers exceptional performance and reliability for low density, multilayer aggregation of high performance servers and workstations.

When to Sell**Sell This Product When a Customer Needs These Features**

Catalyst 4948	• 48-Ports of Gigabit Ethernet switching in 1RU with dual power supplies • Non-blocking Layer 2/3/4 10/100/1000 Gigabit Ethernet performance
Catalyst 4948-10GE	• 48-Ports of Gigabit Ethernet switching in 1RU with dual power supplies • Non-blocking Layer 2/3/4 10/100/1000 Gigabit Ethernet performance with 10 Gigabit Ethernet uplinks

Key Features

- Low-latency and wire-speed switching
- Up to 48 10/100/1000 ports with 4 Small Form-Factor Pluggable (SFP) ports or 48 10/100/1000 ports with two 10 Gigabit Ethernet ports
- Redundant internal AC or DC power supplies with hot swappable fan tray
- SFP or X2 flexibility on fiber port interfaces covering a wide range of cabling distances

Competitive Products

- Extreme Networks: Summit 400
- Foundry: FESX448 and FWS X448

Specifications

Feature	Catalyst 4948	Catalyst 4948-10GE
Fixed Ports	48 10/100/1000 & 4 GE ports (SFP)—shared	48 10/100/100 & 2 10 Gigabit Ethernet ports (X2)
Backplane Capacity	96 Gbps	136 Gbps
Stackable	No	No
Power Supply Redundancy	Yes. 1+1 AC or DC	Same as 4948
Fan Tray	Hot Swappable with redundant fans	Same as 4948
EIGRP, OSPF, IS-IS, BGP	Yes. Enhanced Software required	Same as 4948
Management Ports	Dedicated console port and 10/100 management port for disaster recovery	Dedicated console port and 10/100/1000 management port for disaster recovery
Dimensions (H x W x D)	1.75 x 17.3 x 16.1 in. (4.45 x 43.91 x 40.99 cm.)	Same as 4948
Forwarding bandwidth (Gbps)	96	136
Packets per second (Mpps)	72	102
MAC addresses supported	32,768	55,000
Routes supported	32,000	32,000
Onboard memory (DRAM MB)	256	256
10 GbE density	0	2
Gigabit Ethernet GBIC/SFP 4 density	0	0
10 GbE X2 port density	0	2
10/100/1000 density	48	48
Max. watt power consumption	300	300

Selected Part Numbers and Ordering Information¹**Catalyst 4900 Switch Series**

WS-C4948-S	Catalyst 4948, IPB s/w, 48-Port 10/100/1000+4 SFP, 1 AC p/s
WS-C4948-E	Catalyst 4948, ES s/w, 48-Port 10/100/1000+4 SFP, 1 AC p/s
WS-C4948	Catalyst 4948, optnl sw, 48-Port 10/100/1000+4 SFP, no p/s
WS-C4948-10GE	Catalyst 4948, optnl sw, 48*10/100/1000+2*10GE(X2), no p/s
WS-C4948-10GE-S	Catalyst 4948, IPB s/w, 48*10/100/1000+2*10GE(X2), 1 AC p/s
WS-C4948-10GE-E	Catalyst 4948, ES Image, 48*10/100/1000+2*10GE(X2), 1 AC p/s

1. This is only a small subset of all parts available via URL listed under “For More Information.” Some parts have restricted access or are not available through distribution channels. Resellers: For latest part number and pricing info, see the *Distribution Product Reference Guide* at: <http://www.cisco.com/dprg> (limited country availability).

For More Information

See the Catalyst 4000 series Website: <http://www.cisco.com/go/cat4000>

Cisco Catalyst 4500 Series

The Catalyst 4500 Series switches are mid-range, medium-density modular chassis delivering robust Layer 2-4 intelligent services. Its modular architecture, media flexibility, and expandability extends deployment life, while reducing the cost of ownership by minimizing recurring operational expenses and improving return on investment.



The Supervisor Engine V-10GE continues the nonblocking, robust Layer 2-4 switching with the addition of wire-speed 10-Gigabit Ethernet uplinks, 136-Gbps capacity and 102-mpps throughput, and additional features to further enhance resilient control of converged data, voice, and video networks with high availability. The Supervisor Engine IV integrates non-blocking Layers 2-4 switching with integrated resiliency, further enhancing control of converged networks. The Supervisor Engine II-Plus-10GE is equipped with both Gigabit (SFP) and line rate 10-Gigabit (X2) ports on the supervisor, allowing for 10-Gigabit future proofing and an easy and cost-efficient migration to 10 Gigabit.

When to Sell

Sell This Product

Catalyst 4510R

When a Customer Needs These Features

- When high performance, port density, and network resiliency is crucial to customer success
- Port density up to 384-10/100, 100-FX, 1000BASE-X or 10/100/1000BASE-T and 2 ports 10 GbE
- Layer 2 and Layer 3 Cisco Express Forwarding (CEF)-based switching up to 136 Gbps, 102 Mpps

Catalyst 4507R

- When network resiliency via redundant Supervisor Engines is crucial to customer success
- Port density up to 240-10/100, 100-FX, 1000BASE-X or 10/100/1000BASE-T and 2 ports 10 GbE
- Layer 2 and Layer 3 Cisco Express Forwarding (CEF)-based switching up to 100 Gbps, 72 Mpps

Catalyst 4506

- Port density up to 240-10/100, 100-FX, 1000BASE-X or 10/100/1000BASE-T and 2 ports 10 GbE
- Layer 2 and Layer 3 Cisco Express Forwarding (CEF)-based switching up to 100 Gbps, 75 Mpps

Catalyst 4503

- Port density up to 116-10/100, 100-FX, 1000BASE-X or 10/100/1000BASE-T and 2 ports 10 GbE
- Layer 2 and Layer 3 Cisco Express Forwarding (CEF)-based switching up to 64 Gbps, 48 Mpps

Note: Compatible sparring between Catalyst 4510R, 4507R, 4506, and 4503 chassis provides investment protection with common Supervisor Engines, power supplies and switching line cards.

Key Features

- Flexible Options—Modular 3- and 6-slot single supervisor chassis and 7- and 10-slot redundant supervisor chassis supporting numerous connectivity and service configurations
- Highest Availability—Redundant supervisor engines with Stateful Switchover offering 50ms failover; hot-swappable fan trays with redundant fans
- Comprehensive Security—802.1x; NetFlow; access control lists and SSH
- Comprehensive Management: CiscoWorks; CNA; RSPAN; TDR and NetFlow
- High Port Density—Up to 384 Fast Ethernet or Gigabit Ethernet ports available in copper or fiber in 10 Gigabit uplinks; integrated man-in-middle attack prevention; PoE (Cisco pre-standard and IEEE 802.3af)
- Investment Protection—Functionally transparent line cards allow for easy upgrade of all system ports to higher level functions with Supervisor upgrade

Competitive Products

- Extreme Networks: Alpine and Aspen
- Foundry: Fast Iron and Super-X
- Hewlett Packard: Procurve 5300XL, 4108GL
- Nortel: Passport 8300/8600

Specifications

	WS-C4503	WS-C4506	WS-C4507R	WS-C4510R
Slots	3	6	7	10
Redundant Supervisor Option	No	No	Yes	Yes
Gigabit Ethernet GBIC/SFP density	104	240	240	384
10 GbE X2 port density	2	2	2	2
10/100/1000 density	108	240	240	384
10/100 density	108	240	240	384
100BASE-FX, LX-10, BX-D density	96	240	240	384
Rack Unit (RU)	7	10	11	14
Backplane Capacity	64 Gbps	100 Gbps	100 Gbps	136 Gbps
Stackable	No	No	No	No
Unit weight (chassis only)	31.25 lbs. (14.18 kgs.)	40.5 lbs. (18.37 kgs)	44.25 lbs. (20.07 kgs)	51.50 lbs. (23.36 kgs)
Dimensions (H x W x D)	12.25 x 17.31 x 12.50 in (31.12 x 43.97 x 31.70 cm)	17.38 x 17.31 x 12.50 in (44.13 x 43.97 x 31.70 cm)	19.19 x 17.31 x 12.50 in (48.74 x 43.97 x 31.70 cm)	24.35 x 17.31 x 12.50 in (61.84 x 43.97 x 31.70 cm)
Power Over Ethernet (PoE) Support	Up to 15.4W of PoE on every port	Up to 15.4W of PoE on every port	Up to 15.4W of PoE on every port	Up to 15.4W of PoE on every port
1+1 Power Supply Protection	Yes	Yes	Yes	Yes
Hot-Swappable Power Supplies	Yes	Yes	Yes	Yes
Max. watt power consumption ¹				
AC Internal ¹	4,200	4,200	4,200	4,200

	WS-C4503	WS-C4506	WS-C4507R	WS-C4510R
AC External with power shelf ¹	1,400 + power shelf = 7,500	1,400 + power shelf = 7,500	1,400 + power shelf = 7,500	1,400 + power shelf = 7,500
DC Internal ¹	1,400 + UPS = 7,500	1,400 + UPS = 7,500	1,400 + UPS = 7,500	1,400 + UPS = 7,500
Max. number of Class 3 devices (15.4W) Max. power supplies				
AC Internal ¹	108	240	240	270
AC External with power shelf ¹	108	240	240	364
DC Internal ¹	108	240	240	384

1. Redundant Mode

Supervisor Engines	Supervisor V-10GE (WS-X4516-10 GE)	Supervisor V (WS-X4516)	Supervisor IV (WS-X4515)	Supervisor II-Plus (WS-X4013+)	Supervisor II-Plus-TS (WS-X4013+T S)	WS-X4013+10 GE
Chassis supported	All	All	4503, 4506, 4507R	4503, 4506, 4507R	4503	4507R, 4506, 4503
Enhanced Layer 3 option	yes	yes	yes	no	no	no
Total bandwidth (Gbps)	136	96	64	64	64	64
Packets per second (Mpps)	102	72	48	48	48	48
CPU Mhz	800	400	333	266	266	667
NetFlow	included	option	option	no	no	no
Onboard memory (DRAM)	512 MB	512 MB	512 MB	256 MB	25 6MB	256 MB
On-Board Flash	64 MB	64 MB	64 MB	32 MB	32 MB	
Compact Flash	Yes	Yes	Yes	Yes	Yes	
Support						
Switching Capacity & Throughput	136 Gbps, 102 Mpps	96 Gbps, 72 Mpps	64 Gbps, 48 Mpps	64 Gbps, 48 Mpps	64 Gbps, 48 Mpps	
Multilayer Switching	Enhanced L2/3/4 Services & Routing	Enhanced L2/3/4 Services & Routing	Enhanced L2/3/4 Services & Routing	Basic L2/3/4 Services	Basic L2/3/4 Services	
(E)IGRP, OSPF, IS-IS, BGP	Yes	Yes	Yes	No	No	
Supervisor Redundancy	4507R and 4510R Only	4507R and 4510R Only	4507R Only	4507R Only	No	
QoS	4Q/Port, policing, shaping, congestion avoidance	4Q/Port, policing, shaping, congestion avoidance	4Q/Port, policing, shaping, congestion avoidance	4Q/Port, policing, shaping, congestion avoidance	4Q/Port, policing, shaping, congestion avoidance	
CPU	800 MHz	400 MHz	333 MHz	266 MHz	266 MHz	
NetFlow Support	Yes (Built-in functionality; no Daughter Card Required)	Yes (Optional Daughter Card)	Yes (Optional Daughter Card)	No	No	
ISL	Yes	Yes	Yes	Yes	Yes	
ACLs	Yes	Yes	Yes	Yes	Yes	
IP FIB entries	128K	128K	128K	32K	32K	
MAC Addresses	32K Unicast, 16K Multicast	32K Unicast, 16K Multicast	32K Unicast 16K Multicast	32K Unicast, 16K Multicast	32K Unicast, 16K Multicast	
Non-Blocking Supervisor Ports	2x10GE and 4xGE	2xGE ports	2xGE ports	2xGE ports	12x10/100/1000 BASET, PoE, 8xSFP	

Selected Part Numbers and Ordering Information¹

Catalyst 4500 Series Switches

WS-C4503	3-slot chassis, fan, no power supply
WS-C4506	6-slot chassis, fan, no power supply
WS-C4507R	7-slot chassis, fan, no power supply, redundant-supervisor support
WS-C4510R	10-slot chassis, fan, no power supply, redundant-supervisor support

Catalyst 4x00 Supervisor Engines

WS-X4013+	Catalyst 4500 Supervisor II-Plus (IOS), 2 GbE, Console (RJ-45)
WS-X4013-10GE	Catalyst 4500 Supervisor II-PLUS-10GE, 2x10GE and RJ-45
WS-X4013+TS	Catalyst 4503 Supervisor II-Plus-TS, 12 10/100/1000 PoE + 8 SFP slots
WS-X4515	Catalyst 4500 Supervisor IV (2 GbE), Console (RJ-45)
WS-X4516	Catalyst 4500 Supervisor V (2 GbE), Console (RJ-45)
WS-X4516-10GE	Catalyst 4500 Supervisor V-10 GbE, 2x10 GbE (X2) or 4x1 GbE (SFP)
WS-F4531	Catalyst 4500 NetFlow services card
S45ES-12xxxx	Catalyst 4500 Enterprise Services Software
S45EK9-12xxxx	Catalyst 4500 Enterprise Services Software with 3DES

Catalyst 4x00 Modules

WS-X4124-FX-MT	Catalyst 4500 FE Switching module, 24-port 100FX (MTRJ)
WS-X4148-FE-BD-LC	Catalyst 4500 FE module, 48-port BX-D (LC) (1550)
WS-X4148-FE-LX-MT	Catalyst 4500 FE module, 48-port 100LX-10 SMF (MTRJ)
WS-X4148-FX-MT	Catalyst 4500 FE Switching module, 48-port 100FX MMF (MTRJ)
WS-X4124-RJ45	Catalyst 4500 10/100 module, 24 ports (RJ-45)
WS-X4148-RJ	Catalyst 4500 10/100 Auto module, 48 ports (RJ-45)
WS-X4224-RJ45V	Catalyst 4500 10/100 PoE 802.3af 24 ports (RJ-45)
WS-X4148-RJ21	Catalyst 4500 10/100 module, 48-port Telco (4xRJ21)
WS-X4148-RJ45V	Catalyst 4500 pre-standard PoE 10/100, 48 ports (RJ-45)
WS-X4248-RJ21V	Catalyst 4500 PoE 802.3af 10/100, 48 ports (RJ-21)
WS-X4248-RJ45V	Catalyst 4500 PoE 802.3af 10/100, 48 ports (RJ-45)
WS-X4232-GB-RJ	Catalyst 4500 32-10/100 (RJ-45), 2 GbE (GBIC)
WS-X4232-RJ-XX	Catalyst 4500 10/100 module, 32 ports (RJ-45) + modular uplinks
WS-X4424-GB-RJ45	Catalyst 4500 24-port 10/100/1000 module (RJ-45)
WS-X4306-GB	Catalyst 4500 GbE module, 6 ports (GBIC)
WS-X4506-GB-T	Catalyst 4500 6-port 10/100/1000 PoE or SFP (optional)
WS-X4302-GB	Catalyst 4500 GbE module, 2 ports (GBIC)
WS-X4418-GB	Catalyst 4500 GbE module, Server Switching 18 ports (GBIC)
WS-X4448-GB-RJ45	Catalyst 4500 48-port 10/100/1000 module (RJ-45)
WS-X4448-GB-SFP	Catalyst 4500 48-port 1000BASE-X (SFPs optional)
WS-X4524-GB-RJ45V	Catalyst 4500 PoE 802.3af 10/100/1000 24 ports (RJ-45)
WS-X4548-GB-RJ45	Catalyst 4500 Enhanced 48-port 10/100/1000 BASE-T (RJ-45)
WS-X4548-GB-RJ45V	Catalyst 4500 PoE 802.3af 10/100/1000, 48 ports (RJ-45)

Power Supplies

PWR-C45-4200ACV	Catalyst 4500 4200W AC dual input power supply (Data + PoE)
PWR-C45-4200ACV/2	Catalyst 4500 4200W AC dual input power supply (Data + PoE)
PWR-C45-2800ACV	Catalyst 4500 2800W AC power supply (Data + PoE)
PWR-C45-2800ACV/2	Catalyst 4500 2800W AC power supply (Data + PoE)
PWR-C45-1400AC	Catalyst 4500 1400W AC power supply (Data Only)
PWR-C45-1400AC/2	Catalyst 4500 1400W AC power supply redundant (Data Only)
PWR-C45-1400DC-P	Catalyst 4500 1400W DC power supply with Int. PEM
PWR-C45-1400DC-P/2	Catalyst 4500 1400W DC power supply redundant with Int. PEM
PWR-C45-1400DC	Catalyst 4500 1400W DC Triple Input SP power supply (Data Only)
PWR-C45-1400DC/2	Catalyst 4500 1400W DC Triple Input SP power supply (Data Only)
PWR-C45-1300ACV	Catalyst 4500 1300W AC power supply (Data + PoE)
PWR-C45-1300ACV/2	Catalyst 4500 1300W AC power supply (Data + PoE)
PWR-C45-1000AC	Catalyst 4500 1000W AC power supply (Data Only)
PWR-C45-1000AC/2	Catalyst 4500 1000W AC power supply redundant (Data Only)
WS-P4502-1PSU	Catalyst 4500 Aux. Power Shelf (2 slots), including one PWR-4502
PWR-4502	Catalyst 4500 Aux. Power Shelf redundant power supply

1. This is only a small subset of all parts available via URL listed under "For More Information." Some parts have restricted access or are not available through distribution channels. Resellers: For latest part number and pricing info, see the *Distribution Product Reference Guide* at: <http://www.cisco.com/dprg> (limited country availability).


For More Information

See the Catalyst 4500 series Website:

<http://www.cisco.com/en/US/products/hw/switches/ps4324/index.html>

Cisco Catalyst 6500 Series

The Catalyst 6500 Family delivers highly available secure converged network services for the Enterprise and Service Provider networks. It is designed to address the increased requirements for gigabit scalability, high-availability, rich services, and multilayer switching in backbone, distribution, and wiring closet topologies as well as datacenter environments. The Catalyst 6500 Family delivers exceptional scalability and price/performance, supporting a wide range of interface densities, performance, and integration of powerful service modules.



When to Sell

Sell This Product

Catalyst 6503-E

Catalyst 6504-E

Catalyst 6506-E

Catalyst 6509-E

Catalyst 6513

Supervisor Engine 720

Supervisor Engine 32

When a Customer Needs These Features

- A low-density, wiring-closet chassis sharing interface modules and supervisor engines with larger chassis for common sparring
- A small factor high performance, chassis sharing interface modules and supervisor engines with larger chassis for common sparring, suitable for small/medium enterprise core/distribution. Metro edge and enterprise wan edge
- A traditional chassis for the wiring closet, distribution and core, data center, and WAN edge
- A traditional chassis for the wiring closet, distribution and core, data center, and WAN edge
- A high capacity chassis for Ethernet connectivity, with slots to spare for services modules providing network security and management
- Intelligent, High performance Core, Distribution and Data Center deployments
- Intelligent Access Layer and Wan Edge

Key Features

- Cisco IOS Software Modularity—Modularity boosts operational efficiency and minimizes downtime. Enabling modular allows Cisco IOS subsystems to run as independent, self-healing processes minimizing unplanned downtime through fault containment and stateful process restarts; simplifies software changes through subsystem In-Service Software Upgrades (ISSU), and enables process-level, automated policy control by integrating the Embedded Event Manager (EEM)
- Maximum PoE Scalability—Provides power scalability needed to support high-density PoE deployments; 6- and 9-slot chassis (C6506-E and C6509-E models) are designed to scale beyond the current 6000W power supplies; All existing supervisors, line cards, switch fabrics, and software releases are supported in the E-series chassis
- Supervisor Engine 720—Positioned for enterprise core, distribution, and data centers: Up to 720 Gbps Switch Fabric Connection and up to 400 Mpps of switching performance; Supports new accelerated Cisco Express Forwarding (CEF720) and distributed Cisco Express Forwarding (dCEF720) interface modules; IPv6 and MPLS supported in hardware. Supports Layer 3 routing protocols
- Supervisor Engine 32—Positioned for the intelligent wiring-closet and low end cost effective core and distribution deployments: incorporates a 32-Gbps shared bus connection to modules; Supports up to 15 Mpps of switching performance; Centralized Layer 2 and Layer 3 forwarding and is available in two models, either 8-port 1GE model or 2-port 10GbE uplinks

Competitive Products

- Extreme: Black Diamond
- Foundry: Big Iron
- Lucent: Cajun Switch 550
- Nortel: Passport 8600

Specifications

Feature	6503-E	6504-E	6506-E	6509-E	6509-NEB-A	6513
Modular Slots	3	4	6	9	9	13
Gigabit Ethernet GBIC/SFP density	98	144	242	386	384	410
10 GbE XENPAK/X2 port density	8	12	20	32	32	20
10/100/1000 density	97	144	241	385	385	577
10/100 density	192	288	480	768	768	1152
100BASE-FX density	96	144	240	384	384	576

Feature	6503-E	6504-E	6506-E	6509-E	6509-NEB-A	6513
Max. watt power consumption(redundant mode)						
AC Internal ¹	1,400	2,700	6,000	6,000	6,000	6,000
DC Internal ¹	950	2,700	4,000	4,000	4,000	4,000
Max. number of Class 3 devices (15.4W)Max. power supplies						
AC Internal ¹	48	110	284	288	215	281
DC Internal ¹	31	110	173	184	206	176
WAN Interfaces	DS0 to OC-48	DS0 to OC-48	DS0 to OC-48	DS0 to OC-48		DS0 to OC-48
Available Bandwidth	Scalable to 240 Gbps	Scalable to 320 Gbps	Scalable to 480 Gbps	Scalable to 720 Gbps		Scalable to 720 Gbps
Throughput	Scalable to 99 Mpps	Scalable to 147 Mpps	Scalable to 243 Mpps	Scalable to 387 Mpps		Scalable to 425 Mpps
Redundant Supervisor	Yes	Yes	Yes	Yes		Yes
Hot-Swappable Power Supplies	Yes	Yes	Yes	Yes		Yes
VLAN Maximum	4096	4096	4096	4096		4096
FEC/GEC	Yes	Yes	Yes	Yes		Yes
Management Capabilities	CiscoWorks 2000, RMON, Enhanced Switched Port Analyzer (ESPA), SNMP, Telnet, BOOTP, and Trivial File Transfer Protocol (TFTP)	Same as Catalyst 6503-E	Same as Catalyst 6503-E	Same as Catalyst 6503-E		Same as Catalyst 6503-E
Dimensions (H x W x D)	7 x 17.5 x 21.7 in. (17.8 x 44.1 x 55.2 cm.)	8.7 x 17.5 x 21.6 in. (22.2 x 44.5 x 55.2 cm.)	19.2 x 17.5 x 18.2 in. (48.8 x 44.5 x 46.0 cm.)	24.5 x 17.5 x 18.2 in. (62.2 x 44.5 x 46.0 cm.)	33.3 x 17.3 x 18.1 in. (84.6 x 43.7 x 46.0 cm.)	33.3 x 17.3 x 18.1 in. (84.6 x 43.7 x 46.0 cm.)
Rack Unit (RU)	4	5	12	15	21	20
Unit weight (chassis only)	33 lbs. (15.0 kgs.)	40 lbs. (18.1 kgs.)	50 lbs. (22.7 kgs.)	60 lbs. (27.3 kgs.)	55 lbs. (24.9 kgs.)	98 lbs. (45.0 kgs.)

1. Redundant Mode

	WS-SUP720-3BXL WS-SUP720-3B	WS-SUP32-10GE-3B WS-SUP32-GE-3B	WS-X6K-S2U-MSFC2 WS-X6K-S2-MSFC2 WS-X6K-S2U-PFC2
Supervisor Engines			
Chassis supported	All	All	All
Bandwidth per slot (Gbps)	40GB	32GB shared	32GB shared/8GB if SFM present
Total bandwidth (Gbps)	720	32	256
Packets per second (Mpps)	407	15	210
MAC addresses supported	64K Max./32K effective	64K Max./32K effective	128K Max./32K effective
Routes supported	1,000,000	1,000,000 if PFC3BXL	256,000
Onboard memory (DRAM)	Up to 1GB	Up to 1GB	Up to 512MB

Selected Part Numbers and Ordering Information¹

Catalyst 6500 Chassis

WS-C6503-E	Enhanced 3-slot chassis, no fan or power supply
WS-C6504-E	Enhanced 4-slot 6500 chassis, no fan or power supply
WS-C6506-E	Enhanced 6-slot 6500 chassis, no fan or power supply
WS-C6509-E	Enhanced 9-slot 6500 chassis, no fan or power supply
WS-C6509-NEB-A	9-slot 6500 chassis (vertically oriented slots), no fan or power supply
WS-C6513	13-slot 6500 chassis, no fan or power supply

Catalyst 6500 Supervisor Engines and Switch Fabric Modules

WS-SUP720-3BXL	Supervisor 720 fabric MSFC3 PFC3BXL
WS-SUP720-3B	Supervisor 720 fabric MSFC3 PFC3B
WS-SUP720	Supervisor 720 fabric MSFC3 PFC3A
WS-SUP32-10GE-3B	Supervisor 32 with 2 ports 10 GbE and PFC3B
WS-SUP32-GE-3B	Supervisor 32 with 8 GbE uplinks and PFC3B
WS-X6K-S2U-MSFC2	Supervisor 2U, 256 MB Supervisor, 512 MB MSFC2
WS-X6K-S2-MSFC2	Supervisor Engine-2, 2 GbE, plus MSFC-2/PFC-2
WS-X6K-S2-PFC2	Supervisor Engine-2, 2 GbE, plus PFC-2
WS-X6500-SFM2	Switch Fabric module 2

Catalyst 6500 10 Gigabit Ethernet

WS-X6704-10GE	4-port 10 Gigabit Ethernet module (requires XENPAK)
---------------	---

Catalyst 6500 Gigabit Ethernet

WS-X6408A-GBIC	8-port Gigabit Ethernet module, enhanced QoS (requires GBICs)
WS-X6516A-GBIC	16-port Gigabit Ethernet module, fabric-enabled (requires GBICs)
WS-X6724-SFP	24-port Gigabit Ethernet module, fabric-enabled (requires SFPs)
WS-X6748-SFP	48-port Gigabit Ethernet module, fabric-enabled (requires SFPs)

Catalyst 6500 10/100/1000 Ethernet

WS-X6148A-GE-TX	48-port 10/100/1000 with Jumbo Frame, RJ-45
WS-X6148A-GE-45AF	48-port PoE 802.3af 10/100/1000, with Jumbo Frame
WS-X6516-GE-TX	16-port 10/100/1000 Gigabit Ethernet module, cross-bar
WS-X6548-GE-TX	48-port fabric-enabled 10/100/1000 module
WS-X6548-GE-45AF	PoE 802.3af 10/100/1000 48-port (RJ-45) CEF256 card
WS-X6748-GE-TX	48-port 10/100/1000 Gigabit Ethernet module, fabric-enabled, RJ-45

Catalyst 6500 10/100 Ethernet

WS-X6148-RJ-21	48-port 10/100 upgradeable to voice, RJ-21
WS-X6148-21AF	PoE 802.3af 10/100, 48-port (RJ-21) line card
WS-X6148-RJ21V	48-port 10/100 Inline Power module, RJ-21
WS-X6148A-RJ-45	48-port 10/100 with TDR, upgradeable to PoE 802.3af
WS-X6148A-45AF	48-port PoE 802.3af 10/100, card with TDR
WS-X6148X2-RJ-45	96-port 10/100 (RJ-45), upgradeable to PoE 802.3af
WS-X6148X2-45AF	PoE 802.3af 10/100, 96-port (RJ-45) line card
WS-X6196-RJ-21	96-port 10/100 upgradeable to PoE 802.3af
WS-X6196-21AF	96-port, PoE 802.3af 10/100-RJ-21
WS-X6548-RJ-21	48-port 10/100, RJ-21, fabric-enabled
WS-X6548-RJ-45	48-port 10/100, RJ-45, x-bar

Catalyst 6500 10FL/100FX Ethernet

WS-X6024-10FL-MT	24-port 10BASE-FL MT-RJ module
WS-X6148-FE-SFP	48-port 100BASE-X module (requires SFP)
WS-X6524-100FX-MM	24-port 100FX, MT-RJ, fabric-enabled

WAN Interface Modules

WS-X6582-2PA	Enhanced FlexWAN module, fabric-enabled
OSM-1CHOC12/T1-SI	1-port CHOC-12/CHSTM-4 (SM-IR), to DS0 and T1/E1, with 4 GbE
OSM-12CT3/T1	12-port Channelized DS-3 to DS-1/DS-0
OSM-1CHOC12/T3-SI	1-port CHOC-12/CHSTM-4 OSM, to T3/E3, SM-IR, with 4 GbE
OSM-20C12-ATM-MM+	Enhanced 2-port OC12/STM4 ATM OSM+, MM, with 4 GbE
OSM-20C12-ATM-SI+	Enhanced 2-port OC12/STM4 ATM OSM+, SI, with 4 GbE
OSM-20C48/1DPT-SS	2-port OC-48/STM-16 POS/DPT OSM, SM-SR, with 4 GbE
OSM-20C48/1DPT-SI	2-port OC-48/STM-16 POS/DPT OSM, SM-IR, with 4 GbE
OSM-20C48/1DPT-SL	2-port OC-48/STM-16 POS/DPT OSM, SM-LR, with 4 GbE
OSM-80C3-POS-SL+	Enhanced 8-port OC-3/STM-1 SONET/SDH SM-LR OSM, with 4 GbE
OSM-80C3-POS-SI+	Enhanced 8-port OC-3/STM-1 SONET/SDH SM-IR OSM, with 4 GbE
OSM-40C3-POS-SI+	Enhanced 4-port OC-3/STM-1 SONET/SDH SM-IR OSM, with 4 GbE
OSM-20C12-POS-MM+	Enhanced 2-port OC-12/STM-4 SONET/SDH OSM, MM, with 4 GbE
OSM-40C12-POS-SI+	Enhanced 4-port OC-12/STM-4 SONET/SDH OSM, SM-IR, with 4 GbE
OSM-20C12-POS-SI+	Enhanced 2-port OC-12/STM-4 SONET/SDH OSM, SM-IR, with 4 GbE
OSM-10C48-POS-SS+	Enhanced 1-port OC-48/STM-16 SONET/SDH OSM, SM-SR, with 4 GbE
OSM-10C48-POS-SI+	Enhanced 1-port OC-48/STM-16 SONET/SDH OSM, SM-IR, with 4 GbE
OSM-10C48-POS-SL+	Enhanced 1-port OC-48/STM-16 SONET/SDH OSM, SM-LR, with 4 GbE
OSM-2+4GE-WAN+	Enhanced OSM with 4 GbE WAN ports and 2 GbE LAN ports

Catalyst 6500 Power Supplies

PWR-950-AC	950W AC power supply for Cisco 7603 and Catalyst 6503
PWR-950-DC	950W DC power supply for Cisco 7603 and Catalyst 6503
PWR-1400-AC	1400W AC power supply for Cisco 7603 and Catalyst 6503 chassis
PWR-2700-AC/4	2700W AC power supply for Cisco 7604/6504-E
PWR-2700-DC/4	2700W DC power supply for Cisco 7604/6504-E
PEM-15A-AC	Power Entry module for Cisco 7603 and Catalyst 6503(950W AC power supply)
PEM-20A-AC+	Power Entry module used with 1400W AC power supply for Cisco 7603 and Catalyst WS-C6503
PEM-DC/3	DC Power Entry module for Cisco 7603 and Catalyst 6503
WS-CDC-1300W	Catalyst 6000 1300W DC power supply
WS-CAC-3000W	Catalyst 6500 3000W AC power supply
WS-CDC-2500W	Catalyst 6000 2500W DC power supply
WS-CAC-4000W-INT	4000W AC power supply, International (cable included)
WS-CAC-4000W-US	4000W AC power supply for U.S. (cable attached)
PWR-4000-DC	4000W DC power supply for Cisco 7609/13, Catalyst 6509/13 chassis
WS-CAC-6000W	Catalyst 6500 6000W AC power supply

Catalyst 6500 Optics

GLC-FE-100FX	100BASE-FX SFP for FE port
GLC-FE-100LX	100BASE-LX SFP for FE port
GLC-FE-100BX-U	100BASE-BX10-U SFP
GLC-FE-100BX-D	100BASE-BX10-D SFP
GLC-LH-SM	GE SFP, LC connector LX/LH transceiver
GLC-LH-SM=	GE SFP, LC connector LX/LH transceiver
GLC-SX-MM	GE SFP, LC connector SX transceiver
GLC-SX-MM=	GE SFP, LC connector SX transceiver
GLC-ZX-SM	1000BASE-ZX SFP
GLC-ZX-SM=	1000BASE-ZX SFP
GLC-T	1000BASE-T SFP
GLC-T=	1000BASE-T SFP
WS-G5483=	1000BASE-T GBIC
WS-G5484	1000BASE-SX Short Wavelength GBIC (Multimode only)
WS-G5484=	1000BASE-SX Short Wavelength GBIC (Multimode only)
WS-G5486	1000BASE-LX/LH long haul GBIC (singlemode or multimode)
WS-G5486=	1000BASE-LX/LH long haul GBIC (singlemode or multimode)
WS-G5487	1000Base-ZX extended reach GBIC(singlemode)
WS-G5487=	1000Base-ZX extended reach GBIC(singlemode)
XENPAK-10GB-CX4	Cisco 10GBASE-CX4 XENPAK Module
XENPAK-10GB-CX4=	Cisco 10GBASE-CX4 XENPAK Module
XENPAK-10GB-ER	10GBASE-ER XENPAK Module
XENPAK-10GB-ER=	10GBASE-ER XENPAK Module
XENPAK-10GB-LR=	10GBASE-LR XENPAK module
XENPAK-10GB-LX4	10GBASE-LX4 XENPAK Module
XENPAK-10GB-LX4=	10GBASE-LX4 XENPAK Module
XENPAK-10GB-SR	10GBASE-SR XENPAK Module
XENPAK-10GB-SR=	10GBASE-SR XENPAK Module
XENPAK-10GB-ZR	10GBASE-ZR XENPAK Module
XENPAK-10GB-ZR=	10GBASE-ZR XENPAK Module

1. This is only a small subset of all parts available via URL listed under "For More Information." Some parts have restricted access or are not available through distribution channels.

For More Information

See the Catalyst 6500 Family Website: <http://www.cisco.com/go/6000>



Wireless LAN

Wireless LAN at a Glance (IEEE 802.11 a/b/g)

Product	Features	Page
Cisco Aironet 1000 Series Lightweight Access Point	- Standard-based Lightweight Access Point Protocol (LWAPP) to help ensure interoperability with the existing infrastructure - Cost effective way of delivering advanced WLAN services to enterprise deployments - IEEE 802.11a/b/g access point with internal antennas - Dual 802.11a and 802.11b/g radios provide flexibility for users to meet the performance requirements of the most demanding applications, while security and management capabilities provide uncompromised support for interoperable IEEE 802.11i security and ease of deployment	3-2
Cisco Aironet 1130AG Series Access Point	- With two high-performance radios with integrated antennas, these access points provide simultaneous support for the 802.11a and 802.11g standards, offering 108 Mbps of capacity for your growing WLAN - Cost-compelling solution for a high-capacity, high-security, enterprise-class WLAN - Ideal for easy deployment offices and similar facilities	3-3
Cisco Aironet 1200 Series Access Point	- Modular design allows single or dual radio configuration for up to 54 Mbps connectivity in both the 2.4 and 5 GHz bands - May be field upgraded to support 802.11a with a hardware upgrade module	3-5
Cisco Aironet 1230AG Series Access Point	- Antenna connectors for both 2.4GHz and 5GHz radios ensure optimal coverage, range, and reliability in particularly warehouses, offices, and other high multipath environments. - Cast aluminum case and rugged features support deployment in industrial environments. - Broad operating temperature range and UL 2043 certification for plenum rating requirements set by local fire codes supports installation in environmental air spaces	3-7
Cisco Aironet 1240AG Series Access Point	- Rugged enterprise-class AP designed for indoor industrial deployments and installations that require antenna versatility - Ideal for factories, warehouses and retailers - Link-roll flexibility allows the AP to perform as a wireless bridge between access points for backhaul to the network	3-9
Cisco Aironet 1300 Series Outdoor Access Point/Bridge	- Configurable for access point, bridge, or workgroup bridge roles - Support for both point-to-point or point-to-multipoint configurations - Industry leading range and throughput, supporting data rates up to 54 Mbps - Ruggedized enclosure optimized for harsh outdoor environments with extended operating temperature range - Integrated or optional external antennas for flexibility in deployment	3-11
Cisco Aironet 1500 Series Lightweight Outdoor Wireless Mesh Access Point	- Enable cost-effective, scalable deployment of secure outdoor wireless LANs - Dual-band, simultaneous support for IEEE 802.11a and 802.11b/g standards - Employs a patent-pending Adaptive Wireless Path Protocol to form a dynamic wireless mesh network between remote access points	3-13
Cisco Aironet 802.11a/b/g Wireless CardBus and PCI Adapter	- Secure network communications, with the Cisco Wireless Security Suite and support for Wi-Fi Protected Access (WPA) - Comprehensive utilities for flexible, easy configuration and management - High-performance 54 Mbps connectivity in the 2.4 and 5 GHz bandst - Superior range and throughput - World mode for international roaming	3-14
Cisco Aironet 1400 Series Wireless Bridge	- Support for both point-to-point or point-to-multipoint configurations - Range and throughput supporting data rates up to 54 Mbps - Enhanced security mechanisms based on 802.11 standards - Ruggedized enclosure optimized for harsh outdoor environments with extended operating temperature range	3-15
Cisco Antennas and Accessories	- A wide array of options - FCC-approved directional and omni-directional antennas - Low-loss cable, mounting hardware, and other accessories available	3-17
CiscoWorks Wireless LAN Solution Engine and CiscoWorks Wireless Solution Engine Express	- A hardware-based wireless LAN management solution that provides template-based configuration with user-defined groups to effectively manage a large number of access points and bridges. - Monitors LEAP authentication servers - Enhances security management through mis-configuration detection on access points and bridges	9-22

Product	Features	Page
CiscoWorks Wireless LAN Solution Engine Express	• CiscoWorks WLSE Express speeds deployment by automating configuration and setup, reducing the overall cost to provision WLANs	9
Cisco 2000 Series Wireless LAN Controller	• Ideal for enterprise wireless LAN deployments that require system-level security, scalability, and RF management • Leverages the LWAPP to centrally control Cisco Aironet Lightweight Access Points for WLAN performance optimization and automated network resiliency • Ideal for small and medium-sized enterprise environments. It supports up to six lightweight access points making it a cost-effective solution for small branch offices.	3-20
Cisco 4400 Series Wireless LAN Controller	• Ideal for enterprise wireless LAN deployments that require system-level security, scalability, and RF management • Leverages the LWAPP to centrally control Cisco Aironet Lightweight Access Points for WLAN performance optimization and automated network resiliency	3-22
Cisco Wireless Control System (WCS)	• Complete platform for enterprise-wide WLAN systems management • Wide range of tools for visualizing and controlling the air space • Provides a centralized platform for managing a complete network of Cisco WLAN controllers and lightweight access points, simplifying WLAN planning and deployment and creating a cost effective way of managing and securing ongoing wireless operations	3-23
Cisco Wireless Location Appliance	• Advanced and scalable location tracking that simultaneously tracks thousands of wireless users and devices to within a few meters of their physical location • Integrated location tracking using existing LWAPP enabled infrastructure, minimizing capital expenditures and helping ensure better WLAN visibility • Intuitive management GUI to centrally and easily add, configure, manage and upgrade multiple location appliances	3-24
Product Ordering Website	To place an order, visit the Cisco Ordering Website: http://www.cisco.com/en/US/ordering/index.shtml	

Cisco Aironet 1000 Series Lightweight Access Point

Cisco® 1000 Series lightweight access points handle real-time 802.11 radio functions within a Cisco wireless LAN, including radio transmit and receive, client probe requests, and air monitoring. These devices act as the eyes and ears of the wireless network, feeding valuable information to Cisco wireless LAN controllers and Cisco Wireless Control System (WCS) Software for real-time decisions. In addition, Cisco Aironet 1000 Series Lightweight Access Points handle time-sensitive functions, such as Layer 2 encryption, that enable Cisco wireless LANs to securely support voice, video, and data applications.



When to Sell

Sell This Product

Cisco Aironet 1000 Series Lightweight Access Point

When a Customer Needs These Features

- Designed for complex RF environments that require real-time RF management
- Cost effective way of adding location and wireless IPS to enterprise wireless LANs
- Centralized management and control makes it ideal for large, distributed enterprises

Key Features

- Standard-based LWAPP to help ensure interoperability with the existing infrastructure
- Zero-touch configuration and management that reduces the cost and time to deploy a wireless network
- Simultaneous air monitoring and data service that minimizes equipment requirements, simplifies network design and increases security through complete real-time monitoring across an entire network
- Internal and external antenna options
- Security that works with existing and planned security policies
- QoS to provide effective resource management of the air space

Chapter 3

Specifications

Features	Cisco Aironet 1000 Series Lightweight Access Point
Data Rates Supported	802.11a: 6, 9, 12, 18, 24, 36, 48, and 54 Mbps; 802.11b: 1, 2, 5.5, and 11 Mbps; 802.11g: 1, 2, 5.5, 6, 9, 11, 12, 18, 24, 36, 48, and 54 Mbps
Uplink	Carrier-Sense Multiple Access/Collision Avoidance (CSMA/CA)
Frequency Band and Operating	802.11a: 5.15 to 5.25 GHz, 5.25 to 5.35 GHz, 5.725 to 5.825 GHz; 802.11b: 2.412 to 2.497 GHz, 802.11g: 2.412 to 2.497 GHz
Nonoverlapping Channels	802.11a: Up to 12, 802.11b/g: Up to 3, Dependent upon country-specific regulatory approvals
Wireless Modulation	802.11a: Orthogonal frequency division multiplexing (OFDM), 802.11b: Direct sequence spread spectrum (DSSS), 802.11g: DSSS and OFDM
Receive Sensitivity (Typical)	802.11a: -73 dBm at 54 Mbps, -75 dBm at 48 Mbps, -80 dBm at 36 Mbps, -83 dBm at 24 Mbps, -87 dBm at 18 Mbps, -89 dBm at 12 Mbps, -90 dBm at 9 Mbps, -91 dBm at 6 Mbps; 802.11b: -89 dBm at 11 Mbps, -91 dBm at 5.5 Mbps, -92 dBm at 2 Mbps, -94 dBm at 1 Mbps; 802.11g: -73 dBm at 54 Mbps, -75 dBm at 48 Mbps, -80 dBm at 36 Mbps, -84 dBm at 24 Mbps, -87 dBm at 18 Mbps, -90 dBm at 12 Mbps, -89 dBm at 11 Mbps, -91 dBm at 9 Mbps, -91 dBm at 6 Mbps, -91 dBm at 5.5 Mbps, -92 dBm at 2 Mbps, -94 dBm at 1 Mbps
Available Transmit Power Settings	100, 50, 25, 12.5, and 6.25 percent; 802.11a: 50 mW (17 dBm) conducted; 802.11b: 100 mW (20 dBm) conducted; 802.11g: 100 mW (20 dBm) conducted, Maximum power setting will vary according to channel and individual country regulations
Range	802.11a: Indoor-45 ft (14 m) @ 54 Mbps, 110 ft (34 m) @ 18 Mbps, 165 ft (50 m) @ 6 Mbps; Outdoor- 100 ft (30 m) @ 54 Mbps, 600 ft (183 m) @ 18 Mbps, 1000 ft (305 m) @ 6
Antenna Connectors	AIR-AP1010-x-K9: None; AIR-AP1020-x-K9 and AIR-AP1030-x-K9: 802.11a: One male RP-TNC connector, 802.11b/g: Two male RP-TNC connectors
Integrated Antennas	802.11a/b/g: Two 180-degree sectorized antennas
Compliance	Customers are responsible for verifying approval for use in their country. Please see http://www.cisco.com/go/aironet/compliance to verify approval and to identify the regulatory domain that corresponds to a particular country. All regulatory domains may not have been approved. As they are approved, the part numbers will be available on the Global Price List.
Interface and Indicators	Network: 10/100 Mbps Ethernet (RJ-45 link, activity); Other indicators: Power, alarm
Dimensions (H x W x D)	6 x 4.4 x 1.6 in. (15.2 x 11.2 x 4.1 cm)
Weight	Access point and ceiling clip: 1.3 lb (0.6 kg); Access point with optional wall brackets kit: 2.2 lb (1 kg)
Environmental	Operating: 32 to 122°F (0 to 50°C); Storage: -13 to 158°F (-25 to 70°C)
Power	48 VDC; 250 mA; 10W; Power over Ethernet (IEEE 802.3af); Optional AC power supply (AIR-PWR-1000=)
Warranty	One year

Selected Part Numbers and Ordering Information

Cisco Aironet 1000 Series Lightweight Access Point

AIR-AP1010-X-K9	802.11a/b/g AP w/ integrated antennas, X=regulatory domain
AIR-AP1020-X-K9	802.11a/b/g AP w/ integrated antenna and RP-TNC, X=regulatory domain
AIR-AP1030-X-K9	802.11a/b/g Remote Edge AP w/ integrated antenna and RP-TNC, X=regulatory domain

For More Information

See the Cisco Wireless Website: <http://www.cisco.com/go/wireless>

Cisco Aironet 1130AG Series Access Point

With two high-performance radios, these access points provide simultaneous support for the 802.11a and 802.11g standards, offering 108 Mbps of capacity for your growing WLAN. Incorporating AES encryption in hardware, the Cisco Aironet 1130AG Series complies with the 802.11i security standard and is WPA2-certified, helping to assure that a network employs the strongest security available while maintaining interoperability with products from other manufacturers. Additional design features, including diversity antennas with omnidirectional coverage and an unobtrusive form factor, along with an attractive price, provide low total cost of ownership. For office environments, the Cisco Aironet 1130AG Series is a cost-compelling solution for a high-capacity, high-security, enterprise-class WLAN.



When to Sell

Sell This Product

Cisco Aironet 1130AG Series Access Point

When a Customer Needs These Features

- A high-capacity and high-security WLAN in the enterprise office
- Two high-performance radios providing simultaneous support for the 802.11a and 802.11g standards offering 108 Mbps capacity for your growing WLAN
- A low-profile access point that blends into the environment and is easy to deploy

Key Features

- IEEE 802.11a and 802.11g radios with simultaneous dual band support provides 108 Mbps capacity. Works with dual band clients to optimize usage of network bandwidth while providing backwards compatibility with 802.11b clients; Complies with 802.11i security standards and is WPA2 certified; Incorporates AES encryption in hardware;
- Provides robust signals to long distances and mitigates the effects of multipath signal propagation for more consistent coverage
- Orderable supporting either Cisco IOS® Software or the Lightweight Access Point Protocol (LWAPP); uses radio and network management features for simplified deployment, along with built-in omnidirectional antennas that provide robust and predictable WLAN coverage for offices and similar RF environments
- Variable transmit power settings that allows access point coverage to be tuned for differing requirements
- Integrated 4.5 dBi antennas—Complete system deployable out of the box without external antennas; specifically designed to provide omni-directional coverage for offices and similar radio frequency environments. Low 0.5 mW setting supports closer spacing of access points in high density deployments
- Wi-Fi Certified

Specifications

Features	Cisco Aironet 1130AG Series Access Point
Data rates supported	802.11a: 6, 9, 12, 18, 24, 36, 48, and 54 Mbps; 802.11g: 1, 2, 5.5, 6, 9, 11, 12, 18, 24, 36, 48, and 54 Mbps
Software	Cisco IOS Software Release 12.3(4)JA or later Lightweight Access Point Protocol (LWAPP) 3.1 or later
Network standard	IEEE 802.11a, 802.11b and 802.11g
Uplink	Autosensing 802.3 10/100BaseT Ethernet
Frequency band and Operating Channels	Americas (FCC)= 2.412 to 2.462 GHz-11 channels; 5.15 to 5.35, 5.725 to 5.825 GHz-12 channels China= 2.412 to 2.472 GHz-13 channels; 5.725 to 5.825 GHz; 4 channels ETSI= 2.412 to 2.472 GHz-13 channels; 5.15 to 5.725 GHz; 19 channels Japan (TELEC)= 2.412 to 2.472 GHz-13 channels Orthogonal Frequency Division Multiplexing (OFDM); 2.412 to 2.484 GHz; 14 channels Complementary Code Keying (CCK); 5.15 to 5.25 GHz-4 channels; North America= 2.412 to 2.462 GHz, 11 channels; 5.15 to 5.35, 5.725 to 5.825 GHz, 12 channels
Non-overlapping channels	802.11a—Up to 19; 802.11b/g—3
Receive sensitivity	802.11a—6 Mbps: -87 dBm, 9 Mbps: -86 dBm, 12 Mbps: -85 dBm, 18 Mbps: -84 dBm, 24 Mbps: -80 dBm, 36 Mbps: -78 dBm, 48 Mbps: -73 dBm, 54 Mbps: -71 dBm; 802.11g—1 Mbps: -93 dBm, 2 Mbps: -91 dBm, 5.5 Mbps: -88 dBm, 6 Mbps: -86 dBm, 9 Mbps: -85 dBm, 11 Mbps: -85 dBm, 12 Mbps: -84 dBm, 18 Mbps: -83 dBm, 24 Mbps: -79 dBm, 36 Mbps: -77 dBm, 48 Mbps: -72 dBm, 54 Mbps: -70 dBm
Available transmit power settings	802.11a: OFDM: 50 mW (17 dBm), 32 mW (15 dBm), 25 mW (14 dBm), 10 mW (11 dBm), 5 mW (8 dBm), 3 mW (5 dBm), 2 mW (2 dBm), 1 mW (-1 dBm); 802.11g: CCK—100 mW (20 dBm), 50 mW (17 dBm), 25 mW (14 dBm), 12 mW (11 dBm), 6 mW (8 dBm), 3 mW (5 dBm), 2 mW (2 dBm), 1 mW (-1 dBm); OFDM—50 mW (17 dBm), 25 mW (14 dBm), 10 mW (11 dBm), 5 mW (8 dBm), 3 mW (5 dBm), 1 mW (2 dBm), 1 mW (-1 dBm) Maximum power setting will vary by channel and according to individual country regulations.
Range	Indoor (Distance across open office environment): 802.11a: 80 ft (24 m) @ 54 Mbps, 150 ft (45 m) @ 48 Mbps, 200 ft (60 m) @ 36 Mbps, 225 ft (69 m) @ 24 Mbps, 250 ft (76 m) @ 18 Mbps, 275 ft (84 m) @ 12 Mbps, 300 ft (91 m) @ 9 Mbps, 325 ft (100 m) @ 6 Mbps; 802.11g: 1000 ft (30 m) @ 54 Mbps, 175 ft (53 m) @ 48 Mbps, 250 ft (76 m) @ 36 Mbps, 275 ft (84 m) @ 24 Mbps, 325 ft (100 m) @ 18 Mbps, 350 ft (107 m) @ 12 Mbps, 360 ft (110 m) @ 11 Mbps, 375 ft (114 m) @ 9 Mbps, 400 ft (122 m) @ 6 Mbps Outdoor: 802.11a: 100 ft (30 m) @ 54 Mbps, 300 ft (91 m) @ 48 Mbps, 425 ft (130 m) @ 36 Mbps, 500 ft (152 m) @ 24 Mbps, 550 ft (168 m) @ 18 Mbps, 600 ft (183 m) @ 12 Mbps, 625 ft (190 m) @ 9 Mbps, 650 ft (198 m) @ 6 Mbps; 802.11g: 120 ft (37 m) @ 54 Mbps; 350 ft (107 m) @ 48 Mbps; 550 ft (168 m) @ 36 Mbps; 650 ft (198 m) @ 24 Mbps; 750 ft (229 m) @ 18 Mbps; 800 ft (244 m) @ 12 Mbps; 820 ft (250 m) @ 11 Mbps; 875 ft (267 m) @ 9 Mbps; 900 ft (274 m) @ 6 Mbps; 910 ft (277 m) @ 5.5 Mbps; 940 ft (287 m) @ 2 Mbps; 950 ft (290 m) @ 1 Mbps Ranges and actual throughput vary based upon numerous environmental factors so individual performance may differ.
Compliance	Customers are responsible for verifying approval for use in their country. Please see http://www.cisco.com/go/aironet/compliance to verify approval and to identify the regulatory domain that corresponds to a particular country. All regulatory domains may not have been approved. As they are approved, the part numbers will be available on the Global Price List.
SNMP compliance	MIB I and MIB II
Antennas	2.4 GHz: Gain 3.0 dBi, Horizontal Beamwidth 360°; 5 GHz: Gain 4.5 dBi, Horizontal Beamwidth 360°
Security architecture client authentication and encryption (Cisco Wireless Security Suite supporting WPA and WPA2)	Authentication: 802.1X support, including Cisco LEAP, EAP-Flexible Authentication via Secure Tunneling (EAP-FAST), Protected EAP- Generic Token Card (PEAP-GTC), PEAP-Microsoft Challenge Authentication Protocol Version 2 (PEAP-MSCHAPv2), EAP-Transport Layer Security (EAP-TLS), EAP-Tunneled TLS (EAP-TTLS), and EAP-Subscriber Identity Module (EAP-SIM) to yield mutual authentication and dynamic, per-user, per-session encryption keys (WPA and WPA2); MAC address and by standard 802.11 authentication mechanisms; Encryption: AES-CCMP encryption (WPA2); TKIP encryption enhancements: key hashing (per-packet keying), message integrity check (MIC) and broadcast key rotation via Cisco TKIP or WPA TKIP; Support for static and dynamic IEEE 802.11 WEP keys of 40 bits and 128 bits

Features		Cisco Aironet 1130AG Series Access Point
Status LEDs	External: Status LED indicates operating state, association status, error/warning condition, boot sequence and maintenance status Internal: Ethernet LED indicates activity over the Ethernet, status; Radio LED indicates activity over the radios, status	
Network Management	BootP, Secure Shell (SSH) Protocol, Secure HTTP (HTTPS), Trivial File Transfer Protocol (TFTP), FTP, Telnet, console port, Simple Network Management Protocol (SNMP) MIB I and MIB II, CiscoWorks Resource Manager Essentials (RME), CiscoWorks Software Image Manager (SWIM), CiscoWorks Campus Manager, CiscoWorks CiscoView, and CiscoWorks WLSE	
Dimensions (H x W x D)	7.5 x 7.5 x 1.3 in. (19.1 x 19.1 x 3.3 cm)	
Weight	1.5 lbs. (0.67 kg)	
Environmental	32-104° F (0-40° C); 10-90% humidity (non-condensing)	
System Memory	32 MB RAM; 16 MB FLASH	
Input Power Requirements	100-240 VAC 50-60Hz (power supply); 36-57 VDC (device)	
Power Draw	12.2 watts, max	
Warranty	One year	

Selected Part Numbers and Ordering Information

Cisco Aironet 1130AG Series Access Point

AIR-AP1131AG-A-K9	802.11a/g Non-modular IOS AP; Integrated Antennas; Israel Cnfg
AIR-AP1131AG-C-K9	802.11a/g Non-modular IOS AP; Integrated Antennas; Korea Cnfg
AIR-AP1131AG-E-K9	802.11a/g Non-modular IOS AP; Integrated Antennas; Japan2 Cnfg
AIR-AP1131AG-I-K9	802.11a/g Non-modular IOS AP; Integrated Antennas; Israel Cnfg
AIR-AP1131AG-J-K9	802.11a/g Non-modular IOS AP; Integrated Antennas; Singapore Cnfg
AIR-AP1131AG-K-K9	802.11a/g Non-modular IOS AP; Integrated Antennas; Korea Cnfg
AIR-AP1131AG-N-K9	802.11a/g Non-modular IOS AP; Integrated Antennas; Taiwan Cnfg
AIR-AP1131AG-P-K9	802.11a/g Non-modular IOS AP; Integrated Antennas; Japan2 Cnfg
AIR-AP1131AG-S-K9	802.11a/g Non-modular IOS AP; Integrated Antennas; Singapore Cnfg
AIR-AP1131AG-T-K9	802.11a/g Non-modular IOS AP; Integrated Antennas; Taiwan Cnfg
AIR-LAP1131AG-A-K9	802.11a/g Non-modular LWAPP AP; Integrated Antennas; FCC Cnfg
AIR-LAP1131AG-C-K9	802.11a/g Non-modular LWAPP AP; Integrated Antennas; China Cnfg
AIR-LAP1131AG-E-K9	802.11a/g Non-modular LWAPP AP; Integrated Antennas; ETSI Cnfg
AIR-LAP1131AG-I-K9	802.11a/g Non-modular LWAPP AP; Integrated Antennas; Israel Cnfg
AIR-LAP1131AG-K-K9	802.11a/g Non-modular LWAPP AP; Integrated Antennas; Korea Cnfg
AIR-LAP1131AG-N-K9	802.11a/g Non-modular LWAPP AP; Integrated Antennas; N. America Cnfg (not FCC)
AIR-LAP1131AG-P-K9	802.11a/g Non-modular LWAPP AP; Integrated Antennas; Japan2 Cnfg
AIR-LAP1131AG-S-K9	802.11a/g Non-modular LWAPP AP; Integrated Antennas; Singapore Cnfg
AIR-LAP1131AG-T-K9	802.11a/g Non-modular LWAPP AP; Integrated Antennas; Taiwan Cnfg

For More Information

See the Cisco Wireless Website: <http://www.cisco.com/go/wireless>

Cisco Aironet 1200 Series Access Points

Cisco Aironet 1200 Series modular access points feature antenna connectors for greater range or coverage versatility using a broad selection of available Cisco antennas, as well as a rugged, metal housing for operation over extended temperature ranges typical of demanding environments. The 802.11g radio delivers industry-leading range and throughput, meeting the performance requirements of industrial and enterprise applications, while hardware-assisted AES encryption provides uncompromised support for interoperable IEEE 802.11i and WPA2 security. Orderable with either Cisco IOS® Software or the LWAPP, the Cisco Aironet 1200 Series uses radio and network management features to extend the security, scalability, reliability, ease of deployment, and manageability available in wired networks to the WLAN.



When to Sell

Sell This Product

Cisco Aironet 1200 Series Access Point

When a Customer Needs These Features

- Antenna versatility associated with connectorized antennas, as well as a rugged metal enclosure and a broad operating temperature range
- Support for installation in environmental air spaces, such as areas above suspended ceilings
- Flexibility for frequent LAN wiring changes, either throughout the site or in selected areas
- An alternative to LAN wiring because of building or budget limitations, such as older buildings, leased space or temporary sites

Key Features

- Single 802.11g radio supports maximum data rate of 54 Mbps
- Configurable to meet current and future customer-specific requirements
- Enterprise-class security with the Cisco Wireless Security Suite, WPA and WPA2 providing authentication via IEEE 802.1X and encryption via WPA Temporal Key Integrity Protocol (TKIP), Cisco TKIP, or Advanced Encryption Standard (AES)
- Orderable supporting either Cisco IOS® Software, or the LWAPP
- Offers investment protection because of its upgrade capability and compatibility with current standards
- Supports inline power over Ethernet or local power
- Wi-Fi Certified

Specifications

Feature	Cisco Aironet 1200 Series Access Points
Software	Cisco IOS Software Release 12.3(4)JA or later Lightweight Access Point Protocol (LWAPP) 3.1 or later
Data Rates Supported	802.11g: 1, 2, 5.5, 6, 9, 11, 12, 18, 24, 36, 48, and 54 Mbps
Network Standard	IEEE 802.11b and IEEE 802.11g
Uplink	Autosensing 802.3 10/100BASE-T Ethernet
Radio Module Form	802.11a: CardBus (32-bit); 802.11b or 802.11g: Mini-PCI (32-bit)
Frequency Band and Operating Channels	Americas (FCC): 2.412 to 2.462 GHz; 11 channels; Japan (TELEC): 2.412 to 2.472 GHz; 13 channels Orthogonal Frequency Division Multiplexing (OFDM); ETSI: 2.412 to 2.484 GHz; 14 channels Complementary Code Keying (CCK) 2.412 to 2.472 GHz; 13 channels; Israel: 2.432 to 2.472 GHz; 9 channels; Japan (TELEC): 2.412 to 2.472 GHz; 13 channels Orthogonal Frequency Division Multiplexing (OFDM); 2.412 to 2.484 GHz; 14 channels Complementary Code Keying (CCK)
Nonoverlapping Channels	802.11g: 3
Wireless Modulation	802.11g: Direct sequence spread spectrum (DSSS); OFDM
Receive Sensitivity (Typical)	802.11g: 6 Mbps: -90 dBm, 9 Mbps: -84 dBm, 12 Mbps: -82 dBm, 18 Mbps: -80 dBm, 24 Mbps: -77 dBm, 36 Mbps: -73 dBm, 48 Mbps: -72 dBm, 54 Mbps: -72 dBm
Available Transmit Power Settings¹	802.11g—CCK: 100 mW (20 dBm), 50 mW (17 dBm), 30 mW (15 dBm), 20 mW (13 dBm), 10 mW (10 dBm), 5 mW (7 dBm), 1 mW (0 dBm)
Range	802.11g—Outdoor: 110 ft (34m) @ 54 Mbps, 200 ft (61 m) @ 48 Mbps, 225 ft (69 m) @ 36 Mbps, 325 ft (99 m) @ 24 Mbps, 400 ft (122 m) @ 18 Mbps, 475 ft (145 m) @ 12 Mbps, 490 ft (149 m) @ 11 Mbps, 550 ft (168 m) @ 9 Mbps, 650 ft (198 m) @ 6 Mbps, 660 ft (201 m) @ 5.5 Mbps, 690 ft (210 m) @ 2 Mbps, 700 ft (213 m) @ 1 Mbps 802.11g—Indoor: 90 ft (27 m) @ 54 Mbps, 95 ft (29 m) @ 48 Mbps, 100 ft (30 m) @ 36 Mbps, 140 ft (43 m) @ 24 Mbps, 180 ft (55 m) @ 18 Mbps, 210 ft (64 m) @ 12 Mbps, 220 ft (67 m) @ 11 Mbps, 250 ft (76 m) @ 9 Mbps, 300 ft (91 m) @ 6 Mbps, 310 ft (94 m) @ 5.5 Mbps, 350 ft (107 m) @ 2 Mbps, 410 ft (125 m) @ 1 Mbps (Ranges and actual throughput vary based upon numerous environmental factors so individual performance may differ)
Compliance	Customers are responsible for verifying approval for use in their country. Please see http://www.cisco.com/go/aironet/compliance to verify approval and to identify the regulatory domain that corresponds to a particular country. All regulatory domains may not have been approved. As they are approved, the part numbers will be available on the Global Price List.
Antenna	2.4 GHz Radio: Two RP-TNC connectors; 802.11g approved with AIR-ANT1728, AIR-ANT1729, AIR-ANT2012, AIR-ANT2506, AIR-ANT3213, AIR-ANT3549, AIR-ANT4941, AIR-ANT5959, and AIR-ANT2410Y-R
Network Management	BootP, Secure Shell (SSH) Protocol, Secure HTTP (HTTPS), Trivial File Transfer Protocol (TFTP), FTP, Telnet, console port, Simple Network Management Protocol (SNMP) MIB I and MIB II, CiscoWorks Resource Manager Essentials (RME), CiscoWorks Software Image Manager (SWIM), CiscoWorks Campus Manager, CiscoWorks CiscoView, and CiscoWorks WLSE
LEDs	Three indicators on the top panel report Ethernet activity and status, device operating status, and radio activity and status.
Housing	Die-cast aluminum
Dimensions (H x W x D)	1.660 x 6.562 x 7.232 in. (4.22 x 16.67 x 18.37 cm); add 0.517 in. (1.31 cm) height for mounting bracket
Weight	1.725 lb (0.783 kg); add 0.4 lb (0.181 kg) for mounting bracket
Environmental	-4 to 122°F (-20 to 50°C), 10 to 90 percent humidity (noncondensing)

Feature	Cisco Aironet 1200 Series Access Points
Software	Cisco IOS Software Release 12.3(4)JA or later Lightweight Access Point Protocol (LWAPP) 3.1 or later
Data Rates Supported	802.11g: 1, 2, 5.5, 6, 9, 11, 12, 18, 24, 36, 48, and 54 Mbps
Memory and Processor	IBM PowerPC405 (200 MHz); 16 MB RAM; 8 MB Flash memory
Input Power Requirements	90 to 240 VAC $\pm$ 10 percent (power supply); 48 VDC $\pm$ 10 percent
Power Draw	6W maximum
Warranty	One year

1. Maximum power setting will vary according to individual country regulations.

Selected Part Numbers and Ordering Information¹

1200 Series Access Points

AIR-AP1231G-A-K9	802.11g Modular IOS AP; RP-TNC; Avail Cardbus Slot; FCC Cnfg
AIR-AP1231G-E-K9	802.11g Modular IOS AP; RP-TNC; Avail Cardbus Slot; ETSI Cnfg
AIR-AP1231G-I-K9	802.11g Modular IOS AP; RP-TNC; Avail Cardbus Slot; Israel Cnfg
AIR-AP1231G-J-K9	802.11g Modular IOS AP; RP-TNC; Avail Cardbus Slot; Japan Cnfg
AIR-LAP1231G-A-K9	802.11g Modular LWAPP AP; RP-TNC; Avail Cardbus Slot; FCC Cnfg
AIR-LAP1231G-E-K9	802.11g Modular LWAPP AP; RP-TNC; Avail Cardbus Slot; ETSI Cnfg
AIR-LAP1231G-I-K9	802.11g Modular LWAPP AP; RP-TNC; Avail Cardbus Slot; Israel Cnfg
AIR-LAP1231G-J-K9	802.11g Modular LWAPP AP; RP-TNC; Avail Cardbus Slot; Japan Cnfg

1. This is only a small subset of all parts available via URL listed under “For More Information.” Some parts have restricted access or are not available through distribution channels. Resellers: For latest part number and pricing info, see the Distribution Product Reference Guide at: <http://www.cisco.com/dprg> (limited country availability)

For More Information

See the Cisco Wireless Website: <http://www.cisco.com/go/wireless>

Cisco Aironet 1230AG Series Access Point

The 1230AG Series modular access point features both antenna connectors for greater range or coverage versatility using a broad selection of available Cisco antennas, as well as a rugged, metal housing for operation over extended temperature ranges typical of challenging environments.



When to Sell

Sell This Product

Cisco Aironet 1230AG Series Access Point

When a Customer Needs These Features

- Versatility, high-capacity, security, and Enterprise class features in an industrial environment
- Versatile antenna and flexible installation options in a harsh environment
- Simultaneous support of 802.11a and 802.11g standards with 108 Mbps of data rate in the 2.4 and 5GHz bands are required

Key Features

- Dual 802.11a and 802.11g radios deliver a combined capacity of 108 Mbps
- 2.4 GHz and 5 GHz antenna connectors for greater range or coverage versatility and more flexible installation options using a broad selection of available Cisco antennas
- Supports Cisco IOS Software or the LWAPP
- Hardware-assisted AES encryption provides support for interoperable IEEE 802.11i and WPA2 security
- Wi-Fi Certified

Specifications

Features	Cisco Aironet 1230AG Series Access Point
Software	Cisco IOS Software Release 12.3(4)JA or later LWAPP 3.1 or later
Protocols and Air Interface	IEEE 802.11a/b/g
Uplink	802.3 Ethernet 10/100 Base-T
Radio Module Form Factor	802.11a: CardBus (32-bit); 802.11b or 802.11g: Mini-PCI (32-bit)
Frequency Band and Operating Channels	Americas (FCC): 2.412 to 2.462 GHz-11 channels, 5.15 to 5.35, 5.725 to 5.825 GHz-12 channels; China: 2.412 to 2.472 GHz-13 channels, 5.725 to 5.825 GHz-4 channels; ETSI: 2.412 to 2.472 GHz-13 channels, 5.15 to 5.725 GHz-19 channels; Japan (TELEC): 2.412 to 2.472 GHz-13 channels Orthogonal Frequency Division Multiplexing (OFDM), 2.412 to 2.484 GHz-14 channels Complementary Code Keying (CCK), 5.15 to 5.25 GHz-4 channels; North America: 2.412 to 2.462 GHz-11 channels, 5.15 to 5.35, 5.725 to 5.825 GHz-12 channels; Singapore: 2.412 to 2.472 GHz-13 channels, 5.15 to 5.25 GHz and 5.725 to 5.825 GHz-8 channels; Taiwan: 2.412 to 2.462 GHz-11 channels, 5.25 to 5.35 GHz and 5.725 to 5.825 GHz-8 channels
Media Access Protocol	Carrier sense multiple access with collision avoidance (CSMA/CA)
Wireless Modulation	802.11a—Orthogonal Frequency Division Multiplexing (OFDM); 802.11g—Direct sequence spread spectrum (DSSS); Orthogonal Frequency Division Multiplexing (OFDM)
Data Rates Supported	802.11a—6, 9, 12, 18, 24, 36, 48, 54 Mbps; 802.11g—1, 2, 5.5, 6, 9, 11, 12, 18, 24, 36, 48, and 54 Mbps
Receive Sensitivity	802.11a: 6 Mbps: -87 dBm; 9 Mbps: -87 dBm; 12 Mbps: -85 dBm; 18 Mbps: -84 dBm; 24 Mbps: -81 dBm; 36 Mbps: -78 dBm; 48 Mbps: -73 dBm; 54 Mbps: -72 dBm 802.11g: 6 Mbps: -90 dBm; 9 Mbps: -84 dBm; 12 Mbps: -82 dBm; 18 Mbps: -80 dBm; 24 Mbps: -77 dBm; 36 Mbps: -73 dBm; 48 Mbps: -72 dBm; 54 Mbps: -72 dBm
Transmit Power	802.11a: 50 mW (17 dBm), 25 mW (14 dBm), 10 mW (10 dBm), 5 mW (7 dBm) 802.11g: (CCK): 100 mW (20 dBm), 50 mW (17 dBm), 30 mW (15 dBm), 20 mW (13 dBm), 10 mW (10 dBm), 5 mW (7 dBm), 1 mW (0 dBm) 802.11g: (OFDM): 30 mW (15 dBm), 20 mW (13 dBm), 10 mW (10 dBm), 5 mW (7 dBm), 1 mW (0 dBm) Maximum power setting will vary according to individual country regulations.
Range ¹	Indoor-802.11a: 90 ft (27 m) @ 54 Mbps; 225 ft (69 m) @ 48 Mbps; 300 ft (91 m) @ 36 Mbps; 350 ft (107 m) @ 24 Mbps; 400 ft (122 m) @ 18 Mbps; 450 ft (137 m) @ 12 Mbps; 475 ft (145 m) @ 9 Mbps; 500 ft (152 m) @ 6 Mbps 802.11g: 90 ft (27 m) @ 54 Mbps; 95 ft (29 m) @ 48 Mbps; 100 ft (30 m) @ 36 Mbps; 140 ft (43 m) @ 24 Mbps; 180 ft (55 m) @ 18 Mbps; 210 ft (64 m) @ 12 Mbps; 220 ft (67 m) @ 11 Mbps; 250 ft (76 m) @ 9 Mbps; 300 ft (91 m) @ 6 Mbps; 310 ft (94 m) @ 5.5 Mbps; 350 ft (107 m) @ 2 Mbps; 410 ft (125 m) @ 1 Mbps Outdoor-802.11a: 170 ft (27 m) @ 54 Mbps; 350 ft (69 m) @ 48 Mbps; 550 ft (91 m) @ 36 Mbps; 700 ft (107 m) @ 24 Mbps; 800 ft (122 m) @ 18 Mbps; 875 ft (137 m) @ 12 Mbps; 925 ft (145 m) @ 9 Mbps; 950 ft (152 m) @ 6 Mbps; 802.11g: 110 ft (34 m) @ 54 Mbps; 200 ft (61 m) @ 48 Mbps; 225 ft (69 m) @ 36 Mbps; 325 ft (99 m) @ 24 Mbps; 400 ft (122 m) @ 18 Mbps; 475 ft (145 m) @ 12 Mbps; 490 ft (149 m) @ 11 Mbps; 550 ft (168 m) @ 9 Mbps; 650 ft (198 m) @ 6 Mbps; 660 ft (201 m) @ 5.5 Mbps; 690 ft (210 m) @ 2 Mbps; 700 ft (213 m) @ 1 Mbps
Antenna	2.4 GHz radio: Two RP-TNC connectors; 802.11g approved with: AIR-ANT1728, AIR-ANT1729, AIR-ANT2012, AIR-ANT2506, AIR-ANT3213, AIR-ANT3549, AIR-ANT4941, AIR-ANT5959, and AIR-ANT2410Y-R; 5 GHz radio: Two RP-TNC connectors; 802.11a approved with: AIR-ANT5135D-R, AIR-ANT5145V-R, and AIR-ANT5160V-R
Non Overlapping Channels	802.11a: Up to 19; 802.11b/g: 3
Network Management	BootP, Secure Shell (SSH) Protocol, Secure HTTP (HTTPS), Trivial File Transfer Protocol (TFTP), FTP, Telnet, console port, Simple Network Management Protocol (SNMP), MIB I and MIB II, CiscoWorks Resource Manager Essentials (RME), CiscoWorks Software Image Manager (SWIM), CiscoWorks Campus Manager, CiscoWorks CiscoView, and CiscoWorks WLSE
LEDs	Three indicators on the top panel report association status, operation, error/warning, firmware upgrade, and configuration, network/modem, and radio status.
Housing	Die cast aluminum
Dimensions (H x W x D)	1.66 x 6.562 x 7.232 in. (4.22 x 16.67 x 18.37 cm) add 0.517 in. (1.31 cm) to the height for mounting bracket;
Weight	27.6 oz (783g) add 6.4 oz (181g) for mounting bracket
Environmental	-4 to 122° F (-20 to 50°C), 10 to 90% humidity (noncondensing)
Input Power Requirements	90 to 240 VAC ±10% (power supply); 48 VDC ±10%
Power Draw	11 watts maximum
Warranty	One year

1. Ranges and actual throughput vary based upon numerous environmental factors so individual performance may differ

Selected Part Numbers and Ordering Information

Cisco Aironet 1230AG Series Access Point

AIR-AP1232AG-A-K9	802.11a/g Modular IOS AP; RP-TNC; FCC Cnfg
AIR-AP1232AG-C-K9	802.11a/g Modular IOS AP; RP-TNC; China Cnfg
AIR-AP1232AG-E-K9	802.11a/g Modular IOS AP; RP-TNC; ETSI Cnfg
AIR-AP1232AG-I-K9	802.11a/g Modular IOS AP; RP-TNC; Israel Cnfg
AIR-AP1232AG-J-K9	802.11a/g Modular IOS AP; RP-TNC; Japan
AIR-AP1232AG-K-K9	802.11a/g Modular IOS AP; RP-TNC; Korea Cnfg
AIR-AP1232AG-N-K9	802.11a/g Modular IOS AP; RP-TNC; N. America Cnfg (not FCC)
AIR-AP1232AG-P-K9	802.11a/g Modular IOS AP; RP-TNC; Japan2 Cnfg
AIR-AP1232AG-S-K9	802.11a/g Modular IOS AP; RP-TNC; Singapore Cnfg
AIR-AP1232AG-T-K9	802.11a/g Modular IOS AP; RP-TNC; Taiwan Cnfg
AIR-LAP1232AG-A-K9	802.11a/g Modular LWAPP AP; RP-TNC; FCC Cnfg
AIR-LAP1232AG-C-K9	802.11a/g Modular LWAPP AP; RP-TNC; China Cnfg
AIR-LAP1232AG-E-K9	802.11a/g Modular LWAPP AP; RP-TNC; ETSI Cnfg
AIR-LAP1232AG-I-K9	802.11a/g Modular LWAPP AP; RP-TNC; Israel Cnfg
AIR-LAP1232AG-J-K9	802.11a/g Modular LWAPP AP; RP-TNC; Japan
AIR-LAP1232AG-K-K9	802.11a/g Modular LWAPP AP; RP-TNC; Korea Cnfg
AIR-LAP1232AG-N-K9	802.11a/g Modular LWAPP AP; RP-TNC; N. America Cnfg (not FCC)
AIR-LAP1232AG-P-K9	802.11a/g Modular LWAPP AP; RP-TNC; Japan2 Cnfg
AIR-LAP1232AG-S-K9	802.11a/g Modular LWAPP AP; RP-TNC; Singapore Cnfg
AIR-LAP1232AG-T-K9	802.11a/g Modular LWAPP AP; RP-TNC; Taiwan Cnfg

1. This is only a small subset of all parts available via URL listed under "For More Information." Some parts have restricted access or are not available through distribution channels. Resellers: For latest part number and pricing info, see the Distribution Product Reference Guide at: <http://www.cisco.com/dprg> (limited country availability)

For More Information

See the Cisco Wireless Website: <http://www.cisco.com/go/wireless>

Cisco Aironet 1240AG Series Access Point

Cisco® Aironet® 1240AG Series IEEE 802.11a/b/g access points deliver the versatility, high capacity, security, and enterprise-class features demanded by WLAN customers. It is designed specifically for challenging RF environments like factories, warehouses, and large retail establishments that require the antenna versatility associated with connectorized antennas, a rugged metal enclosure, and a broad operating temperature range. The Cisco Aironet 1240AG Series provides local as well as inline power, including support for IEEE 802.3af Power over Ethernet (PoE).



When to Sell

Sell This Product

Cisco Aironet 1240AG Series Access Point

When a Customer Needs These Features

- Rugged enterprise-class AP designed for indoor industrial deployments and installations that require antenna versatility
- For factories, warehouses and retailers
- Link-roll flexibility allowing the AP to perform as a wireless bridge between access points for backhaul to the network

Key Features

- Integrated 802.11a/b/g radios
- Connectors for a variety of both 2.4 and 5GHz antennas
- Orderable as Autonomous or Lightweight
- May be configured to function as an access point or bridge enabling a broad array of applications
- 4 Power options offering deployment flexibility and cost savings -802.3af, Cisco legacy PoE, Cisco Power Injector or local power supply

Specifications

Features	Cisco Aironet 1240AG Series Access Point
Software	Cisco IOS Software Release 12.3(4)JA or later LWAPP 3.1 or later
Data Rates Supported	802.11a—6, 9, 12, 18, 24, 36, 48, 54 Mbps; 802.11g—1, 2, 5.5, 6, 9, 11, 12, 18, 24, 36, 48, and 54 Mbps
Network Standards	IEEE 802.11a/b/g
Uplink	Autosensing 802.3 10/100BASE-T Ethernet
Frequency Band and Operating Channels	Americas (FCC): 2.412 to 2.462 GHz-11 channels, 5.15 to 5.35, 5.725 to 5.825 GHz-12 channels; China: 2.412 to 2.472 GHz-13 channels, 5.725 to 5.825 GHz-4 channels; ETSI: 2.412 to 2.472 GHz-13 channels, 5.15 to 5.725 GHz-19 channels; Japan (TELEC): 2.412 to 2.472 GHz-13 channels Orthogonal Frequency Division Multiplexing (OFDM), 2.412 to 2.484 GHz-14 channels Complementary Code Keying (CCK), 5.15 to 5.25 GHz-4 channels; North America: 2.412 to 2.462 GHz-11 channels, 5.15 to 5.35, 5.725 to 5.825 GHz-12 channels; Singapore: 2.412 to 2.472 GHz-13 channels, 5.15 to 5.25 GHz and 5.725 to 5.825 GHz-8 channels; Taiwan: 2.412 to 2.462 GHz-11 channels, 5.25 to 5.35 GHz and 5.725 to 5.825 GHz-8 channels
Non-Overlapping Channels	802.11a: 12 channels (FCC; other regulatory domains support different numbers of 802.11a channels) FCC currently supports 12 non-overlapping channels, with potentially up to 23 channels via a future firmware release depending on FCC rules; 802.11b/g: 3 channels
Receive Sensitivity	802.11a: 6 Mbps: -87 dBm; 9 Mbps: -87 dBm; 12 Mbps: -85 dBm; 18 Mbps: -84 dBm; 24 Mbps: -81 dBm; 36 Mbps: -78 dBm; 48 Mbps: -73 dBm; 54 Mbps: -72 dBm 802.11g: 6 Mbps: -90 dBm; 9 Mbps: -84 dBm; 12 Mbps: -82 dBm; 18 Mbps: -80 dBm; 24 Mbps: -77 dBm; 36 Mbps: -73 dBm; 48 Mbps: -72 dBm; 54 Mbps: -72 dBm
Range ¹	Indoor-802.11a: 85 ft (26 m) @ 54 Mbps; 150 ft (46 m) @ 48 Mbps; 210 ft (64 m) @ 36 Mbps; 230 ft (70 m) @ 24 Mbps; 260 ft (79 m) @ 18 Mbps; 280 ft (85 m) @ 12 Mbps; 310 ft (94 m) @ 9 Mbps; 330 ft (100 m) @ 6 Mbps; 802.11g: 105 ft (32 m) @ 54 Mbps; 180 ft (55 m) @ 48 Mbps; 260 ft (79 m) @ 36 Mbps; 285 ft (87 m) @ 24 Mbps; 330 ft (100 m) @ 18 Mbps; 355 ft (108 m) @ 12 Mbps; 365 ft (111 m) @ 11 Mbps; 380 ft (116 m) @ 9 Mbps; 410 ft (125 m) @ 6 Mbps; 425 ft (130 m) @ 5.5 Mbps; 445 ft (136 m) @ 2 Mbps; 460 ft (140 m) @ 1 Mbps; Outdoor-802.11a: 100 ft (30 m) @ 54 Mbps; 300 ft (91 m) @ 48 Mbps; 425 ft (130 m) @ 36 Mbps; 500 ft (152 m) @ 24 Mbps; 550 ft (168 m) @ 18 Mbps; 600 ft (183 m) @ 12 Mbps; 625 ft (190 m) @ 9 Mbps; 650 ft (198 m) @ 6 Mbps; 802.11g: 120 ft (37 m) @ 54 Mbps; 350 ft (107 m) @ 48 Mbps; 550 ft (168 m) @ 36 Mbps; 650 ft (198 m) @ 24 Mbps; 750 ft (229 m) @ 18 Mbps; 800 ft (244 m) @ 12 Mbps; 820 ft (250 m) @ 11 Mbps; 875 ft (267 m) @ 9 Mbps; 900 ft (274 m) @ 6 Mbps; 910 ft (277 m) @ 5.5 Mbps; 940 ft (287 m) @ 2 Mbps; 950 ft (290 m) @ 1 Mbps;
Antenna	2.4 GHz: Dual RP-TNC connectors 5 GHz: Dual RP-TNC connectors
Network Management	BootP, Secure Shell (SSH) Protocol, Secure HTTP (HTTPS), Trivial File Transfer Protocol (TFTP), FTP, Telnet, console port, Simple Network Management Protocol (SNMP) MIB I and MIB II, CiscoWorks Resource Manager Essentials (RME), CiscoWorks Software Image Manager (SWIM), CiscoWorks Campus Manager, CiscoWorks CiscoView, and CiscoWorks Wireless LAN Solution Engine (WLSE)
LEDs	Status LED indicates operating state, association status, error/warning condition, boot sequence, and maintenance status: Ethernet LED indicates activity over the Ethernet, status; Radio LED indicates activity over the radio, status
Dimensions (H x W x D)	6.6 x 8.5 x 1.1 in. (16.76 x 21.59 x 2.79 cm)
Weight	2.0 lbs
Environmental	Nonoperating (storage) temperature: 40 to 185°F (-40 to 85°C); Operating temperature: -4 to +131°F (-20 to +55°C) Operating/noncondensing humidity: 10 to 90 percent
System Memory	32 MB RAM; 16 MB flash
Input Power Requirements	100 to 240 VAC; 50 to 60Hz (power supply); 36 to 57 VDC (device)
Power Draw	Local power; 802.3 AF switches; Cisco legacy PoE switches; Cisco Aironet power Injectors (PWRINJ3 and PWRINJ-FIB); Third-party PoE devices (must meet input power and power draw requirements)
Power Draw	12.95W ² maximum
Warranty	One year

1. Ranges and actual throughput vary based upon numerous environmental factors so individual performance may differ
2. The maximum power required at the powered device. If the access point is being used in a PoE configuration, the power drawn from the power sourcing equipment will be higher by some amount dependent on the length of the interconnecting cable. This additional power may be as high as 2.45W, bringing the total system power draw (access point + cabling) to 15.4W.

Selected Part Numbers and Ordering Information

Cisco Aironet 1240AG Series Access Point

AIR-AP1242AG-A-K9	802.11a/g Non-modular Cisco IOS access point; RP-TNC; FCC configuration
AIR-AP1242AG-C-K9	802.11a/g Non-modular Cisco IOS access point; RP-TNC; China configuration
AIR-AP1242AG-E-K9	802.11a/g Non-modular Cisco IOS access point; RP-TNC; ETSI configuration
AIR-AP1242AG-I-K9	802.11a/g Non-modular Cisco IOS access point; RP-TNC; Israel configuration
AIR-AP1242AG-J-K9	802.11a/g Non-modular Cisco IOS access point; RP-TNC; Japan configuration
AIR-AP1242AG-K-K9	802.11a/g Non-modular Cisco IOS access point; RP-TNC; Korea configuration
AIR-AP1242AG-N-K9	802.11a/g Non-modular Cisco IOS access point; RP-TNC; North America configuration (not FCC)
AIR-AP1242AG-P-K9	802.11a/g Non-modular Cisco IOS access point; RP-TNC; Japan2 configuration
AIR-AP1242AG-S-K9	802.11a/g Non-modular Cisco IOS access point; RP-TNC; Singapore configuration
AIR-AP1242AG-T-K9	802.11a/g Non-modular Cisco IOS access point; RP-TNC; Taiwan configuration
AIR-LAP1242AG-A-K9	802.11ag Non-modular LWAPP access point; RP-TNC; FCC configuration
AIR-LAP1242AG-C-K9	802.11ag Non-modular LWAPP access point; RP-TNC; China configuration
AIR-LAP1242AG-E-K9	802.11ag Non-modular LWAPP access point; RP-TNC; ETSI configuration
AIR-LAP1242AG-I-K9	802.11ag Non-modular LWAPP access point; RP-TNC; Israel configuration
AIR-LAP1242AG-K-K9	802.11ag Non-modular LWAPP access point; RP-TNC; Korea configuration
AIR-LAP1242AG-N-K9	802.11ag Non-modular LWAPP access point; RP-TNC; North America configuration (not FCC)
AIR-LAP1242AG-P-K9	802.11ag Non-modular LWAPP access point; RP-TNC; Japan2 configuration
AIR-LAP1242AG-S-K9	802.11ag Non-modular LWAPP access point; RP-TNC; Singapore configuration
AIR-LAP1242AG-T-K9	802.11ag Non-modular LWAPP access point; RP-TNC; Taiwan configuration

1. This is only a small subset of all parts available via URL listed under “For More Information.” Some parts have restricted access or are not available through distribution channels. Resellers: For latest part number and pricing info, see the Distribution Product Reference Guide at: <http://www.cisco.com/dprg> (limited country availability)

For More Information

See the Cisco Wireless Website: <http://www.cisco.com/go/wireless>

Cisco Aironet 1300 Series

The Cisco Aironet 1300 Series is an 802.11g access point and bridge that provides high-speed and cost-effective wireless connectivity between multiple fixed or mobile networks and clients.



When to Sell

Sell This Product

Cisco Aironet 1300 Series

When a Customer Needs These Features

- Configurable for access point, bridge, or workgroup bridge roles
- Support for both point-to-point or point-to-multipoint configurations
- Industry leading range and throughput, supporting data rates up to 54 Mbps
- Enhanced security mechanisms based on 802.1X standards
- Ruggedized enclosure optimized for harsh outdoor environments with extended operating temperature range

Key Features

- Network connections within a campus area; Outdoor infrastructure for mobile networks and users; Public access for outdoor areas
- Supports temporary networks for portable or military operations
- Supports the 802.11g standard providing 54-Mbps data rates with secure technology while maintaining full backward compatibility with legacy 802.11b devices
- Easy maintenance and installation by integrating it with your wired network via SWAN solution
- Provides advanced features such as Fast Secure Roaming, QoS, and VLANs based on Cisco IOS Software
- Operates as a wireless bridge, access point, or a workgroup bridge
- Provides ongoing savings of leased-line expenses, a method to connect networks despite physical barriers such as lakes or highways, and rapid deployment of network connections
- Wi-Fi Certified in Access Point mode

Specifications

Compatibility	Access Point—Compatible with any Wi-Fi Certified client device for basic capability; Compatible with Cisco Aironet clients and Cisco Compatible clients for extended capability Workgroup Bridge—Supports operation with Cisco Aironet access points and Cisco bridges	
Air interface standard¹	IEEE 802.11b or IEEE 802.11g	
Frequency band	2.412 to 2.462 GHz (FCC); 2.412 to 2.472 GHz (ETSI); 2.412 to 2.472 GHz (TELEC)	
Wireless modulation	802.11b—Direct Sequence Spread Spectrum (DSSS): Differential Binary Phase Shift Keying (DBPSK) at 1 Mbps; Differential Quadrature Phase Shift Keying (DQPSK) at 2 Mbps; Complementary Code Keying (CCK) at 5.5 and 11 Mbps 802.11g—Orthogonal Frequency Divisional Multiplexing (OFDM): BPSK at 6 and 9 Mbps; QPSK at 12 and 18 Mbps; 16-quadrature amplitude modulation (QAM) at 24 and 36 Mbps; 64-QAM at 48 and 54 Mbps	
Media access protocol	Carrier Sense Multiple Access/Collision Avoidance (CSMA/CA)	
Operating channels	802.11b/g—ETSI: 13; Americas: 11; TELEC (Japan): 13	
Non-overlapping channels	3	
Security	Bridge—Authentication: 802.1X support including LEAP to yield mutual authentication and dynamic per-user, per-session encryption keys; Encryption: Cisco TKIP, key hashing (per-packet keying) and message, Integrity Check (MIC), AES-ready Access Point: Authentication: 802.1X support including LEAP, PEAP, EAP Message Digest 5 (EAP MD5), EAP TLS, and EAP FAST to yield mutual authentication and dynamic per-user, per-session encryption keys; Encryption: Cisco TKIP and WPA TKIP; key hashing (per-packet keying) and MIC; AES-ready Workgroup-Bridge—Authentication: 802.1X support including LEAP to yield mutual authentication and dynamic per-user, per-session encryption keys; Encryption: Cisco TKIP, key hashing (per-packet keying) and MIC, AES-ready	
Warranty	One year	
SNMP compliance	Versions 1 and 2	
Feature	AIR-BR1310G-x-K9	AIR-BR1310G-x-K9-R
Available transmit power settings²	802.11b: 100 mW (20 dBm), 50 mW (17 dBm), 30 mW (15 dBm), 20 mW (13 dBm), 10 mW (10 dBm), 5 mW (7 dBm), 1 mW (0 dBm); 802.11g: 30 mW (15 dBm); 20 mW (13 dBm); 10 mW (10 dBm); 5 mW (7 dBm); 1 mW (0 dBm)	
Maximum operational receive level	-20 dBm	Same as AIR-BR1310G-x-K9
Maximum survivable receive level	10 dBm	Same as AIR-BR1310G-x-K9
Receive sensitivity (10 percent with 3200-byte packets)	1 Mbps: -94 dBm, 2 Mbps: -91 dBm, 5.5 Mbps: -89 dBm, Same as AIR-BR1310G-x-K9 11 Mbps: -85 dBm; 6 Mbps: -90 dBm, 9 Mbps: -89 dBm; 12 Mbps: -86 dBm, 18 Mbps: -84 dBm; 24 Mbps: -81 dBm, 36 Mbps: -77 dBm; 48 Mbps: -73 dBm, 54 Mbps: -72 dBm	
Access-point role (Outdoor range)	Americas: 865 feet (260 meters) at 54 Mbps, 3465 feet (1055 meters) at 11 Mbps; ETSI: 150 feet (45 meters) at 54 Mbps, 775 feet (235 meters) at 11 Mbps; TELEC: 485 feet (145 meters) at 54 Mbps, 1095 feet (330 meters) at 11 Mbps Note: Access Point with 13 dBi integrated antenna and Cisco clients	Americas: 350 feet (105 meters) at 54 Mbps, 1410 feet (430 meters) at 11 Mbps; ETSI: 195 feet (60 meters) at 54 Mbps, 630 feet (190 meters) at 11 Mbps; TELEC: 195 feet (60 meters) at 54 Mbps, 445 feet (135 meters) at 11 Mbps Note: Access Point with 5.2dBi patch antenna and Cisco clients
Bridge role (Point-to-point range)³	Americas: 1.3 miles (2 km) at 54 Mbps, 9 miles (15 km) at 11 Mbps; EMEA: 0.2 miles (0.36 km) at 54 Mbps, 2.3 miles (3.5 km) at 11 Mbps; TELEC: 0.7 miles (1.1 km) at 54 Mbps, 3.2 miles (5 km) at 11 Mbps Note: 13 dBi integrated antenna at root and non-root bridge	Americas: 4.5 miles (7 km) at 54 Mbps, 14 miles (23 km) at 11 Mbps; EMEA: 5.5 miles (9 km) at 11 Mbps; TELEC: 4.5 miles (7 km) at 54 Mbps, 12 miles (20 km) at 11 Mbps Note: 21-dBi dish antenna at root and non-root bridge
Bridge role (Point-to-multipoint range)³	Americas: 1.1 miles (1.8 km) at 54 Mbps, 8 miles (13 km) at 11 Mbps; EMEA: 0.25 miles (0.4 km) at 54 Mbps, 1.1 miles (1.8 km) at 11 Mbps; TELEC: 0.8 miles (1.3 km) at 54 Mbps, 3.6 miles (5.8 km) at 11 Mbps Note: 14-dBi sector antenna at root and 13dBi integrated antenna at non-root	Americas: 2.0 miles (3.3 km) at 54 Mbps, 10 miles (16 km) at 11 Mbps; EMEA: 2.5 miles (4 km) at 11 Mbps; TELEC: 2.0 miles (3.3 km) at 54 Mbps, 9.0 miles (14 km) at 11 Mbps Note: 14-dBi sector at root and 21-dBi dish at non-root
	AIR-BR1310G-x-K9 and AIR-BR1310G-x-K9-R	AIR-PWRINJ-BLR2 and AIR-PWRINJ-BLR2T
Dimensions (H x W x D)	8 x 8.1 x 3.12 in. (20.3 x 20.57 x 7.87 cm)	4.62 x 4.76 x 1.07 in. (11.73 x 12.09 x 2.71 cm)
Weight	2.5 lb (1.25 kg)	2 lb (1 kg)
Operational temperature	-22½ to 131½°F (-30½ to 55½°C)	Same As AIR-BR1310G-x-K9 and AIR-BR1310G-x-K9-R
Storage temperature	-40½ to 185½°F (-40½ to 85½°C)	Same As AIR-BR1310G-x-K9 and AIR-BR1310G-x-K9-R
Operational altitude	13,800 ft (4206 m)	Same As AIR-BR1310G-x-K9 and AIR-BR1310G-x-K9-R
Storage altitude	16,000 ft (4877 m)	Same As AIR-BR1310G-x-K9 and AIR-BR1310G-x-K9-R
Humidity	0 to 100% at 100½°F (38½°C) (condensing)	0 to 90% at 100°F (38°C) (non-condensing)

1. Bridge mode has enhancements to the standard to allow longer-range bridging communication

2. Maximum power setting will vary according to individual country regulations

3. The distances referenced here are approximations and should be used for estimation purposes only.

Selected Part Numbers and Ordering Information

Cisco Aironet 1300 Series

AIR-BR1310G-A-K9 2.4 GHz (802.11g) Outdoor Access Point/Bridge with integrated patch antenna (FCC regulatory domain)
AIR-BR1310G-A-K9-R (FCC regulatory domain) 2.4 GHz (802.11g) Outdoor Access Point/Bridge with RP-TNC type connector

For More Information

See the Cisco Wireless Website: <http://www.cisco.com/go/wireless>

Cisco Aironet 1500 Series Lightweight Outdoor Wireless Mesh Access Point



Cisco® Aironet® 1500 Series lightweight outdoor mesh access points enable cost-effective, scalable deployment of secure outdoor wireless LANs. With dual-band, simultaneous support for IEEE 802.11a and 802.11b/g standards, the Cisco Aironet 1500 Series employs a patent-pending Adaptive Wireless Path Protocol to form a dynamic wireless mesh network between remote access points, and delivers secure wireless access with the total lowest cost of ownership.

When to Sell

Sell This Product

**Cisco Aironet 1500 Series
Lightweight Outdoor
Wireless Mesh Access
Point**

When a Customer Needs These Features

- Network connections within a campus area
- Outdoor infrastructure for mobile users
- Public access for outdoor areas

Key Features

- Adaptive Wireless Path Protocol
- Integrated dual radio design
- Configurable for access point and bridging
- Support for point-to-point, point-to-multipoint and mesh configurations
- Standards-based LWAPP

Specifications

Features	Cisco Aironet 1500 Series
Wireless Standards	802.11a; 802.11b/g
Media Access Protocol	Carrier Sense Multiple Access/Collision Avoidance (CSMA/CA)
Date Rates and Modulation	802.11a: 54, 48, 36, 24, 18, 12, 9, 6 Mbps, Orthogonal Frequency Division Multiplexing (OFDM); 802.11b: 11, 5.5, 2, 1 Mbps, Direct Sequence Spread Spectrum (DSSS); 802.11g: 54, 48, 36, 24, 18, 12, 9, 6 Mbps, OFDM
Frequency Band and Operating Channels	802.11a : 5.725–5.850 GHz 5 channels; 5.725–5.850 GHz 5 channels 802.11b/g: 2.412–2.462 GHz; 11 channels; 2.412–2.462 GHz; 11 channels Regulatory Version: -A; -N
Transmit Power ¹	Maximum: 802.11a: 28 dBm; 802.11b: 24 dBm; 802.11g: 24 dBm Available power settings are at the following percentages of the above maximum transmit power: 100, 50, 25, 12.5, 6.25
Receive Sensitivity	802.11a: 6 Mbps: -87 dBm; 9 Mbps: -87 dBm; 12 Mbps: -86 dBm; 18 Mbps: -84 dBm; 24 Mbps: -80 dBm; 36 Mbps: -76 dBm; 48 Mbps: -72 dBm; 54 Mbps: -71 dBm; 802.11b: 1 Mbps: -90 dBm; 2 Mbps: -89 dBm; 5.5 Mbps: -87 dBm; 11 Mbps: -84 dBm; 802.11g: 6 Mbps: -88 dBm; 9 Mbps: -87 dBm; 12 Mbps: -87 dBm; 18 Mbps: -84 dBm; 24 Mbps: -80 dBm; 36 Mbps: -78 dBm; 48 Mbps: -72 dBm; 54 Mbps: -71 dBm;
Network Interface	802.3u 10/100 Ethernet, autosensing
Networking Features	16 Broadcast SSIDs; HTTP web page re-direct
Management	LWAPP-based; Managed by Cisco Wireless LAN Controller
Security	Wireless Bridging/Mesh: X.509 digital certificates; MAC address authentication; Hardware-assisted AES encryption Wireless Access: 802.11i; 802.1x authentication, including EAP-SIM, EAP-PEAP, EAP-TLS, EAP-TTLS, Cisco LEAP; Hardware-assisted AES, WPA, Temporal Key Integrity Protocol-Message Identity Check (TKIP-MIC) encryption; VPN passthrough; IPSec, L2TP; MAC address filtering

Compliance	Customers are responsible for verifying approval for use in their country. Please see http://www.cisco.com/go/aironet/compliance to verify approval and to identify the regulatory domain that corresponds to a particular country. All regulatory domains may not have been approved. As they are approved, the part numbers will be available on the Global Price List.
Dimensions	15.0i x 7.3i x 5.7i (25.4 cm x 18.5 cm x 14.5 cm) (including antenna mount)
Weight	10 lbs. (4.55 kg)
Operating Temperature	-30 to 55°C (-22 to 131°F)
Storage Temperature	-50 to 85°C (-58 to 185°F)
Environmental Ratings	IP66; NEMA 4
Immunity	<= 5 mJ for 6kV/3kA @ 8/20 ms waveform; ANSI/IEEE C62.41; EN61000-4-5 Level 4 AC Surge Immunity; EN61000-4-4 Level 4 Electrical Fast Transient Burst Immunity; EN61000-4-3 Level 4 EMC Field Immunity; EN61000-4-2 Level 4 ESD Immunity; EN60950 Overvoltage Category IV
Power	95-260 VAC, 47-63 Hz; Power over Ethernet: 48 VDC, +/-10 percent

1. Maximum transmit power will vary by channel, data rate, and individual country regulations

Selected Part Numbers and Ordering Information

Cisco Aironet 1500 Series

AIR-LAP1510AG-A-K9	Cisco Aironet 1510AG Lightweight Outdoor Mesh Access Point, FCC configuration
AIR-LAP1510AG-N-K9	Cisco Aironet 1510AG Lightweight Outdoor Mesh Access Point, Non-FCC configuration

1. This is only a small subset of all parts available via URL listed under "For More Information." Some parts have restricted access or are not available through distribution channels. Resellers: For latest part number and pricing info, see the Distribution Product Reference Guide at: <http://www.cisco.com/dprg> (limited country availability)

For More Information

See the Cisco Wireless Website: <http://www.cisco.com/go/wireless>

Cisco Aironet 802.11a/b/g Wireless CardBus and PCI Adapters



The Cisco Aironet IEEE 802.11a/b/g Wireless CardBus and PCI Adapters provides high-performance 54 Mbps connectivity in the 2.4 and 5 GHz bands that combines the freedom of wireless connectivity with the performance, security, and manageability that businesses require.

When to Sell

Sell This Product

Cisco Aironet 802.11a/b/g Wireless CardBus Adapter

When a Customer Needs These Features

- Ability to operate in a mixed mode environment
- Mobility within the enterprise to increase productivity, as an addition or alternative to wired networks or need flexibility for frequent LAN wiring changes

Key Features

- Secure network communications using the Cisco Wireless Security Suite
- Includes the Aironet Desktop Utility (ADU), Aironet System Tray Utility (ASTU), and Aironet Client Administration Utility (ACAU)
- World mode for international roaming
- Superior range and throughput
- Supports single 802.11b coverage, single 802.11g coverage, single 802.11a coverage, dual-mode 802.11a/g coverage or tri-mode 802.11a/b/g coverage
- Wi-Fi Certified; Support for WPA
- PCI Adapter—Optimal placement for maximum performance using dual-band 2.4/5 GHz 1 dBi effective gain antenna has a 2-meter cable
- PCI Adapter—Provides a low-profile form factor and two-meter cable length providing flexibility for installation in low-profile devices, such as slim desktops and point-of-sale (POS) devices.

Specifications

Feature	Cisco Aironet 802.11a/b/g Wireless CardBus Adapter	Cisco Aironet 802.11a/b/g Wireless PCI Adapter
Form Factor	CardBus Type II	Standard and Low Profile Type II PCI
Interface	32-bit CardBus with standard 68-pin connector; PC-Card Rev. 7.0 compliant	Standard PCI Interface, PCI Rev. 2.3 compliant
Data Rates Supported	1, 2, 5.5, 6, 9, 11, 12, 18, 24, 36, 48, 54 Mbps	Same as CardBus Adapter
Network Standard	IEEE 802.11a/b/g	Same as CardBus Adapter
Operating Voltage	3.3 V (± 0.3 V)	Same as CardBus Adapter
Media Access Protocol	Carrier-Sense Multiple Access w/ Collision Avoidance (CSMA/CA)	Same as CardBus Adapter
Wireless Medium	802.11g: Direct Sequence Spread Spectrum (DSSS) and Orthogonal Frequency Divisional Multiplexing (OFDM); 802.11a: OFDM	Same as CardBus Adapter
Modulation	802.11b: DSSS--Differential Binary Phase Shift Keying (DBPSK) @ 1 Mbps; Differential Quadrature Phase Shift Keying (DQPSK) @ 2 Mbps; Complementary Code Keying (CCK) @ 5.5 and 11 Mbps 802.11g and 802.11a: OFDM--BPSK @ 6 and 9 Mbps; QPSK @ 12 and 18 Mbps; 16-Quadrature Amplitude Modulation (QAM) @ 24 and 36 Mbps; 64-QAM @ 48 and 54 Mbps	Same as CardBus Adapter
Frequency Bands	2.40 to 2.4897 GHz; 5.15 to 5.35 GHz (FCC UNII 1 and UNII 2); 5.725 to 5.85 GHz (FCC UNII 3); 5.15 to 5.35 GHz (ETSI); 5.470 to 5.725 (ETSI); 5.15 to 5.25 GHz (Japan)	Same as CardBus Adapter
Range (With 2.2 dBi dipole antenna for 802.11g and 802.11b and 6 dBi gain patch for 802.11a)	802.11b—Indoor: 45 ft (13 m) @ 54 Mbps, 110 ft (33 m) @ 18 Mbps, 165 ft (50 m) @ 6 Mbps; Outdoor: 100 ft (30 m) @ 54 Mbps, 600 ft (183 m) @ 18 Mbps, 1000 ft (304 m) @ 6 Mbps 802.11b/g—Indoor: 90 ft (27 m) @ 54 Mbps, 180 ft (54 m) @ 18 Mbps, 160 ft (48 m) @ 11 Mbps, 300 ft (91 m) @ 6 Mbps, @ 410 ft (124 m); Outdoor: 250 ft (76 m) @ 54 Mbps, 600 ft (183 m) @ 18 Mbps, 1000 ft (304 m) @ 11 Mbps, 1300 ft (396 m) @ 6 Mbps, 2000 ft (610 m) @ 1 Mbps	Same as CardBus Adapter
Antenna	Integrated diversity dual-band 2.4/5 GHz antenna	
Security Architecture Client Authentication (Cisco Wireless Security Suite)	Authentication: WPA and 802.1X support for Cisco LEAP, PEAP-GTC, PEAP-MSCHAPv2, and EAP-TLS; MAC address and by standard 802.11 authentication mechanisms Encryption: Support for static and dynamic IEEE 802.11 WEP keys of 40 bits and 128 bits; Cisco TKIP and WPA TKIP encryption enhancements: key hashing (per-packet keying), message integrity check (MIC) and broadcast key rotation	Same as CardBus Adapter
Drivers	Windows XP and Windows 2000	Same as CardBus Adapter
Dimensions (H x W x D)	0.19 x 2.05 x 4.46 in. (4.80 x 52.08 x 113.35 mm)	3.12205 x 4.72 in. (79.3 x 119.9 mm)
Weight	1.6 oz (44.0g)	Standard (frame) PCI w/Antenna: 3.64 oz. (103.2 g), Standard (frame) PCI w/o Antenna: 1.92 oz. (54.7 g), Low Profile PCI w/Antenna: 3.43 oz. (97.5 g), Low Profile PCI w/o Antenna: 1.72 oz. (49.0 g)
Warranty	One Year	Same as CardBus Adapter

For More Information

See the Cisco Wireless Website: <http://www.cisco.com/go/wireless>

Cisco Aironet 1400 Series Wireless Bridge

The Cisco Aironet 1400 Series Wireless Bridge provides a high-performance and feature-rich solution for connecting multiple LANs in a metro area.



When to Sell

Sell This Product

Cisco Aironet 1400 Series Wireless Bridge

When a Customer Needs These Features

- A cost-effective, high-bandwidth way to connect networks in multiple locations within a metro area
- A rapid payback period and a lower total cost of ownership than a leased line
- High performance data rates of 54 Mbps at point-to-point ranges of 7.5 miles and 2 miles for point-to-multipoint ranges

Key Features

- Support for both point-to-point or point-to-multipoint configurations
- Industry leading range and throughput, supporting data rates up to 54 Mbps
- Enhanced security mechanisms based on 802.11 standards
- Ruggedized enclosure optimized for harsh outdoor environments with extended operating temperature range
- Integrated or optional external antennas for flexibility in deployment
- Designed specifically for ease-of-installation and operation

Specifications

Feature	AIR-BR1410A-A-K9	AIR-BR1410A-A-K9-N	Power Injector LR
Frequency band	5.725 to 5.825 GHz (FCC UNII 3)	Same as AIR-BR1410A-A-K9	
Wireless modulation	Coded Orthogonal Frequency Division Multiplexing (COFDM)	Same as AIR-BR1410A-A-K9	
Media access protocol	Carrier Sense Multiple Access with Collision Avoidance (CSMA/CA)	Same as AIR-BR1410A-A-K9	
Modulation	BPSK @ 6 and 9 Mbps, QPSK @ 12 and 18 Mbps, 16-QAM @ 24 and 36 Mbps, 64-QAM @ 48 and 54 Mbps	Same as AIR-BR1410A-A-K9	
Non-overlapping channels	4	Same as AIR-BR1410A-A-K9	
Receive sensitivity (10% PER with 3200byte packets)	6 Mbps: -83 dBm, 9 Mbps: -83 dBm, 12 Mbps: -81 dBm, 18 Mbps: -80 dBm, 24 Mbps: -77 dBm, 36 Mbps: -74 dBm, 48 Mbps: -70 dBm, 54 Mbps: -68 dBm	Same as AIR-BR1410A-A-K9	
Maximum Operational Receive Level	-19 dBm	Same as AIR-BR1410A-A-K9	
Maximum Survivable Receive Level	0 dBm	Same as AIR-BR1410A-A-K9	
Available transmit power settings	250 mW (24 dBm), 200 mW (23 dBm), 155 mW (22 dBm), 125 mW (21 dBm), 60 mW (18 dBm), 30 mW (15 dBm), 15 mW (12 dBm) Maximum power setting will vary according to individual country regulations	Same as AIR-BR1410A-A-K9	
Point-to-point range¹	7.5 miles (13 km) @ 54 Mbps, 16 miles (26 km) @ 9 Mbps	12 miles (19 km) @ 54 Mbps, 23 miles (37 km) @ 9 Mbps, (Antennas are 28 dBi dish)	
Point-to-multipoint range (sector antenna at root)²	2 miles (3 km) @ 54 Mbps, 8 miles (13 km) @ 9 Mbps	4 miles (7 km) @ 54 Mbps, 11 miles (18 km) @ 9 Mbps, (Non-root antenna is 28 dBi dish)	
Antenna	Captured Linear Polarization; 22.5dBi gain; 10 E-plane by 12 H-plane beamwidth	One N-Type connector for professional installations (antennas sold separately)	
Security	Cisco Wireless Security Suite, including: Authentication: 802.1x support including LEAP to yield mutual authentication and dynamic per-user, per-session encryption keys Encryption: Support for static and dynamic IEEE 802.11 WEP keys of 40 bits and 128 bits Pre-standard TKIP WEP enhancements: key hashing (per packet keying) and Message Integrity Check (MIC)	Same as AIR-BR1410A-A-K9	
SNMP compliance	v1 and v2	Same as AIR-BR1410A-A-K9	
Status LEDs	Four LEDs: Install, Radio, Status, Ethernet	Same as AIR-BR1410A-A-K9	Four LEDs: Power ON, Injector status, LAN Ethernet status, Bridge Ethernet status
RSSI port	BNC connector DC Voltage port (0VDC to 2.7 VDC)	BNC connector DC Voltage port (0VDC to 2.7 VDC)	NA
Uplink	100 Mbps over dual coaxial cables	100 Mbps over dual coaxial cables	10/100BaseT Ethernet
Configuration support	Telnet, HTTP, FTP, TFTP, SNMP	Telnet, HTTP, FTP, TFTP, SNMP	NA


Feature	AIR-BR1410A-A-K9	AIR-BR1410A-A-K9-N	Power Injector LR
Compliance	Customers are responsible for verifying approval for use in their country. Please see http://www.cisco.com/go/aironet/compliance to verify approval and to identify the regulatory domain that corresponds to a particular country. All regulatory domains may not have been approved. As they are approved, the part numbers will be available on the Global Price List. individual country regulations)		
Dimensions (H x W x D)	11.4 x 11.4 x 4.2 in. (29 x 29 x 11 cm)	11.6 x 11.6 x 3.6 in. (29 x 29 x 9 cm)	6.7 x 6.3 x 1.3 in (17 x 16 x 3 cm)
Weight	11 lbs. (5 kg)	10 lbs. (5 kg)	1.4lbs. (0.6kg)
Operational temperature	-30 to +55°C (-22 to +131°F)	Same as AIR-BR1410A-A-K9	0 to +50C (32 to 122F)
Storage temperature	-40 to +85°C (-40 to +185°F)	Same as AIR-BR1410A-A-K9	-40 to +70C (-40 to +158F)
Operational altitude	4206 m (13,800 ft.)	Same as AIR-BR1410A-A-K9	Same as AIR-BR1410A-A-K9
Storage altitude	4877 m (16,000 ft.)	Same as AIR-BR1410A-A-K9	Same as AIR-BR1410A-A-K9
Humidity	0 to 100% (condensing)	Same as AIR-BR1410A-A-K9	0 to 90% (non-condensing)
Vibration	0.001 G2/Hz from 5 - 100 Hz	Same as AIR-BR1410A-A-K9	Same as AIR-BR1410A-A-K9
Storage vibration	0.01 G2/Hz from 5 - 100 Hz	Same as AIR-BR1410A-A-K9	Same as AIR-BR1410A-A-K9
Enclosure	Aluminum with environmentally sealed plastic radome	NEMA-4, aluminum	Metal case
AC power	Not Required as uses DC voltage from Power Injector	Same as AIR-BR1410A-A-K9	100 to 240 VAC, +/- 10% (power supply)
DC power	48 VDC +/-2V	Same as AIR-BR1410A-A-K9	Same as AIR-BR1410A-A-K9
Warranty	One year	Same as AIR-BR1410A-A-K9	Same as AIR-BR1410A-A-K9

For More Information

See the Cisco Wireless Website: <http://www.cisco.com/go/wireless>

Cisco Antennas and Accessories

Every wireless LAN deployment is different. When engineering an in-building solution, varying facility sizes, construction materials, and interior divisions raise transmission and multipath considerations. Cisco has the widest range of antennas, cable, and accessories available from any wireless manufacturer. Cisco offers a complete range of 2.4 GHz and 5 GHz antennas for access point and bridge equipment that enable a customized wireless solution for almost any installation



Key Features

- **Client Adapter Antennas**—To extend the transmission range for more specialized applications, a variety of optional, higher-gain antennas are provided that are compatible with selected client adapters
- **Access Point Antennas**—Compatible with all Cisco RP-TNC-equipped access points; Available with different gain and range capabilities, beam widths, and form factors
- **Bridge Antennas**—Available in directional configurations for point-to-point transmission and omnidirectional configuration for point-to-multipoint implementations
- **Low-loss cable** extends the length between any Cisco Aironet bridge and the antenna. With a loss of 6.7 dB per 100 feet (30m), low-loss cable provides installation flexibility without a significant sacrifice in range
- **Complete range of antennas** for 5 GHz bridging applications

Specifications

Access Point Antennas

Feature	AIR-ANT5959	AIR-ANT2410Y-R	AIR-ANT2012	AIR-ANT3213	AIR-ANT2410Y-R
Description	Diversity omni-directional ceiling mount	Yagi mast or wall mount	Diversity patch wall mount	Pillar mount diversity omni	Yagi mast or wall mount
Application	Indoor unobtrusive antenna, best for ceiling mount. Excellent throughput and coverage solution in high multipath cells and dense user population	Indoor/Outdoor directional antenna for use with Access Points or Bridges	Indoor/Outdoor, unobtrusive medium range antenna	Indoor, unobtrusive medium-range antenna	Indoor/outdoor directional antenna for use with access points or bridges
Approximate Indoor Range¹	6 Mbps: 295 ft (90 m) 54 Mbps: 88 ft (27 m)	6 Mbps: 548 ft (167 m) 54 Mbps: 165 ft (50 m)	6 Mbps: 418 ft (127 m) 54 Mbps: 126 ft (38 m)	6 Mbps: 379 ft (121 m) 54 Mbps: 114 ft (35 m)	6 Mbps: 548 ft (167 m) 54 Mbps: 165 ft (50 m)
Cable Length	3 ft. (0.91m)	3 ft. (0.91 m)	3 ft. (0.91m)	3 ft. (0.91m)	3 ft. (0.91 m)
Dimensions (H x W x D)	5.3 x 2.8 x 0.9 in. (13.5 x 7.1 x 2.3 cm)	7.25 x 5 in. (18.4 x 12.7 cm)	4.78 x 6.66 x .82 in. (12.14 x 16.92 x 2.08 cm)	10 x 1 in. (25.4 x 2.5 cm)	7.25 x 5 in. (18.4 x 12.7 cm)
Weight	0.3 lbs. (0.14kg)	8 oz.	9.6 oz. (272g)	1 lb. (460g)	8 oz (227 g)

1. All range estimations are based on an integrated client adapter antenna associating with an access point under ideal indoor conditions. The distances referenced here are approximations and should be used for estimation only.

Access Point Antennas (cont.)

Feature	AIR-ANT1728	AIR-ANT4941	AIR-ANT3549	AIR-ANT1729	AIR-ANT5135D-R
Description	High gain omnidirectional ceiling mount	2.2 dBi dipole antenna	Patch wall mount	Patch wall mount	Indoor omnidirectional coverage
Application	Indoor medium-range antenna, typically hung from crossbars of drop ceilings	Indoor omni-directional coverage	Indoor, unobtrusive, long-range antenna (may also be used as a medium-range bridge antenna)	Indoor, unobtrusive, medium-range antenna (may also be used as a medium-range bridge antenna)	3.5 dBi
Approximate Indoor Range¹	6 Mbps: 379 ft (116 m) 54 Mbps: 114 ft (35 m)	6 Mbps: 300 ft (91 m) 54 Mbps: 90 ft (27 m)	6 Mbps: 507 ft (155 m) 54 Mbps: 153 ft (47 m)	6 Mbps: 403 ft (123 m) 54 Mbps: 121 ft (37 m)	6 Mbps: 675 ft (206 m) 54 Mbps: 75 ft (21 m)
Cable Length	3 ft. (0.91m)	N/A	3 ft. (0.91m)	3 ft. (0.91m)	360° H 40° E
Dimensions (L x D)	9 x 1 in. (22 x 2.5 cm)	5.5 in. (14 cm)	5 x 5 in. (12.4 x 12.4 cm)	4 x 5 in. (9.7 x 13 cm)	N/A
Weight	4.6 oz. (131g)	1.1 oz. (31 g)	5.3 oz. (150g)	4.9 oz. (139g)	5 1/3 x 0.6 in

1. All range estimations are based on an integrated client adapter antenna associating with an access point under ideal indoor conditions. The distances referenced here are approximations and should be used for estimation only.

Access Point Antennas (Con.)

Feature	AIR-ANT5145V-R	AIR-ANT5160V-R	AIR-ANT5170P-R	AIR-ANT5195P-R
Application	Indoor medium-range antenna	Indoor medium-range antenna	Indoor/outdoor directional wall mount antenna	Indoor/outdoor patch antenna provides different mounting options
Gain	4.5 dBi	6 dBi	7.0 dBi	9.5 dBi
Approximate Range¹	6 Mbps: 732 ft (223 m) 54 Mbps: 82 ft (25 m)	6 Mbps: 822 ft (251 mm) 54 Mbps: 92 ft (28 m)	6 Mbps: 880 ft (270 m) 54 Mbps: 140 ft (43 m)	6 Mbps: 1030 ft (313 m) 54 Mbps: 170 ft (52 m)
Beam Width	360° H 50° E	360° H 17° E	70° H, 50° V	50° H, 43° V
Cable Length	3 ft. (0.91 m)	3 ft. (0.91 m)	36"	36"
Dimensions (L x D)	6 3/4" x 4.2"	12 x 1 in.	5.7 in. (14.5 cm) x 4.3 in. (10.9 cm) x 0.7 in. (1.8 cm)	5.1 in. (12.9 cm) x 5.1 in. (12.9 cm) x 1.0 in. (2.5 cm)
Weight	11.5 oz	5.3 oz	8 oz (0.2 kg)	10 oz (0.2 kg)

1. All range estimations are based on an integrated client adapter antenna associating with an access point under ideal indoor conditions. The distances referenced here are approximations and should be used for estimation only.

Bridge Antennas

Feature	AIR-ANT2506	AIR-ANT24120	AIR-ANT2414S-R	AIR-ANT1949	AIR-ANT3338
Description	Omnidirectional Mast mount	High-gain omnidirectional Mast mount	Vertically polarized sector; -15 dBc, 0 to 30°; Declination lower; side lobe null fill; Mast mount	Yagi mast mount	Solid dish
Application	Outdoor short-range point-to-multipoint applications	Outdoor medium-range point-to-multipoint applications	Outdoor long range point-to-multipoint applications	Outdoor medium-range directional connections	Outdoor long-range directional connections

Chapter 3

Feature	AIR-ANT2506	AIR-ANT24120	AIR-ANT2414S-R	AIR-ANT1949	AIR-ANT3338
Approximate Indoor Range ¹	2 Mbps: 3.3 miles (5.31 km) 11 Mbps: 1.66 miles (2.66 km) 54 Mbps: .21 miles (.34 km)	2 Mbps: 15.81 miles (25.43 km) 11 Mbps: 7.92 miles (12.75 km) 54 Mbps: 1.0 miles (1.6 km)	2 Mbps: 16.71 miles (26.89 km) 11 Mbps: 8.89 miles (14.30 km) 54 Mbps: 1.26 miles (2.02 km)	2 Mbps: 18.33 miles (29.49 km) 11 Mbps: 11.19 miles (18.01 km) 54 Mbps: 1.41 miles (2.27 km)	2 Mbps: 26.49 miles (42.62 km) 11 Mbps: 20.1 miles (32.33 km) 54 Mbps: 4.46 miles (7.17 km)
Cable Length	3 ft. (0.91m)	1 ft. (0.30m)	5 ft (3 m)	1.5 ft. (0.46m)	2 ft. (0.61m)
Dimensions (L x D)	13 x 1 in. (33 x 2.5 cm)	42 x 1.5 in. (103 x 3 cm)	36 x 5 in. (91 x 15 cm)	18 x 3 in. (46 x 7.6 cm)	24 in. d (61 cm)
Weight	6 oz. (17g)	1.5 lb. (0.68 kg)	6.5 lb. (3 kg)	1.5 lb. (0.68 kg)	11 lb. (5 kg)

1. All range estimations are based on an integrated client adapter antenna associating with an access point under ideal indoor conditions. The distances referenced here are approximations and should be used for estimation only.

Low-Loss/Ultra Low-Loss Antenna Cable

Feature	AIR-CAB020LL-R	AIR-CAB050LL-R	AIR-CAB100ULL-R	AIR-CAB150ULL-R
Cable Length	20 ft. (6m)	50 ft. (15m)	100 ft. (30m)	150 ft. (46m)
Transmission Loss	1.3 dB	3.4 dB	4.4 dB	6.6 dB

Cisco Aironet Accessories

Feature	AIR-ACC2537-060	AIR-ACC3354	AIR-ACC245LA-R	AIR-ACC2662
Description	60 in. (152 cm) bulkhead extender	Lightning arrester 60 in. (152 cm) bulkhead extender	Yagi articulating mount	Yagi articulating mount
Application	Flexible antenna cable that extends access point cabling typically within an enclosure	Helps prevent damage due to lightning-induced surges or static electricity; Flexible antenna cable that extends access point cabling typically within an enclosure	Helps prevent damage due to lightning-induced surges or static electricity; Helps prevent damage due to lightning-induced surges or static electricity	Adds swiveling capability to mast-mounted Yagi antennas

Cisco Aironet 1400 Wireless Bridge Antennas (5 GHz)

Feature	AIR-ANT58G9VOA-N	AIR-ANT58G10SSA-N	AIR-ANT58G28SDA-N
Description	Omni-directional Mast mount	Sector antenna Mast mount	Dish antenna Mast mount
Application	Outdoor short-range point-to-multipoint applications	Outdoor medium-range point-to-point and point-to-multipoint applications	Outdoor long-range directional connections
Gain (including supplied jumper cable)	9.0 dBi	9.5 dBi	28.0 dBi
Polarization	Vertical	Vertical or horizontal Field configurable	Vertical or horizontal Field configurable
Elevation adjustment	None	None	+/- 12.5 degrees
Approximate range at 9 Mbps	8 miles (13 km) (with 22.5 dBi captive antenna on the remote site)	Same as AIR-ANT58G9VOA-N	23 miles (37 km) (with 28 dBi antennas on each end)
Approximate range at 54 Mbps	2 miles (3 km) (with 22.5 dBi captive antenna on the remote site)	Same as AIR-ANT58G9VOA-N	12 miles (19 km) (with 28 dBi antennas on each end)
Beam width	360 H, 6 V	60 H, 60 V	5.7 H, 6 V
Supplied jumper cable length	4.9 ft. (1.5 m)	Same as AIR-ANT58G9VOA-N	Same as AIR-ANT58G9VOA-N
Dimensions (H x W x D)	18 x 1 in. (46 x 2.5 cm) (L x W)	2.5 x 2.5 x 1.75 in. (6.4 x 6.4 x 4.5 cm)	Diameter: 29 in. (74 cm) Depth: 14.5 in. (36.8 cm)
Weight	2.0 lb. (0.9 kg)	1.25 lb. (0.6 kg)	9.5 lb. (4.3 kg)

Cisco Aironet Bridge Accessory

Feature	AIR-ACCRWM1400	AIR-ACCRGB=	AIR-ACCMFM1400=
Description	Roof/Wall mount kit	Grounding block	Multifunction mount
Application	Allows mounting to flat surfaces Includes full elevation and azimuth adjustment	Helps prevent damage due to lightning-induced surges or static electricity	Allows mounting to poles with a diameter between 1.5 in. and 2.5 in. Includes both elevation and polarization adjustment

Cisco Aironet Power Injector Cables

Feature	AIR-CAB020DRG6-F=	AIR-CAB050DRG6-F=	AIR-CAB100DRG6-F
Cable length	20 ft. (6m)	50 ft. (15m)	100 ft. (30m)

Selected Part Numbers and Ordering Information¹

Cisco Aironet Accessories

AIR-ACC2662	Yagi Antenna Articulating Mount
AIR-ACC3354	Lightning Arrestor w/ grounding ring
AIR-CAB020LL-R	20 ft. (6m) low-loss antenna cable
AIR-CAB050LL-R	50 ft. (15m) low loss antenna cable
AIR-CAB100ULL-R	100 ft. (30m) low loss antenna cable
AIR-CAB150ULL-R	150 ft. (46m) low loss antenna cable

Cisco Aironet Antennas

AIR-ANT1728	5.2 dBi Omni Ceiling Mount Antenna
AIR-ANT1729	6 dBi Patch Wall Mount Antenna
AIR-ANT1949	13.5 dBi Yagi Mast Mount Antenna
AIR-ANT2012	6.5 dBi Diversity Patch Wall Mount Antenna
AIR-ANT2506	5.2 dBi Omnidirectional Mast Mount Antenna
AIR-ANT3195	3 dBi Patch Wall Mount Antenna
AIR-ANT3213	5.2 dBi Pillar-Mount Diversity Omni Antenna
AIR-ANT2410Y-R	10 dBi Yagi mast or wall mount
AIR-ANT3338	21 dBi Solid Dish Antenna
AIR-ANT3351	2.2 dBi POS Diversity Dipole Antenna
AIR-ANT3549	8.5 dBi Hemispherical Patch Antenna
AIR-ANT24120	12 dBi Omnidirectional Mast Mount Antenna
AIR-ANT4941	2.2 dBi Dipole Antenna (Standard Rubber Duck)
AIR-ANT5959	2.0dBi Diversity Omni Ceiling Mount Antenna
AIR-ANT2414S-R	14dBi Sector Mast Mount Antenna
AIR-ANT5135D-R	3.5 dBi dipole antenna
AIR-ANT5145V-R	4.5 dBi omni
AIR-ANT5160V-R	6 dBi omni
AIR-ANT5170P-R	7.0 dBi Diversity patch wall mount
AIR-ANT5195P-R	9.5 dBi Patch wall or articulating mast mount

1. This is only a small subset of all parts available via URL listed under "For More Information." Some parts have restricted access or are not available through distribution channels. Resellers: For latest part number and pricing info, see the *Distribution Product Reference Guide* at: <http://www.cisco.com/dprg> (limited country availability).

For More Information

See the Aironet Antennas & Accessories Website <http://www.cisco.com/go/antenna>

Cisco 2000 Series Wireless LAN Controller



Cisco® Wireless LAN Controllers are responsible for system wide wireless LAN functions, such as security policies, intrusion prevention, RF management, quality of service (QoS), and mobility. They work in conjunction with Cisco Aironet 1000 Series Lightweight Access Points and the Cisco Wireless Control System (WCS) to support business-critical wireless applications. From voice and data services to location tracking, Cisco Wireless LAN Controllers provide the control, scalability, security, and reliability that network managers need to build secure, enterprise-scale wireless networks—from branch offices to main campuses. The Cisco 2000 Series Wireless LAN Controller supports up to six lightweight access points making it ideal for small— to medium—sized enterprise facilities such as branch offices.

When to Sell

Sell This Product

Cisco 2000 Series Wireless LAN Controller

When a Customer Needs These Features

- An enterprise scalable architecture that provides business-critical wireless services for locations of all sizes
- Create an intelligent RF control plane for self-configuration, self-healing, and self-optimization
- Require a system that is deployed without modifying existing routing and switching infrastructures without touching access points

Key Features

- Enterprise scalability
- Integrated Radio Resource Management (RRM)
- Zero-configuration deployment
- Multi-layered security
- Rogue access point detection, location, and containment
- Mobility management
- Enterprise reliability
- Intuitive management interfaces

Specifications

Features	Cisco 2000 Series Wireless LAN Controller
Wireless	IEEE 802.11a, 802.11b, 802.11g, 802.11d, 802.11h
Wired/Switching	IEEE 802.3 10BASE-T, IEEE 802.3u 100BASE-TX specification, and IEEE 802.1Q VLAN tagging
Data RFCs	RFC 768 UDP, RFC 791 IP, RFC 792 ICMP, RFC 793 TCP, RFC 826 ARP, RFC 1122 Requirements for Internet Hosts, RFC 1519 CIDR, RFC 1542 BOOTP, RFC 2131 DHCP
Security Standards	Wi-Fi Protected Access (WPA), IEEE 802.11i (WPA2, RSN), RFC 1321 MD5 Message-Digest Algorithm, RFC 2104 HMAC: Keyed Hashing for Message Authentication, RFC 2246 TLS Protocol Version 1.0, RFC 3280 X.509 PKI Certificate and CRL Profile
Encryption	WEP and TKIP-MIC: RC4 40, 104 and 128 bits (both static and shared keys), Secure Sockets Layer (SSL) and TLS: RC4 128-bit and RSA 1024- and 2048-bit, AES: CCM, CCMP
AAA	IEEE 802.1x, RFC 2548 Microsoft Vendor-Specific RADIUS Attributes, RFC 2716 PPP EAP-TLS, RFC 2865 RADIUS Authentication, RFC 2866 RADIUS Accounting, RFC 2867 RADIUS Tunnel Accounting, RFC 2869 RADIUS Extensions, RFC 3576 Dynamic Authorization Extensions to RADIUS, RFC 3579 RADIUS Support for EAP, RFC 3580 IEEE 802.1x RADIUS Guidelines, RFC 3748 Extensible Authentication Protocol, Web-based authentication
Management	SNMP v1, v2c, v3, RFC 854 Telnet, RFC 1155 Management Information for TCP/IP-Based Internets, RFC 1156 MIB, RFC 1157 SNMP, RFC 1213 SNMP MIB II, RFC 1350 TFTP, RFC 1643 Ethernet MIB, RFC 2030 SNMP, RFC 2616 HTTP, RFC 2665 Ethernet-Like Interface types MIB, RFC 2674 Definitions of Managed Objects for Bridges with Traffic Classes, Multicast Filtering, and Virtual LAN Extensions, RFC 2819 RMON MIB, RFC 2863 Interfaces Group MIB, RFC 3164 Syslog, RFC 3414 User-Based Security Model (USM) for SNMPv3, RFC 3418 MIB for SNMP, RFC 3636 Definitions of Managed Objects for IEEE 802.3 MAUs, Cisco private MIBs
Management Interfaces	Web-based: HTTP/HTTPS, Command-line interface: Telnet, SSH, serial port
Interfaces and Indicators	Console port: RS-232 (DB-9 male, DTE interface), Network: Four 10/100 Mbps Ethernet (RJ-45-10/100 link, activity), Other indicators: Power
Regulatory Compliance	CE Mark; Safety: UL 60950-1:2003, EN 60950:2000; EMI and susceptibility (Class B): U.S.—FCC Part 15.107 and 15.109, Canada—ICES-003, Japan—VCCI, Europe—EN 55022, EN 55024
Temperature	Operating: 32 to 104°F (0 to 40°C); Storage: -13 to 158°F (-25 to 70°C); Operating humidity: 10 to 95 percent, noncondensing; Storage humidity: Up to 95 percent;
Dimensions (W x D x H)	1.6 x 9.5 x 6.0 in. (41 x 241 x 152 mm)
Weight	2.45 lb (1.11 kg)
Power	Input power: 100 to 240 VAC; 50/60 Hz; Output power: +5V @ 3A; +12V @ 1A; 27W

Selected Part Numbers and Ordering Information

Cisco 2000 Series Wireless LAN Controller

AIR-WLC2006-K9

Cisco 2000 Series Wireless LAN Controller for up to six Cisco Aironet Lightweight Access Points

For More Information

See the Cisco Wireless Website: <http://www.cisco.com/go/wireless>

Cisco 4400 Series Wireless LAN Controller



When to Sell

Sell This Product

Cisco 4400 Series Wireless LAN Controller

When a Customer Needs These Features

- Enterprise Scalability—Scalable architecture provides business-critical wireless services for locations of all sizes
- Integrated Radio Resource Management (RRM)—Create an intelligent RF control plane for self-configuration, self-healing, and self-optimization
- Enterprise Reliability—Automated recovery from lightweight access point and Wireless LAN controller failures maximizes the availability of the wireless network

Key Features

- Component of Cisco lightweight access point solution
- Enterprise scalability
- Zero-configuration deployment
- Multi-layered security
- Rogue access point detection, location, and containment
- Mobility management

Specifications

Features	Cisco 4400 Series Wireless LAN Controller
Wireless	IEEE 802.11a, 802.11b, 802.11g, 802.11d, 802.11h
Data RFCs	RFC 768 UDP, RFC 791 IP, RFC 792 ICMP, RFC 793 TCP, RFC 826 ARP, RFC 1122 Requirements for Internet Hosts, RFC 1519 CIDR, RFC 1542 BOOTP, RFC 2131 DHCP
Security Standards	Wi-Fi Protected Access (WPA); IEEE 802.11i (WPA2, RSN); RFC 1321 MD5 Message-Digest Algorithm; RFC 2104 HMAC: Keyed Hashing for Message Authentication; RFC 2246 TLS Protocol Version 1.0; RFC 3280 X.509 PKI Certificate and CRL Profile
Encryption	WEP and TKIP-MIC: RC4 40, 104 and 128 bits (both static and shared keys); Secure Sockets Layer (SSL) and TLS: RC4 128-bit and RSA 1024- and 2048-bit; AES: CCM, CCMP
AAA	IEEE 802.1X; RFC 2548 Microsoft Vendor-Specific RADIUS Attributes; RFC 2716 PPP EAP-TLS; RFC 2865 RADIUS Authentication; RFC 2866 RADIUS Accounting; RFC 2867 RADIUS Tunnel Accounting; RFC 2869 RADIUS Extensions; RFC 3576 Dynamic Authorization Extensions to RADIUS; RFC 3579 RADIUS Support for EAP; RFC 3580 IEEE 802.1X RADIUS Guidelines; RFC 3748 Extensible Authentication Protocol; Web-based authentication
Management	SNMP v1, v2c, v3; RFC 854 Telnet; RFC 1155 Management Information for TCP/IP-Based Internets; RFC 1156 MIB; RFC 1157 SNMP; RFC 1213 SNMP MIB II; RFC 1350 TFTP; RFC 1643 Ethernet MIB; RFC 2030 SNMP; RFC 2616 HTTP; RFC 2665 Ethernet-Like Interface types MIB; RFC 2674 Definitions of Managed Objects for Bridges with Traffic Classes, Multicast Filtering, and Virtual LAN Extensions; RFC 2819 RMON MIB; RFC 2863 Interfaces Group MIB; RFC 3164 Syslog; RFC 3414 User-Based Security Model (USM) for SNMPv3; RFC 3418 MIB for SNMP; RFC 3636 Definitions of Managed Objects for IEEE 802.3 MAUs; Cisco private MIBs
Management Interfaces	Web-based: HTTP/HTTPS; Command-line interface: Telnet, SSH, serial port
Interfaces and Indicators	Uplink: 2 (4402) or 4 (4404) 1000Base-X mini-GBIC transceiver slots (SFP): –LED indicators: link, activity; Service Port: 10/100 Mbps Ethernet (RJ45); LED indicators: link, activity; Utility Port: 10/100/1000 Mbps Ethernet (RJ45); LED indicators: link, activity; Expansion Slots: 1 (4402) or 2 (4404); Console Port: RS232 (DB-9 male, DTE interface); Other Indicators: Status, Alarm, Power Supply 1, Power Supply 2
Regulatory Compliance	CE Mark; Safety: UL 60950-1:2003, EN 60950:2000; EMI and susceptibility (Class A): U.S.: FCC Part 15.107 and 15.109, Canada: ICES-003, Japan: VCCI, Europe: EN 55022, EN 55024

Selected Part Numbers and Ordering Information

Cisco 4400 Series Wireless LAN Controller

AIR-WLC4402-12-K9	4400 Series WLAN Controller for up to twelve 1000 Series APs
AIR-WLC4402-25-K9	4400 Series WLAN Controller for up to twenty-five 1000 Series APs
AIR-WLC4402-50-K9	4400 Series WLAN Controller for up to fifty 1000 Series APs
AIR-WLC4404-100-K9	4400 Series WLAN Controller for up to one-hundred 1000 Series APs

For More Information

See the Cisco Wireless Website: <http://www.cisco.com/go/wireless>

Cisco Wireless Control System (WCS)

Cisco® Wireless Control System (WCS) is the industry leading platform for wireless LAN planning, configuration, and management. It provides a powerful foundation that allows IT managers to design, control, and monitor enterprise wireless networks from a centralized location, simplifying operations and reducing total cost of ownership. With Cisco WCS, network administrators have a single solution for RF prediction, policy provisioning, network optimization, troubleshooting, user tracking, security monitoring, and wireless LAN systems management. Robust graphical interfaces make wireless LAN deployment and operations simple and cost-effective. Detailed trending and analysis reports make Cisco WCS vital to ongoing network operations.

When to Sell

Sell This Product

Cisco Wireless Control System (WCS)

When a Customer Needs These Features

- Centralized platform for managing a complete network of Cisco WLAN controllers and lightweight access points
- WLAN planning tools to increase the effectiveness of WLAN design and deployment

Key Features

- Intuitive GUI so IT staff can easily configure, monitor, and troubleshoot their wireless networks with minimal training
- Hierarchical maps so IT staff can quickly access different geographies, campuses, buildings, floors, and regions for better visibility and control
- WLAN planning tools to increase the effectiveness of WLAN design and deployment
- Integrated location tracking to protect assets and increase WLAN security
- Policy management templates for easy creation and enforcement across an entire enterprise
- Complete wireless intrusion protection
- Simple, hands-off software upgrades
- Robust APIs for integration with external software systems

Specifications

Features	Cisco Wireless Control System (WCS)
Minimum Server Requirements	Redhat Enterprise Linux ES or Windows 2000/2003 server or workstation, SP4 or greater, 2.4 GHz Pentium or better, 1 Gig RAM or better, 20 GB hard drive
Minimum Client Requirements	Internet Explorer 6.0/SP1 or later
Management	SNMP v1, v2c, v3
Managed Devices	Cisco 2000 Series and Cisco 4100 Series wireless LAN controllers; Cisco Aironet 1000 Series Lightweight Access Points
Database	Integrated Solid FlowEngine SQL

Selected Part Numbers and Ordering Information

Cisco Wireless Control System (WCS)

AIR-WCS-WB-1.0-K9	Cisco WCS v1.0 for up to 50 Cisco Aironet 1000 Series Lightweight Access Points; Windows XP/2000
AIR-WCS-LB-1.0-K9	Cisco WCS v1.0 for up to 50 Cisco Aironet 1000 Series Lightweight Access Points; Linux
AIR-WCS-WL-1.0-K9	Cisco WCS w/ Location v1.0 for up to 50 Cisco Aironet 1000 Series Lightweight Access Points; Windows XP/2000
AIR-WCS-LL-1.0-K9	Cisco WCS w/ Location v1.0 for up to 50 Cisco Aironet 1000 Series Lightweight Access Points; Linux
AIR-WCS-WLB-100EX	Cisco WCS Expansion License add 100 access points, Windows/Linux
AIR-WCS-WLL-100EX	Cisco WCS w/Location Expansion License add 100 access points, Windows/Linux
AIR-WCS-WL-UG-K9	Cisco WCS to WCS w/ Location feature per AP upgrade, Windows
AIR-WCS-LL-UG-K9	Cisco WCS to WCS w/ Location feature per AP upgrade, Linux
AIR-WCS-WL-S-UG-K9	Cisco WCS to WCS w/ Location Site License upgrade, Windows
AIR-WCS-LL-S-UG-K9	Cisco WCS to WCS w/ Location Site License upgrade, Linux
AIR-WCS-WLB-SITE	Cisco WCS Site License for unlimited APs, Win/Linux
AIR-WCS-WLL-SITE	Cisco WCS w/Location Site License for unlimited APs, Win/Linux

For More Information

See the Cisco Wireless Website: <http://www.cisco.com/go/wireless>

Cisco Wireless Location Appliance



The Cisco® Wireless Location Appliance is the industry's first location solution that simultaneously tracks thousands of devices from directly within the WLAN infrastructure—bringing the power of a cost effective, high-resolution location solution to critical applications such as high-value asset tracking, IT management and location based security. Integrates tightly with a spectrum of technology and application partners through a rich and open API facilitating the deployment of new and important business applications.

When to Sell

Sell This Product

Cisco Wireless Location Appliance

When a Customer Needs These Features

- Advanced and scalable location tracking that simultaneously tracks thousands of wireless users and devices to within a few meters of their physical location
- Integrated location tracking using existing Cisco LWAPP (lightweight access point protocol) enabled infrastructure, minimizing capital expenditures and helping ensure better WLAN visibility
- Intuitive management GUI to centrally and easily add, configure, manage and upgrade multiple location appliances

Key Features

- **Increased Accuracy**—Cisco Wireless Location Appliance uses the Cisco Systems® patent-pending RF fingerprinting technology to determine the location of wireless devices. Cisco provides the only WLAN infrastructure that correlates known RF characteristics of a building, such as multipath or attenuation, with real-time user information to track mobile devices within a few meters
- **Scalability**—Thousands of wireless clients and Wi-Fi tags can be tracked simultaneously helping ensure that location services can be applied to an entire enterprise environment
- **Lowered Total Cost of Ownership**—Reduces operating expenses by using the existing Cisco WLAN network infrastructure in conjunction with the location appliance. This results in being more cost-effective than proprietary or single-purpose location tracking solutions by using standard 802.11 components which does not require dedicated access points for location tracking

Specifications

Features	Cisco Wireless Location Appliance
Memory	1-GB memory
Ports	Serial: One 9-pin connector, RJ-45: Two RJ-45 connectors for connection to two 10/100/1000 Ethernet controllers, 2 USB ports: One USB connector in front and one in back, 2 PS2 ports: One mouse and one keyboard, 2 VGA ports: One in front and one in back
Connectivity	Network: Two 10/100/1000 (RJ-45) ports
Management	SNMP v1, v2c, and v3
Network Management	Cisco WCS v.3.0 or greater running Internet Explorer 6.0/Service Pack 1 or later
Network Devices	Cisco Wireless LAN Controllers and Cisco lightweight access points
Programming Interfaces	SOAP/XML APIs
Dimensions (H x W x D)	1.68 x 16.8 x 23 in. (4.27 x 42.7 x 58.4 cm)
Weight	28.6lbs (13kg) maximum
Power	AC power supply wattage: 230W; AC power supply voltage: 100-120V at 50-60Hz; 200-240V at 50-60Hz
Environmental	Operating Temperature: 50 to 95°F (10-35°C); Storage Temperature: -40 to 149°F (-40°-65°C)
Approvals and Compliance	Safety UL 60950, CAN/CSA -C22.2 No. 60950, EN60950, IEC 60950; EMC FCC Part 15 (CFR 47) Class A, ICES-003 Class A, EN 55022 Class A, CISPR22 Class A, AS/NZS 3548 Class A, VCCI Class A, EN 55024, EN 50082-1

Selected Part Numbers and Ordering Information

Cisco Wireless Location Appliance

AIR-LOC2700-L-K9

Cisco 2700 Series Wireless Location Appliance

For More Information

See the Cisco Wireless Website: <http://www.cisco.com/go/wireless>



Voice and IP Communications

Voice and IP Communications at a Glance

Product	Features	Page
Call Control		
Cisco CallManager 4.1	- The server-based call processing and call control component of Cisco's IP Telephony solution - Resides on Cisco Media Convergence Servers (MCS), or selected third-party servers (CallManager 4.1)	4-4
Cisco CallManager Express	- IOS-based call control - supported on standard Cisco access and Integrated Services routers 2800, 3800 and IAD 2400 series) - Configurable Key-system or Hybrid-PBX feature set for up to 240 users - Intuitive GUI for system administration and administration - Supports all Cisco standard IP phones	4-7
Cisco Survivable Remote Site Telephony Software (SRST)	IOS software feature that runs on local branch office router provides IP Telephony backup redundancy for IP phones during WAN outage or CallManager is unreachable	4-8
Voice Mail and Unified Messaging		
Cisco Unity—Unified Messaging and Voice Mail	Voice mail and unified messaging system delivers all messages into single inbox for access via phone, email or Internet	4-9
Cisco Unity Connection	Combines integrated messaging, speech recognition and call routing rules into an easy-to-manage system for mid-market customers	4-9
Cisco Unity Express	- Integrated voice mail and automated attendant services locally delivered for either Cisco CallManager or Cisco CallManager Express solution - Leverages the data infrastructure; supported on broad range of Cisco access routers and new Cisco Integrated Services Routers - Increases employee productivity and customer service for businesses of various sizes and operational models	4-12
Cisco Personal Assistant	Software application allows users to browse voice mail, dial by name, and conference from any phone using voice commands instead of telephone keypad via speech recognition	4-12
Cisco Unified Contact Center Product Family		
Cisco IP Contact Center (IPCC) Enterprise Edition	Delivers intelligent call routing, network-to-desktop CTI, and multi-channel contact management to contact center agents over an IP infrastructure. - Pre-routing and post-routing of contacts - Ability to handle voice, Web and e-mail contacts, as well as inbound and outbound campaigns - Computer telephony integration (CTI), universal queue, IVR integration and remote agent support	4-14
Cisco IP Contact Center (IPCC) Express Edition	- A software-based ACD, IVR, and CTI application for departmental, enterprise branch, or small to mid-sized contact centers with Cisco IP Telephony networks. - Provided in Standard, Enhanced and Premium versions - Offers an open systems platform allowing ease of installation and configuration - Provides a graphically driven workflow editor providing a common interface for creating interactions, or call flows, and creates business logic between IVR and ACD functions	4-15
Cisco IP Contact Center (IPCC) Hosted Edition	Suitable for both enterprise customers and service providers. - The service provider hosts the contact center infrastructure software-which is shared by multiple business customers-in its central office or data center - Subscribing business customers can have IP infrastructures, TDM infrastructures, or a combination of the two - For the enterprise customer, multiple branch offices or divisions share a partitioned, centralized contact center infrastructure	4-16
Cisco ICM Enterprise Edition	Provides call routing and CTI for multi-site, TDM based contact centers in a distributed, fault-tolerant architecture - Cisco Pre-Routing and Post-Routing; Customer Profile Routing (CPRI); Enterprise Reporting - CTI, Web collaboration, E-mail management, IVR integration - Multi-carrier, multi-vendor capabilities; Inbound and outbound campaign management	4-17

Product	Features	Page
Cisco ICM Hosted Edition	Helps service providers address a full range of business opportunities. - Open architecture—enables a smooth migration from TDM circuit-switched to IP based voice technology while enabling business-to-business services, e-commerce, and multimedia applications such as Web collaboration and e-mail response management - For the service provider—Offers a unique opportunity to deliver critical applications tailored to each customer's business strategy - For the customer—Services leverage value-added service provider capabilities to meet business goals	4-17
Cisco IP IVR	Provides a feature-rich foundation for the creation of an IP-based interactive voice response (IVR) system that is open and expandable. - Provides an IP-empowered application-generation environment for self service and call treatment solutions - Offers Web-based activation and administration - Interoperates with automatic speech recognition (ASR) and text to speech (TTS) - Extendable through custom Java steps	4-18
Cisco Customer Voice Portal	Offers a Web-based prompt, collect, queuing, and call control service, using standard Internet technologies - Supports ASR and TTS - Integrates fully with both traditional TDM and IP-based contact centers	4-19
IP Phones		
Cisco IP Phones IP 7900 Series	An exciting, distinctively stylish, and pure Voice over IP phone portfolio to meet the wide range of business communication needs at affordable prices - Display-based technology provides ease-of-use - Integrated inline power and 2-port Ethernet Switch provides end-to-end infrastructure integration - Rich application environment enabled by open APIs based on XML	4-19
Cisco ATA Series of Analog Telephone Adaptors	Turns any analog telephone into an IP telephone. Each of the two voice ports supports independent telephone numbers, providing two separate lines. - Interoperable with SIP and SCCP - Enables analog devices, such as phones and fax machines, to support Voice over IP services by converting the analog signal into an IP signal	4-21
Cisco IP Communicator	- Softphone client that gives computers the capabilities and features of a Cisco IP phone - A supplemental telephone that provides access to phone extensions and services outside the office - Unified administration with Cisco IP phones and automatic software updates makes it easy to manage	4-23
Cisco VT Advantage	- Brings video telephony functionality to Cisco IP phones - Adds video to phone calls through the use of a personal computer without button-pushing or mouse-clicking - Video telephony is now just a phone call	4-23
Voice Applications		
Cisco Emergency Responder	- Works with Cisco CallManager to automatically provide E9-1-1 features in North America, and is compatible with any emergency number - Dynamically tracks the location of IP phones, routes emergency calls to the appropriate E9-1-1 network, and provides the current location information to E9-1-1 call center dispatchers. - Provides real-time alert notifications to on-site or contracted security groups, to facilitate a timely response to emergency situations	4-24
Cisco IP Manager Assistant	Improves productivity by extending commonly used features such as call filtering, immediate call diversion, and line state monitoring to administrative assistants and managers.	4-25
Voice Network Management		
CiscoWorks IP Communications Operations Manager	A suite of management applications that helps ensure the readiness and manageability of converged networks that are supporting VoIP and IP telephony traffic and applications. The bundle includes: Voice Health Monitor; Default Fault Manager; CiscoView CCO Downloadable Modules: IP Phone Information Utility; IP Phone Help Desk Utility; Fault History Manager	9-16
Voice Servers		
Cisco MCS 7800 Series	High availability server platform for Cisco IP telephony systems	4-26
Media Convergence Servers	- Turnkey solution, includes CallManager or other software - For large- and medium-sized enterprise IP telephony deployments	

Product	Features	Page
Voice Gateways		
Cisco Voice Gateways¹	The Cisco VG248 and VG224 dedicated voice gateway provides connectivity between IP networks and legacy telephones • VG248 supports up to 48 Foreign eXchange Station (FXS) ports for connecting analog telephones or legacy voice mail systems; Fully manageable by Cisco CallManager, a CLI interface via Telnet, or via SNMP • VG224 supports up to 24 FXS ports for connecting analog telephones and is IOS based; fully manageable by Cisco CallManager or Cisco CallManager Express via CLI interface or GUI	4-27
Cisco AS5350 Series Universal Gateways	• High performance, 1RU, universal gateway offering best in class voice, fax, and remote access services • Two models—Cisco AS5350XM and Cisco AS5350 • 2, 4, & 8 CT1/7 CE1/PRI configurations for 48 to 240 channels	4-28
Cisco AS5400 Series Universal Gateways	• High performance, 2RU, universal gateway offering best in class voice, fax, and remote access services • Three models—Cisco AS5400XM, AS5400HPX and Cisco AS5400 • 8 to 16 CT1/CE1/PRI or 1 T3 configuration for 192 to 648 channels • Low power and high availability design	4-30
Cisco AS5850 Universal Gateway	• The highest density universal gateway in the marketplace • Supporting at least 2,688 sessions data, voice, and fax services on any port at any time using T1, E1, DS3 or STM-1 trunk interface • Constant density regardless of codec type, ECAN or VAD settings • Extensive high availability features • TDM grooming capability	4-32
Cisco Conferencing		
Cisco IP/VC 3500 Series Videoconferencing Products	• Videoconferencing over IP solution • Cost-effective, easy-to-manage • Translates between H.323 and H.320 systems • Management and QoS	4-34
Cisco MeetingPlace	• Integrated voice, video and web conferencing • On-network conferencing solution that integrates directly into an organization's private voice and data networks • Cost-effective and secure with a superior user experience	4-35
Cisco MeetingPlace Express 1.1	• Integrated voice and Web conferencing system for reservationless and scheduled meetings that include powerful features like meeting controls, screen sharing, and voice recordings. • Makes it easy and affordable for midsize organizations to realize the cost savings and productivity benefits of deploying conferencing over their converged IP network • Provides simple, powerful conferencing functions that are easy to deploy and manage	4-37
Bundles		
Cisco Voice Bundles²	Cisco 2800 and 3800 Voice Bundles for handling toll bypass applications or PSTN/PBX to IP Connectivity for Cisco CallManager deployments.	4-38
Cisco CallManager Express Bundles²	Cisco 2800 and 3800 Cisco CallManager Express Bundles for customers wanting a complete all in one router IP Telephony Solution for the Small Office or Enterprise Branch location.	4-39
Cisco Survivable Remote Site (SRST) Bundles²	Cisco 2800 and 3800 Voice Bundles for customers' branch locations where they need data connectivity plus local PSTN call handling with a centralized Cisco CallManager deployment.	4-39
Cisco V3PN Bundles²	Cisco 2800 and 3800 Voice Bundles for remote branch locations needing VPN and IP Telephony using Cisco CallManager Express or SRST with centralized Cisco CallManager Express deployment.	4-40
Product Ordering Website	To place an order, visit the Cisco Ordering Website: http://www.cisco.com/en/US/ordering/index.shtml	

1. Cisco's full line of multiservice routers also provide analog and digital voice gateway functionality through use of network modules and voice interface cards. Please see Chapter 1—Routers, as well as Chapter 7—Access Products.
2. Bundles provide a discount compare to ordering the parts individually. With each bundle, the customer needs to choose the country explicit PSTN module required plus any additional features or modules for the applications.

Cisco CallManager 4.1

Cisco CallManager Version 4.1 provides a secure, scalable, distributable, and highly available enterprise IP telephony call-processing solution. Multiple Cisco CallManager servers are clustered and managed as a single entity. Clustering multiple call-processing servers on an IP network is a unique capability in the industry. Cisco CallManager clustering yields scalability of from 1 to 30,000 IP phones per cluster, load balancing, and call-processing service redundancy. By interlinking multiple clusters, system capacity can be increased up to one million users in a 100+ site system. Clustering aggregates the power of multiple, distributed Cisco CallManagers, enhancing the scalability and accessibility of the servers to phones, gateways, and applications. Triple call-processing server redundancy improves overall system availability.

The benefit of this distributed architecture is improved system availability, load balancing, and scalability. Call Admission Control (CAC) helps ensure that voice QoS is maintained across constricted WAN links, and automatically diverts calls to alternate public switched telephone network (PSTN) routes when WAN bandwidth is not available.

Cisco CallManager 4.1 has the ability to verify identity of the devices or servers that they communicate with, ensure the integrity of data they are receiving, and provide privacy of communications via encryption. The devices that can participate in secure communications now includes the Cisco IP Phone 7940G, IP Phone 7960G, IP Phone 7970G, and Media Gateway Control Protocol (MGCP) gateways.

Enhancements to the CallManager APIs (AXL, JTAPI, TSP) provide customers and 3rd party vendors increased ability to develop improved applications that can be integrated with CallManager and IP Phones.

Key Features

- Supplementary and enhanced services such as hold, transfer, forward, conference, multiple line appearances, automatic route selection, speed dial, last-number redial, and other features are extended to IP phones and gateways
- Capabilities enhancements are achieved through software upgradeability, avoiding expensive hardware costs traditional to legacy PBX systems
- Cisco CallManager Attendant Console—This Web-enabled application supports the traditional role of a manual attendant console and allows the attendant to quickly accept and dispatch calls to enterprise users. An integrated directory service provides traditional busy lamp field (BLF) and direct station select (DSS) functions for any line in the system. It monitors the state of every line in the system without requiring hardware-based line monitoring devices, thereby saving costs
- Software-only applications such as the Cisco Interactive Voice Response system, Cisco IP Contact Center, Cisco Automated Attendant, and Cisco SoftPhone are applications that interact with the CallManager through telephony APIs
- Video telephony gives users the ability to place video calls using traditional telephony features such as hold, resume, park, transfer, conference; Provides a common dial plan and administration between voice and video
- Comprehensive and wide range of security features; Encryption and Authentication are available across the most widely used Cisco IP phones and gateways; Secure system and user administration
- Call coverage/call routing features allow calls to be routed based on time of day, source of call and destination of call to handle the complex routing requirements of many of our customers

- By supporting a wide set of Q.SIG features, installable along with a TDM based PBX to allow peaceful co-existence and migration to an all IP environment while delivering some of the key features needed between the TDM PBX and CallManager; Path replacement and call completion allow integrating with other Q.SIG compatible systems; H.323 Annex M.1 support gives users improved feature transparency between CallManager clusters

Specifications

Feature	Cisco CallManager 4.1 ¹
Platforms	Media Convergence Server (MCS); Selected third-party servers
Pre-Installed Software	Auto attendant Bulk Administration Tool (BAT) CDR Analysis and Reporting (CAR) tool Cisco Attendant Console Cisco CallManager Administration software Cisco CallManager version 4.1 (call processing and call-control application) Cisco CallManager version 4.1 configuration database (contains system and device configuration information, including dial plan) Cisco Conference Bridge Cisco Customer Directory Configuration Plugin Cisco Dialed Number Analyzer—Serviceability tool that analyzes the dialing plan for specific numbers. Cisco IP Manager Assistant (IPMA) Cisco IP Phone Address Book Synchronizer Cisco IP Telephony Locale Installer Cisco JTAPI Cisco TAPS Cisco Telephony Service Provider Real Time Monitoring Tool RTMT
Sample Subset of System Capabilities	Anti-Virus checker certification Cisco IPS Host-Based Sensor certification Cisco Security Agent (CSA) bundled with CallManager. Data integrity with TLS cipher “NULL-SHA” Device Authentication with X.509v3 certificates. Distributed Call Processing Encryption of signaling and media on many Cisco IP endpoints and gateways. Forced Authorization Codes/Client Matter Codes H.323 FastStart H.323 scalability improvements - 1,000 H.323 calls per CallManager server in cluster H.323 T.38 fax support Multi-level Precedence and Pre-emption (MLPP) Secure HTTPS support SIP trunk SRST

Feature	Cisco CallManager 4.1 ¹
Sample Subset of Administrative Features	Application discovery and registration to SNMP manager Automated Alternate Routing Groups AXL SOAP API with performance and real-time informationBulk Administration Call Back Call Detail Records (CDR) Call forward reason code delivery Centralized, replicated configuration database, distributed Web-based management viewers Configurable and default ringer WAV files per phone Configuration database API Database automated change notification Date/time display format configurable per phone Debug information to common syslog file Device addition through wizards Device downloadable feature upgrades—Phones, hardware transcoder resource, hardware conference bridge resource, VoIP gateway resource Device groups and pools for large system management Device mapping tool-IP address to MAC address Dialed Number Identification Service (DNIS) Dialed number translation table (inbound/outbound translation) Distinctive ring per line DHCP block IP assignment-phones and gateways Enhanced 911 service H.323-compliant interface to H.323 clients, gateways, and gatekeepers Individual line Call Waiting Alert Configuration Integration with Unity voice mail JTAPI 1.2 computer telephony interface LDAP version 3 directory interface to selected vendor's LDAP directories • Active Directory • Netscape Directory Server
Sample Subset of User Features	Abbreviated Dialing or speed dials Answer/answer release Auto-answer/intercom Barge Call back Call connection Call coverage Call forward-all (off-net/on-net); Call forward-busy; Call forward-no answer Call hold/retrieve Call Join Call park/pickup; Call pickup group-universal Call status per line (state, duration, number) Call waiting/retrieve Calling Line Identification (CLID); Calling party name identification (CNID) Calling Line Identification Restriction (CLIR) Direct inward dial (DID); Direct outward dial (DOD) Direct Transfer Directories-missed, placed, received calls list stored on selected IP phones Directory dial from phone-corporate, 2personal Distinctive ring (on-net vs. off-net); Distinctive ring per phone Drop last conference party (ad-hoc conferences) Extension Mobility Extension mobility support H.264 video Codec support Hands-free, full-duplex speakerphone HTML help access from phone Immediate Divert to voice mail Last number redial (off-net/on-net) List and drop conference participate Manager-assistant service (IPMA application) Message waiting indication Multiparty conference-Ad-hoc with add-on, Meet-me Multiple line appearances per phone Music-on-hold

1. Additional RAM may be required in Media Convergence Servers to support existing and enhanced services in Cisco CallManager 4.1

Selected Part Numbers and Ordering Information¹

Cisco CallManager Software Installation Kits

CM4.1-K9-7815SE	SW CallManager Install for MCS-7815-I1, 100 users maximum
CM4.1-K9-7815-I1	SW CallManager Install for MCS-7815-I1, 300 users maximum
CM4.1-K9-7825-H1	SW CallManager Install for MCS-7825-H1, 1000 users maximum
CM4.1-K9-7825-I1	SW CallManager Install for MCS-7825-I1, 1000 users maximum
CM4.1-K9-7835	SW CallManager Install for MCS-7835-H1 and MCS-7835-I1, 2500 users maximum
CM4.1-K9-7845	SW CallManager Install for MCS-7845-H1 and MCS-7845-I1, 5000 users maximum

1. This is only a small subset of all parts available via URL listed under “For More Information.” Some parts have restricted access or are not available through distribution channels.

For More Information

See the Cisco CallManager Websites: <http://www.cisco.com/go/callmgr>

Cisco CallManager Express

Cisco CallManager Express is a solution embedded in Cisco IOS Software that provides call processing for Cisco IP phones. This solution enables the large portfolio of Cisco multiservice access and new Integrated Services routers to deliver features similar to those of a key system or low-end private branch exchange (PBX), thereby enabling deployment of a cost-effective, highly reliable, IP Communications solution for the small office. Customers can now scale IP telephony to a small site or branch office for a deployment of up to 240 users.

Key Features

- Cost-effective operations through a single, integrated voice-and-data platform for the Commercial Small Medium business or branch office needs
- Provides integrated IP telephony services for access and Integrated Services routers that allows customers to deploy one device in their office to address all their business needs, simplifying management, maintenance, and operations, and delivering a lower total cost of ownership (TCO)
- Robust set of key system and low-end PBX capabilities—Delivers a robust set of telephony features for the small office, and delivers unique value-added capabilities through XML that enhance the productivity of the end user and of the business, and that cannot be delivered by traditional solutions
- Investment protection and ease of upgrade to centralized call-processing solutions—Simple software upgrade capabilities
- Remote maintenance and troubleshooting using Cisco IOS Software command-line interface (CLI) or Web-based GUI—Acts as a standalone call-processing engine for IP phones located in the branch office

Specifications

Feature	Cisco CallManager Express
Platform	Cisco 2800 and 3800 Series Routers.
Phone supported	Cisco IP Phones 7911G-GE, 7970G, 7961G-GE, 7961G, 7960G, 7941G-GE, 7941G, 7940G, 7912G, 7911G, 7905G, 7902G, 7910G-SV, Cisco Wireless IP Phone 7920, Cisco IP Conference Station 7936, Cisco IP Phone Expansion Module 7914, ATA, VG 224
IOS Images	Cisco Call Manager Express version 3.3 supported with IOS 12.4 mainline or version 3.4 with IOS 12.4(4)T

Selected Part Numbers and Ordering Information

Cisco CCME Router Bundles

CISCO1760-V-CCME	1760 Router, 32MB Flash, 96MB DRAM, PVDM-256K-4, FL-CCME-SMALL (24 users), IOS IP Voice Feature Set
CISCO-2611XM-V-CCME	2611XM router, 32 MB Flash, 128 MB DRAM, NM-HD-2V (for 8 calls), FL-CCME-MEDIUM (48 users), Cisco IOS SP Services Voice
CISCO2651XM-V-CCME	2651 Router, 32MB Flash, 128MB DRAM, AIM-VOICE-30 (DSP for 30 calls), FL-CCME-MEDIUM (48 users), IOS SP Services .
CISCO3845-CCME/K9	Cisco 3845 Voice Bundle with IOS SP Services, PVDM2-64, FL-CCME (240 users), 64 MB Flash/256 MB DRAM
CISCO3825-CCME/K9	Cisco 3825 Voice Bundle with IOS SP Services, PVDM2-64, FL-CCME (168 users), 64 MB Flash/256 MB DRAM
CISCO2851-CCME/K9	Cisco 2851 Voice Bundle with IOS SP Services, PVDM2-48, FL-CCME (72/96 ¹ users), 64 MB Flash/256 MB DRAM
CISCO2821-CCME/K9	Cisco 2821 Voice Bundle with IOS SP Services, PVDM2-32, FL-CCME (48 users), 64 MB Flash/256 MB DRAM
CISCO2811-CCME/K9	Cisco 2811 Voice Bundle with IOS SP Services, PVDM2-16, FL-CCME (36 users), 64 MB Flash/256 MB DRAM
CISCO2801-CCME/K9	Cisco 2801 Voice Bundle with IOS SP Services, PVDM2-8,FL-CCME (24 users), 64 MB Flash/256 MB DRAM

1. Available with IOS Version 12.3(11)T release

For More Information

See the Cisco CallManager Express Website: <http://www.cisco.com/go/ccme>

Cisco Survivable Remote Site Telephony (SRST)

Cisco SRST provides key backup telephony functions at remote branch office if connectivity to the centrally-located Cisco CallManager fails (i.e. WAN link is interrupted). During WAN outage the Cisco SRST-enabled router will provide robust telephony services (including off-net calls to 911). It is ideal for enterprise organizations looking to cost-effectively deploy IP telephony in their branch office location. SRST v3.3 with IOS 12.4 mainline is available on Cisco 1760V, 2600XM, 2691, 2800, 3700, and 3800 series of routers and with the Cisco Catalyst 6500 with the Cisco Communications Media Module (CMM). The Cisco 7200 also supports previous versions of SRST.

Key Features

- Business resiliency through redundant, localized call processing with intelligent and automatic failover configuration-no manual IT or telecom intervention required
- SRST 3.3—Support for all Cisco IP Phones, 24 to 720 phones supported per platform
- All common PSTN Interfaces/protocols supported. Support for both internal and external calling during failover with calls maintained during failover and fall back.
- Voice Mail Support during WAN outage with local Cisco Unity Express or Centralized Cisco Unity via PSTN

Selected Part Numbers and Ordering Information

SRST 3.2 Platform Density and Feature License Part Numbers

Platform	Number of Phones Supported	Part Number	Part Number (Spare)
Cisco 1751V, 1760V, 2801	Up to 24 phones	FL-SRST-SMALL	FL-SRST-SMALL=
Cisco 261x-XM, 262x-XM, 2811	Up to 36 phones	FL-SRST-36	FL-SRST-36=
Cisco 265xXM, 2821	Up to 48 phones	FL-SRST-MEDIUM	FL-SRST-MEDIUM=
Cisco 2691	Up to 72 phones	FL-SRST-SMALL and FL-SRST-MEDIUM	FL-SRST-SMALL= and FL-SRST-MEDIUM=
Cisco 2851	Up to 96 phones	FL-SRST-96	FL-SRST-96=
Cisco 3725	Up to 144 phones	FL-SRST-144	FL-SRST-144=
Cisco, 3745, 7200 NPE300/400	Up to 240 phones	FL-SRST-240	FL-SRST-240=
Cisco 3825	Up to 336 phones	FL-SRST-336	FL-SRST-336 =
Cisco 7200NPE400/G1	Up to 480 phones	FL-SRST-480	FL-SRST-480=
Cisco 3845	Up to 720 phones	FL-SRST-720	FL-SRST-720=

SRST bundles

CISCO2801-SRST/K9	Feature License FL-SRST-SMALL: 8 G.711 channels of DSPs included
CISCO2811-SRST/K9	Feature License FL-SRST-36: 16 G.711 channels of DSPs included
CISCO2821-SRST/K9	Feature License FL-SRST-MEDIUM: 32 G.711 channels of DSPs included
CISCO2851-SRST/K9	Feature License FL-SRST-96: 48 G.711 channels of DSPs included
CISCO3825-SRST/K9	Feature License FL-SRST-168: 64 G.711 channels of DSPs included
CISCO3845-SRST/K9	Feature License FL-SRST-240: 64 G.711 channels of DSPs included
CISCO1760-V-SRST	Feature License FL-SRST-SMALL: 4 G.711 channels of DSPs included
CISCO2651XM-V-SRST	Feature License FL-SRST-MEDIUM: 30 G.711 channels of DSPs included

For More Information

See the Cisco SRS Telephony Website: <http://www.cisco.com/go/srst>

Cisco Unity—Unified Messaging and Voice Mail

Cisco Unity is a powerful Unified Communications server that provides advanced, convergence-based communication services and integrates them with the desktop applications business professionals use everyday, improving customer service and productivity. Designed for enterprise-scale organizations, Cisco Unity delivers unified messaging that gives subscribers the ability to access and manage messages and calls from anywhere, at any time, regardless of device or media type. Subscribers can listen to e-mail over the telephone, check voice messages from the Internet, and if a fax server is present, forward faxes to any local fax machine. Cisco Unity's optional digital networking module enables connectivity to other Cisco Unity servers at the same site via the LAN or remotely via WAN.

Cisco Unity supports both Cisco CallManager and leading legacy telephone systems—even simultaneously—to help smooth the transition to IP telephony and protect existing infrastructure investments. Built on a scalable platform, it uses streaming media and an intuitive HTML browser-style system administration interface.

Key Features

- Architecture allows IT staff to set one back-up procedure, one message storage policy, and one security policy
- Scalable to 72 ports and 1500 users per server; up to 7,500 subscribers per server; or a total of 250,000 users in an Exchange environment or 100,000 users in a Domino environment up; Server options with multiple processors, redundant fans, redundant power supplies and RAID hard disk drives
- Support for Exchange 2000/Active Directory as the single message store and directory
- AMIS-A and VPIM interoperability for legacy voice mail system interoperability
- Integration with many legacy PBX switches using analog, serial or digital set emulations; Enhanced networking for large deployments
- Support for multiple CCM clusters; ability to light Message Waiting Indicators
- With Exchange/Domino off-line, utilizes pre-MTA queue to take messages and give basic message access; Support for Lotus Domino as the single message store
- Fault-tolerant system tools—robust security, file replication, and event logging
- Support for Windows 2000 and Windows 2003 operating systems
- Unity Inbox/VMI (Visual Messaging Interface) is an Internet Explorer-based voice mail inbox providing unified messaging
- IMAP-based message interface to provide basic desktop message access
- Unity Bridge provides advanced message interchange functionality with legacy Avaya/Octel voice mail systems—unlocking proprietary networking to deliver open standards-based IP migration

Specifications

Feature	Cisco Unity 4.0
Unity Voice Mail (VM) and Unified Messaging (UM)	16, 32 and Max sessions Configured for CallManager or configured for legacy PBX/dual integration ¹
Possible Configurations	
Options	Voice Mail; Voice Mail with Multi-lingual option; Unified Messaging with TTS option Unified Messaging with Multi-lingual option; Exchange or Domino; AMIS for Exchange; VPIM for Exchange; Unity Inbox/Visual Messaging Interface; Failover for Exchange; Unity Bridge for Exchange

1. Contact your Cisco Software Sales Representative for integration information.

Selected Part Numbers and Ordering Information¹

Cisco Unity Servers

MCS-7815-I1-ECS1	MCS 7815 tower; Unity and Unity Bridge; 1GB; Win2K
MCS-7825-I1-ECS1	MCS 7825-IBM rack; 1GB RAM; sATA RAID; Win2K
MCS-7825-H1-ECS1	MCS 7825-HP rack; 1GB RAM; sATA RAID; Win2K
MCS-7835-I1-ECS1	MCS 7835-IBM; rack; 2GB; RAID 1; Win2K
MCS-7835-H1-ECS1	MCS 7835-HP; rack; 2GB; RAID 1; Win2K
MCS-7845-I1-ECS1	MCS 7845-IBM; VM-6HDD; rack; 4GB; RAID 1(x3) DUAL CPU; Win2K
MCS-7845-I1-ECS2	MCS 7845-IBM; UM-4HDD; rack; 4GB; RAID 1(x2) DUAL CPU; Win2K
MCS-7845-H1-ECS1	MCS 7845-HP; VM-6HDD; rack; 4GB; RAID 1(x3) DUAL CPU; Win2K
MCS-7845-H1-ECS2	MCS 7845-HP; UM-4HDD; rack; 4GB; RAID 1(x2) DUAL CPU; Win2K
UNITY-MCS-ML-DAT=	Hot-Swap tape drive for MCS-7835H and MCS-7845H
DAT-7835-I1	Hot swap IBM DAT tape drive for MCS-7835-I1
DAT-7845-I1	Hot swap IBM DAT tape drive for MCS-7845-I1
MCS-EXT-DAT	External DAT tape drive for MCS servers
MCS-EXT-SDLT	External SDLT drive for MCS servers
MCS-EXT-SCSI	SCSI card option for external DAT drive
UNITY-EXP-CHAS=	Expansion chassis

Cisco Unity 4.0 Unified Messaging and Voice mail Software

UNITYU4-50USR-E=	Unity UM Exchange, 50 users, 16 session, 2 TTS
UNITYU4-100USR-E=	Unity UM Exchange, 100 users, 16 session, 2 TTS
UNITYU4-200USR-E=	Unity UM Exchange, 200 users, 16 session, 2 TTS
UNITYU4-300USR-E=	Unity UM Exchange, 300 users, 16 session, 2 TTS
UNITYV4-50USR=	Unity VM, 50 users, 16 sessions
UNITYV4-100USR=	Unity VM, 100 users, 16 sessions
UNITYV4-200USR=	Unity VM, 200 users, 16 sessions
UNITYV4-300USR=	Unity VM, 300 users, 16 sessions
UNITY-DVD-4.0=	UNITY 4.0 DVD set
UNITY-CD-4.0=	UNITY 4.0 CD set

Cisco Unity Integrations

UNITY-D/41U-LS	D/41 Universal PCI - US/CANADA
UNITY-D/41U-EU	D/41 Universal PCI - Europe, Aus, NZ
UNITY-D/120U-LS	D/120JCT Universal PCI rev 2 - US/CANADA
UNITY-D/120U-EU	D/120JCT Universal PCI Euro - Europe, Aus, NZ
UNITY-PBXLINK-1	PBXLink, 4-24 ports for Lucent; 4-20 ports for Nortel
UNITY-PBXLINK-2	PBXLink, 4-40 ports for Lucent; 4-48 ports for Nortel
UNITY-PIMG-DIG	PBX IP Media gateway for digital integrations

Cisco Unity Bridge

UNITY-BRIDGE-3.0	Unity Bridge 3.0, requires Unity 4.0.3 or later
UNITY-BRIDGE-2.1	Unity Bridge 2.1, requires Unity 4.0.2 or earlier

1. This is only a small subset of all parts available via URL listed under "For More Information." Some parts have restricted access or are not available through distribution channels.

For More Information

See the Cisco Unity site: <http://www.cisco.com/go/unity>

Cisco Unity Connection

Cisco Unity Connection transparently integrates messaging and speech components with data networks to provide continuous global access to calls and messages. These advanced, convergence-based communication services help use voice commands to place calls or listen to messages in ‘hands-free’ mode and check voice messages from desktops, either integrated into an e-mail inbox or from a Web browser. It also features robust automated-attendant functions that include intelligent routing and easily customizable call-screening and message notification options.

Built on a platform that is easy to install and maintain, Cisco Unity Connection provides an intuitive Web browser based system administration interface that dramatically simplifies the installation, support, and ongoing management of the system, ultimately lowering an organization’s total cost of ownership.

Key Features

- Intelligent voice messaging allows users to interact with the system in the way that is most comfortable and convenient for them—Simple and intuitive telephone user interface (TUI) provides traditional access to voice messages; Desktop interface offers visual access to voice messages using either IMAP or a dedicated Web-browser application; Speech-enabled interface provides natural language access to voice messages and directories
- Integrates with Cisco CallManager and leading traditional telephone systems simultaneously
- Natively supports SIP proxy servers, designated SIP phones and clients, and SIP-enabled access gateways
- Browser-based system administration console and tools for easy installation and maintenance
- Cisco Unity Assistant enables IT staff to help end users manage more of their own accounts
- Supports physical terminal line (TTY) conversation for accessibility
- Scalable to 72 ports and 1500 users per server; up to 7,500 subscribers per server; or a total of 250,000 users in an Exchange environment or 100,000 users in a Domino environment up; Server options with multiple processors, redundant fans, redundant power supplies and RAID hard disk drives
- Support for Exchange 2000/Active Directory as the single message store and directory
- Integration with many legacy PBX switches using digital set emulations
- Support for multiple CCM clusters; ability to light Message Waiting Indicators
- Fault-tolerant system tools—robust security, file replication, and event logging
- IMAP-based message interface to provide basic desktop message access

Specifications

Feature	Cisco Unity Connection 1.1
Unity Voice Mail (VM) and Unified Messaging (UM)	16, 32 and Max sessions Configured for CallManager or configured for legacy PBX/dual integration ¹
Possible Configurations	
Options	Voice Mail; Integrated Messaging with TTS option Unity Inbox/Visual Messaging Interface;

1. Contact your Cisco Software Sales Representative for integration information.

Selected Part Numbers and Ordering Information¹

Cisco Unity Connection Servers

MCS-7815-I1-ECS1	MCS 7815 tower; 1GB; Win2K
MCS-7825-I1-ECS1	MCS 7825-IBM rack; 1GB RAM; sATA RAID; Win2K
MCS-7825-H1-ECS1	MCS 7825-HP rack; 1GB RAM; sATA RAID; Win2K
MCS-7835-I1-ECS1	MCS 7835-IBM; rack; 2GB; RAID 1; Win2K
MCS-7835-H1-ECS1	MCS 7835-HP; rack; 2GB; RAID 1; Win2K
MCS-7845-I1-ECS1	MCS 7845-IBM; VM-6HDD; rack; 4GB; RAID 1(x3) DUAL CPU; Win2K
MCS-7845-I1-ECS2	MCS 7845-IBM; UM-4HDD; rack; 4GB; RAID 1(x2) DUAL CPU; Win2K
MCS-7845-H1-ECS1	MCS 7845-HP; VM-6HDD; rack; 4GB; RAID 1(x3) DUAL CPU; Win2K
MCS-7845-H1-ECS2	MCS 7845-HP; UM-4HDD; rack; 4GB; RAID 1(x2) DUAL CPU; Win2K
UNITY-MCS-ML-DAT=	Hot-Swap tape drive for MCS-7835H and MCS-7845H
DAT-7835-I1	Hot swap IBM DAT tape drive for MCS-7835-I1
DAT-7845-I1	Hot swap IBM DAT tape drive for MCS-7845-I1
MCS-EXT-DAT	External DAT tape drive for MCS servers
MCS-EXT-SDLT	External SDLT drive for MCS servers
MCS-EXT-SCSI	SCSI card option for external DAT drive
UNITY-EXP-CHAS=	Expansion chassis

Cisco Unity Connection 1.1 Software

UNITYU4-50USR-E=	Unity UM Exchange, 50 users, 16 session, 2 TTS
UNITYU4-100USR-E=	Unity UM Exchange, 100 users, 16 session, 2 TTS
UNITYU4-200USR-E=	Unity UM Exchange, 200 users, 16 session, 2 TTS
UNITYU4-300USR-E=	Unity UM Exchange, 300 users, 16 session, 2 TTS
UNITYV4-50USR=	Unity VM, 50 users, 16 sessions
UNITYV4-100USR=	Unity VM, 100 users, 16 sessions
UNITYV4-200USR=	Unity VM, 200 users, 16 sessions
UNITYV4-300USR=	Unity VM, 300 users, 16 sessions
UNITY-DVD-4.0=	UNITY 4.0 DVD set
UNITY-CD-4.0=	UNITY 4.0 CD set

Cisco Unity Integrations

UNITY-PBXLINK-1	PBXLink, 4-24 ports for Lucent; 4-20 ports for Nortel
UNITY-PBXLINK-2	PBXLink, 4-40 ports for Lucent; 4-48 ports for Nortel
UNITY-PIMG-DIG	PBX IP Media gateway for digital integrations

1. This is only a small subset of all parts available via URL listed under "For More Information." Some parts have restricted access or are not available through distribution channels.

For More Information

See the Cisco Unity Connection site: <http://www.cisco.com/go/unity>

Cisco Unity Express

Cisco Unity Express provides voice mail and automated attendant services specifically for the small and medium office or branch. It's application is delivered on either a network module or advanced integration module which are supported on a variety of Cisco access router platforms and the Cisco Integrated Services Router family.

In a Cisco CallManager environment, Cisco Unity Express provides local storage and processing of voice mail and automated attendant services for the branch office, thereby alleviating WAN bandwidth and QoS concerns. Cisco CallManager Express and Unity Express combine to create the Cisco IP Communications Express solution which provides voice, data, and telephony management services integrated on a single, router-based platform.

Key Features

- Cost-effective operations through a single, integrated voice-and-data platform for all small and medium office or branch needs
- Boosts the professionalism, productivity and customer service available to the small and medium office through built-in automated attendant and voice mail capabilities; Customizable automated attendant to support business hours, day-of-week treatment and multi-level, nested automated attendant menus with up to 5 separate automated attendants per system
- Both standard and advanced voice mail features such as remote message access, save and delete, forward, pause, fast forward or rewind messages, alternate greetings, zero-out to designated alternate phone number or extension, per user storage allocation, plus much, much more
- Support for VPIMv2 for voice mail message exchange with other Cisco Unity or Unity Express systems.
- Remote maintenance and troubleshooting using Cisco CLI or Web-based GUI

Specifications

Feature	Cisco Unity Express
Hardware	NM-CUE, NM-CUE-EC, or AIM-CUE, fully self-contained modules with onboard storage, memory and processing supporting a variety of mailbox densities, storage capacities and concurrent sessions to meet the needs of every small and medium office or branch
Software	Cisco Unity Express release 1.1.2, 2.1, 2.2 and Cisco IOS 12.3.4T, 12.3.7T, 12.3.8T, 12.3.11T, 12.3(6th)T
Platform Supported	Cisco 2600XM, 2691,3700 Series Multi-Service Routers and Cisco 2800, 3800 Integrated Services Routers

For More Information

See the Cisco Unity Express Website: <http://www.cisco.com/go/ccmecue>

Cisco Personal Assistant

Cisco Personal Assistant streamlines communications with personal call rules, speech recognition, an optional enhanced text-to-speech engine and productivity services for IP phones. As an integral part of Cisco’s Architecture for Voice, Video and Integrated Data (AVVID), it interoperates with Cisco CallManager and scales to meet the present and future needs of businesses.

Key Features

- Automatic Speech Recognition (ASR)—Allows users to utilize simple voice commands to perform tasks such as retrieval, replying, recording, and deletion of voice messages from any telephone; Dial from personal address books or an enterprise LDAP directory; Synchronize Microsoft Exchange contact lists for quick name-dialing and ad-hoc group conferencing; Access controlled by user authentication
- Manage Inbound and Outbound Calls (Rules-Based Routing)—Using a Web interface to create rules, users can forward and screen calls based on caller identification, time of day, and meeting schedules; With “follow me,” a special rule that uses speech recognition, users can forward all calls to a phone number immediately; Users can activate sets of pre-created rules from any telephone
- CalendarView—Keep track of appointments on the IP phone, directly from the Microsoft Exchange server with no synchronization necessary; Upcoming event notification via phone display or by pager
- MailView—Access e-mail and Cisco Unity voice mail messages on the messaging server from anywhere; Any operation performed on messages is automatically reflected in Microsoft Exchange and Cisco Unity

Specifications

Feature	Cisco Personal Assistant
Platform	Cisco Media Convergence Server MCS-7825H-2.2-EVV1 and MCS-7835H-2.4-EVV1
Web Server Requirements for IP Phone Productivity Services Platform	Basic Web Server: Microsoft IIS 4.0 or later; Separate server for Cisco Personal Assistant Server and Speech Recognition Server
Software Compatibility	Cisco CallManager 3.1+, 3.2+, and 3.3+ Cisco Unity 2.46+, 3.0+, and 4.0+ for voice-mail features Microsoft Exchange 5.5 and Exchange 2000 for calendar, e-mail, contact synchronization features

Selected Part Numbers and Ordering Information¹

Cisco Personal Assistant

PASR-BUNDLE	Cisco Personal Assistant Bundle
SW_PASR1.4-SVR2S=	Cisco Personal Assistant 1.2 Server Software with Speech Recognition
SW-PASR1-USR=	Personal Productivity User License
SW-PASR1-USR10=	Personal Productivity 10 User License
SW-PASR1-KX=	Cisco Personal Assistant 1.4, Expansion Speech Recognition Session
SW-PASR1-TX=	Cisco Personal Assistant 1.4 Enhanced Text-to-Speech Session

1. This is only a small subset of all parts available via URL listed under "For More Information." Some parts have restricted access or are not available through distribution channels.

For More Information

See the Cisco Personal Assistant Website: <http://www.cisco.com/go/personalassist>

Cisco IP Contact Center (IPCC) Enterprise Edition

Cisco IPCC Enterprise Edition delivers skills-based contact routing, voice self-service, computer telephony integration (CTI), and multichannel contact management over an IP infrastructure. By combining multichannel automatic-call-distributor (ACD) functions with IP telephony in a unified solution, it helps enable companies to rapidly deploy a distributed contact center infrastructure.

Cisco IPCC Enterprise Edition segments customers, monitors resource availability, and delivers each contact to the most appropriate resource anywhere in the enterprise. The software profiles each customer contact using related data such as dialed number and calling line ID, caller-entered digits, data submitted on a Web form, and information obtained from a customer database lookup. This combination of customer and contact center data is processed through user-defined routing scripts that graphically reflect a company's business rules.

Key Features

- Full Scalability from less than a hundred to thousands of seats; Multi-site Contact Centers support; CRM Integration
- Carrier-class, distributed fault tolerance helps ensure uninterrupted operation
- Multi-channel interaction—Web collaboration with chat and callback, email, voice mail and fax routing
- Cradle-to-grave contact call detail records
- Common agent and supervisor desktops across all Cisco customer interaction management products
- Pre-defined and custom historical reports; Real-time reports integrated in the agent and supervisor desktops
- Support for custom call treatment for calls in queue includes support for music in queue and custom messaging; Standard screen pop allows any caller-entered information to be popped to the agent
- Support for agent/supervisor interaction via chat; pre-define agent-supervisor messages

Selected Part Numbers and Ordering Information¹**Cisco IP Contact Center**

IPCE-Bundle Requires the purchase of one IPCC Server license. This license entitles the user to deploy the following necessary components: (redundant) Router; (redundant) Logger; (redundant) CallManager Peripheral Gateway(s); (redundant) IVR Peripheral Gateway(s) for connection to Cisco IVR systems ISN and IP-IVR (Non-Cisco IVRs require Third part IVR port licenses); Administrative Workstation(s); Historical Database server(s); WebView server and WebView user connections; Internet Script Editor (ISE) server and ISE user connections; Application Gateways; (redundant) CTI Server for 3rd party CTI connections (only for non-agent desktop application)

IPCE-SVR IPCC ENTERPRISE SERVER LICENSE

1. This is only a small subset of all parts available via URL listed under "For More Information." Some parts have restricted access or are not available through distribution channels.

For More Information

See the Cisco IPCC Enterprise Edition Website: <http://www.cisco.com/go/ipcc>

Cisco IPCC Express Edition

Cisco IPCC Express Edition provides easy-to-deploy, easy-to-use, highly available, and sophisticated customer interaction management for 1 to 300 agents by supporting a highly available virtual contact center with integrated self-service applications across multiple sites secured with CSA. All Cisco IPCC Express Edition solutions are tightly integrated with Cisco CallManager.

Key Features¹

- Reduces business costs while improving customer response by providing sophisticated and distributed ACD, IVR, CTI, and agent/desktop services
- Browser-based administration; integrates with Cisco CallManager browser-based administration
- Cradle-to-grave contact call detail records
- Standard screen allows any caller-entered information to be popped to the agent
- Pre-defined or custom historical reports; Real-time reports within the agent and supervisor desktops
- High Availability with automatic failover for mission critical deployments
- Complete, enterprise wide scalable IP Contact Center solution with Cisco Customer Interaction Network
- Full support for agent/supervisor interaction via chat and to pre-define messages
- Full IP call queue points and prompt; Collect voice interaction capabilities
- Optional ASR and TTS capabilities
- Support for custom call treatment such as music for calls in queue

Selected Part Numbers and Ordering Information¹**Cisco IPCC Express Edition**

IPCX-40-STANDARD	NEW 4.0 STANDARD Deployment
IPCX-40-ENHANCED	NEW 4.0 ENHANCED Deployment
IPCX-40-PREMIUM	NEW 4.0 PREMIUM Deployment
IPCX-40-STD-ADDON	ADD ONs to an EXISTING 4.0 STANDARD Deployment
IPCX-40-ENH-ADDON	ADD ONs to an EXISTING 4.0 ENHANCED Deployment
IPCX-40-PRE-ADDON	ADD ONs to an EXISTING 4.0 PREMIUM Deployment

1. This is only a small subset of all parts available via URL listed under "For More Information." Some parts have restricted access or are not available through distribution channels.

For More Information

See the Cisco IPCC Express Edition Website: <http://www.cisco.com/go/icd>

1. Abbreviated list of IPCC Features

Cisco IPCC Hosted Edition

The Cisco IPCC Hosted Edition is suitable for both enterprise customers and service providers. For service providers, it creates a new, high-margin service revenue stream for incumbent providers as well as new service carriers. The service provider hosts the contact center infrastructure software—which is shared by multiple business customers—in its central office or data center. Subscribing business customers can have IP infrastructures, TDM infrastructures, or a combination of the two. For the enterprise customer with multiple branch offices or divisions the value is a centralized contact center infrastructure with the ability to offer services to its various divisions or satellite offices. The solution includes a suite of integrated services that can be introduced all at once or incrementally.

Key Features

- Virtual call center—Calls are routed to contact center agents independent of their location, a service especially appealing to businesses with branch offices or home agents
- Network routing with CTI-Network-based ACD is combined with CTI services
- Network IVR functionality is located in the network to provide information to callers or to collect information from callers before they speak with a live agent
- Calls are routed between contact centers based on call context information (dialed number and caller ID), agent availability, and customer information from databases

Selected Part Numbers and Ordering Information¹

Cisco IPCC Hosted Edition

IPCH-BUNDLE

The IPCC Hosted Edition bundle consists of two separately licensed sets of components:

The Base licenses for the shared infrastructure, such as the NAM, the network interfaces, shared network IVRs, CICMs and Hosted IPCC Agent licenses.; (redundant) Router; (redundant) Logger; (redundant) CallManager Peripheral Gateway(s); (redundant) IVR Peripheral Gateway(s) for connection to Cisco IVR systems ISN and IP-IVR (Non-Cisco IVRs require Third part IVR port licenses); Administrative Workstation(s); Historical Database server(s); WebView server and WebView user connections; Internet Script Editor (ISE) server and ISE user connections; Application Gateways; (redundant) CTI Server for 3rd party CTI connections (only for non-agent desktop application)

1. This is only a small subset of all parts available via URL listed under “For More Information.” Some parts have restricted access or are not available through distribution channels.

For More Information

See the Cisco IPCC Hosted Edition Website: <http://www.cisco.com/go/ipcchosted>

Cisco ICM Enterprise Edition

Through a combination of multi-channel contact management, intelligent routing, and network-to-desktop CTI, the Cisco ICM Enterprise Edition segments customers, monitors resource availability, and delivers each contact to the most appropriate resource anywhere in the enterprise.

Key Features

- Carrier-class, distributed fault tolerance for uninterrupted operation
- Profiles using contact-related data—dialed number and calling line ID, caller-entered digits, data submitted on a Web form, or information obtained from a customer profile database lookup; Processed using user-defined routing scripts that graphically reflect business rules; Routes each contact to the optimum resource anywhere in the enterprise; Delivers a unique and rich set of call event and customer profile data to the targeted desktop as a contact arrives, personalizing service and maximizing efficiency
- Gives customers the choice to interact via phone, Web, VoIP, text chat, or e-mail
- Provides centralized management control over customer contacts, allowing users to implement a single set of business rules that uniformly address customer needs independent of contact channel or resource location

Selected Part Numbers and Ordering Information¹

Cisco ICM Enterprise Edition
ICME-BUNDLE

Requires the purchase of at least one ACD PG and one ICM Agent license. Functionality included: Monitor 3rd party ACD (call and agent) activity; Call routing, including pre-routing from a carrier network and post-routing from an ACD; Historical Database server(s); WebView server and WebView user connections; Internet Script Editor (ISE) server and ISE user connections; Application, SQL and ICM-to-ICM Gateways; Redundant deployment of all licensed components; Integrations through the ICM's CTI interfaces with 3rd party devices that are not intended for agent desktop usage; Connections to Cisco IVR systems (IP-IVR and ISN) and all related functions an ICM can perform, such as monitoring, reporting and routing.

1. This is only a small subset of all parts available via URL listed under "For More Information." Some parts have restricted access or are not available through distribution channels.

For More Information

See the Cisco ICM Enterprise Edition Website: <http://www.cisco.com/go/icmee>

Cisco ICM Hosted Edition

The Cisco ICM Hosted Edition enables a service provider to quickly become a strategic business partner by hosting a broad continuum of mission-critical customer applications. With current users, it's functionality creates new revenue opportunities while strengthening customer loyalty.

When to Sell

Sell This Product

Cisco ICM Hosted Edition

When a Customer Needs These Features

- A direct and seamless evolution to the Internet economy and VoIP
- Open architecture—enables a smooth migration from circuit-switched to packet-based voice technology while enabling business-to-business services, e-commerce, and multimedia applications such as Web collaboration and e-mail response management—all transparent to the end user
- For the service provider—a unique opportunity to deliver critical applications tailored to each customer's business strategy; To sharply differentiate from competitors, making it easier to gain entry and obtain feature and/or transport revenues
- For the customer—Services to leverage value-added service provider capabilities to meet business goals

Key Features

- Virtual call center—Calls are routed to contact center agents independent of their location, a service especially appealing to businesses with branch offices or home agents
- Network routing—Network-based ACD is combined with CTI services
- Network IVR functionality is located in the network to provide information to callers or to collect information from callers before they speak with a live agent
- Calls are routed between contact centers based on call context information (dialed number and caller ID), agent availability, and customer information from databases

Selected Part Numbers and Ordering Information¹

Cisco ICM Hosted Edition HOSTED-BUNDLE

Consists of two separately licensed sets of components:

- The Base licenses for the shared infrastructure, such as the NAM and the network interfaces. This is an 'a la carte' licensing model, a customized system can be licensed by selecting the required volume and options
- The software licenses for the dedicated customer components such as the ICM instances, Peripheral gateway, agents, etc. These are ACD PG and Agent licenses.

1. This is only a small subset of all parts available via URL listed under "For More Information." Some parts have restricted access or are not available through distribution channels.

For More Information

See the Cisco ICM Hosted Edition Website:

<http://www.cisco.com/en/US/products/sw/custcosw/ps1973/index.html>

Cisco IP IVR

Cisco IP IVR is designed to enhance the efficiency of any organization by simplifying business integration, increasing flexibility, and providing efficiency gains in network hosting. These features reduce business costs while dramatically improving customer satisfaction. Enabled by Cisco AVVID, and tightly integrated with Cisco CallManager, the Cisco IP IVR offers ease of installation, configuration and application hosting because it is constructed specifically to exploit the power of IP-based communications. It facilitates concurrent multimedia communication processing.

Key Features

- Written in Java to provide customer flexibility; Support for VoiceXML
- Multimedia (voice/data/Web) IP-empowered application-generation environment
- Interoperates with ASR and TTS servers via Media Resource Control Protocol (MRCP)
- Offers web-based activation and administration; Multiple Language support
- Supports VoiceXML application servers via VoiceXML 2.0
- Flows (the IP IVR applications) are stored in an industry standard LDAP directory
- Sold with Cisco CallManager; Can be co-resident on the same server as CallManager; Can function on a separate, dedicated media convergence servers (MCSs) or Cisco-approved customer provided server
- Packages available to scale up to 300 ports

For More Information

See the Cisco IP IVR Website:

<http://www.cisco.com/en/US/products/sw/custcosw/ps3651/index.html>

Cisco Customer Voice Portal

The Cisco Customer Voice Portal integrates with both traditional time-division multiplexing (TDM) and IP-based contact centers to provide an unparalleled call-management and call-treatment solution with a self-service IVR option that can use information available to customers on the corporate Web server. With support for ASR and TTS capabilities, callers can obtain personalized answers to increasingly complex questions and can conduct business in new and innovative ways—all without the costs of interacting with a live agent. The CVP solution offers a unique capability of providing the voice processing on Cisco ISR, AS5350 or AS5400 Access Servers, thus allowing the same self-service application to be deployed at a retail office or at large customer call centers, thus significantly reducing customers bandwidth utilization.

The Customer Interaction Network is a suite of innovative multi-channel IP communications applications for the contact center that is accessible from any point on the network and integrated with core business processes.

Selected Part Numbers and Ordering Information¹

Cisco Customer Voice Portal

CVP-31-SVR	CVP 3.1 Self-Service Server Software
CVP-31-STUDIO	CVP 3.1 Studio
CVP-3X-PT	CVP 3.X Self-Service Port License
CVP-3X-PT-MN500	CVP 3.X Self-Service Pt License Min 500
CVP-3X-RED	CVP 3.X Self-Service Redundancy License

1. This is only a small subset of all parts available via URL listed under “For More Information.” Some parts have restricted access or are not available through distribution channels.

For More Information

See the Cisco Internet Service Node Website: <http://www.cisco.com/go/cvp>

Cisco 7900 Series IP Phones

Cisco IP Phones provide unmatched levels of integrated business functionality and converged environment. The Cisco IP Phone 7971G-GE, 7961G-GE, and 7941G-GE offer a Gigabit Ethernet port for integration to a PC or desktop server. The Cisco IP Phone 7970G and 7971G-GE includes a color, high-resolution backlit touch-screen display. The Cisco IP Phone 7960G manager set and the Cisco IP Phone 7961G enhanced manager set address the communication needs for a high or busy amount of phone traffic. The Cisco IP Phone 7940G business set and the Cisco IP Phone 7941G enhanced business set address the communication needs for medium to high telephone traffic. The Cisco IP Phone 7912G, 7911G and 7905G “basic sets” address the communication needs for low to medium telephone traffic. The Cisco IP Phone 7902G “entry set” addresses voice communication needs where only a minimal amount of features are required. The Cisco IP Phone Expansion Module 7914 provides additional buttons and LCD to the Cisco IP Phone 796X series and 797X series, increasing the total number of buttons to 20 with one module, or 34 with two modules. The Cisco IP Conference Station 7936, a high-quality hands-free conference station, is designed for use on desktops and offices and in small to medium-sized conference rooms.



Key Features

- Dynamic soft keys present calling options based on context
- Open APIs using XML to deliver applications to the display
- Automatic phone discovery, VLAN configuration, and registration
- QoS is provided via support of 802.1Q/p, in addition to configurable DIFFSERV and TOS
- Voice-activity detection, silence suppression, comfort-noise generation, and error concealment
- G.711a, G.711u, G.729ab audio-compression coder-decoders (codecs); Software upgrade support via Trivial File Transfer Protocol (TFTP) server
- Microsoft NetMeeting enabled—application sharing and video conferencing
- Integrated Ethernet Switch supporting Ethernet connectivity for a downstream PC
- Integrated Inline power support allows the phone to receive power over the LAN
- A hearing-aid-compatible handset

Specifications

Feature	7970G	7971G-GE	7985G	7914 Expansion Module	IP Conference Station 7936
Display	Pixel-based, color, touch-screen	Pixel-based, color, touch-screen	Pixel-based, color, integrated IP video	Pixel-based	Pixel-Based
Dynamic Soft Keys	8	8	5	N/A	3
Inline Power	Yes	IEEE power only	Yes	Yes	No
Ethernet Switch	10/100	10/100/ 1000	10/100	N/A	No
Lines	8	8	1	14	1
Speaker Phone	Yes	Yes	Yes	N/A	Yes
Headset Jack	Yes	Yes	Yes	N/A	No
3rd Party XML Applications	Yes	Yes	No	N/A	No

Feature	7941G	7941G-GE	7960G	7961G	7961G-GE
Display	Enhanced Pixel-based		Pixel-based	Enhanced Pixel-based	
Dynamic Soft Keys	4	4	4	4	4
Inline Power	Yes	Yes	Yes	Yes	Yes
Ethernet Switch	10/100/1000	10/100/1000	10/100	10/100/1000	10/100/ 1000
Lines	2	2	6	6	6
Speaker Phone	Yes	Yes	Yes	Yes	Yes
Headset Jack	Yes	Yes	Yes	Yes	Yes
3rd Party XML Applications	Yes	Yes	Yes	Yes	Yes

Feature	7902G	7905G	7912G	7911G	7940G
Display	None	Pixel-Based	Pixel-based	Pixel-Based	Pixel-Based
Dynamic Soft Keys	0	4	4	4	4
Inline Power	Yes	Yes	Yes	Yes	Yes
Ethernet Switch	No	No	Yes	Yes	10/100
Lines	1	1	1	1	2
Speaker Phone	No	Monitor Only	Monitor Only	Monitor Only	Yes
Headset Jack	No	No	No	No	Yes
3rd Party XML Applications	No	Yes	Yes	Yes	Yes

Selected Part Numbers and Ordering Information¹

Cisco 7900 Series IP Power and Phones

CP-7985-NTSC	Cisco IP Phone 7985G (NTSC)
CP-7985-PAL	Cisco IP Phone 7985G (PAL)
CP-7971G-GE	Cisco IP Phone 7971G-GE, Executive Set w/GigE Switch
CP-7970G	Cisco IP Phone 7970G, Executive Set
CP-7961G-GE	Cisco IP Phone 7961G-GE, Enhanced Manager Set w/GigE Switch
CP-7961G	Cisco IP Phone 7961G, Enhanced Manager Set
CP-7960G	Cisco IP Phone 7960G, Manager Set
CP-7941G-GE	Cisco IP Phone 7941G-GE, Enhanced Business Set w/GigE Switch
CP-7941G	Cisco IP Phone 79451G, Enhanced Business Set
CP-7940G	Cisco IP Phone 7940G, Business Set
CP-7912G-A	Cisco IP Phone 7912G, Basic Set w/ Switch
CP-7911G	Cisco IP Phone 7911G, Basic Set w/switch
CP-7905G	Cisco IP Phone 7905G, Basic Set
CP-7902G	Cisco IP Phone 7902G, Entry Set
CP-7936	Cisco IP Conference Station
CP-7914=	Cisco 7914 IP Phone Expansion Module for the Cisco IP Phone 796X series and 797X series
CP-SINGLFOOTSTAND=	Single module footstand
CP-DOUBLFOOTSTAND=	Double module footstand
CP-WALLMOUNTKIT=	Non-Locking Wall Mount Kit for 7910/40/60G series IP phones
CP-LCKNGWALLMOUNT=	Locking Wallmount Kit for the 7910/40/60G series IP phones
CP-LCKNGWALLMNT2=	Locking Wallmount Kit for all 7900 series IP phones
CP-PWR-CUBE=	IP Phone power transformer for 7900 series IP phones
WS-PWR-PANEL	Catalyst 48 port Inline Power Patch Panel

1. This is only a small subset of all parts.

For More Information

See the Cisco IP Telephones Website: <http://www.cisco.com/go/iptel>

Cisco ATA Series of Analog Telephone Adaptors



The Cisco ATA 186 and 188 Analog Telephone Adaptors bring analog telephones into the networked world. The Cisco ATA series of products address the low-end product portfolio need by targeting the enterprise, business local services, small-office environment and the emerging managed voice services market. These cost effective handset-to-Ethernet adaptors enable analog devices, such as phones and fax machines, to support voice-over-IP (VoIP) services. The Cisco ATA 186 is equipped with, and a single RJ-45 Ethernet port. The Cisco ATA 188 has two RJ-11 voice ports and two RJ-45 ports. The internal Ethernet switch allows for a direct connection to a 10/100BASE-T Ethernet network and connectivity to a co-located PC or other Ethernet-based device via the RJ-45 ports.

Both models ship with a bootload image and must be upgraded to a signaling firmware image available on Cisco.com before deployment. Cisco ATAs can be configured¹ to use the standards-based VoIP protocols SIP as well as Skinny Client Control Protocol (SCCP).

When to Sell

Sell This Product

Cisco ATA Series of Analog Telephone Adaptors

When a Customer Needs These Features

- Enable analog devices, such as phones and fax machines, to support Voice over IP services by converting the analog signal into an IP signal
- Continue use of existing analog phones with IP network

1. Two software image combinations are available on Cisco.com: H.323/SIP and MGCP/SCCP. MGCP/SCCP image includes the letters, ms, in its name.

Key Features

- Auto-provisioning with Trivial FTP provisioning servers
- Automatic assignment of IP address, network route IP, and subnet mask via DHCP
- Optional web configuration through built-in Web server
- Optional touch-tone telephone keypad configuration with voice prompt
- Administration password to protect configuration and access
- Advanced pre-processing to optimize full-duplex voice compression
- High performance line-echo cancellation eliminates noise and echo
- Voice activity detection (VAD) and comfort noise generation (CNG) save bandwidth by delivering voice, not silence
- Dynamic network monitoring to reduce jitter artifacts such as packet loss

Specifications

Feature	Cisco ATA 186	Cisco ATA 188
Telephone and network interfaces	2 RJ-11 FXS ports 1 RJ-45 interface for network connection	2 RJ-11 FXS ports 1 RJ-45 interface for network connection 1 RJ-45 "switch port" for connection to PC or another downstream Ethernet device Note: "Daisy chaining" multiple ATAs together through the second RJ45 port is not supported
Dimensions (H x W x D)	1.5 x 6.5 x 5.75 in. (3.8 x 16.5 x14.6 cm)	1.5 x 6.5 x 5.75 in. (3.8 x 16.5 x14.6 cm)
Weights	15 oz (425 gm)	15 oz (425 gm)
Voice-over-IP (VoIP) protocols	SIP (RFC 2543); SCCP	SIP (RFC 2543); SCCP

Selected Part Numbers and Ordering Information¹

Cisco ATA Series of Analog Telephone Adaptors

ATA186-I1-A	Cisco ATA 186 2-port adaptor, 600 ohm impedance
ATA186-I2-A	Cisco ATA 186 2-port adaptor, complex impedance (270 ohm in series with 750 ohm and 150 nF in parallel)
ATA188-I1-A	Cisco ATA 188 2-port adaptor with switch, 600 ohm impedance
ATA188-I2-A	Cisco ATA 188 2-port adaptor with switch, complex impedance (270 ohm in series with 750 ohm and 150 nF in parallel)

Cisco ATA Series of Analog Telephone Adaptors Power Supply Cables

ATACAB-NA	ATA power supply cable for North American-style power systems
ATACAB-EU	ATA power supply cable for Continental European-style power systems
ATACAB-UK	ATA power supply cable for United Kingdom
ATACAB-AR	ATA power supply cable for Argentina
ATACAB-JP	ATA power supply cable for Japan
ATACAB-AU	ATA power supply cable for Australia

1. Some countries have telephone networks that list multiple impedance requirements. It is important to closely approximate the impedance of the typical handsets used in the region when selecting the proper configuration. The incorrect choice may lead to poor echo cancellation performance.

For More Information

See the Cisco ATA Series Website: <http://www.cisco.com/go/ata186> and <http://www.cisco.com/go/ata188>

Cisco IP Communicator

Cisco IP Communicator is a software-based application that gives computers the capabilities and features of Cisco IP phones, providing high-quality voice calls and connection to company services while on the road, in the office, or from wherever users may have access to the corporate network. When used remotely, users have access to the same familiar phone services they have in the office. While registered to the Cisco CallManager call processing system, Cisco IP Communicator has the features and functionality of a full-featured Cisco IP Phone including the ability to transfer calls, forward calls, and conference additional participants to an existing call.

Key Features

- Easy to use—Feature parity with Cisco’s advanced IP phones, IP phone services support (XML) to deliver company specific applications to the desktop, and auto-detection of Cisco VPN client
- Premium voice quality—Audio Tuning Wizard for setting audio levels properly, advanced jitter buffer and packet loss concealment algorithms, and echo suppression and noise cancellation
- Easy to manage—Unified administration with Cisco IP phones and automatic software upgrades; system administrators can provision as they would any other Cisco IP Phone

Selected Part Numbers and Ordering Information

Cisco IP Communicator

SW-IPCOMM-E1

SW-CCM-UL-IPCOMM-E

Cisco IP Communicator Software

Station User License for Cisco CallManager

For More Information

See the Cisco IP Communicator Website:

<http://www.cisco.com/en/US/products/sw/voicesw/ps5475/index.html>

Cisco VT Advantage

Cisco VT Advantage brings video telephony functionality to Cisco IP Phones, providing users with the ability to add video easily to their communications experience. The software application and included USB camera allow a personal computer associated with a supported Cisco IP Phone adds video to phone calls. When registered to Cisco CallManager, the Cisco VT Advantage-enabled IP Phone has the features and functionality of a full-featured IP Phone.

Key Features

- Consistent voice and video user experience—Easy, low-cost, high-quality video calling; Familiar call features such as call forward, transfer, conference, hold, and mute are initiated through the phone while available video is viewed through the PC
- Easy to manage—Unified administration with Cisco IP phones and automatic software upgrades

Selected Part Numbers and Ordering Information

Cisco VT Advantage

CVT-ADV-E1=

Cisco VT Advantage (software and camera included)

For More Information

See the Cisco VT Advantage Website:

<http://www.cisco.com/en/US/products/sw/voicesw/ps5662/index.html>

Cisco Emergency Responder

Cisco Emergency Responder (ER) enhances emergency calling from Cisco CallManager. It assures that Cisco Callmanager sends emergency calls to the appropriate Public Safety Answering Point (PSAP). Cisco ER helps the PSAP identify the caller’s location and, if necessary, return the call. It can also notify customer security personnel of an emergency call in progress helping comply more effectively with legal or regulatory obligations and reduce risk of liability related to emergency calls.

Key Features

- Automatically Tracks IP Phone Location—Tracks IP phones by their IP address; Changes in phone locations can be detected within minutes; Analog phones connected to Foreign Exchange Station (FXS) ports are manually configured
- Provides Emergency Call Routing Instructions to Cisco CallManager
- Identifies Caller Location to LECs and PSAPs—Replaces the calling party number associated with an emergency call with one that corresponds to the caller’s location
- Eliminates Administration for IP Phone Relocation
- Supports Emergency Callback—ELINs are configured for Direct Inward Dialing (DID) and can be used by PSAPs to return emergency calls, if necessary; can be returned directly to phones with non-DID line numbers
- Alerts Customer Security Personnel to Emergency Calls in Progress
- Logs Emergency Calls and Location Record Changes

Specifications

Feature	Cisco Emergency Responder			
Supported Platform	Cisco 7800 series Media Convergence Servers; Cisco IP Telephony Operating System; Cisco IP Telephony Applications Backup and Restore System; Optional Security Script; Cisco Security Agent; Network Associates McAfee VirusScan Enterprise; Symantec Antivirus Corporate Edition;			
Product Compatibility	Cisco IP Phones 7902G, 7905G, 7910G, 7910G+SW, 7911G, 7912G, 7940G, 7941G, 7941G-GE, 7960G, 7961G, 7961G-GE, 7970G, 7971G, 7985G Cisco Wireless IP Phone 7920 (IP-subnet-based tracking only) Cisco IP Conference Stations 7935, 7936 Cisco Unified Client Cisco IP Communicator Cisco IP SoftPhone (does not support CDP-based tracking) Cisco ATA 180 series Analog Telephone Adaptors (manual configuration only) Cisco VG 200 series Analog Phone Gateways (manual configuration only) Cisco Catalyst 2900 XL, 2940, 2950, 2960, 2970, 3500 XL, 3550, 3560, 3750, 4000, 4500, 4900, 5000, 5500, 6000 and 6500 series LAN Switches Cisco Ethernet Switching Network Modules in Cisco 3700 series Multiservice Access Routers, 2800 and 3800 series Integrated Services Routers			
Software Compatibility	Cisco CallManager CiscoWorks IP Communications Operations Manager CiscoWorks IP Telephony Environment Monitor			
System Capacity	MCS 7815	MCS 7825	MCS 7835	MCS 7845
Automatically Tracked Phones	6,000	12,000	20,000	30,000
Manually Configured Phones	1,000	2,500	5,000	10,000
Roaming Phones (per Cisco 600 Emergency Responder Cluster)		1,200	2,000	3,000
Switches	200	500	1,000	2,000
Switch Ports	12,000	30,000	60,000	120,000

Selected Part Numbers and Ordering Information¹**Cisco Emergency Responder**

SW-CER-1.3-SVR=	CER 1.3 Software Plus CER 1.X User License 100 Phones
KEY-CER1.X-100=	CER 1.X (1.2 or Higher) User License 100 Phones
KEY-CER1.X-500=	CER 1.X (1.2 or Higher) User License 500 Phones
KEY-CER1.X-1K=	CER 1.X (1.2 or Higher) User License 1000 Phones
KEY-CER1.X-5K=	CER 1.X (1.2 or Higher) User License 5000 Phones
KEY-CER1.X-10K=	CER 1.X (1.2 or Higher) User License 10000 Phones

1. Redundant user licenses are not required when ordering redundant CER servers for a single CER group.

For More Information

See the Cisco Emergency Responder Website: <http://www.cisco.com/go/cer>

Cisco IP Manager Assistant

Cisco IP Manager Assistant (IPMA) provides the call-routing and call management capabilities required in a manager/administrative assistant business environment while giving users a choice of phone devices that better fit their needs. By combining a PC-based console application with various soft keys and display panes on Cisco IP phones, Cisco IPMA can present users job-specific tools—such as directories with click to dial, drag and drop functionality—to more efficiently manage calls.

Cisco IPMA is configured in either proxy-line mode or shared-line mode. In proxy-line mode, managers and assistants have different directory numbers or lines on their phones, but calls to managers are usually diverted to the assistant's line based on customizable dynamic filters. In shared-line mode, both managers and assistants share the same directory number, but assistants can handle calls without disturbing managers. Either mode can be used in conjunction with the PC based console application or a new XML based phone service that does not require a PC.

For More Information

See the Cisco IPMA Website: <http://www.cisco.com/go/ipma>

Cisco MCS 7800 Series Media Convergence Servers

Cisco MCS 7815-I1

- Provides an entry level tower server equipped with an Intel Pentium™ 4 3060MHz processor, 80GB Serial Attached ATA (SATA) hard drive and single non-hot-swap power supply



Cisco MCS 7825-H1 and Cisco MCS 7825-I1

- Each provides an entry level rack mount server that occupies only one rack mounting space
- Equipped with an Intel Pentium™ 4 3.4GHz processor, two 80GB Serial Attached ATA (SATA) hard drives configured as RAID1 and a single non-hot-swap power supply

Cisco MCS 7835-H1 and Cisco MCS 7835-I1

- Each provides a highly available mid-level rack mounted server solution that is equipped with an Intel Nocona Xeon™ 3400MHz processor, up to six hot-swap small computer system interface (SCSI) hard disks, a Redundant Array of Independent Disks (RAID) 1/0 Controller, hot-swap redundant fans and redundant hot-swap power supplies.
- An optional tape backup is available (Tape on 7835-I1 only supported for Unity)

Cisco MCS 7845-H1 and Cisco MCS 7845-I1

- Each provides a powerful and highly reliable high level rack mounted server solutions
- Equipped with two Intel Nocona Xeon™ 3400MHz processors, up to six hot-swap SCSI hard disks, RAID 1/0 controller, redundant hot-swap fans and redundant hot-swap power supplies
- An optional tape backup is available (Tape on 7845-I1 only supported for Unity)

Specifications

MCS-7815-I1	MCS-7825-H1	MCS-7825-I1	MCS 7835-H1
Intel Pentium® 4 3060-MHz processor 512KB L2 Cache 1024MB SDRAM or 2048MB SDRAM ¹ 80GB SATA Hard Disk 1.44MB Floppy Disk DVD Drive Integrated SATA Controller Single 10/100/1000 Ethernet NIC Tower System with optional rack mount kit.	Intel Pentium® 4 3400-MHz processor 1024KB L2 Cache 1024MB SDRAM Dual 80GB SATA Hard Disk 1.44MB Floppy Disk DVD Drive Integrated SATA Controller-RAID1 Dual 10/100/1000 Ethernet NIC1U Rack Mount System	Intel Pentium® 4 3400-MHz processor 1024KB L2 Cache 1024MB SDRAM Dual 80GB SATA Hard Disk 1.44MB Floppy Disk DVD Drive Integrated SATA Controller-RAID1 Dual 10/100/1000 Ethernet NIC1U Rack Mount System	Intel Xeon® 3400-MHz processor 1024KB Cache 2048MB SDRAM Two-72GB SCSI Hard Disk 1.44MB Floppy Disk DVD Drive SCSI Controller. Dual 10/100/1000 Ethernet NIC2U Rack Mount System

1. MCS-7815-I1-ECS1 contains 1024MB SDRAM while MCS-7815-I1-IPC3 and MCS-7815-I1-CC2 contains 2048MB SDRAM

Specifications (Con.)

MCS-7835-I1	MCS-7845-H1	MCS-7845-I1
Intel Xeon® 3400-MHz processor 1024KB Cache 2048MB SDRAM Two-72GB SCSI Hard Disk 1.44MB Floppy Disk DVD Drive SCSI Controller. Dual 10/100/1000 Ethernet NIC2U Rack Mount System	Dual Intel Xeon® 3400-MHz processor 1024KB Cache SDRAM is configuration dependant Hard Disk is configuration dependant 1.44MB Floppy Disk DVD Drive SCSI Controller. Dual 10/100/1000 Ethernet NIC2U Rack Mount System	Dual Intel Xeon® 3400-MHz processor 1024KB Cache SDRAM is configuration dependant Hard Disk is configuration dependant 1.44MB Floppy Disk DVD Drive SCSI Controller. Dual 10/100/1000 Ethernet NIC2U Rack Mount System

Selected Part Numbers and Ordering Information¹**Cisco Media Convergence Server 7800**

MCS-7815-I1-IPC3, MCS-7815-I1-ECS1, MCS-7815-I1-CC2	Cisco Media Convergence Server 7815-I1
MCS-7825-H1-IPC1, MCS-7825-H1-ECS1, MCS-7825-H1-CC1	Cisco Media Convergence Server 7825-H1
MCS-7825-I1-IPC1, MCS-7825-I1-ECS1, MCS-7825-I1-CC1	Cisco Media Convergence Server 7825-I1
MCS-7835-H1-IPC1, MCS-7835-H1-ECS1, MCS-7835-H1-CC1	Cisco Media Convergence Server 7835-H1
MCS-7835-I1-IPC1, MCS-7835-I1-ECS1, MCS-7835-I1-CC1	Cisco Media Convergence Server 7835-I1
MCS-7845-H1-IPC1, MCS-7845-H1-ECS1,	Cisco Media Convergence Server 7845-H1
MCS-7845-H1-ECS2, MCS-7845-H1-CC1	
MCS-7845-I1-IPC1, MCS-7845-I1-ECS1, MCS-7845-I1-ECS2,	Cisco Media Convergence Server 7845-I1
MCS-7845-I1-CC1	

1. This is only a small subset of all parts available via URL listed under “For More Information.” Some parts have restricted access or are not available through distribution channels.

For More Information

See the Cisco Media Convergence Server Website: <http://www.cisco.com/go/mcs>

Cisco Voice Gateways

Voice Gateways interface directly to PBXs or public telephone networks to carry voice traffic across IP networks—by converting IP calls to standard telephony calls and vice versa. They provide connectivity between packet telephony and legacy telephony such as PSTN, PBX, fax machines, and other devices. Cisco offers the Cisco VG 248 and VG 224 dedicated analog voice gateways.

Cisco’s full line of access and integrated routers can also add analog and digital voice gateway functionality through the use of network modules and voice interface cards.

Cisco VG 224 Voice Gateway

The Cisco VG 224 is a Cisco IOS high-density 24-port gateway for analog phones, fax machines, modems, and speakerphones within an enterprise voice system based on Cisco CallManager or CallManager Express. Having these devices tightly integrated with the IP-based phone system is advantageous for increased manageability, scalability, and cost-effectiveness. Commercial businesses can also use the Cisco VG 224 in conjunction with Cisco CallManager Express to effectively augment an Integrated Services Router (ISR) environment. This topology environment supports a business which needs a high concentration of analog voice ports for basic calls, with supplementary services such as transfer, hold, park and pickup.

With Cisco CallManager or Cisco CallManager Express, the Cisco VG 224 can provide supplementary analog services while leveraging Cisco IOS for reliable fax and modem delivery.

Cisco VG 248 Voice Gateway

The Cisco VG 248 Voice Gateway is a 1 unit high rack mountable device allowing 48 analog devices (phones, fax machines and modems) to be used with Cisco CallManager. It enables organizations like hotels, universities, and hospitals with large numbers of analog phones to deploy IP Telephony while maintaining the investment in legacy handsets. The analog lines are full featured with caller id, message waiting lights, and feature codes. The price per port is competitive with a legacy PBX.

The VG 248 supports the legacy voice mail Simple Message Desk Interface (SMDI) voice mail interface that allows the connection of a Cisco CallManager network to a legacy voice mail system. It also will allow the sharing of existing SMDI based voice mail systems between the Cisco CallManager and the legacy PBX.

Selected Part Numbers and Ordering Information

Cisco VG 200 Voice Gateway	
VG 224	Cisco VG 224 Analog Phone Gateway
VG 248	48 Port Voice over IP analog phone gateway

For More Information

See the Cisco Voice Gateways Website: <http://www.cisco.com/go/voicegate>

Memory Information for Universal Gateways

Router	Memory Type	Slots	Default Memory	Max Memory	Default Config. (Notes)
Cisco AS5350XM	Main SDRAM	2	512 MB	1 GB	
	System Flash	1	128 MB	1 GB	
Cisco AS5350	Main SDRAM	2	256 MB	512 MB	
	Shared	1	128 MB	128 MB	
	Boot Flash	1	16 MB	16 MB	
	System Flash	2	64 MB	64 MB	
Cisco AS5400XM	Main SDRAM	2	512 MB	1 GB	
	System Flash	1	128 MB	1 GB	
Cisco AS5400HPX	Main SDRAM	2	512 MB	512 MB	Cisco AS5400HPX and Cisco AS5400 use different Boot and System Flash — NOT interchangeable
	Shared	1	128 MB	128 MB	
	Boot Flash (3V)	1	16 MB	16 MB	
	System Flash (3V)	2	64 MB	64 MB	
Cisco AS5400	Main SDRAM	2	256 MB	512 MB	Cisco AS5400HPX and Cisco AS5400 use different Boot and System Flash — NOT interchangeable
	Shared	1	128 MB	128 MB	
	Boot Flash (5V)	1	16 MB	16 MB	
	System Flash (5V)	2	64 MB	64 MB	
Cisco AS5850	RSC SDRAM		1 GB	1 GB	Ships with all required memory
	Feature Cards SDRAMS		128 MB	128 MB	

Cisco AS5350 Series Universal Gateway

The Cisco AS5350 Series Universal Gateway is a one-rack-unit (1RU) gateway supporting two-, four-, or eight-port T1/seven-port E1 configurations that provides voice, fax, and data services on any port at any time. This cost-effective platform is ideally suited for SP and enterprise environments that require innovative voice, fax, and data services.

The Cisco AS5350 Series consists of two models—the Cisco AS5350XM and the Cisco AS5350. The Cisco AS5350XM Universal Gateway doubles the performance of the Cisco AS5350 and delivers significant memory enhancements to offer high performance and high reliability in a compact, modular design. The Cisco AS5350XM Universal Gateway supports existing Cisco AS5350 trunk termination and universal port feature cards in a more powerful chassis to ensure continuing network investment protection.



When to Sell

Sell This Product

Cisco AS5350XM

When a Customer Needs These Features

- High density in a small footprint (2 CT1/CE1, 4 CT1/CE1 or 8 CT1/7 CE1)
- High performance voice, fax, and data services
- Enhanced performance for processor intensive voice and fax applications
- Low power per port
- Two 10/100/1000BaseT Gigabit Ethernet ports
- T.38 real-time fax relay, T.37 fax store and forward, fax detection, unified communications
- 2 to 8 channelized CT1/7 CE1/PRI compact and modular universal
- Universal port services (data, voice, fax)
- Two 10/100BaseT Ethernet ports

Cisco AS5350

Key Features

- 1 RU modular high-performance 2 to 8 channelized CT1/7 CE1/PRI system
- Universal Gateway—offering best in class voice, fax, and remote access services
- Ideal for Tier 2/3 ISPs and enterprises requiring innovative universal services
- Feature cards: 2, 4, or 8 CT1/7 E1/PRI feature cards (ISDN calls terminated on the card); 60 or 108 channel Universal Port feature card
- Cisco AS5350XM—Two 10/100/1000BaseT autosensing Gigabit Ethernet LAN ports
- Cisco AS5350—Two 10/100BaseT autosensing Ethernet LAN ports
- Two 8 MB serial WAN ports for Frame Relay, HDLC, or PPP WAN backhaul
- Carrier Class Resiliency: All feature cards and fan tray are hot swappable, modem and voice DSP are pooled and can be configured as spares, internal power supply with dual fans, Redundant LAN/WAN backhaul ports, Thermal management and environmental monitoring, ETSI/NEBS Level 3 compliant
- Single or Redundant AC or DC power supply with dual fans
- Cisco SS7 signaling gateway interoperability

Competitive Products

- Lucent/Ascend: Max TNT
- 3Com/CommWorks: Total Control 1000
- Alcatel: 7505 Series
- Nuera: BTX Series
- Siemens: HiPath Series

Specifications

Feature	Cisco AS5350	Cisco AS5350XM
Processor	250 MHz RISC processor	750 MHz RISC processor
SDRAM	256 MB (default), 512 MB (maximum)	512 MB (default), 1 GB (maximum)
Boot Flash	16 MB (default), 16 MB (maximum)	N/A
System Flash	64 MB (default), 64 MB (maximum)	128 MB (default), 1 GB (maximum)
Shared input/output (I/O)	128 MB (default), 128 MB (maximum)	N/A
Feature Card Slots	Three slots	Same as Cisco AS5650
Egress Ports	Two 10/100BaseT Ethernet ports Two 8-Mbps serial ports T1/E1 DS1 trunk feature cards	Two 10/100/1000BaseT Gigabit Ethernet ports Two 8-Mbps serial ports T1/E1 DS1 trunk feature cards
LAN Protocols	IP, IPX, AppleTalk, DECnet, ARA, NetBEUI, bridging, HSRP, 802.1Q	
WAN Protocols	Frame Relay, PPP, HDLC (leased line)	
Routing Protocols	Routing Information Protocol (RIP), RIPv2, OSPF, IGRP, EIGRP, BGPv4, IS-IS, AVEIGRP, IPX-EIGRP, Next Hop Resolution Protocol (NHRP), AppleTalk Update-Based Routing Protocol (AURP)	
QoS Protocols	IP Precedence, Resource Reservation Protocol (RSVP), Weighted Fair Queuing (WFQ), Weighted Random Early Detection (WRED), Multichassis Multilink PPP (MMP) fragmentation and interleaving, 802.1P	
Access Protocols	PPP, Serial Line Internet Protocol (SLIP), TCP Clear, IPXCP, ATCP, ARA, NBFCP, NetBIOS over TCP/IP, NetBIOS over PPP, protocol translation (PPP, SLIP, ARA, X.25, TCP, local-area transport [LAT], Telnet), and Xremote	
Bandwidth Optimization	Multilink PPP (MLPPP), TCP/IP header compression, Bandwidth Allocation Control Protocol (BACP)	
Voice Compression	G.711, G.723.1 (5.3K and 6.3K), G.726, G.729ab, G.729, GSM-FR	
DSP Voice Features	Echo cancellation, programmable up to 128 ms Transparent transcoding between A-law and mu-law encoding Voice activity detection, silence suppression, comfort noise generation Fixed and adaptive jitter buffering Call progress tone detection and generation - Dial tone, busy, ring-back, congestion, and re-order tones with local country variants DTMF, Multifrequency (MF) Continuity Testing (COT)	
Voice and Fax Signaling Protocols	H.323v2, H.323v3, H.323v4, SIP, MGCP 1.0, TGCP 1.0, Voice XML, Real-Time Streaming Protocol (RTSP), Extended Simple Mail Transfer Protocol (ESMTP) T.38 real-time fax relay T.37 fax store and forward Fax detection Fax and modem passthrough Open Settlements Protocol (OSP) Media Recording Control Protocol (MRCP) TTS Servers ASR Servers	
SS7	Integrated Signaling Link Terminal (ISLT), MTP1, MTP2, IUA, RUDD backhaul	

Feature	Cisco AS5350	Cisco AS5350XM
Network Security	RADIUS or TACACS+, PAP, CHAP and MSCHAP authentication, local user/password database DNIS, CLID, call-type preauthentication Inbound/outbound traffic filtering (including IP, IPX, AppleTalk, bridged traffic) Network Address Translation (NAT) and dynamic access lists (ACLs)SNMPv2, SNMPv3, SSHv2 H.235	
Virtual Private Networking	IP Security (IPSec) and policy enforcement (RADIUS or TACACS+),L2TP, Layer 2 Forwarding (L2F), and generic routing encapsulation (GRE) tunnels Firewall security and intrusion detection QoS features (committed access rate [CAR], Random Early Detection [RED], IP Precedence, policy-based routing)	
Channelized T1	Robbed-bit signaling; Loop Start, Immediate Start, and Wink Start Protocols	
Channelized E1	CAS, PRI, E1 R1, E1 R2, leased line, Frame Relay, G.703, G.704	
ISDN Protocols Supported	Sync mode PPP, V.120, V.110 at rates up to 38400 bps Network- and User-side ISDN NFAS with backup D-channel QSIG, Feature Group B, Feature Group D DoVBS	
Modem Protocols Supported	V.90 or V.92 standard supporting rates of 56000 to 28000 in 1333 bps increments V.92 Modem on Hold and Quick Connect V.44 Compression supporting increased throughput by more than 100 percent for Internet browsing K56Flex at 56000 to 32000 in 2000-bps increments ITU-T V.34 Annex 12 at 33600 and 31200-bps ITU-T V.34 at 28800, 26400, 24000, 21600, 19200, 16800, 14400, 12000, 9600, 7200, 4800, or 2400-bps V.32bis 14400, 12000, 9600, 7200, 4800; V.32 9600, 4800; V.22bis 2400, 1200; V.21 300; Bell 103, 300; V.22 1200; V.23 1200/75 ITU-T V.42 (including Microcom Networking Protocol [MNP] 2-4 and Link Access Procedure for Modems [LAPM]) error correction ITU-T V.42bis (1000 nodes) and MNP 5 data compression Async-mode PPP	
Full Cisco IOS Support	IP Plus and Enterprise Plus feature sets including 3DES and Lawful Intercept images	
Console and Auxiliary Ports	Asynchronous serial (RJ-45)	
Chassis	Dimensions (H x W x D): 1.75 x 17.5 x 20.5 in. Weight (fully loaded): 22 lbs. (10 kg)	

For More Information

See the Cisco Universal Gateways and Access Servers Website:

<http://www.cisco.com/en/US/products/hw/iad/index.html>

Cisco AS5400 Series Universal Gateways



Cisco AS5400 Series Universal Gateways offer unparalleled capacity in only two rack units (2RUs) and provide voice, fax and data servicess on any port at any time. High-density (up to 1 CT3 of VoIP and 2 CT3 of TDM switching), low-power consumption (7.2A at 48 VDC per CT3), and universal port DSPs make the Cisco AS5400 Universal Gateways ideal for many network deployment architectures, especially colocation environments and mega POPs.

The Cisco AS5400 Series consists of three models, the Cisco AS5400XM, the Cisco AS5400 and the Cisco AS5400HPX. The Cisco AS5400XM Universal Gateway doubles the performance of the Cisco AS5400 and Cisco AS5400HPX and delivers significant memory enhancements to offer high performance and high reliability in a compact, modular design. The Cisco AS5400XM Universal Gateway supports existing Cisco AS5400 and AS5400HPX trunk termination and universal port feature cards in a more powerful chassis to ensure continuing network investment protection. This cost-effective platform is ideally suited for SP and enterprise environments that require innovative voice, fax, and data services.

When to Sell

Sell This Product

Cisco AS5400XM

When a Customer Needs These Features

- High density in a small footprint (16 CT1/CE1 or 1 CT3)
- High performance voice, fax, and data services up to 1 CT3
- Enhanced performance for processor intensive voice and fax applications
- Compact form factor-easy to add capacity as the network grows
- Low power per port
- Two 10/100/1000BaseT Gigabit Ethernet ports
- T.38 real-time fax relay, T.37 fax store and forward, fax detection, unified communications
- Voice and fax applications up to 480 sessions
- Universal port services (data, voice, fax)
- Two 10/100BaseT Ethernet ports
- Data applications up to 1 CT3
- Universal port services (data, voice, fax)
- Two 10/100BaseT Ethernet ports

Cisco AS5400HPX

Cisco AS5400

Key Features

- The Industry's only 2RU, CT3-capable universal gateway on the market with hot-swappable cards, internal redundant power supply
- Universal Gateway offering best in class voice, fax, and remote access services Feature cards: 8 CT1/CE1 and CT3 feature cards; 60 or 108 channel Universal Port feature card; All feature cards and fan trays are hot-swappable
- Cisco AS5400XM—Two 10/100/1000BaseT autosensing Gigabit Ethernet LAN ports
- Cisco AS5400 and Cisco AS5400HPX—Two 10/100BaseT autosensing Ethernet LAN ports
- Redundant 8 Mbps serial backhaul ports for Frame Relay, HDLC or PPP WAN Backhaul
- One fast console port for local administrative access; one auxiliary port for remote administrative access
- Redundant LAN/WAN backhaul ports
- ETSI/NEBS Level 3 compliant
- Redundant AC or DC power supply with dual fans
- Cisco SS7 signaling gateway interoperability

Competitive Products

- 3Com/CommWorks: Total Control C1000
- Alcatel: 7505 Series
- Lucent: Max TNT
- Siemens: HiPath Series

Specifications

Features	Cisco AS5400XM	Cisco AS5400HPX	Cisco AS5400
Processor Type	750 MHz RISC processor	390 MHz RISC processor	250 MHz RISC processor
Calls Supported	Voice, fax and remote access services up to 648 concurrent calls (to 1CT3/16E1s)	Cisco AS5400HPX: Voice or fax services - to 480 concurrent calls (to 20T1s/16E1s) or remote access services - to 648 calls (to 1CT3/16E1s)	Remote access services - to 648 calls (to 1CT3/16E1s)
SDRAM	512 MB (default), 1 GB (maximum)	512 MB (default), 512 MB (maximum)	256 MB (default), 512 MB (maximum)
Boot Flash	N/A	16 MB (default) 16 MB (maximum)	Same as AS5400HPX
System Flash	128 MB (default), 1 GB (maximum)	64 MB (default) 64 MB (maximum)	Same as AS5400HPX
Shared input/output (I/O)	N/A	128 MB (default), 128 MB (maximum)	Same as AS5400HPX
Feature Slots	7	Same as AS5400XM	Same as AS5400XM
Trunk Feature Cards	8 T1/E1/PRI, 1 CT3	Same as AS5400XM	Same as AS5400XM
DSP Feature Card	60/180 Universal ports	Same as AS5400XM	Same as AS5400XM
LAN Protocols	IP, IPX, AppleTalk, DECnet, ARA, NetBEUI, bridging, HSRP, 802.1Q		
WAN Protocols	Frame Relay, PPP, HDLC (leased line)		
Routing Protocols	Routing Information Protocol (RIP), RIPv2, OSPF, IGRP, EIGRP, BGPv4, IS-IS,AY-EIGRP, IPX-EIGRP, Next Hop Resolution Protocol (NHRP), AppleTalk Update-Based Routing Protocol (AURP)		
QoS Protocols	IP Precedence, Resource Reservation Protocol (RSVP), Weighted Fair Queuing (WFQ), Weighted Random Early Detection (WRED), Multichassis Multilink PPP (MMP) fragmentation and interleaving, 802.1P		

Access Protocols	PPP, Serial Line Internet Protocol (SLIP), TCP Clear, IPXCP, ATCP, ARA, NBFCP, NetBIOS over TCP/IP, NetBEUI over
Bandwidth Optimization	PPP, protocol translation (PPP, SLIP, ARA, X.25, TCP, local-area transport [LAT], Telnet), and Xremote Multilink PPP (MLPPP), TCP/IP header compression, Bandwidth Allocation Control Protocol (BACP)
Voice Compression	G.711, G.723.1 (5.3K and 6.3K), G.726, G.729ab, G.729, GSM-FR
DSP Voice Features	Echo cancellation, programmable up to 128 ms Transparent transcoding between A-law and mu-law encoding Voice activity detection, silence suppression, comfort noise generation Fixed and adaptive jitter buffering Call progress tone detection and generation - Dial tone, busy, ring-back, congestion, and re-order tones with local country variants DTMF, Multifrequency (MF) Continuity Testing (COT)
Voice and Fax Signaling Protocols	H.323v2, H.323v4, SIP, MGCP 1.0, TGCP 1.0, Voice XML, Real-Time Streaming Protocol (RTSP), Extended Simple Mail Transfer Protocol (ESMTP), T.38 real-time fax relay, T.37 fax store and forward Fax out (transmission) Group 3, standards EIA 2388 Class 2 and EIA 592 Class 2.0 at modulations V.33, V.17, V.29, V.27ter, V.21 ITU-T T.30, T.4 Fax detection, fax and modem passthrough Open Settlements Protocol (OSP), Media Resource Control Protocol (MRCP) to enable TTS and ASR Services
Virtual Private Networking	IP Security (IPSec) and Policy enforcement (RADIUS or TACACS+), L2TP, Layer 2 Forwarding (L2F), and generic routing encapsulation (GRE) tunnels Firewall security and intrusion detection QoS features (committed access rate [CAR], Random Early Detection [RED], IP Precedence, policy-based routing)
Channelized T1	Robbed-bit signaling; Loop Start, Immediate Start, and Wink Start Protocols
Channelized E1	CAS, PRI, E1 R1, E1 R2, leased line, Frame Relay, G.703, G.704
ISDN Protocols Supported	Sync mode PPP, V.120, V.110 at rates up to 38400 bps, Network- and User-side ISDN NFAS with backup D-channel QSIG, Feature Group B, Feature Group D DoVBS
Modem Protocols Supported	V.90 or V.92 standard supporting rates of 56000 to 28000 in 1333 bps increments V.92 Modem on Hold and Quick Connect V.44 Compression supporting increased throughput by more than 100 percent for Internet browsing K56Flex at 56000 to 32000 in 2000-bps increments ITU-T V.34 Annex 12 at 33600 and 31200-bps ITU-T V.34 at 28800, 26400, 24000, 21600, 19200, 16800, 14400, 12000, 9600, 7200, 4800, or 2400-bps V.32bis 14400, 12000, 9600, 7200, 4800; V.32 9600, 4800; V.22bis 2400, 1200; V.21 300; Bell 103, 300; V.22 1200; V.23 1200/75 ITU-T V.42 (including Microcom Networking Protocol [MNP] 2-4 and Link Access Procedure for Modems [LAPM]) error correction ITU-T V.42bis (1000 nodes) and MNP 5 data compression
Full Cisco IOS Support	IP Plus and Enterprise Plus feature sets including 3DES and Lawful Intercept images
Console and Auxiliary Ports	Asynchronous serial (RJ-45)
Chassis Dimensions (H x W x D)	3.5 x 17.5 x 18.25 in.
Chassis Weight (fully loaded)	35 lb maximum (15.8 kg)

For More Information

See the Cisco Universal Gateways and Access Servers Website:

<http://www.cisco.com/en/US/products/hw/iad/index.html>

Cisco AS5850 Universal Gateway

The Cisco AS5850 Universal Gateway is a high-density universal gateway, with carrier-class attributes, offering highest capacity and high availability in its class. Higher capacity configurations, depending on dial, voice, and fax application types are also supported. It supports a wide range of IP-based value-added services such as high-volume Internet access, corporate VPNs, long distance for ISPs, international wholesale long distance, distributed prepaid calling, SS7 interconnect, and managed voice services such as hosted IP telephony, managed IP-PBX, multiservice VPNs, and IP contact centers.

Using the rich set of Cisco IOS Software features and SS7 interconnection, service providers can quickly provision their network for new services to meet the rapidly changing demands of the communications provider marketplace.



When to Sell

Sell This Product

Cisco AS5850

When a Customer Needs These Features

- Supporting at least 2,688 sessions of data, voice, and fax services on any port at any time using T1, E1, channelized DS3 and STM-1 trunk interfaces. Larger configurations are supported for dial, MGCP voice, TDM switching, and simple H.323 or SIP applications.
- Service provider or IP-focused installations
- Highly available single system with multiple redundancy
- Wholesale dial/voice, retail dial/voice, TDM grooming or wireless applications

Key Features

- Hot-swappable redundant power supplies and power feeds
- Redundant DSPs and RSC; redundant blower for cooling; CAC
- Supports any coder-decoder (CODEC) at 100-percent capacity; simplify network engineering
- Router Processor Redundancy+ for high availability
- Thermal/Power management and redundant fans
- DSP Resource Recovery Feature
- Supports H.323v2, H.323v3, H.323v4, SIP and MGCP 1.0; An open programmable architecture streamlines rapid voice service creation.
- Application-specific support including AOL and Prodigy traffic
- WAN optimization—routing filters, snapshot routine, dial-on-demand routing ASAP
- ETSI/NEBS Level 3 compliant
- Cisco SS7 signaling gateway interoperability
- Stratum-3 clock support
- 802.1Q/1p VLAN/ISL support

Competitive Products

- 3Com: TC 2000
- Lucent: APX 8000
- Siemens: HiPath Series
- Alcatel: 7505 Series

Specifications

Feature	Cisco AS5850
Slots	12 feature board slots; 2 eRSC slots
Processor Type	650 MHz Broadcom 1250 Dual Core
RSC Switch Fabric	5 Gbps, Layer 3 / 4 switching
Memory	1 GB SDRAM with ECC per ERSC 128 MB SDRAM (with parity) per feature card
Trunk Cards	Single CT3 plus 216 DSP Channel feature card; 24 CE1/CT1 feature card; Single port Channelized STM-1 feature card
Universal Port Card	324 Channel DSP-feature card
Egress Ports	Dual Gigabit load-balanced redundant Ethernet ports with GBIC interfaces for user traffic Dual 10/100-Mbps Ethernet port with RJ45 connector for management traffic
LAN Protocols	IP, IPX, AppleTalk, DECnet, ARA, NetBEUI, bridging, HSRP, 802.1Q
Service Support	Port Policy Management and SS7/C7
Routing Protocols	RIP, RIPv2, OSPF, IGRP, EIGRP, BGPv4, IS-IS, Next Hop Resolution Protocol (NHRP)
Access Protocols	PPP, Serial Line Internet Protocol (SLIP), TCP Clear
Bandwidth Optimization	Multilink PPP (MLPPP), TCP/IP header compression, Bandwidth Allocation Control Protocol (BACP), Bandwidth on demand, Nonfacility-associated signaling (NFAS), traffic shaping
Network Security	RADIUS or TACACS+, PAP or CHAP authentication, local user/password database, DNIS, CLID, call-type pre-authentication, Inbound/outbound traffic filtering (including IP), SNMPv2, SNMPv3
Virtual Private Networking	IP Security (IPSec) and Policy enforcement (RADIUS or TACACS+), L2TP, Layer 2 Forwarding (L2F), and generic routing encapsulation (GRE) tunnels, Firewall security and intrusion detection, IP Precedence, policy-based routing
Channelized T1	PRI, robbed-bit signaling; loop start, immediate start, and wink start protocols, SS7 IMT
Channelized DS3	PRI, robbed-bit signaling; loop start, immediate start, and wink start protocols, SS7 IMT
Channelized E1	CAS, E1 R2, PRI, SS7 IMT
Channelized STM-1	CAS, E1 R2, PRI, SS7 IMT
ISDN Protocols	Sync mode PPP, V. 120, V. 110 at rates up to 38400
Voice Protocols	G.711, G.723.1, G.726, G.729ab, G.Clear, GSM-FR; H.323v2, H.323v3, H.323v4, SIP, MGCP 1.0; ECAN up to 128ms; T.38 real-time fax relay; Fax detection; Fax and modem passthrough

Modem Protocols	V.90 or V.92 standard supporting rates of 56000 to 28000 in 1333-bps increments; V.44 supporting increased throughput by more than 100 percent for Internet browsing; Fax out (transmission) Group 3, standards EIA 2388 Class 2 and EIA 592 Class 2.0, at modulations V.33, V.17, V.29, V.27ter, and V.21; K56Flex at 56000 to 32000 in 2000-bps increments; ITU-T V.34 Annex 12 at 33600 and 31200 bps; and more
ISDN Protocols	Sync mode PPP, V.120, V.110 at rates up to 38400 bps
Wireless Protocol	V.110
Console	Asynchronous serial (RJ-45)
Dimensions (H x W x D)	24.5 x 17.5 x 24 in.
Chassis Weight	220 lb (100 kg)

For More Information

See the Cisco Universal Gateways and Access Servers Website:
<http://www.cisco.com/en/US/products/hw/iad/index.html>

Cisco IP/VC 3500 Series Videoconferencing Products

Cisco® IPVC – part of the Cisco IP Communications system—is a complete portfolio of IP video Multipoint Control Units (MCU’s) and ISDN gateways for traditional video conferencing networks, and Cisco Video Telephony and Cisco MeetingPlace solutions. Cisco Video Telephony integrates video into Cisco CallManager to enable desktop video communications—making video as easy to use and administer as a telephone.

Key Features

- Scalability—Create large conferences by cascading conferences between multiple Cisco IPVC 3511 Multipoint Control Units and Cisco IPVC 3540 Series Multipoint Control Units. Cascaded conferences can be centralized in the data center or geographically distributed utilizing WAN bandwidth more efficiently. Increase the conferencing capacity by creating an MCU cluster of up to six Cisco IPVC 3540 MCUs
- Supports standard video conferencing for IP and ISDN video endpoints-ISDN video endpoints require the use of the IPVC ISDN Gateway
- SIP Support—Targeted at enabling the creation of many diverse end points and video-enabled applications; The Cisco IPVC MCU provides multi-party voice and video conferencing for SIP-enabled video end points (examples: Microsoft Messenger, eConf, and Polycom VSX 8000). Further more, inter-working functionality is provided allowing multi-protocol end points-SIP, SCCP, H.323, and H.320-to attend the same conference
- Integrates video conferencing into the Cisco MeetingPlace solution— Enables users to set up, attend, and manage voice, video and web rich-media conferences
- Integrating Cisco IPVC into Cisco MeetingPlace leverages disparate conferencing investments to maximize conferencing resources and provide new levels of user satisfaction and productivity
- Scheduling-Enables the Cisco MeetingPlace Web user interface, Microsoft Outlook, and Lotus Notes interfaces to set-up scheduled and reservation-less video conferences
- Notification-Cisco MeetingPlace meeting notifications include meeting dial in and dial out information for video conferences
- Management-New Cisco MeetingPlace information and commands targeted at video end points
- Cisco Video Telephony is a capability of Cisco CallManager extending phone usage and administration models to desktop video communications. Video calls now have familiar phone features such as hold, transfer, and call forward. Dial plans for video and telephony are integrated along with call detail records (CDRs) and administration points

Specifications

Feature	Cisco IP/VC 3500 Series Videoconferencing
Protocols	H.323 V.4, SCCP, SIP, H.320 through the IPVC Gateway, H.239, H.235, H.281 FECC; G.711; H.261, H.263, H.263+, H.264; T.120
SCCP Protocol Support	All Cisco IPVC MCU platforms support SCCP and/or H.323/SIP ports active; Port designation is strictly for call control and MCU port access; IPVC MCU Port Designations: Cisco IPVC 3540 MCU-Port protocol designation can be applied by a percentage to MCU port resources; Cisco IPVC 3511 MCU-Port protocol designation can be applied as SCCP or H.323/SIP modes only; IPVC MCU ports integrate video media from all protocols-SCCP, H.323, SIP, H.320 (through IPVC Gateway)
SIP Protocol Support	Fully interoperability with ISDN, H.323 network solutions
Audio Transcoding	All Cisco IPVC MCU platforms support SCCP and/or H.323/SIP ports active; Port designation is strictly for call control and MCU port access; IPVC MCU Port Designations: Cisco IPVC 3540 MCU-Port protocol designation can be applied by a percentage to MCU port resources; Cisco IPVC 3511 MCU-Port protocol designation can be applied as SCCP or H.323/SIP modes only; IPVC MCU ports integrate video media from all protocols-SCCP, H.323, SIP, H.320 (through IPVC Gateway)
Resolutions	Quarter Common Intermediate Format (QCIF), CIF, 4CIF, SIF, 4SIF, Video Graphics Array (VGA), Super-eXtended Graphics Array (SXGA), eXtended Graphic array (XGA)
Rate Matching	Each endpoint in a video conference can participate according to individual video bandwidth capabilities without affecting the connection of other participants
Downspeeding	Enables the completion and maintaining of a call during the loss of ISDN B channels
QoS	Support for Differentiated Services (DiffServ) markings
Security and Privacy	Password protection for administrative functions and for conferences—helps to ensure privacy for participants
DuoVideo Support	In addition to standard-based H.239 support, MCU also supports Tandberg end point when transmitting more than one video channel (DuoVideo)
LAN Interface	One 10/100 Ethernet port, IEEE 802.3, 8-pin RJ-45
Physical Dimensions	IPVC 3540 Chassis: 3.50 in. x 17.25 in. x 10.0 in. (4.445 cm x 43.815 cm x 25.4 cm); IPVC-3511-MCU(E): 1.75 in. x 17.25 in. x 10.0 in. (4.445 cm x 43.815 cm x 25.4 cm)
Weight	Cisco IPVC 3540 Chassis: 15.43 lb (7 kg); Cisco IPVC 3511 Multipoint Control Unit: 7.50 lb (3.5 kg); Cisco IPVC 3511 Multipoint Control Unit with EMP: 8.00 lb (3.75 kg)
Power	100 to 240 VAC autosense, 50 to 60 Hz, 75W maximum; U.S. power cable included; Other power cables available separately
Environment	Operating temperature: 0 to 40°C (32 to 104°F); Storage temperature: -25 to 70°C (-13 to 158°F); Humidity: 5 to 90 percent noncondensing

Selected Part Numbers and Ordering Information¹**Cisco IP/VC 3500 Series Videoconferencing Products**

IPVC-3511-MCU	IP/VC 3511 Multipoint Control Unit
IPVC-3511-MCU-E	IP/VC 3511 Multipoint Control Unit and Enhanced Media Processor
IPVC-3544-CHAS	IPVC 3544 Four Slot Chassis
IPVC-3540-MC03A	IPVC 3540 Series MCU Modules - 30 Port Session
IPVC-3540-MC06A	IPVC 3540 Series MCU Modules - 60 Port Session
IPVC-3540-MC10A	IPVC 3540 Series MCU Modules - 100 Port Session
IPVC-3540-EMP	IP/VC 3540 Enhanced Media Processor
IPVC-3540-EMP3	IP/VC 3540 Enhanced Media Processor 3
IPVC-3540-XAM03	IP/VC 3540 MCU Audio Transcoder Cards - 30 Port MCU Daughter card
IPVC-3540-XAM06	IP/VC 3540 MCU Audio Transcoder Cards - 60 Port MCU Daughter card

1. This is only a small subset of all parts available. Some parts have restricted access or are not available through distribution channels.

For More Information

See the Cisco IP/VC 3500 series Website: <http://www.cisco.com/go/ipvc>

Cisco MeetingPlace

Cisco MeetingPlace—part of the Cisco IP Communications system—is a complete rich-media conferencing solution that seamlessly integrates voice, video, and Web conferencing capabilities to make remote meetings as natural and effective as face-to-face meetings for unmatched productivity gains. It is deployed “on network” behind the firewall and integrated directly into an organization’s private voice and data networks and collaborative applications to provide significant cost savings, the utmost in security, and a superior user experience. Intuitive interfaces make setting up, attending, and managing meetings easy.

Key Features

- Voice, video, and Web conferences can be set up and attended in a single step—from Cisco IP phones, instant messaging clients, Web browsers, and Microsoft Outlook and Lotus Notes calendars; Meeting participants have total control from a single browser interface; Provides a highly collaborative meeting and training environment
- Isolate confidential meetings and content behind the firewall for secure data network transport while providing the flexibility to meet with external parties
- Know who attended a meeting, how it was attended—voice, video, or Web, who is speaking, and who is sharing; With the appropriate permissions, control meeting characteristics including Web conferencing permissions, speaking permissions—mute and listen only, recording, and meeting security
- Deployed in a variety of ways—on premises or hosted, customer managed or outsourced; Cisco Managed Solutions and managed services partners can provide system administration and end-user help desk functions for on-premises or hosted systems

Selected Part Numbers and Ordering Information¹

Cisco MeetingPlace 8100 Solution Bundles

MP-8106-30IP	Cisco MeetingPlace 8106 30UL IP Solution Bundle
MP-8106-48	Cisco MeetingPlace 8106 48UL T1-CAS Solution Bundle
MP-8106-60IP-C	Cisco MeetingPlace 8106 60UL IP Commercial Bundle
MP-8106-48T1-C	Cisco MeetingPlace 8106 48UL T1-CAS Commercial Bundle
MP-8106-30PRI-C	Cisco MeetingPlace 8106 30UL PRI Commercial Bundle
MP-8106-60IP-C	Cisco MeetingPlace 8106 60UL IP Commercial Bundle
MP-8106-48T1-C	Cisco MeetingPlace 8106 48UL T1-CAS Commercial Bundle
MP-8106-30PRI-C	Cisco MeetingPlace 8106 30UL PRI Commercial Bundle
MP-8106-120IP	Cisco MeetingPlace 8106 120UL IP Solution Bundle
MP-8112-180IP	Cisco MeetingPlace 8112 180UL IP Solution Bundle
MP-8112-180PRI	Cisco MeetingPlace 8112 180UL PRI Solution Bundle
MP-8112-192	Cisco MeetingPlace 8112 192UL T1-CAS Solution Bundle
MP-8112-510IP	Cisco MeetingPlace 8112 510UL IP Solution Bundle
MP-8112-510PRI	Cisco MeetingPlace 8112 510UL PRI Solution Bundle
MP-8112-600	Cisco MeetingPlace 8112 600UL T1-CAS Solution Bundle

Cisco MeetingPlace Hardware and Software options

MP-SMARTBLADE	Cisco MeetingPlace Audio Conference Module, 96 ports with 4xT1-CAS
MP-MA-4	Cisco MeetingPlace Gateway Module, 120 IP ports
MP-MA-4-PRI	Cisco MeetingPlace Gateway Mod., 4xPRI (T1/E1)
MP-MA-16	Cisco MeetingPlace Gateway Mod., 480 IP ports
MP-MA-16-PRI	Cisco MeetingPlace Gateway Module 16xPRI (T1/E1)
MP-AUDIO-UL-24	Cisco MeetingPlace Audio Conference user license bundle, 24 user licenses
MP-AUDIO-UL-30	Cisco MeetingPlace Audio Conference. user license bundle, 30 user licenses
MP-MTGM-SITE-5.3	Cisco MeetingPlace MeetingTime Site License
MP-FLEX-MENU	Cisco MeetingPlace Flex Menu Option
MP-LANG-5.3	Cisco MeetingPlace Multilingual System License

Web Conferencing Options

MP-WEBCONFWSW-5.3	Cisco MeetingPlace Web Conferencing Server Application (includes 20 concurrent Web conferencing user licenses)
MP-RM-RECORDING	Cisco MeetingPlace Web Voice Recording System License
MP-CONF-UI-5.3	Cisco MeetingPlace Conferencing User Interface (included in Cisco MeetingPlace Solution Bundles)
MP-WEB-UL-20	Cisco MeetingPlace Web Conferencing 20 user licenses bundle

Integration Applications

MP-VIDEO	Cisco MeetingPlace Video Integration
MP-IP-GW	Cisco MeetingPlace H.323/SIP Gateway Application (included in Cisco MeetingPlace Solution Bundles)
MP-EMAIL-5.3	Cisco MeetingPlace SMTP E-mail Gateway Application (included in Cisco MeetingPlace Solution Bundles)
MP-OUTLOOK-5.3	Cisco MeetingPlace for Outlook Integration Application
MP-NOTES-5.3	Cisco MeetingPlace for Lotus Notes Integration Application
MP-DIRSVCS-5.3	Cisco MeetingPlace Directory Services 5.3
MP-IM	Cisco MeetingPlace Instant Messaging Integration Application

1. Some countries have telephone networks that list multiple impedance requirements. It is important to closely approximate the impedance of the typical handsets used in the region when selecting the proper configuration. The incorrect choice may lead to poor echo cancellation performance.

For More Information

See the Cisco MeetingPlace Website: <http://www.cisco.com/go/meetingplace>

Cisco MeetingPlace Express

Cisco MeetingPlace Express—part of the Cisco IP Communications solution—is an integrated voice and Web conferencing solution that makes it easy and affordable for midsize organizations to realize the cost savings, security and productivity benefits of deploying conferencing with Cisco CallManager. It provides simple, powerful conferencing functions that are easy to deploy and manage. Organizations expand their market reach, improve operational effectiveness, and speed decisions by integrating virtual meetings into everyday communications. With just a phone and a Web browser, users collaborate with co-workers, demonstrate products and services to customers, and deliver compelling presentations. Cisco MeetingPlace Express helps enable highly productive virtual meetings by integrating meeting management and control capabilities directly into Web and Cisco IP phone interfaces.

Key Features

- **Advanced Voice Conferencing**—Capabilities include real-time mixing of up to three simultaneous speakers, input volume (gain) adjustment of each participant, recording, entry and exit notification (e.g. beep plus name), breakout sessions (up to nine simultaneously per meeting), automatic meeting extension (capacity and configuration allowing) and end-of-meeting warning
- **Powerful Meeting Management**—From the Web interface, users can mute/unmute themselves and see who is in the meeting, how they are participating (voice or Web), who is speaking, and who is sharing. Users with the appropriate permission level can mute other attendees, control attendee sharing permission levels, and bring others into the meeting by dialing out or sending e-mail invitations.
- **Streamlined Web Conferencing**—Macromedia Flash-based Web conferencing interface streamlined for meeting management and simple screen sharing of applications or the entire desktop; Shared content scales to any screen resolution on multiple platforms, including Windows and Macintosh computers; Additional capabilities include annotations, text chat and meeting notes for an agenda
- **Simple Meeting Setup and Attendance**—Includes Web, Cisco IP phone, and touchtone phone interfaces for setting up and attending meetings
- **Strong Security**—Secure meetings using SSL encryption—behind the firewall deployment—and multiple meeting security options, including meeting access authentication and in-meeting controls such as “lock meeting” and “remove participants” functionality

- Easy Deployment and Management—Installed on a single server and supports industry standard protocols—H.323 and SIP—for connectivity with a range of telephony systems; Integrates with the Cisco CallManager directory to simplify profile management automating user authentication and profile setup; Web-based administration capabilities include report generation, conference monitoring, diagnostics, and interface configuration

Specifications

Features	Cisco MeetingPlace Express
Platform	Cisco Media Convergence Server: MCS-7825-H1-RC1, MCS-7825-I1-RC1, MCS-7835-H1-RC1, MCS-7835-I1-RC1
Capacity	Up to 120 concurrent voice and 120 concurrent Web conferencing users
Call Control System Compatibility	Cisco CallManager, Cisco CallManager Express, Cisco SIP Proxy Server, Standard-based H.323 or SIP call-control systems
Client Compatibility	Windows, Mac, Linux, Solaris; Internet Explorer, Safari, Netscape, Mozilla, Firefox; Macromedia Flash Player
IP Phone Application Compatibility	Cisco IP Phone 7940 series, Cisco IP Phone 7960 series, Cisco IP Phone 7970 series, Cisco IP Communicator

Selected Part Numbers and Ordering Information¹

Cisco MeetingPlace Express

MPE-1.1-MED	MeetingPlace Express 1.1 Medium Bundle-25V,6W CUL(~300seats)
MPE-1.1-SMALL	MeetingPlace Express 1.1 Small Bundle-20V,6W CUL(~200 seats)
MPE-LANG	MeetingPlace Express Language License, 2 Or More Languages
MPE-MED-1V	MeetingPlace Express Medium Package Upgrade-1V CUL(~20seats)
MPE-PLUS10-V-UPG=	MeetingPlace Express Voice Lic Pack Upg, 10 CUL (~200 seats)
MPE-PLUS10-W=	MeetingPlace Express Web License Pack, 10 CUL (~200 seats)
MPE-PLUS1-W	MeetingPlace Express Web License-1 CUL (~20 seats)
MPE-PLUS80-V-UPG=	MeetingPlace Express Voice Lic Pack Upg-80 CUL (~1600 seats)
MPE-SMALL-1V	MeetingPlace Express Small Package Upgrade-1V CUL(~20 seats)
MPE-SMTOMED-UPG=	MeetingPlace Express License Upgrade from SE to ME SW

1. Some countries have telephone networks that list multiple impedance requirements. It is important to closely approximate the impedance of the typical handsets used in the region when selecting the proper configuration. The incorrect choice may lead to poor echo cancellation performance.

For More Information

See the Cisco MeetingPlace Express Website:

<http://www.cisco.com/go/meetingplaceexpress>

Cisco Voice Router Bundles

Cisco Voice router bundles based on the Cisco 2800 and 3800 access router platforms provide customers with a single part number for ease of ordering. These voice bundles are especially designed for the application of toll bypass, PSTN or PBX to IP connectivity with Cisco CallManager, or other voice applications where connectivity from IP to PSTN is required.

Each Voice bundle provides DSP resources to support PSTN connectivity to IP, necessary memory, and recommended Cisco IOS feature set.

When to Sell

Sell This Product

Cisco Voice Router Bundles

When a Customer Needs These Features

- Deploying access router where toll bypass application is required
- Deploying Cisco CallManager and PSTN or PBX gateway is required
- Customer may need voice application in the future and wants investment protection on initial purchase

Selected Part Numbers and Ordering Information¹**Cisco Voice Router Bundles**

CISCO2801-V/K9	2801 Router, 64MB Flash, 256MB DRAM, PVDM2-8 (DSP for 8 calls), IOS SP Services
CISCO2811-V/K9	2811 Router, 64MB Flash, 256MB DRAM, PVDM2-16 (DSP for 16 calls), IOS SP Services
CISCO2821-V/K9	2821 Router, 64MB Flash, 256MB DRAM, PVDM2-32 (DSP for 32 calls), IOS SP Services
CISCO2851-V/K9	2851 Router, 64MB Flash, 256MB DRAM, PVDM2-48 (DSP for 48 calls), IOS SP Services
CISCO3825-V/K9	3825 Router, 64MB Flash, 256MB DRAM, PVDM2-64 (DSP for 64 calls), IOS SP Services
CISCO3845-V/K9	3845 Router, 64MB Flash, 256MB DRAM, PVDM2-64 (DSP for 64 calls), IOS SP Services

1. This is only a small subset of all parts available via URL listed under “For More Information.” Some parts have restricted access or are not available through distribution channels.

For More Information

See Routing, page 1-1 for product details.

Cisco CallManager Express Bundles

Designed for enterprise branch offices, small and midsize businesses, and managed network service providers who seek consolidated, easy to order CallManager Express enabled routers. Each of these bundles provide a versatile, cost-effective solution that offer integrated IP Telephony and data services via a single router platform and include Cisco CallManager Express feature license, DSP resources to support PSTN connectivity to IP, necessary memory and recommended Cisco IOS feature set.

When to Sell**Sell This Product****Cisco CCME Router Bundles****When a Customer Needs These Features**

- SMB or Enterprise branch locations looking for data and distributed call processing using Cisco CallManager Express in a all-in-one solution based on Cisco access router
- Support for 24 to 240 Phones per location
- Customers who may need IP Telephony application in the future and wants investment protection on initial purchase

Selected Part Numbers and Ordering Information¹**Cisco CCME Router Bundles**

CISCO3845-CCME/K9	Cisco 3845 Voice Bundle with IOS SP Services, PVDM2-64, FL-CCME (240 users), 64 MB Flash/256 MB DRAM
CISCO3825-CCME/K9	Cisco 3825 Voice Bundle with IOS SP Services, PVDM2-64, FL-CCME (168 users), 64 MB Flash/256 MB DRAM
CISCO2851-CCME/K9	Cisco 2851 Voice Bundle with IOS SP Services, PVDM2-48, FL-CCME (72/96 ² users), 64 MB Flash/256 MB DRAM
CISCO2821-CCME/K9	Cisco 2821 Voice Bundle with IOS SP Services, PVDM2-32, FL-CCME (48 users), 64 MB Flash/256 MB DRAM
CISCO2811-CCME/K9	Cisco 2811 Voice Bundle with IOS SP Services, PVDM2-16, FL-CCME (36 users), 64 MB Flash/256 MB DRAM
CISCO2801-CCME/K9	Cisco 2801 Voice Bundle with IOS SP Services, PVDM2-8, FL-CCME (24 users), 64 MB Flash/256 MB DRAM

1. This is only a small subset of all parts available via URL listed under “For More Information.” Some parts have restricted access or are not available through distribution channels.
2. Available with IOS Version 12.3(11)T release

For More Information

See Routing, Page 1-1 for detailed product information.

See Cisco CallManager Express, page 4-7 for product details.

SRST Bundles

Designed for enterprise branch offices, small and midsize businesses, and managed network service providers who seek consolidated, easy to order SRST enabled routers. These bundles provide a versatile, cost-effective solution that offer voice connectivity, call processing redundancy and data services via a single Enterprise Router platform and include Cisco SRST feature license, DSP resources to support PSTN connectivity to IP, necessary memory and recommended Cisco IOS feature set.

When to Sell

Sell This Product

Cisco SRST Bundles

When a Customer Needs These Features

- SRST for remote branch locations with Centralized Cisco CallManager deployments
- Support for 24 to 720 phones in SRST mode
- Customers who may deploy Cisco CallManager in the future and who want investment protection

Selected Part Numbers and Ordering Information¹

Cisco Survivable Remote Site (SRST) Bundles

CISCO3845-SRST/K9	Cisco 3845 Voice Bundle with IOS SP Services, PVDM2-64, FL-SRST (240 users), 64 MB Flash/256 MB DRAM
CISCO3825-SRST/K9	Cisco 3825 Voice Bundle with IOS SP Services, PVDM2-64, FL-SRST (168 users), 64 MB Flash/256 MB DRAM
CISCO2851-SRST/K9	Cisco 2851 Voice Bundle with IOS SP Services, PVDM2-48, FL-SRST (96 users), 64 MB Flash/256 MB DRAM
CISCO2821-SRST/K9	Cisco 2821 Voice Bundle with IOS SP Services, PVDM2-32, FL-SRST(48 users), 64 MB Flash/256 MB DRAM
CISCO2811-SRST/K9	Cisco 2811 Voice Bundle with IOS SP Services, PVDM2-16, FL-SRST (36 users), 64 MB Flash/256 MB DRAM
CISCO2801-SRST/K9	Cisco 2801 Voice Bundle with IOS SP Services, PVDM2-8,FL-SRST (24 users), 64 MB Flash/256 MB DRAM

1. This is only a small subset of all parts available via URL listed under “For More Information.” Some parts have restricted access or are not available through distribution channels.

For More Information

See Cisco Survivable Remote Site Telephony (SRST), page 4-8 for product details.

Cisco V3PN Bundles

Designed for enterprise branch offices, small and midsize businesses, and managed network service providers who seek security and IPCommunications capabilities in the same platform. V3PN bundle includes CallManager Express Features license—can be used for SRST—DSP resources for PSTN to IP calls, Advanced IP Services and AIM-VPN Accelerator card for maximum performance of security features including VPN tunneling

When to Sell

Sell This Product

Cisco V3PN Bundles

When a Customer Needs These Features

- SMB or Enterprise branch locations looking for data, IP Telephony and VPN in a all in one solution based on Cisco Access router
- Support for 24 to 240 Phones per location
- Customers who may need IP Telephony application in the future and who want investment protection

Selected Part Numbers and Ordering Information¹

Cisco V3PN Bundles

CISCO3845-V3PN/K9	Cisco 3845 V3PN Bundle with IOS Advanced IP Services, PVDM2-64, AIM-VPN/HP11-PLUS, FL-CCME (240 users), 64 MB Flash/256 MB DRAM
CISCO3825-V3PN/K9	Cisco 3825 V3PN Bundle with IOS Advanced IP Services, PVDM2-64, AIM-VPN/EP11-PLUS, FL-CCME (168 users), 64 MB Flash/256 MB DRAM
CISCO2851-V3PN/K9	Cisco 2851 V3PN Bundle with IOS Advanced IP Services Image, PVDM2-48, FL-CCME (72/96 ² users), AIM-VPN/EP11-PLUS, 64 MB Flash/256 MB DRAM
CISCO2821-V3PN/K9	Cisco 2821 V3PN Bundle with IOS Advanced IP Services Image, PVDM2-32, FL-CCME (48 users), AIM-VPN/EP11-PLUS, 64 MB Flash/256 MB DRAM
CISCO2811-V3PN/K9	Cisco 2811 V3PN Bundle with IOS Advanced IP Services Image, PVDM2-16, FL-CCME (36 users), AIM-VPN/EP11-PLUS, 64 MB Flash/256 MB DRAM
CISCO2801-V3PN/K9	Cisco 2801 V3PN bundle with IOS Advanced IP Services, PVDM2-8, FL-CCME (24 users), AIM-VPN/EP11-PLUS, 64 MB Flash/256 MB DRAM

1. This is only a small subset of all parts available via URL listed under “For More Information.” Some parts have restricted access or are not available through distribution channels.
2. Available with IOS Version 12.3(11)T release

For More Information

See individual product pages for more detail



VPN and Security

VPN and Security Products at a Glance

Product	Features	Page
Cisco ASA 5500 Series Adaptive Security Appliances	A powerful multifunction network security appliance family that provides the security breadth and 5-3 depth for protecting small and medium-sized business and enterprise networks while reducing the overall deployment and operations costs and complexities associated with providing this new level of security. • Combines security and VPN services with the Cisco Adaptive Identification and Mitigation (AIM) architecture • Designed as a key component of the Cisco Self-Defending Network • Provides proactive threat defense stopping attacks before they spread	
Cisco PIX Security Appliances	The market-leading Cisco PIX Security Appliance Series provides robust user and application 5-6 policy enforcement, multi-vector attack protection, and secure connectivity services through a wide range of rich security and networking services, including: • Advanced Application-Aware Firewall Services • Market-Leading Voice-Over-IP and Multimedia Security • Robust Site-to-Site and Remote Access IPSec VPN Connectivity • Award-Winning Resiliency	
Cisco IPS 4200 Series Sensors	Cisco's IPS Sensors allow businesses to minimize the total cost of ownership of their IPS 5-8 deployments by delivering: • Inline intrusion prevention functionality with IPS v5.0 Software • Unprecedented price/performance ratios the ability to simultaneously protect multiple network subnets through the support for multiple interfaces—up to 8 interfaces (on the appliances) • Dual operation in both promiscuous as well as inline modes simultaneously a wide array of performance options—from 80 Mbps • Embedded web-based management solutions packaged with the sensor	
Cisco Incident Control System	Prevents new worm and virus outbreaks from affecting businesses by enabling the network to 5-10 rapidly adapt and provide a distributed response. • Use of up-to-the-moment threat intelligence, provided by Trend Micro, an industry-leading expert in antivirus and worm mitigation • Rapid response, enabling proactive prevention of worms and viruses • Empowering existing Cisco network and security devices to adapt in real time for a coordinated network-wide response • Detailed control of how Cisco ICS mitigation policies are deployed in the business network	
Cisco Security Monitoring Analysis and Response System (CS-MARS)	Centralized Monitoring and event correlation system for Cisco and non-Cisco platforms 5-11 • Timely Attack Mitigation—identify and disable offending layer 2 switch port • End to End Network Awareness—identifies the attack path and keeps track of NAT's • Netflow Analysis to detect Day Zero Worms and Virus • 10,000 events per second on a single box as well as a highly scalable distributed architecture • Make sense of data—reduce millions of security events down to a handful of incidents	
Cisco VPN 3000 Family	Remote access Virtual Private Network platform 5-14 • Supports IPsec and SSL (WebVPN) remote connectivity • Has models for all size companies, from small to large enterprise organizations • Reduces communications expenditures • Enables users to easily add capacity and throughput	
Network Admission Control	NAC is part of the Cisco Self-Defending Network, an initiative to increase network intelligence in 5-17 order to enable the network to automatically identify, prevent, and adapt to security threats. • Organizations can provide network access to endpoint devices such as PCs, PDAs, and servers that are verified to be fully compliant with established security policy. • Identify noncompliant devices and deny them access, place them in a quarantined area, or give them restricted access to computing resources • Enforce security policy compliance on all devices seeking to access network computing resources, thereby limiting damage from viruses and worms	

Product	Features	Page
Cisco NAC Appliance (Cisco Clean Access)	Easily deployed network admission control product that allows network administrators to authenticate, authorize, evaluate, and remediate wired, wireless and remote users and their machines prior to allowing access to the network. • Integrated authentication, posture assessment, quarantine, remediation into one product • Pre-packaged rulesets for updates, definition files, and hot fixes from Microsoft® and all major anti-virus and anti-spyware vendors • Generates significant cost savings by enlisting users to repair and update their own machines • Improves network health and resiliency by requiring that all incoming devices comply with a certain standard of security • Scales from 50 user to 100,000 user deployments	5-17
Cisco Security Agent	Provides threat protection for desktop and server computing systems by identifying and preventing malicious activity: • Aggregates and extends multiple endpoint security functions • Protects against known and unknown attacks on both servers and desktops; • Scalable to 100,000 agents per management server • Compliant with SDN/NAC Cisco Trust Agent. Integrated management with Cisco PIX, Cisco Secure IDS, and Cisco VPN security devices and built-in Cisco Secure VPN "Are You There" (AYT)	5-19
Cisco Security Auditor	• Scalable and intuitive automatic auditing process management to eliminate the error-prone and time-consuming manual process • Best-practice guidelines gathered from industry standards (NSA, SAFE, CIS) for security compliance auditing	5-20
Cisco Secure Access Control Server (ACS) for Windows	Provides a comprehensive identity networking solution and secure user experience for Cisco intelligent information networks. It is the integration and control layer among all enterprise users, administrators, and the resources of the network infrastructure	5-22
Cisco Secure Access Control Server (ACS) Solution Engine	A high-performance and highly scalable user and administrative access control solution that operates as a centralized RADIUS or TACACS+ server system in a turnkey security-hardened solution	5-23
Cisco Guard Appliance and Cisco Traffic Anomaly Detector Appliance	Provides threat protection for Enterprise and Service Provider networks from the broadest range of DDoS attacks: • Protects against spoofed, non-spoofed and Zombie attacks • Granular, per-flow analysis and blocking of attack traffic using dynamic filters • Allows legitimate transactions to flow through freely; • 1GB line rate attack analysis and cleaning in standalone mode • Web based GUI for policy definition, operational monitoring and report generation	5-24
Cisco Router and Security Device Manager	An intuitive, Web-based device-management tool for Cisco IOS® Software-based routers • Simplified Cisco router deployments: Easy to use Smart wizards, built-in tutorials • Application intelligence: Knowledgebase of TAC-approved Cisco IOS configurations • Delivers simplified management support and real-time performance monitoring for concurrent ISR services, collaborative security solutions and application level inspection and control. • Supported in seven international languages including English, Japanese, Simplified Chinese, French, German, Spanish and Italian	5-25
CiscoWorks VPN/Security Management Solution	Combines general device management tools for configuring, monitoring, and troubleshooting enterprise networks with powerful security solutions for managing virtual private networks (VPNs), firewalls, and network and host-based intrusion protection systems (IPS). An integral part of the Cisco SAFE Blueprint for Enterprise, this bundle also delivers network device inventory, change audit and software distribution features. See Chapter 9-1—IOS Software and Network Management for more information on CiscoWorks VPN/Security Management Solution	9-13
CiscoWorks Security Information Management Solution and CiscoWorks Security Information Management Solution Engine	A solution that collects, analyzes, and correlates security event data from across the enterprise- letting you detect and respond to security events as they occur. • Event monitoring of multivendor security environments • Extensive reporting for operators and high-level administrators • Risk assessment information to understand overall vulnerability of critical network assets within the enterprise; Forensics tools to investigate attacks • Traffic utilization reports and graphs to understand changes in traffic patterns See Chapter 9-1—IOS Software and Network Management for more information on CiscoWorks Security Information Management Solution	9-15
Cisco Firewall Services Module (FWSM) for Catalyst 6500	Firewall Module is a high performance integrated stateful firewall solution for Catalyst 6500 family 2-19 of switches with performance exceeding 5GB. It is based on proven PIX technology while providing the following benefits to the customers • Investment protection; Low cost of ownership; Ease of use; Operational Consistency; Scalability See the Catalyst 6500 Series Switch in Chapter 2: LAN Switching, page 2-19, for more information	2-19
IPSec VPN Shared Port Adapter (SPA) for Catalyst 6500	Offers next-generation encryption technology as well as a form factor designed to enable a more flexible and scalable network infrastructure. • Next-generation encryption technology • High speed VPN performance • Scalability • Attractive form factor • Comprehensive VPN features See the Catalyst 6500 Series Switch in Chapter 2: LAN Switching, page 2-19, for more information	2-19

Product	Features	Page
Intrusion Detection System Services Module (IDSM-2) for Catalyst 6500	- Integrates full-featured IPS functions directly into the network infrastructure - Monitor traffic directly off the switch backplane—a logical platform for additional services such as firewall, VPN, and IPS - When in passive mode, IDSM-2 provides promiscuous inspection of packet copies via VACL capture and Switch Port Analyzer/Remote SPAN (SPAN/RSPAN) - Advanced false positive reduction features - One rack-unit (RU) size takes up only a single slot in the Cisco Catalyst 6500 or Catalyst 7600 chassis - Up to 500 megabits per second (Mbps) of IDS/IPS inspection provides high-speed packet-examination capabilities and allows for more protection of a wider variety of networks and traffic See the Catalyst 6500 Series Switch in Chapter 2: LAN Switching, page 2-19	2-19
Cisco IOS Firewall	- Tightly integrated with IOS VPN and advanced routing technologies - Application aware stateful packet inspection via context-based access control (CBAC) for TCP, UDP, SIP, Skinny, H.323 and others - Supports user authentication for https, ftp and telnet connections - URL filtering through router exclusive domains or use of external Websense and N2H2 servers - Inline intrusion prevention for real-time response to network attacks dynamically supporting thousands of common attack signatures - Dynamic, network-to network, per-user authentication and authorization via TACACS+ and RADIUS	5-27
Cisco Security Router Bundles	Cisco 800, 1700, 1800, 2600, 2800, 3700, 3800 7200 and 7301 Security Router Bundles with Enhanced 1-1 Integrated Network Security. See individual product pages for more detail (page 1-1)	
Cisco 800, 1700, 1800, 2600, 2800, 3700, 3800, 7200, and 7301	Wide variety of modular router platforms with options for Cisco IOS-based and hardware-enabled 1-1 VPN, Cisco IOS Firewall, Intrusion Prevention, Network Admission Control (NAC), and security support.	
Product Ordering Website	To place an order, visit the Cisco Ordering Website: http://www.cisco.com/en/US/ordering/index.shtml	

Cisco ASA 5500 Series Adaptive Security Appliance



The Cisco ASA 5500 Series delivers a powerful combination of multiple market-proven technologies in a single platform, making it operationally and economically feasible to deploy comprehensive security services to more locations. And its multifunction security profile virtually eliminates the difficult—and risky—decision of making trade-offs between robust security protection and the operational costs associated with multiple devices in numerous locations.

The Cisco ASA 5500 Series offers tailored packages for location-specific needs of small and medium-sized businesses (SMBs), enterprises, and service providers. This enables standardization on the ASA 5500 series platform to reduce costs in management, training, and sparing. It provides superior protection by providing the right services for the right location in the network. Furthermore, it simplifies design and deployment by providing pre-packaged location-specific security solutions. These pre-packaged solutions are available in four types: Cisco ASA 5500 Series Firewall, IPS, Anti-X and VPN bundles.

When to Sell

Sell This Product Firewall Bundles

When a Customer Needs These Features

- To deploy new applications securely, while protecting valuable assets from unauthorized access
- Flexible, Reliable Deployment Options—Provides a wide range of services such as transparent firewall, virtualization, and intelligent network integration
- Comprehensive Management Solutions to Lower Operational Costs—Flexible centralized management solutions provide full featured provisioning and monitoring services
- Control Access to Critical Assets—Firewall access control and application policy enforcement provide authenticated access to critical resources
- Accurate, Multi-vector Threat Prevention—Achieves maximum attack identification via multiple analysis techniques and technologies
- Complete Incident Life-cycle Management—Complete solution covering Management, Monitoring, Incident Response, and Outbreak Prevention

IPS Bundles

Sell This Product

Anti-X Bundles

VPN Bundles

When a Customer Needs These Features

- Enterprise-grade Firewall—Built and deployed on Cisco PIX firewall technology for solid access and policy control
- High-quality Malware Protection
- Unified Security and Content Control
- VPN for Any Deployment Environment—Clientless and full network VPN access delivers unsurpassed customizability for diverse requirements
- Threat Protected VPN—Integrated endpoint and network security technologies ensure the VPN is not a conduit for damaging security threats
- More Cost Effective VPNs—Integrated load balancing, network intelligence and security reduces the number of devices required to scale and secure the VPN

Key Features

- Proven security and VPN capabilities—Full-featured, high-performance firewall, IPS, anti-X, and IPSec and SSL VPN technologies deliver robust application security, user- and application-based access control, worm and virus mitigation, malware protection, anti-phishing and anti-spam, URL blocking and filtering, and remote user/site connectivity
- Extensible Adaptive Identification and Mitigation services architecture—Leveraging a modular services processing and policy framework, AIM enables the application of specific security or network services on a per traffic flow basis, delivering highly granular policy controls and anti-x protection with streamlined traffic processing.
 - Enables evolution of existing services as well as deployment of new services without requiring a platform replacement or performance compromise
 - Enables highly customizable security policies and services to help protect against a fast evolving threat environment
- Reduced deployment and operations costs—Multifunction appliance allows for configuration and management standardization helping decrease the costs of deployment and ongoing operations

Competitive Products

- Juniper: NetScreen Security Appliances
- Check Point Software: FireWall-1 / VPN-1
- Nokia: IP-Series Security Appliances
- SonicWALL: SonicWALL Security Appliances
- WatchGuard Technologies: Firebox X Security Appliances

Specifications

Feature	Cisco ASA 5510	Cisco ASA 5540	Cisco ASA 5540
Users/Nodes	Unlimited	Unlimited	Unlimited
Firewall Throughput	Up to 300 Mbps	Up to 450 Mbps	Up to 650 Mbps
Concurrent Threat Mitigation Throughput (Firewall + IPS Services)	Up to 150 Mbps with AIP-SSM-10	Up to 225 Mbps with AIP-SSM-10	Up to 450 Mbps with AIP-SSM-20
3DES/AES VPN Throughput	Up to 170 Mbps	Up to 225 Mbps	Up to 325 Mbps
IPSec VPN Peers¹	150	750	5000
WebVPN Peers	10 ¹ / 25 ¹ / 50 ¹ / 100 ¹ / 150 ¹ / 250 ¹	10 ¹ / 25 ¹ / 50 ¹ / 100 ¹ / 150 ¹ / 250 ¹ / 500 ¹ / 750 ¹	10 ¹ / 25 ¹ / 50 ¹ / 100 ¹ / 150 ¹ / 250 ¹ / 500 ¹ / 750 ¹ / 1000 ¹ / 2500 ¹
Concurrent Sessions	50,000/130,000 ¹	280,000	400,000
Integrated Network Ports	3 + 1 Management Fast Ethernet Ports / Upgradable to 5 Fast Ethernet Ports	4 Gigabit Ethernet, 1 Fast Ethernet	4 Gigabit Ethernet, 1 Fast Ethernet
Virtual Interfaces (VLANs)	0 in base system / 25 with Security Plus license upgrade	100	200
Security Contexts (Included/Maximum)	0/0	2/10	2/50
High Availability	Not supported / Active/Standby with Security Plus license upgrade	Active/Active and Active/Standby	Active/Active and Active/Standby
SSM Expansion Slot	1	1	1
USB 2.0 Ports	2	2	2
RAM	256 Mb	512 Mb	1 Gb
Flash Memory	64 Mb	64 Mb	64 Mb
Size	1 RU	1 RU	1 RU
License Type	Five Licenses: ASA 5500 SSL VPN 10, 25, 50, 100, and 250 Peer Licenses	Seven Licenses: ASA 5500 SSL VPN 10, 25, 50, 100, 250, 500, and 750 Peer Licenses	Nine Licenses: ASA 5500 SSL VPN 10, 25, 50, 100, 250, 500, 750, 1000, and 2500 Peer Licenses

Feature	Cisco ASA 5510	Cisco ASA 5540	Cisco ASA 5540
Content Security and Control Features License	Cisco ASA 5500 CSC Plus Licenses for CSC SSM-10 and CSC SSM-20 Enables Anti-Spam, URL Blocking and Filtering and Anti-Phishing with 1 Year Subscription Cisco ASA 5500 CSC 30-Day Evaluation License for CSC SSM-10 and CSC SSM-20 Plus License Pack		
Content Security and Control User License	Cisco ASA 5500 CSC SSM-10 100, 250, and 500 User Licenses Cisco ASA 5500 CSC SSM-20 750 and 1000 User Licenses		

1. Available through an upgrade license

Selected Part Numbers and Ordering Information¹

Cisco ASA 5500 Firewall Bundles

ASA5510-BUN-K9	Cisco ASA 5510 Appliance with Firewall and IPsec VPN (150 Peers) Software, 3 FE Ports
ASA5510-SEC-BUN-K9	Cisco ASA 5510 Sec Plus Appliance with Firewall and IPsec VPN (150 Peers) Software, 5 FE Ports
ASA5520-BUN-K9	Cisco ASA 5520 Appliance with Firewall and IPsec VPN (750 Peers) Software, 4 GE and 1 FE Ports
ASA5540-BUN-K9	Cisco ASA 5540 Appliance with Firewall and IPsec VPN (5,000 Peers) Software, 4 GE and 1 FE Ports
Cisco ASA 5500 IPS Bundles	
ASA5510-AIP10-K9	Cisco ASA 5510 Appliance with AIP-SSM-10, Firewall, IPsec VPN (150 Peers), and IPS Software, 3 FE Ports
ASA5520-AIP10-K9	Cisco ASA 5520 Appliance with AIP-SSM-10, Firewall, IPsec VPN (750 Peers), and IPS Software, 4 GE and 1 FE Ports
ASA5520-AIP20-K9	Cisco ASA 5520 Appliance with AIP-SSM-20, Firewall, IPsec VPN (750 Peers), and IPS Software, 4 GE and 1 FE Ports
ASA5540-AIP20-K9	Cisco ASA 5540 Appliance with AIP-SSM-20, Firewall, IPsec VPN (5,000 Peers), and IPS Software, 4 GE and 1 FE Ports

Cisco ASA 5500 Anti-X Bundles

ASA5510-CSC10-K9	Cisco ASA 5510 Appliance with CSC-10, Firewall, IPsec VPN (150 Peers), and 50 Users Anti-Virus/Anti-Spyware Software, 1 Year Subscription
ASA5510-CSC20-K9	Cisco ASA 5510 Appliance with CSC-20, Firewall, IPsec VPN (150 Peers), and 500 Users Anti-Virus/Anti-Spyware Software, 1 Year Subscription
ASA5520-CSC10-K9	Cisco ASA 5520 Appliance with CSC-10, Firewall, IPsec VPN (750 Peers), and 50 Users Anti-Virus/Anti-Spyware Software, 1 Year Subscription
ASA5520-CSC20-K9	Cisco ASA 5520 Appliance with CSC-20, Firewall, IPsec VPN (750 Peers), and 500 Users Anti-Virus/Anti-Spyware Software, 1 Year Subscription

Cisco ASA 5500 VPN Bundles

ASA5510-SSL50-K9	Cisco ASA 5510 Appliance with SSL VPN 50 / IPsec VPN 150 user and Firewall Software Bundle
ASA5510-SSL100-K9	Cisco ASA 5510 Appliance with SSL VPN 100 / IPsec VPN 150 user and Firewall Software Bundle
ASA5510-SSL250-K9	Cisco ASA 5510 Appliance with SSL VPN 250 / IPsec VPN 150 user and Firewall Software Bundle
ASA5520-SSL500-K9	Cisco ASA 5520 Appliance with SSL VPN 500 / IPsec VPN 750 user and Firewall Software Bundle
ASA5540-SSL1000-K9	Cisco ASA 5540 Appliance with SSL VPN 1,000 / IPsec VPN 5,000 user and Firewall Software Bundle
ASA5540-SSL2500-K9	Cisco ASA 5540 Appliance with SSL VPN 2,500 / IPsec VPN 5,000 user and Firewall Software Bundle

Security Service Modules

ASA-SSM-AIP-10-K9=	Cisco ASA Advanced Inspection and Prevention (AIP) Security Service Module-10
ASA-SSM-AIP-20-K9=	Cisco ASA Advanced Inspection and Prevention (AIP) Security Service Module-20
ASA-SSM-CSC-10-K9=	Cisco ASA Content Security and Control SSM-10 with 50 Users Anti-Virus/Anti-Spyware, 1 Year Subscription
ASA-SSM-CSC-20-K9=	Cisco ASA Content Security and Control SSM-20 with 500 Users Anti-Virus/Anti-Spyware, 1 Year Subscription
SSM-4GE=	Cisco ASA 5500 4-Port Gigabit Ethernet SSM (RJ-45 + SFP)

1. This is only a small subset of all parts available via URL listed under "For More Information". Some parts have restricted access or are not available through distribution channels. Resellers: For latest part number and pricing info, see the *Distribution Product Reference Guide* at: <http://www.cisco.com/dprg> (limited country availability).

For More Information

See the Cisco ASA 5500 Series Adaptive Security Appliance Website:
<http://www.cisco.com/go/asa>

Cisco PIX Security Appliance Series

The market-leading Cisco PIX Security Appliance Series delivers robust user and application policy enforcement, multi-vector attack protection, and secure connectivity services in cost-effective, easy-to-deploy solutions. Ranging from compact, “plug-and-play” desktop appliances for small and home offices to modular gigabit appliances with superior investment protection for enterprise and service-provider environments, Cisco PIX Security Appliances provide robust security, performance, and reliability for network environments of all sizes.



When to Sell

Sell This Product

PIX 501

When a Customer Needs These Features

- Small Office / Home Office desktop integrated security appliance
- Up to 60 Mbps of firewall throughput
- Up to 3 Mbps of 3DES and 3.4 Mbps of AES-256 IPsec VPN throughput¹
- Hardware VPN client (Easy VPN Remote)
- VPN concentrator services (Easy VPN Server) for up to 10 remote users
- Integrated four port 10/100 Mbps switch

PIX 506E

- Remote Office / Branch Office desktop integrated security appliance
- Up to 100 Mbps of firewall throughput
- Up to 15 Mbps of 3DES and 25 Mbps of AES-256 IPsec VPN throughput¹
- Hardware VPN client (Easy VPN Remote)
- VPN concentrator services (Easy VPN Server) for up to 25 remote users
- Maximum of two 10BASE-T Ethernet interfaces

PIX 515E

- VLAN trunking (802.1q tag-based) and OSPF dynamic routing support
- Small-to-Medium Business (SMB) integrated security appliance
- Up to 190 Mbps of firewall throughput¹
- Up to 130 Mbps of 3DES/AES-256 VPN throughput¹ using hardware acceleration (integrated in select models, optional for others)
- VPN concentrator services (Easy VPN Server) for up to 2,000 remote users
- Up to six 10/100 FE interfaces
- VLAN trunking (802.1q tag-based) and OSPF dynamic routing support
- Security contexts (virtual firewall services) support
- Active/Active and Active/Standby firewall stateful failover support
- Active/standby IPSec VPN failover support

PIX 525

- Enterprise-class integrated security appliance
- Up to 330 Mbps of firewall throughput¹
- Up to 145 Mbps of 3DES and 135 Mbps of AES-256 VPN throughput¹ using hardware acceleration (integrated in select models, optional for others)
- VPN concentrator services (Easy VPN Server) for up to 2,000 remote users
- Gigabit Ethernet support; Up to eight 10/100 FE or three Gigabit Ethernet interfaces
- VLAN trunking (802.1q tag-based) and OSPF dynamic routing support
- Security contexts (virtual firewall services) support
- Active/Active and Active/Standby firewall stateful failover support
- Active/standby IPSec VPN failover support

PIX 535

- Carrier class large enterprise and service provider firewall appliance
- Up to 1.7 Gbps of firewall throughput¹
- Up to 425 Mbps of 3DES/AES-256 VPN throughput using hardware acceleration (integrated in select models, optional for others)
- VPN concentrator services (Easy VPN Server) for up to 2,000 remote users
- Gigabit Ethernet throughput; Up to ten 10/100 FE or nine Gigabit Ethernet interfaces
- VLAN trunking (802.1q tag-based) and OSPF dynamic routing support
- Security contexts (virtual firewall services) support
- Active/Active and Active/Standby firewall stateful failover support
- Active/standby IPSec VPN failover support
- Redundant, hot-swappable power supplies

1. At 1400-byte packets

Key Features

- Advanced Firewall Services—Deep inspection firewall services such as HTTP, FTP, and ESMTP; Instant messaging, peer-to-peer, and tunneling application blocking; Cisco Modular Policy Framework with flow-based security policies; Virtual firewall services; Layer 2 transparent firewall; 3G Mobile Wireless security services;
- Robust IPSEC VPN Services—VPN client security posture enforcement; Automatic VPN client software updating; OSPF dynamic routing over VPN tunnels
- High Availability Services—Award-winning Active/Standby or more advanced Active/Active failover with asymmetric routing support; Remote-access and site-to-site VPN stateful failover; Zero-downtime software upgrades
- Intelligent Network Services—PIM multicast routing; Quality of service (QoS); IPv6 networking
- Flexible Management Solutions—SSHv2 and SNMPv2c; Configuration rollback; Usability enhancements; Web-based Adaptive Security Device Manager (ASDM)

Competitive Products

- Check Point Software: FireWall-1 / VPN-1
- Juniper Networks: NetScreen Security Appliances
- Nokia: IP-Series Security Appliances
- SonicWALL: SonicWALL Security Appliances
- WatchGuard Technologies: Firebox-series Security Appliances

Specifications

Feature	PIX 501	PIX 506E	PIX 515E	PIX 525	PIX 535
Processor	133 MHz	300 MHz	433 MHz	600 MHz	1.0 GHz
RAM	16 MB	32 MB	64 or 128 MB	128 or 256 MB	512 MB or 1 GB
Flash Memory	8 MB	8 MB	16 MB	16 MB	16 MB
PCI Slots	None	None	2	3	9
Fixed Interfaces (Physical)	Four port 10/100 switch (inside), One 10Base-T Ethernet (outside)	Two 10Base-T Ethernet	Two 10/100 Fast Ethernet	Two 10/100 Fast Ethernet	Two 10/100 Fast Ethernet
Maximum Interfaces (Physical)	Four port 10/100 switch (inside), One 10Base-T Ethernet (outside)	Two 10Base-T Ethernet	Six 10/100 Fast Ethernet (FE)	Eight 10/100 FE or GE	Ten-10/100 FE or GE
Maximum Virtual Interfaces (VLAN)	0	2 (DMZ)	25	100	150
Supported Security Contexts	No	No	Yes, 2/5 ¹	Yes, 2/50 ¹	Yes, 2/50 ¹
VPN Accelerator Card+ (VAC+) Option	No	No	Yes, integrated in select models	Yes, integrated in select models	Yes, integrated in select models
High Availability Support	No	No	A/S, A/A ²	A/S, A/A	A/S, A/A
Size	Desktop	Desktop	1 RU	2 RU	3 RU

1. Licensed feature on UR, FO, and AA Platform Licenses, requires Cisco PIX Security Appliance Software Version 7.0(1) or higher

2. Requires Cisco PIX Security Appliance Software Version 7.0(1) or higher; A/A high availability requires one UR and one FO-AA unit (A/S = Active/Standby; A/A = Active/Active)

Selected Part Numbers and Ordering Information¹

Cisco PIX Security Appliance Bundles

PIX-535-UR-BUN	PIX 535 Unrestricted Bundle (Chassis, license, unrestricted software, two 10/100 ports, VPN Accelerator Card+)
PIX-535-R-BUN	PIX 535 Restricted Bundle (Chassis, license, restricted software, two 10/100 ports)
PIX-535-F0-BUN	PIX 535 Failover Bundle (Chassis, license, failover software, two 10/100 ports, VPN Accelerator Card+)
PIX-535-UR-GE-BUN	PIX 535-UR-GE Bundle (Chassis, unrestricted license, software, three GE, two FE, VPN Accelerator Card+, 2 AC)
PIX-535-F0-GE-BUN	PIX 535-F0-GE Bundle (Chassis, failover license, software, three GE, Two FE, VPN Accelerator Card+, 2 AC)
PIX-535-AA-GE-BUN	PIX 535-AA Bundle (Chassis, active/active failover license, software, three GE, two FE, VPN Accelerator Card+, 2 AC)
PIX-525-UR-GE-BUN	PIX 525 Unrestricted GE Bundle (Chassis, license, unrestricted software, two GE ports, two 10/100 ports, VPN Acceleration Card+)
PIX-525-F0-GE-BUN	PIX 525 Failover GE Bundle (Chassis, license, failover software, two GE ports, two 10/100 ports, VPN Acceleration Card+)
PIX-525-UR-BUN	PIX 525 Unrestricted Bundle (Chassis, license, unrestricted software, two 10/100 ports, VPN Accelerator Card+)
PIX-525-R-BUN	PIX 525 Restricted Bundle (Chassis, license, restricted software, two 10/100 ports)
PIX-525-F0-BUN	PIX 525 Failover Bundle (Chassis, license, failover software, two 10/100 ports, VPN Accelerator Card+)
PIX-525-AA-GE-BUN	PIX 525 F0-AA Bundle (Chassis, active/active failover license, software, two GE, two FE, VPN Accelerator Card+)
PIX-515E-UR-FE-BUN	PIX 515E Unrestricted Bundle (Chassis, license, unrestricted software, six 10/100 ports, VPN Accelerator Card+)
PIX-515E-F0-FE-BUN	PIX 515E Failover Bundle (Chassis, license, failover software, six 10/100 ports, VPN Accelerator Card+)
PIX-515E-UR-BUN	PIX 515E Unrestricted Bundle (Chassis, license, unrestricted software, two 10/100 ports, VPN Accelerator Card+)
PIX-515E-R-BUN	PIX 515E Restricted Bundle (Chassis, license, restricted software, two 10/100 ports)
PIX-515E-F0-BUN	PIX 515E Failover Bundle (Chassis, license, failover software, two 10/100 ports, VPN Accelerator Card+)
PIX-515E-AA-FE-BUN	PIX 515E F0-AA Bundle (Chassis, active/active failover license, software, six FE, VPN Accelerator Card+)
PIX-515E-R-DMZ-BUN	PIX 515E DMZ Bundle (Chassis, license, restricted software, three 10/100 ports)
PIX515E-DMZ-CSA-K9	Cisco Security Starter Bundle with PIX 515E-R-DMZ system, CSA, VMS Basic Software
PIX-506E-BUN-K9	PIX 506E 3DES/AES Bundle (Chassis, license, software, 3DES/AES license, two 10-BaseT ports)2
PIX-501-BUN-K9	PIX 501 10 User/3DES/AES Bundle (Chassis, software, 10 user/3DES/AES license, 4 port 10/100 switch)
PIX-501-50-BUN-K9	PIX 501 50 User/3DES/AES Bundle (Chassis, software, 50 user/3DES/AES license, 4 port 10/100 switch)
PIX-501-UL-BUN-K9	PIX 501 Unlimited User/3DES/AES Bundle (Chassis, software, Unlimited Users 3DES/AES license, 4 port 10/100 switch)

Cisco PIX Security Appliance Interfaces and Cards

PIX-1GE-66	PIX 66-MHz Single-port Gigabit Ethernet interface card (multimode fiber, SC connector)
PIX-4FE-66	PIX 66-MHz Four-port 10/100 Fast Ethernet interface card, RJ45
PIX-1FE	PIX Single-port 10/100 Fast Ethernet interface card
PIX-VPN-ACCEL	PIX DES/3DES VPN Accelerator Card (VAC)
PIX-VPN-PLUS	PIX DES/3DES/AES VPN Accelerator Card+ (VAC+)

1. This is only a small subset of all parts available via URL listed under "For More Information". Some parts have restricted access or are not available through distribution channels. Resellers: For latest part number and pricing info, see the *Distribution Product Reference Guide* at: <http://www.cisco.com/dprg> (limited country availability).

For More Information

See the PIX Security Appliance Website: <http://www.cisco.com/go/pix>

Cisco Intrusion Protection System (IPS) Network Sensors



The Cisco IPS 4200 Series sensors are a key component of the Cisco Self Defending Network. In busy network environments, business continuity relies on efficient network intrusion security to stop malicious attacks, worms and viruses before they affect your data and resources. The Cisco IPS sensors, utilizing IPS v5.0 software, accurately detect, classify, and stop malicious traffic through the use of inline prevention functionality.

Cisco's family of purpose-built IPS devices includes the Cisco IPS 4200 Series appliances and the Cisco Catalyst 6500 Series switch module. The intrusion detection system (IDS) module for Cisco access routers provides traditional detection with enhanced capabilities. Additionally, a focused set of intrusion prevention capabilities is available as a Cisco IOS® Software solution for Cisco routers. For device configuration and event viewing, Cisco solutions include the IPS Device Manager for single device management and event monitoring, and CiscoWorks VPN/Security Management Solution (VMS) for multidevice, multievent-type correlation.

When combined, these elements provide a comprehensive inline prevention solution, giving you the confidence to detect and stop the broadest range of malicious traffic before it affects business continuity.

The current Cisco IDS/IPS sensing portfolio includes IDS 4215, IPS 4240, IPS 4255 and IDS 4250-XL. Additional Cisco IDS integrated solutions include Intrusion Detection System Module (IDSM-2) for the Catalyst 6500 switch and the IDS Network Module (NM-CIDS) for Cisco Access Routers.

When to Sell

Sell This Product When a Customer Needs These Features

Cisco IPS Network Sensors

- A distributed intrusion prevention system capable of directing and forwarding alarms between local, regional, and headquarters-based monitoring consoles
- A scalable architecture to allow the deployment of large numbers of sensors in order to provide comprehensive security coverage in large network environments
- Cisco network IPS appliances (Cisco IPS 4200 Series Appliances) that can be deployed throughout the network with the ability to monitor multiple subnets using a single appliance through the support of multiple interfaces
- The Cisco IDS Switch Module (IDSM2) enables customers to perform both security monitoring and switching functions within the same chassis
- The Cisco IDS Network Module enables full features intrusion protection integrated into the Cisco Access Routers
- Broad performance range from 45 Mbps
- Flexible IDS signature customization options
- Broad range of management and monitoring options to fit any environment.
- A robust, 24 hour x 7 day-a-week monitoring and response system with the latest attack detection capabilities

Key Features

- Multivector threat identification—Protects your network from policy violations, vulnerability exploitations, and anomalous activity through the detailed inspection of Layers 2-7 traffic.
- Accurate prevention technologies—Provides the confidence to enable prevention actions on a broader range of threats without the risk of dropping legitimate traffic. The Cisco innovative Risk Rating and Meta-Event Generator (MEG) accurately identify attacks, allowing for rapid mitigation activity.
- Unique network collaboration—Provides enhanced scalability and resiliency through network collaboration, including efficient traffic capture techniques, load-balancing capabilities, and visibility into encrypted traffic.
- Comprehensive deployment solutions—Provides intrusion detection and prevention solutions for all environments from the small to midsize business (SMB) and branch office location to the large enterprise and service provider installations.

Competitive Products

- Internet Security Systems (ISS): Proventia
- Symantec: Recourse Manhunt & ManTrap/NetProwler
- Enterasys: Dragon IDS
- Intrusion.com: SecureNet
- Juniper: OneSecure IDP
- Snort: IDS
- Tipping Point—Unity One
- NAI: Intrushield
- Network Flight Recorder, Inc.: NFR

Specifications

Feature	IPS-4255	IPS-4240	IDS-4215	IDS-4250-XL	IDS Module (IDSM-2)	IDS Network Module (NM-CIDS)
Performance	600 Mbps	250 Mbps	650 Mbps	800 Mbps	600 Mbps	45Mbps
Monitoring Interface	Four 10/100/1000BASE-TX	Four 10/100/1000BASE-TX	Autosensing 10/100 Base-T Ethernet, (upgradable to support up to 5 monitoring interfaces)	Dual 1000BASE-SX PCI interface with MTRJ		Internal 10-/100-Mbps Ethernet and external 10-100-Mbps Ethernet

Feature	IPS-4255	IPS-4240	IDS-4215	IDS-4250-XL	IDS Module (IDSM-2)	IDS Network Module (NM-CIDS)
Optional Interface			Four 10/100 Base-Tx (4FE) sniffing interfaces (allowing a total of 5 sniffing interfaces)	1000Base-Sx (fiber)		
Command & Control Interface	10/100 Base-TX	10/100 Base-TX	10/100 Base-TX	100Base-SX (fiber) PCI		10/10/100Base T

Selected Part Numbers and Ordering Information¹

Cisco IDS/IPS Network Appliance Sensor

IDS-4215-K9	4215 Cisco IDS 4215 Sensor (chassis, software, SSH, 2 onboard 10/100Base-TX with RJ-45 connector) 65-Mbps
IDS-4215-4FE-K9	Cisco IDS 4215 Sensor (chassis, software, SSH, 2 onboard 10/100BASE-TX with RJ-45 connector plus 4FE interface card), 65-Mbps
IPS-4240-K9	Cisco IPS 4240 Sensor (chassis, software, SSH, four 10/100/1000BASE-T with RJ-45 connector) 250 Mbps
IPS-4255-K9	Cisco IPS 4255 Sensor (chassis, software, SSH, four 10/100/1000BASE-T with RJ-45 connector) 500 Mbps
IDS-4250-XL-K9	Cisco IDS 4250-XL Sensor (chassis, software, SSH, hardware accelerator with dual 1000BASE-SX and MTRJ connectors) 800 Mbps

Cisco IDS Network Module for Cisco Access Routers

WS-SVC-IDS2-BUN-K9	Cisco IDS Network Module, for 26xx, 3660 and 37xx routers as well as the ISR router series, 45Mbps
--------------------	--

1. This is only a small subset of all parts available via URL listed under "For More Information". Some parts have restricted access or are not available through distribution channels. Resellers: For latest part number and pricing info, see the *Distribution Product Reference Guide* at: <http://www.cisco.com/dprg> (limited country availability).



Note

Export Considerations: The Cisco IDS 4215, Cisco IDS 4240, Cisco IDS 4255, Cisco IDS 4250-XL, Cisco IDSM-2 & Cisco IDS Network Module are subject to export controls. Please refer to the export compliance website at <http://www.cisco.com/www/export/crypto> for guidance. For specific export questions, please contact export@cisco.com.

For More Information

See the Cisco IPS Website: <http://www.cisco.com/go/ips>

Cisco Incident Control System (ICS)

The Cisco Incident Control System fills an important void in network defense by focusing on newly discovered outbreaks, with response times in minutes rather than hours and the ability to extend the defense against these new threats across a wide variety of products in multiple network topologies. The result is that devices across the entire network infrastructure are able to respond and adapt to the emerging threat in advance of its arrival, in a coordinated manner. This proactive network-wide approach increases the likelihood that the outbreak will be denied access or, if it finds its way in, will be rapidly contained.

When to Sell

Sell This Product Cisco Incident Control System (ICS)

When a Customer Needs These Features

- For customers who have invested or plan to invest in Cisco routers or switches especially those that have any Cisco IPS-capable products like IPS-4200 Series appliances, IDSM2 blades for Catalyst 6500, ASA-5500 Series appliances with AIP-SSM cards, Integrated Services Routers (ISRs), or Any routers running Cisco IOS Security images
- When customers want to maximize their current investment by allowing these devices to serve double-duty as outbreak mitigation points

Key Features

- Protection against newly discovered threats in the wild
- Industry leading response time to new threats
- Ability to mitigate against infection across a wide variety of points in the network
- Leverage existing—or maximize new—investment in Cisco security and networking products such as any IPS capable products as well as routers and switches
- Coarse-grained ACL-type defense for wide variety of Cisco security and networking products within typically 15 minutes of an outbreak’s discovery; Fine-grained high fidelity signature defense for all IPS-capable Cisco products within typically 90 minutes of an outbreak’s discovery
- Full control over how and when mitigation measures are deployed to all devices with either automatic deployment or notification, inspection, edit capability and manual deployment

Specifications

Feature	Cisco Incident Control (ICS)
Operating Systems	Windows 2000 Server or Advanced Server with SP3; Windows 2003 Server Standard Edition or Enterprise Edition (English); IIS: Windows 2000 IIS 5.0 or Windows 2003 IIS 6.0; Apache: 2.0
Web Server (for Console Access)	Internet Explorer version 5.5 SP2
Hardware	866-MHz Intel Pentium III processor or equivalent; 512 MB of RAM; 350 MB of disk space

Selected Part Numbers and Ordering Information¹

Cisco Incident Control System (ICS)

ICS-EVAL-K9	Cisco ICS 60-Day Evaluation Kit: includes the 4 parts numbers below
ICS-SVR-V10-K9	Cisco Incident Control Server Software v1.0
ICS-LIC-IPS-HE-1	Cisco ICS License: ACL plus IPS Service for high-end devices, Qty 1
ICS-LIC-IPS-LE-5	Cisco ICS License: ACL plus IPS Service for low-end devices, Qty 5
ICS-LIC-ACL-25	Cisco ICS License: ACL Service, Qty 25

1. This is only a small subset of all parts available via URL listed under “For More Information”. Some parts have restricted access or are not available through distribution channels. Resellers: For latest part number and pricing info, see the *Distribution Product Reference Guide* at: <http://www.cisco.com/dprg> (limited country availability).

For More Information

See the Cisco Incident Control System Website: <http://www.cisco.com/go/ics>

Cisco Security Monitoring and Response System (CS-MARS)

The CS-MARS is a family of high performance, scalable appliances for threat management, monitoring and mitigation that enable customers to make more effective use of network and security devices by combining traditional security event monitoring with network intelligence, context correlation, vector analysis, anomaly detection, hotspot identification and automated mitigation capabilities. By combining network intelligence, an understanding of network topology and automated mitigation capabilities, CS-MARS help companies to accurately identify and eliminate network attacks while maintaining network compliance.

When to Sell

Sell This Product

CS-MARS 20

When a Customer Needs These Features

- Small Office, Test lab, Departments, Small Retail, DMZ, CPE
- Low end device to plot network topology and gain insight of their network topology
- Up to 500 events per second
- Up to 15,000 Netflow flows per second
- 120 Gig Storage

CS-MARS 50

- Small to Medium Office, remote branch office, retail, small business, DMZ, CPE
- Consolidate Firewall and IDS with network events and network flows in small network
- Up to 1,000 events per second
- Up to 30,000 Netflow flows per second
- 240 Gig Storage

CS-MARS 100e

- Medium Regional Office, large remote branch office, mid-tier company, CPE
- Up to 3,000 events per second
- Up to 75,000 Netflow flows per second
- 750 Gig Storage

CS-MARS 100

- Large regional, large Branch Office, mid tier company, CPE
- Up to 5,000 events per second
- Up to 150,000 Netflow flows per second
- 750 Gig storage

CS-MARS 200

- Large Enterprise, Central Office, large Firewalls (FWSM)
- Up to 10,000 events per second
- Up to 300,000 Netflow flows per second

CS-MARS GC

- Large Distributed Environment (large Enterprise or Service Provider Companies), MSSP
- Preserve WAN
- Autonomous business units rolling activity to Global team
- State and Federal government consolidating activities from various agencies
- Consolidates reports from distributed "Local" controller
- Small distributed customer environment
- Preserve WAN

CS-MARS GCm

- Consolidates reports from distributed "Local" controller
- Up to (5) MARS 20 or MARS 50 connection

Key Features

- Redundant, hot-swappable power supplies—CS-MARS 100, 100e, 200, GC, and GCm
- Raid 10 disk Drive (Hot Swappable)—CS-MARS 100, 100e, 200, GC, and GCm
- 1 Terabyte of storage—CS-MARS 200, GC, and GCm
- Centralized Monitoring—Provides detailed information about the network infrastructure including routers, switches, firewalls, VPN concentrators, and endpoint devices through a variety of device logs, alerts, and Netflow communication; Process threat information down to the IP and MAC address, nearest attached switch port, as well as providing the attack path through the network
- Central Event Repository—Serves as a central repository for all events generated by Security devices, such as firewalls, authentication servers, Network IDS/IPS, and proxy servers; All collected events are cross-correlated in real-time.
- Data reduction—Can reduce millions of security events to a handful of actual reported network incidents
- Timely attack mitigation—Performance and the built-in expertise to recognize and recommend mitigation for attacks before they can bring down an entire network
- End-to-end network awareness—Integrates NAT/PAT and MAC address information to identify attackers, targets, and network hot spots in graphical form for quick action; Uses the full configurations of all types of network devices and end systems; Pre and Post NAT addresses can be displayed
- Integrated Vulnerability Assessment—Determines whether a possible network attack is genuine or a false positive reducing the number of alarms and the time needed to take action

- **Reduced Deployment and Operation Cost**—Discovers then maps the topology and becomes operational in a very short period of time
- **Cisco NAC phase II Support**—Reports on overall posture, and identifying compliant, non-compliant workstations; Verifies when hosts that pass the company's posture criteria display inappropriate behavior
- **802.1x Support**—Enables a host connecting to the switch port to be authenticated before obtaining an IP address
- **Cisco Distributed Threat Mitigation (DTM) and CICS Support**—A collaborative solution that proactively identifies the most active signatures from the IPS appliance deployed in the network and, based on the most active threats detected on the network; Distributes the same IPS signatures to the user defined IOS IPS devices.
- **Case Management**—Escalate an incident by creating a case and forward the case with notes to other users and security administrators; Annotate the case by including incidents and queries performed; User's audit and conform to the customer's policy regarding regulatory compliance; Addresses the lifecycle of security event management
- **Netflow Analysis**—Netflow data from routers are collected by the CS-MARS, as high as 300K flows per second

Competitive Products

- Internet Security Systems (ISS) SiteProtector
- Checkpoint Eventia
- Network Intelligence
- ArcSight
- Intellitactics
- Sensage
- Guardednet
- Q1 Labs

Specifications

Feature	CS-MARS-20-K9	CS-MARS-50-K9	CS-MARS-100E-K9	CS-MARS-100-K9	CS-MARS-200-K9	CS-MARS-GCM-K9	CS-MARS-GC-K9
Storage	120GB (non-RAID)	240GB RAID0	750GB RAID10; Hot Swappable	750GB RAID10; Hot Swappable	1TB RAID10; Hot Swappable	1TB RAID10; Hot Swappable	1TB RAID10; Hot Swappable
Form Factor	1RU x16	1RU x25.6	3RU x25.6	3RU x25.6	4RU x25.6	4RU x25.6	4RU x25.6
Power Supply	300W	300W	500W Dual Redundant	500W Dual Redundant	500W Dual Redundant	500W Dual Redundant	500W Dual Redundant
Performance							
Events/sec	500	1,000	3,000	5,000	10,000		
NetFlows/sec	15,000	30,000	75,000	150,000	300,000		
Distributed Monitoring							
Supported Models						From MARS 20/50 Only	5
Maximum Connections						Any	Not Restricted

Selected Part Numbers and Ordering Information¹

Cisco Security Monitoring and Response System (CS-MARS)

CS-MARS-100-K9	PN-MARS 100 3RU Appliance, 5,000 EPS, 750GB RAID10, HW/SW
CS-MARS-100E-K9	PN-MARS 100e 3RU Appliance, 3,000 EPS, 750GB RAID10, HW/SW
CS-MARS-20-K9	PN-MARS 20 1RU Appliance, 500 EPS, 120GB, HW/SW
CS-MARS-200-K9	PN-MARS 200 4RU Appliance, 10,000 EPS, 1TB RAID10, HW/SW
CS-MARS-50-K9	PN-MARS 50 1RU Appliance, 1,000 EPS, 240GB RAID0, HW/SW
CS-MARS-GC-K9	PN-MARS Global Controller (Any Model LC), HW/SW
CS-MARS-GCM-K9	PN-MARS GCm (Restricted, Up to 5 MARS 20/50 LCs Only), HW/SW

1. This is only a small subset of all parts available via URL listed under "For More Information". Some parts have restricted access or are not available through distribution channels.

For More Information

See the CS-MARS Website:

www.cisco.com/en/US/partner/products/ps6241/tsd_products_support_series_home.html

Cisco VPN 3000 Family



The Cisco VPN 3000 Series Concentrator is a best-in-class, remote-access VPN solution for enterprise-class deployment. A standards-based, easy-to-use VPN client and scalable VPN tunnel termination devices are included, as well as a management system that enables corporations to easily install, configure, and monitor their remote access VPNs. Remote connections can be established either from a SSL-capable Web browser or an installed VPN Client, allowing for maximum flexibility and application access without the need to deploy and manage multiple unique devices for secure corporate or partner application access. Incorporating the most advanced, high-availability capabilities with a unique purpose-built, remote-access architecture, it allows corporations to build high-performance, scalable, and robust VPN infrastructures to support their mission-critical, remote-access applications.

Unique to the industry, it is the only scalable platform to offer components that are field-swappable and can be upgraded by the customer. These components, called Scalable Encryption Processing (SEP/SEP-E) modules, enable users to easily add capacity and throughput.

The Cisco VPN 3000 Series Concentrator supports the widest range of connectivity options, including WebVPN (Clientless using a Web browser), the Cisco VPN Client, the Microsoft L2TP/IPSec, and Microsoft PPTP.

When to Sell

Sell This

Product

When a Customer Needs These Features

VPN 3005 and 3015 Concentrators

- Cisco VPN 3005 Concentrator
 - Designed for small to medium-sized organizations with bandwidth requirements up to full-duplex T1/E1 (4 Mbps maximum performance) with support for up to 200 simultaneous IPSec sessions or 50 simultaneous clientless sessions
 - Encryption processing is performed in software
 - Does not have built-in upgrade capability
- Cisco VPN 3015 Concentrator
 - Designed for small- to medium-sized organizations with bandwidth requirements up to full-duplex T1/E1 (4 Mbps maximum performance) and up to 100 simultaneous IPSec sessions or 75 simultaneous clientless sessions
 - Encryption processing is performed in software
 - Field-upgradable to the Cisco VPN 3030 and 3060 models

VPN 3020 Concentrator

- Designed for medium to large organizations with bandwidth requirements from full T1/E1 through T3/E3 (50 Mbps maximum performance) with support for up to 750 simultaneous IPSec sessions or 200 simultaneous clientless sessions
- Specialized SEP modules (SEP-E) perform hardware-based acceleration
- Cannot be upgraded to other products in the family
- Redundant and nonredundant configurations are available

VPN 3030 and 3060 Concentrators

- Cisco VPN 3030 Concentrator
 - Designed for medium to large organizations with bandwidth requirements from full T1/E1 through T3/E3 (50 Mbps maximum performance) with support for up to 1,500 simultaneous IPSec sessions or 500 simultaneous clientless sessions
 - Specialized SEP modules perform hardware-based acceleration
 - Field upgradeable to the Cisco VPN 3060
 - Redundant and nonredundant configurations are available
- Cisco VPN 3060 Concentrator
 - Designed for large organizations demanding the highest level of performance and reliability, with high-bandwidth requirements from fractional T3 through full T3/E3 or greater (100 Mbps maximum performance) with support for up to 5,000 simultaneous IPSec sessions or 500 simultaneous clientless sessions
 - Specialized SEP modules perform hardware-based acceleration
 - Redundant and nonredundant configurations are available

VPN 3080 Concentrator

- Optimized to support large enterprise organizations that demand the highest level of performance combined with support for up to 10,000 simultaneous IPSec sessions or 500 simultaneous clientless sessions
- Specialized SEP modules perform hardware-based acceleration
- Available in a fully redundant configuration only

Sell This Product
VPN Client**When a Customer Needs These Features**

- Simple to deploy and operate
- Used to establish secure, end-to-end encrypted tunnels to the Cisco VPN 3000 Concentrator and other Cisco EasyVPN compliant devices
- Thin design, IPSec-compliant implementation is provided
- Licensed for an unlimited number of users
- Client can be pre-configured for mass deployments and the initial logons require very little user intervention
- VPN access policies are created and stored centrally and pushed to the client when a connection is established
- Provided at no charge, installs on PCs and is available for Windows, Mac OS X and Linux Intel/Solaris UltraSparc environments
- Emulates the software client in hardware
- Ideal for mixed operating system environments and where a corporation does not own/control remote PCs or for very large applications requiring large number of devices due to ease of deployment, upgradability & scalability

VPN 3002 Hardware Client**Key Features**

- Cisco VPN 3000 Concentrators Series
 - Support for industry standard IPSec DES/3DES/AES and Cisco IPSec/NAT for VPN Access through Port Address Translation firewalls
 - Unlimited-use license for Cisco VPN Client distribution included at no cost with multiple OS support including Windows, MAC OS X, Linux and Solaris; also integrates with Zone Alarms personal firewall
 - Supports standard authentication: RADIUS, SDI Tokens, and Digital Certificates
 - VPN load balancing allows for multiple units to cluster as a single shared pool
- Cisco VPN 3002 Hardware Client supports up to 253 users/stations per VPN 3002
 - Works with most operating systems including Windows, Linux, Solaris, and MAC OS X
 - Auto-upgrade capability automates upgrades with no user intervention required
 - Client technology employs push policy and automatic address assignment from the central site concentrator, enabling virtually unlimited scalability

Competitive Products

- Nortel: Contivity products (IPSec)
- Juniper (Neteoris): SSL VPN Secure Access products
- Juniper (Netscreen): LAN to LAN environments
- Nokia

Specifications**Cisco VPN 3000 Series Concentrators**

Feature	VPN 3005	VPN 3015	VPN 3020	VPN 3030	VPN 3060	VPN 3080
Simultaneous IPSec Users	200	100	750	1500	5000	10000
Simultaneous WebVPN (Clientless) Users	50	75	200	500	500	500
Encryption Throughput	4 Mbps	4 Mbps	50 Mbps	50 Mbps	100 Mbps	100 Mbps
Encryption Method	Software	Software	Hardware	Hardware	Hardware	Hardware
Encryption (SEP) Module	0	0	1	1	2	4
Redundant SEP	No	No	Optional	Optional	Optional	Yes
Expansion Slots	0	4	1 (Redundant)	3	2	N/A
Upgradeable	No	Yes		Yes	N/A	N/A
Memory	32/64 MB (fixed)	128 MB	256 MB	128-512 MB	256/512 MB	256/512MB
Hardware Configuration	1U, Fixed	2U, Scalable	Fixed 2U	2U, Scalable	2U, Scalable	2U
Power Supply	Single	Single, with a dual option	Single, with a dual option	Single, with a dual option	Single, with a dual option	Dual
Client License	Unlimited	Unlimited	Unlimited	Unlimited	Unlimited	Unlimited
LAN-to-LAN Connections (internal user database)	100	100	250	500	1000	1000
Dimensions (HxWxD)	1.75 x 17.5 x 11.5 in. 3.5 x 17.5 x 14.5 in. 3.5 x 17.5 x 14.5 in. 3.5 x 17.5 x 14.5 in. 3.5 x 17.5 x 14.5 in. 3.5 x 17.5 x 14.5 in.					

Cisco VPN 3002 Hardware Client

Feature	VPN 3002 Hardware Client
Hardware Processor	Motorola PowerPC processor; Dual flash image architecture
Network Interfaces	CPVN3002-K9: One Public 10/100Mbps RJ-45 Ethernet Interface and One Private Port 10/100Mbps RJ-45 Ethernet Interface CVPN3002-8E-K9: One Public 10/100Mbps RJ-45 Ethernet Interface and Eight Private Port 10/100Mbps RJ-45 Ethernet Interfaces via AUTO-MDIX switch
Physical Dimensions	1.967 x 8.6 x 6.5 in. (5 x 8.6 x 16.51 cm)
Power Supply	External AC Operation: 100-240V at 50/60 Hz with universal power factor correction; 4 foot cord included and international "pigtail" power cord selection
Tunneling Protocol Support	IPsec with IKE key management
Monitoring & Configuration	Event logging; SNMP MIB-II support Embedded management interface is accessible via console port or local web browser; SSH/SSL
Encryption Algorithms, Key Management & Authentication Algorithms	56-bit DES (IPsec); 168-bit Triple DES (IPsec); AES 128 & 256-bit (IPsec)
Authentication and Accounting Servers	Support for redundant external authentication servers including RADIUS Microsoft NT Domain authentication, X.509v3 Digital Certs (PKC7-PKCS10)
Configuration Modes	Client Mode—acts as client, receives random IP address from Concentrator Pool; Uses NAPT to hide stations 3002; Network behind 3002 is unroutable; few configuration parameters Network Extension Mode—acts as site-to-site device; Uses NAPT to hide stations only to Internet (stations visible to central site); Network behind 3002 is routable; additional configuration parameters

Selected Part Numbers and Ordering Information¹

Cisco VPN 3000 Concentrator

CVPN3005-E/FE-BUN	VPN3005:Chassis, 2FE, 200 user, client, SW, US PWR
CVPN3015-NR-BUN	VPN3015:Chassis, 3FE, 100 user, client, SW, US PWR
CVPN3020E-NRBUN-K9	VPN3020:Chassis, 3FE, SEP-E, 750 user, client, SW, US PWR
CVPN3020E-RDBUN-K9	VPN3020:Chassis, 3FE, 2SEP-E, 750 user, client, SW, 2 US PWR
CVPN3030E-NRBUN-K9	VPN3030:Chassis, 3FE, SEP-E, 1500 user, client, SW, US PWR
CVPN3030E-RDBUN-K9	VPN3030:Chassis, 3FE, 2SEP-E, 1500 user, client, SW, 2 US PWR
CVPN3060E-NRBUN-K9	VPN3060:Chassis, 3FE, 2SEP-E, 5k user, client, SW, US PWR
CVPN3060E-RDBUN-K9	VPN3060:Chassis, 3FE, 4SEP-E, 5k user, client, SW, 2 US PWR
CVPN3080E-RDBUN-K9	VPN3080:Chassis, 3FE, 4SEP-E, 10k user, client, SW, 2 US PWR

Cisco VPN 3000 Series Upgrades

CVPN3000-UKITA-K9=	1SEP-E,1PS,512MB memory,4.0 OS and boot,client SW
CVPN3000-UKITB-K9=	2SEP-E,1PS,512MB memory,4.0 OS and boot,client SW
CVPN3000-UKITC-K9=	3SEP-E,1PS,512MB memory,4.0 OS and boot,client SW
CVPN3000-UKITD-K9=	4SEP-E,1PS,512MB memory,4.0 OS and boot,client SW

Cisco VPN 3000 Series Accessories

CVPN3000-PWR=	Cisco VPN 3000 Concentrator Power Supply
CVPN30XX-MEMKIT9=	VPN 3030, 3060, 3080: 2x256MB RAM

Cisco VPN 3000 Series Basic Maintenance

CON-SNT-PKG4	SMARTnet Maintenance for Cisco CVPN3005-E/FE-BUN
CON-SNT-PKG8	SMARTnet Maintenance for Cisco CVPN3015-NR-BUN
CON-SNT-PKG11	SMARTnet Maintenance for Cisco CVPN3030-NR-BUN
CON-SNT-PKG13	SMARTnet Maintenance for Cisco CVPN3030-RED-BUN
CON-SNT-PKG14	SMARTnet Maintenance for Cisco CVPN3060-RED-BUN

Cisco VPN Client

CVPN-CLIENT-K9=	Cisco VPN Client CD (included with Concentrator purchase)
-----------------	---

For More Information

See the Cisco VPN 3000 series Website: <http://www.cisco.com/go/vpn3000>

Network Admission Control (NAC)

The Cisco NAC Framework is an industry-wide initiative led by Cisco Systems that leverages the network infrastructure and third party security, management, and remediation technologies to enforce security policy compliance on all endpoints. The Cisco NAC Appliance, based on Cisco Clean Access technology, is a self-contained, turn-key solution that controls network access based on user authentication and policy. It works in conjunction with anti-virus vendor's software by assessing the condition or "posture" of a wired and wireless endpoint (PDA, PCs, laptops) prior to granting network access. Cisco NAC then ensures compliance using built-in auditing, policy, and device remediation tools.

Cisco NAC is a unique approach to preventing vulnerable and noncompliant hosts from affecting enterprise resilience. It enables customers to use their existing network and antivirus infrastructures.

Key Features

- Dramatically improved security through proactive protection against viruses, worms, malware, spyware, and other endpoint attacks by ensuring that all endpoint devices comply with corporate security policy
- Extension of existing investments in network infrastructure and host security to audit and enforce security policies on every device seeking network access
- Increased resilience by providing comprehensive admission control policy across all access methods (wired, wireless, dial-up, IPSec and SSL VPN, Layer 2, and Layer 3, etc.), and for all user types (corporate users, guests, contractors, vendors, etc.)
- Based on collaboration between leading security and management software vendors—Cisco, IBM, Network Associates, Symantec, and Trend Micro—to identify vulnerable systems and enforce effective network admission controls.

For More Information

See the Cisco Network Admission Control Website:

http://www.cisco.com/en/US/partner/netsol/ns466/networking_solutions_package.html

Cisco NAC Appliance (Cisco Clean Access)

Cisco NAC Appliance (Cisco Clean Access) is an easily deployed network admission control product that allows network administrators to authenticate, authorize, evaluate, and remediate wired, wireless and remote users and their machines prior to permitting access to the network. It identifies whether machines are compliant with security policies and repairs vulnerabilities before network access is allowed. To enhance its ease-of-use, the NAC Appliance comes pre-installed with rule sets for operating system updates, antivirus software updates, and anti-spyware software from all major vendors, simplifying the task of determining which policies to enforce and how to enforce them.

Customers will need at least one Cisco NAC Appliance Server, which serves as the gateway, and one Cisco NAC Appliance Manager to manage the Server(s). The NAC Appliance Agent (Clean Access Agent) is an optional component for more stringent vulnerability assessment.

When to Sell

Sell This Product Cisco NAC Appliance

When a Customer Needs These Features

- Ideal for mid-sized and large enterprises that are looking for a client policy enforcement solution. It complements wireless deployments, remote access deployments, and other security products, such as Cisco Security Agent and CS-MARS. The NAC Appliance is the market's most widely-deployed NAC solution, and also preserves the option to sell NAC Framework in the future.
- Available with the following license-based restrictions: 100-user, 250-user, 500-user and 1,500-user. Number of users is defined as online, concurrent users;
- Available either as a "standard" Manager, which can support up to 20 NAC Appliance Servers, or as a Manager "lite," which can support up to 3 NAC Appliance Servers

Key Features

- **Authentication Integration**—Supports roles-based access control by acting as an authentication proxy for most forms of authentication, natively integrating with Kerberos, LDAP, RADIUS, Active Directory, and S/Ident; Supports single sign-on with VPN clients; Enables administrators to maintain multiple user profiles with varying degrees of access.
- **Vulnerability Assessment**—Supports scanning of all Windows-based operating systems, Mac OS, Linux machines, and non-PC networked devices such as Xbox, PlayStation 2, and personal digital assistants; Conducts network-based scans or can use custom-built scans as required; In a managed domain, it can also conduct scans of Windows registries without client software.
- **Device Quarantine**—Places noncompliant machines into quarantine, which prevents the spread of infection while maintaining access to remediation resources; Accomplished by using subnets as small as /30, or by using a quarantine VLAN.
- **Automatic Security Policy Updates**—Provides predefined policies for the most common network access criteria, including policies that check for critical operating system updates and common antivirus software virus definition updates; Eases the management cost on network administrators who can rely on the Clean Access system to constantly maintain updated policies.
- **Centralized Management**—The Web-based management console allows administrators to define the types of scans required for each role as well as the related remediation packages necessary for recovery; One management console can manage several servers.
- **Remediation and Repair**—Gives devices access to remediation servers during quarantine that can provide operating system patches and updates, virus definition files, or endpoint security solutions such as Cisco Security Agent. Administrators have the option of automatically installing these fixes using the Cisco NAC Appliance enforcement agent.

Competitive Products

- Bradford Networks Campus Manager
- Sygate Secure Enterprise (now part of Symantec)
- ENDFORCE Enterprise
- Lockdown Networks

Selected Part Numbers and Ordering Information

Part Number	Description	SASU Part Number
Cisco Clean Access Managers		
CCA-MGR-K9	Cisco Clean Access Manager	CON-SAU-CCAMGR
CCA-MGR-FB-K9	Cisco Clean Access Manager Failover Bundle	CON-SAU-CCAMGRFB
CCA-MGR-U-K9	Cisco Clean Access Manager Failover Upgrade	CON-SAU-CCAMGRFB
Cisco Clean Access Servers In-Band		
CCA-START-IB-K9	Cisco Clean Access Server + Manager In-Band (750 users)	CON-SAU-CCASTIB
CCA-BRSVR-IB-K9	Cisco Clean Access Branch Office In-Band Server (250 Users)	CON-SAU-CCABSVIB
CCA-SVR-IB-K9	Cisco Clean Access Server In-Band	CON-SAU-CCASVIB
CCA-SVR-IB-FB-K9	Cisco Clean Access Server In-Band Failover Bundle	CON-SAU-CCASVIBF
CCA-10SVR-IB-K9	Cisco Clean Access 10 Server In-Band Bundle	CON-SAU-CCA10IB
CCA-10SVR-IBF-K9	Cisco Clean Access 10 Server Failover In-Band Bundle	CON-SAU-CCA10IBF
CCA-SVR-IBU-K9	Cisco Clean Access Server In-Band Failover Upgrade	CON-SAU-CCASVIBF
CCA-10SVR-IBU-K9	Cisco Clean Access 10 Server In-Band Failover Upgrade	CON-SAU-CCA10IBF

Cisco Clean Access Servers Out-of-Band

CCA-START-OB-K9	Cisco Clean Access Server + Manager Out-of-Band (750 users)	CON-SAU-CCASTOB
CCA-BRSVR-OB-K9	Cisco Clean Access Branch Office Out-of-Band Server (250 Users)	CON-SAU-CCABSVIB
CCA-SVR-OB-K9	Cisco Clean Access Server Out-of-Band	CON-SAU-CCASV0B
CCA-SVR-OB-FB-K9	Cisco Clean Access Server Out-of-Band Failover Bundle	CON-SAU-CCASV0BF
CCA-10SVR-OB-K9	Cisco Clean Access 10 Server Out-of-Band Bundle	CON-SAU-CCA100B
CCA-10SVR-0BF-K9	Cisco Clean Access 10 Server Failover Out-of-Band Bundle	CON-SAU-CCA100BF
CCA-SVR-0BU-K9	Cisco Clean Access Server Out-of-Band Failover Upgrade	CON-SAU-CCASV0BF
CCA-10SVR-0BU-K9	Cisco Clean Access 10 Server Out-of-Band Failover Upgrade	CON-SAU-CCA100BF
Cisco Clean Access Commercial		
CCA-100-SM-BUN-K9	Cisco Clean Access Server + Manager (100 users)	CON-SAU-CCABU100
CCA-250-SM-BUN-K9	Cisco Clean Access Server + Manager (250 users)	CON-SAU-CCABU250
CCA-500-SM-BUN-K9	Cisco Clean Access Server + Manager (500 users)	CON-SAU-CCABU500

For More Information

See the Cisco Clean Access Website: <http://www.cisco.com/go/cca>

Cisco Security Agent

The next-generation Cisco Security Agent network security software provides threat protection for server and desktop computing systems, also known as “endpoints.” The Cisco Security Agent goes beyond conventional host and desktop security solutions by identifying and preventing malicious behavior that threaten enterprise networks and applications before it can occur. It aggregates and extends multiple endpoint security functions by providing host intrusion prevention, antispymware, distributed firewall, malicious mobile code protection, operating system integrity assurance, and audit log consolidation all within a single agent package.

The Cisco Security Agent analyzes behavior rather than relying on signature matching, its solution provides robust protection with reduced operational costs. It provides patch relief to reduce the system administration workload allowing companies to wait for “roll-ups” and Service Packs, which come better qualified from the vendor. Testing and implementation of updates can be scheduled without undue change control interruption. Fewer updates reduce the cost of ownership.

When to Sell**Sell This Product****Cisco Security Agent****When a Customer Needs These Features**

- Host intrusion protection, antispymware, distributed firewall, malicious mobile code protection, operating system hardening, file integrity and/or audit log consolidation. The Cisco Security Agent provides all of these features in one integrated package
- Protection against both known and unknown attacks
- Protection for servers and/or desktops/laptops
- A solution that is scalable to protect thousands of servers and desktops for large enterprise deployments
- Provides endpoint protection enabling businesses to participate in e-commerce securely and take advantage of the Internet economy

Key Features

- Provides industry-leading protection for Unix and Windows servers
- Multiple security functions in a single agent
- Open, extensible architecture offers the capability to define and enforce security according to corporate policy
- “Zero Update” prevention for known and unknown attacks
- Integrates with Cisco Network Security Products
- Provides application inventory and use tracking, hotfix and Service Pack status checking, and antivirus DAT version check for Symantec and McAfee antivirus agents
- A key component of the SAFE blueprint for secure e-business

Competitive Products

- Internet Security Systems (ISS)
 - Symantec: Intruder Alert
 - Enterasys: Squire
- Sana Security: Primary Response
 - NAI: Intercept
 - NFR (Centrax)

Specifications

Feature	Cisco Security Server Agent	Cisco Security Desktop Agent	Cisco Security Agent Manager
Platforms	Windows 2000 Server and Advanced Server (up to Service Pack 3) Windows NT v4.0 Server and Enterprise Server (Service Pack 5 or later) Solaris 8 SPARC architecture (64-bit kernel)	Windows NT v4.0 Workstation (Service Pack 5 or later) Windows 2000 Professional (up to Service Pack 3) Windows XP Professional (up to Service 1)	Microsoft Windows 2000 Server and Advanced Server (up to SP 2)

Selected Part Numbers and Ordering Information¹

Cisco Security Agent Options

CSA-SRVR-K9=	Cisco Security Server Agent (Win + Sol), 1 Agent
CSA-B10-SRVR-K9	Cisco Security Server Agent (Win + Sol), 10 Agent Bundle
CSA-B25-SRVR-K9	Cisco Security Server Agent (Win + Sol), 25 Agent Bundle
CSA-B50-SRVR-K9	Cisco Security Server Agent (Win + Sol), 50 Agent Bundle
CSA-B100-SRVR-K9	Cisco Security Server Agent (Win + Sol), 100 Agent Bundle
CSA-B25-DTOP-K9	Cisco Security Desktop Agent (Win + Sol), 25 Agent Bundle
CSA-B100-DTOP-K9	Cisco Security Desktop Agent (Win + Sol), 100 Agent Bundle
CSA-B250-DTOP-K9	Cisco Security Desktop Agent (Win + Sol), 250 Agent Bundle
CSA-B500-DTOP-K9	Cisco Security Desktop Agent (Win + Sol), 500 Agent Bundle
CSA-B500-SRVR-K9	Cisco Security Server Agent (Win + Sol), 500 Agent Bundle
CSA-B1000-DTOP-K9	Cisco Security Desktop Agent (Win + Sol), 1000 Agent Bundle
CSA-B5000-DTOP-K9	Cisco Security Desktop Agent (Win + Sol), 5000 Agent Bundle
CSA-PROFILER-K9	Cisco Security Agent Profiler



Note

Export Considerations: The Cisco Security Agent is subject to export controls. Please refer to the export compliance website at <http://www.cisco.com/wwl/export/crypto> for guidance. For specific export questions, please contact export@cisco.com.

For More Information

See the Cisco Security Agent Website: <http://www.cisco.com/go/csa>

Cisco Security Auditor

The Cisco Security Auditor is a software solution that extends Cisco’s portfolio of lifecycle security management products. Privacy mandates, improved network availability and security assurance demands drive the need for security compliance auditing. Cisco Security Auditor provides customers with new levels of security assurance enabling them to cost-effectively audit their network infrastructure against corporate security policies and industry best practices.

The automated auditing capabilities of the software allow customers to eliminate costly manual auditing operations for large scale networks, drastically reducing the time required to perform an audit. Cisco Security Auditor also provides security improvement recommendations and reporting simplifying the process of addressing network security vulnerabilities. This allows management operations to effectively manage the risks related to their network. The result is a powerful software solution that ensures organizational security compliance and network availability, while increasing productivity and overall return on investment.

When to Sell

Sell This Product Cisco Security Auditor

When a Customer Needs These Features

- Scalable, automated auditing capabilities
- Best-practice guidelines gathered from industry standards (NSA, SAFE, CIS) for security compliance auditing
- Assistance to meet organizational regulatory compliance for standards such as Sarbanes-Oxley and HIPAA
- Cisco security customers that are looking for security assurance and improved network availability

Key Features

- Built-in security best practices, including National Security Agency (NSA), SAFE Blueprint from Cisco, and Center for Internet Security (CIS) best security practice guidelines
- Integrated custom corporate security policies providing maximum flexibility
- Weighted security policy to reflect varied importance of corporate enforced policies
- Scalable and intuitive automatic auditing process management to eliminate the error-prone and time-consuming manual process
- Audit-compliance scores for easy and quick view of a complex security network; Audit-detail reports providing insight into current network security deployment; Audit security-policy reports to measure compliancy with best practices
- Detailed security-enhancement recommendations to efficiently protect network resources
- Security-improvement trending analysis to monitor the ongoing security performance of a network

Competitive Products

- IESE Crocodile
- Router Audit Tool (RAT)

Specifications

Feature	Cisco Security Auditor
Component	Recommendation
System Hardware	IBM PC-compatible system with 1 GHz or faster Pentium processor, Color monitor, CD-ROM drive
Memory (RAM)	2 GB
Disk Space	20 GB (depending on the data amount); Paging file space equal to double the amount of memory (RAM); New Technology File System (NTFS) file system required for secure operation; Cisco does not recommend installing the product on a File Allocation Tables (FAT) file system; Minimum 1024 MB swap space
System Software	Windows 2000 Professional with Service Pack 3 (SP3) or SP4; Windows 2000 Server with SP3 or SP4; Windows 2000 Advanced Server with SP3 and SP4; Windows 2003 Server Standard Edition; Windows 2003 Server Enterprise Edition;
Supported Web Browsers	Microsoft Internet Explorer 6.0.26 and Microsoft Internet Explorer 6.0.28; Netscape Navigator 7.1; Mozilla 1.7.1

Selected Part Numbers and Ordering Information

Part Number	Description
CSAU1.0-BASE25-K9	Cisco Security Auditor 1.0 base package for auditing up to 25 Cisco network devices
CSAU1.0-ADD25	Cisco Security Auditor 1.0 add-on 25-device license for each additional 25 devices audited
CSAU1.0-ADD100	Cisco Security Auditor 1.0 add-on 100-device license for each additional 100 devices audited
CSAU1.0-ADD500	Cisco Security Auditor 1.0 add-on 500-device license for each additional 500 devices audited
CSAU1.0-ADD1000	Cisco Security Auditor 1.0 add-on 1000-device license for each additional 1000 devices audited



Note

Export Considerations: The Cisco Security Auditor is subject to export controls. Please refer to the export compliance website at <http://www.cisco.com/wwl/export/crypto> for guidance. For specific export questions, please contact export@cisco.com.

For More Information

See the Cisco Security Auditor Website:

<http://www.cisco.com/en/US/products/ps6263/index.html>

Cisco Secure Access Control Server (ACS) for Windows

Cisco Secure Access Control Server (ACS) is a highly scalable, high-performance access control server that provides a comprehensive identity networking solution and is an important component of the Cisco Identity-Based Networking Services (IBNS) architecture. It extends access security by combining authentication, user or administrator access, and policy control from a centralized identity networking framework. This allows enterprise networks to have greater flexibility and mobility, increased security, and user productivity gains. Cisco Secure ACS supports a wide array of access connection types, including wired and wireless LAN, dialup, broadband, content, storage, VoIP, firewalls, and VPNs. Cisco Secure ACS is also an important component of Cisco Network Admission Control.

When to Sell

Sell This Product
Cisco Secure Access Control Server (ACS) for Windows

When a Customer Needs These Features

- Centrally manage who can log in to the network from wired or wireless connections
- Privileges each user has in the network
- Accounting information recorded in terms of security audits or account billing
- What access and command controls are enabled for each configuration administrator
- Virtual VSA for Aironet rekey
- Secure server authentication and encryption
- Simplified firewall access and control through Dynamic Port Assignment
- Same User AAA services

Key Features

- Cisco NAC Phase 2 support
- Profile-based policies
- Scale and performance improvements, with the introduction of a standards-based RDBMS as the internal repository
- Extensible Authentication Protocol-Flexible Authentication via Secure Tunneling (EAP-FAST) support for wireless authentication
- Performance improvements in Certification Revocation List (CRL) comparison for EAP-Transport Layer Security (EAP-TLS) authentication
- Exception lists to machine access restriction, complementing 802.1X machine authentication
- Replication enhancements that allowing more granular replication selections

Competitive Products

- Funk: Steel Belted RADIUS
- Lucent/Avaya: Security Management Server (LSMS)
- Nortel: Preside RADIUS Server (OEM of Funk product)

Specifications

Feature	Cisco Secure Access Control Server (ACS) for Windows
Hardware	• Pentium IV processor, 1.8 GHz or faster • Minimum 1 GB RAM • 250 MB free disk space • Minimum resolution of 800 x 600 with 256 colors

Selected Part Numbers and Ordering Information¹

Cisco Secure Access Control Server (ACS) for Windows

CSACS-4.0-WIN-K9	Cisco Secure ACS for Windows 4.0
CSACS-4.0-WINUP-K9	Upgrade to Cisco Secure ACS 4.0 for Windows from versions 1.x, 2.x, 3.x, and Cisco Secure ACS for UNIX 2.x

1. This is only a small subset of all parts available via URL listed under “For More Information”. Some parts have restricted access or are not available through distribution channels. Resellers: For latest part number and pricing info, see the *Distribution Product Reference Guide* at: <http://www.cisco.com/dprg> (limited country availability).

For More Information

See the Cisco Secure ACS for Windows Website: <http://www.cisco.com/go/acs>

Cisco Secure Access Control Solution Engine

The Cisco Secure ACS Solution Engine is a highly secure, OS-independent, and dedicated platform that offers a highly manageable access control solution with an increasingly reduced setup and troubleshooting time. It provides plug-and-play deployment, a highly reliable authentication, authorization, and accounting (AAA) solution, and increased total cost of ownership (TCO) protection. A Cisco Secure ACS remote agent is available with each Cisco Secure ACS Solution Engine to enable remote logging and Windows authentication.

When to Sell

Sell This Product Cisco Secure Access Control Solution Engine

When a Customer Needs These Features

- Need a dedicated, security-hardened, application-specific appliance package
- Simplified day-to-day management with overall reliability and security of the Cisco Secure ACS service
- Suitable alternative for Cisco Secure ACS UNIX customers not willing to install or manage Cisco Secure ACS on the Windows OS

Key Features

- Dedicated to run only the Cisco Secure ACS service preventing any appliance-based OS changes, additions, or configuration modifications
- A serial console interface is provided for initial configuration, subsequent management of IP connections, access to the Cisco Secure ACS HTML interface, and applying upgrade and recovery procedures
- Solution Engine-specific management tools provide generic appliance management capabilities including backup, recovery, software upgrades, monitoring, maintenance, and troubleshooting functions
- Provides authentication against Windows domains and remote logging capabilities of user accounting records
- A packet-filtering service to block traffic on all but the necessary Cisco Secure ACS-specific TCP and User Datagram Protocol ports
- Preinstalled, standalone Cisco Security Agent helps protect Cisco Secure ACS Solution Engine from day-zero attacks
- Built-in NTP functions to maintain network timing synchronization and consistency with other Cisco Secure ACS appliances or network devices

Specifications

Feature	Cisco Secure Access Control Solution Engine ¹
Processor speed	Pentium IV, 3.2 GHz
Memory	1 GB RAM
Hard Drive	80 GB free disk space
Interfaces	2 built-in 10/100 Ethernet controllers and 1 floppy disk drive

1. Specific to Cisco ACS Solution Engine. Additional features are found under Cisco Secure Access Control Server (ACS) for Windows, page 5-22

Selected Part Numbers and Ordering Information¹

Cisco Secure ACS Solution Engine

CSACSE-1112-K9	Cisco Secure ACS 3.3 Solution; includes HW and SW
CSACSE-1112-UP-K9	Upg. for ACS 3.X open server or 1111 to Cisco 1112 w/ACS 3.3
CSACSE-APR05MR-K9	Minor Release update for Cisco Secure Access Control Solution Engine- 3.3.3 software update -April 2005 – Customers that do not have a SAS support contract

1. This is only a small subset of all parts available via URL listed under “For More Information”. Resellers: For latest part number and pricing info, see the *Distribution Product Reference Guide* at: <http://www.cisco.com/dprg> (limited country availability).

For More Information

See the Cisco Secure ACS Solution Engine Website:

<http://www.cisco.com/en/US/products/sw/secursw/ps5338/index.html>

Cisco Guard Appliance



The Cisco Guard XT 5650 DDoS Mitigation Appliance from Cisco Systems delivers a powerful and extensive distributed denial-of-service (DDoS) protection system. It defends against the widest range of DDoS attacks that are composed of legitimate-appearing requests, massive numbers of “zombies” and spoofed identities that make it extremely difficult to identify and block, enabling companies to conduct business without compromising their mission-critical and revenue-bearing operations. Based on a unique multi-verification process (MVP) architecture, the Cisco Guard XT employs the most advanced anomaly recognition, source verification, and anti-spoofing technologies to identify and block individual attack flows while allowing legitimate transactions to pass.

Combined with the Cisco Guard XT, the Cisco Traffic Anomaly Detector XT detects, diverts, isolates, and removes malicious attack flows without impacting legitimate transactions, helping to deliver robust protection to networks and business-critical traffic. It utilizes the latest behavioral analysis and attack recognition technology to proactively detect and identify all types of cyber assaults. By constantly monitoring traffic destined for a protected device, such as a Web or e-commerce application server, the Cisco Traffic Anomaly Detector XT compiles detailed profiles that indicate how individual devices behave under “normal” operating conditions. If it detects any per-flow deviations from the profile, it considers the anomalous behavior of a potential attack and responds based on user preference—by sending an operator alert to initiate a manual response, by triggering an existing management system, or by launching the Cisco Guard XT DDoS Mitigation Appliance to immediately begin mitigation services.

When to Sell

Sell This Product
Cisco Guard Appliance

When a Customer Needs These Features

- To protect their data center, network infrastructure and last mile bandwidth from DDoS attacks
- Multi-gigabit protection for large enterprise, Service Provider deployments
- Protection from broadest range of spoofed, non-spoofed and zombie attacks

Key Features

- Featuring two Gigabit Ethernet interfaces, a single Cisco Guard XT can process attack traffic at line rates as high as a full Gbps; Working together, multiple Cisco Guard XTs can incrementally scale to support multi-gigabit rates, delivering an extensible solution that easily adapts to large and growing enterprise environments
- Intuitive GUI and extensive multilevel monitoring with reporting designed to provide a comprehensive overview of all attack activity
- Available as a service module for the Cisco Catalyst 6500 Series switches and Cisco 7600 series routers; Supports the same feature set as the appliance
- Protect web servers, email servers, DNS servers and other network resources from DDoS attacks
- Provides industry-leading protection from broadest range of DDoS attacks
- Line rate 1 gigabit-per-second processing of attack traffic
- “Day Zero” protection from anomaly based attacks

Competitive Products

- Cloudshield: CS-2000
- Arbor networks: DoS

Specifications

Feature	Cisco Guard Appliance
Memory	2 GB DDRAM
Hard Drive	80 GB

Feature	Cisco Guard Appliance
Interfaces	Two Gigabit Ethernet; Two 100BASE-T (management)
Power Supply	Dual 110-220V, 350W
Weight	62 lb /28.2 Kg
Height	3.36 in. / 8.53 cm
Width	17.5 in. / 44.5 cm
Depth	27.5 in. / 69.9 cm
Rack-mountable	Yes
Management	Secure Web-based GUI; CLI: Console, Telnet, SSH; Cisco (Riverhead) SNMP MIB and MIB II; TACACS+; Syslog
Certifications	UL recognized; CE; FCC Rules Part 15 compliant
Attack Protection	Spoofed and Non-spoofed Attacks; TCP (syns, syn-acks, acks, fins, fragments); UDP (random port floods, fragments); ICMP (unreachable, echo, fragments); DNS; Client Attacks; Inactive and total connections; HTTP Get flood; BGP Attacks

Selected Part Numbers and Ordering Information¹

Cisco Guard Appliance

AGXT-5650-MMF-A-K9	Cisco Guard XT 5650 with 1000BASE-SX Multimode Fiber Optic Ports with LC Connectors, Dual AC Power, RAID
SC-AGXT-5.0-K9	Cisco Traffic Anomaly Guard XT Appliance 5.0 SW
WS-SVC-AGM-1-K9	Cisco Catalyst6500/Cisco 7600 Router Anomaly Guard Module
c6svc-agm-k9.5.0-3.bin	Anomaly Guard Module R5.0 Software

Cisco Traffic Anomaly Detector

ADXT-5600-MMF-A-K9	Cisco Traffic Anomaly Detector XT 5600 with 1000BASE-SX Multi; Mode Fiber Optic Ports with LC Connectors, Dual AC Power, RAID
SC-ADXT-5.0-K9	Cisco Traffic Anomaly Detector XT Appliance 5.0 SW
WS-SVC-ADM-1-K9	Cisco Catalyst 6500/Cisco 7600 Router Traffic Anomaly Detector Module
SC-ADM-5.0-K9=	Cisco Traffic Anomaly Detector Service Module 5.0 SW

1. This is only a small subset of all parts available via URL listed under "For More Information". Some parts have restricted access or are not available through distribution channels. Resellers: For latest part number and pricing info, see the *Distribution Product Reference Guide* at: <http://www.cisco.com/dprg> (limited country availability).

For More Information

See the Cisco Guard Appliance Website: <http://www.cisco.com/go/guard>

See the Cisco Traffic Anomaly Detector Appliance Website:

<http://www.cisco.com/go/detector>

Cisco Router and Security Device Manager

Cisco Router and Security Device Manager (SDM) is an intuitive Web-based device-management tool for Cisco IOS Software based routers that can improve the productivity of network managers, simplify router deployments, and help troubleshoot complex network and VPN connectivity issues. Cisco SDM supports a wide range of Cisco IOS Software releases and is available free of charge on Cisco router models from Cisco SB 100, Cisco 830 Series to Cisco 7301. It ships preinstalled on all new Cisco 850 Series, Cisco 870 Series, Cisco 1800 Series, Cisco 2800 Series, and Cisco 3800 Series integrated services routers. Network and security administrators and channel partners can use Cisco SDM for faster and easier deployment of Cisco routers for integrated services such as dynamic routing, WAN access, WLAN, firewall, VPN, IPS, and QoS.

When to Sell

Sell This Product When a Customer Needs These Features

Cisco Router and Security Device Manager

- Cisco SDM is a valuable productivity-enhancing tool for businesses and channel partners and allows them to implement router security and network configurations with reduced cost and increased confidence and ease.
- Pilots and Proof of Concept
- Cisco Router Initial Deployment
- Cisco IOS Services Management and Security Solutions Deployment
- Partial CPE Control to End User (with role based access)
- Cisco Router Operational Management (Day to Day Real Time Performance Monitoring & Troubleshooting)

Key Features

- Accelerates new feature acceptance and adoption with easy to use UI and feature wizards
- SDM Express Setup wizard for deploying fixed configuration ISR in less than 30 minutes (includes LAN, WAN, WLAN, DHCP server, firewall and auto security)
- Quickly generate standard configurations for cookie cutter deployments
- Task based SDM user interface for faster and easier configuration of security and other services
- Supported IOS features include VPN, IPS, Application Firewall, ICS, Digital Certificates, Security Audit, NAC, QoS, Wireless, NAT, Routing, DHCP, Dynamic DNS, SSH, eToken and Role based access.
- End user self installation for novice users or installation by less skilled technician
- Minimal touch mass deployment of end CPE devices
- End user self help tool for device/service troubleshooting and device recovery by NOC staff

Competitive Products

- Sonicwall
- Fortinet
- Checkpoint
- Netscreen

Specifications

Feature	Cisco Router and Security Device Manager
Router Flash Memory	Minimum of 6 MB of free Flash memory on the router for Cisco SDM files, or Minimum of 2 MB of free Flash memory on the router for Cisco SDM Express. Wireless Management file requires additional 1.7 MB. Rest of the SDM files can be installed on PC hard disk.
PC Hardware	Pentium III or later series processor
PC Operating System	Windows XP Professional; Windows 2003 Server (Standard Edition); Windows 2000 Professional; Windows NT 4.0 Workstation (Service Pack 4); Windows ME Japanese, Simplified Chinese, French, German, Spanish, and Italian language OS support Windows XP Professional Windows 2000 Professional
Browser Software	Microsoft Internet Explorer 5.5 or later; Netscape Navigator 7.1 and 7.2; Firefox 1.0.5
Java Software	Java Virtual Machine (JVM) built-in browsers required; Java plug-in (Java Runtime Environment Version 1.4.2_05 or later)

Part Numbers and Ordering Information

Cisco 831 Ethernet Broadband Router, Cisco 836 ADSL over ISDN Broadband Router, Cisco 837 ADSL Broadband Router, Cisco Small Business 100 Series, Cisco 850 Series, and Cisco 870 Series	Cisco SDM software ships by default from factory; SDM Express is factory installed on router Flash memory, and a Cisco SDM CD is bundled with the router.
Cisco 1700 Series Modular Access Routers and Cisco 2600XM Series	Cisco SDM software ships by default on security bundles; Cisco SDM software \$0 configuration option (ROUTER-SDM or ROUTER-SDM-NOCF) is available on all SKUs. Cisco SDM Express is factory installed on router Flash memory, and a Cisco SDM CD is bundled with the router.
Cisco 1800, 2800, and 3800 Series Integrated Services Routers (ISRs)	Cisco SDM software ships by default from factory Cisco SDM is factory installed on router Flash memory.
Cisco 2691 Multiservice Platform and Cisco 3700 Series Multiservice Access Routers	Cisco SDM software ships by default on security bundles (k9); Cisco SDM software \$0 configuration option (part number ROUTER-SDM or ROUTER-SDM-NOCF) is available on all SKUs; Cisco SDM is factory installed on router Flash memory.
Cisco 7204VXR, 7206VXR, and 7301 Routers	Cisco SDM software ships by default on security bundles (k9); Cisco SDM software \$0 configuration option (part number ROUTER-SDM or ROUTER-SDM-NOCF) is available on all SKUs; Cisco SDM is factory installed on router Flash memory.
Customers desiring Auto-Install feature in Cisco IOS Software	Two US\$0 SKUs are offered: ROUTER-SDM-NOCF and ROUTER-SDM-CD-NOCF. If either of these SKUs is ordered with a Cisco router, then manufacturing only loads Cisco SDM files on the router Flash memory, and the default startup configuration is not loaded in the router's NVRAM.

For More Information

See the Cisco Router and Security Device Manager Website: <http://www.cisco.com/go/sdm>

Cisco IOS® Firewall

The Cisco IOS Firewall enriches Cisco IOS Software security capabilities, integrating robust firewall functionality and intrusion prevention for every network perimeter. When combined with Cisco IOS IPSec software and other Cisco IOS Software-based technologies such as L2TP tunneling and QoS, it provides a complete, integrated virtual private network solution. Because it is available for a wide range of Cisco routers, it gives customers the flexibility to choose a solution that meets their bandwidth, LAN/WAN density, and multiservice requirements, while benefiting from advanced security.

When to Sell

Sell This Product

Cisco IOS Firewall

When a Customer Needs These Features

- An integrated stateful firewall solution with powerful security and multiprotocol routing all on the same platform
- Scalability options from the Cisco 800 up to the Cisco 7200
- Low cost solution that leverages existing infrastructure
- For secure extranet and intranet perimeters and Internet connectivity for branch and remote offices
- Secure remote access or data transfer via a Cisco IOS Software-based VPN solution
- Real-time (inline) integrated Cisco IOS IPS to complement firewall or existing IPS (Cisco Secure IPS) solutions
- Security and access to the network on a per-user basis

Key Features

- Context-based access control (CBAC) provides secure, stateful, application-based packet inspection, supporting the latest protocols and advanced applications
- Cisco IOS Inline Intrusion Prevention for real-time monitoring, interception, and response to network misuse for supporting thousands of attack signatures
- Supports URL Filtering either local on the router through exclusive domains as well as use of external Websense and N2H2 servers.
- Dynamic, per-user authentication/authorization for LAN, WAN, and VPN clients
- Authentication proxy for https, ftp and telnet connections
- Supports Cisco Router and Security Device Manager (SDM)
- Graphical configuration and management via the VPN/Security Management Solution (VMS) and the IP Solution Center (ISC)
- Provides strong perimeter security for a complete Cisco IOS Software-based VPN solution, including IPSec, QoS, and tunneling

Competitive Products

• Nortel: BaySecure Firewall-1

• Checkpoint, Nokia, Netscreen, etc

Specifications

Feature	Cisco IOS Firewall
Supported Network Interfaces	All network interfaces on supported platforms
Supported Platforms	Cisco 1720, 1800, 2600/2600XM, 2800, 3700, 3800, 7100, 7200, and 7301 series router platforms (supports full feature set) Cisco 800, UBR900, 1600, and 2500 series router platforms include all firewall features with exception of intrusion detection/prevention and authentication proxy
Simultaneous Sessions	No maximum; dependent on platform, network connection, and traffic
Cisco IOS Firewall Performance	C800 - 10Mbps; C1700: 20Mbps; Cisco 1800: 125 Mbps; C2600XM: 35Mbps; C2691-VPN: 197Mbps; Cisco 2800: 530Mbps; C3725-VPN, C3745-VPN: 197 Mbps; Cisco 3825: 855Mbps; Cisco 3845: 1 Gbps, 7200/7301 Bundles: 1Gbps

Part Numbers and Ordering Information

For Cisco IOS Images containing firewall (FW) and intrusion prevention (IPS) capabilities, see individual product pages of supported platforms and the Cisco IOS Feature Navigator at <http://www.cisco.com/go/fn> (CCO login required) for part numbers and more info.

For More Information

See the Cisco IOS Firewall Feature Set Website: <http://www.cisco.com/go/firewall>

Cisco Security Router Bundles with Integrated Network Security

The Cisco Security Router Bundles are based on the Cisco 800, 1700, 1800, 2600XM, 2691, 2800, 3700, 3800 7200 and 7301 router platforms. They include the Entry Security bundles, Enhanced Security bundles for added performance and scale, and V3PN bundles for combined Security and IPCommunications.

Key Features

- Single part number when ordering a Cisco router with all the necessary Security components at a reduced price compared to ordering each component separately
- All Security bundles come pre-installed with Router and Security Device Manager (SDM) for fast and easy deployment based on Cisco TAC and ICSA Labs recommended router security configurations
- Entry Security Bundles, Enhanced Security Bundles, and V3PN bundles allow varying capabilities and price points to meet a variety of needs
- Cisco 2800, 3700, and 3800 Series now have Advanced Security Network Modules available for ULR Filtering and hardware-based IDS
- Cisco 1700, 2600XM, 2691, 3700, 7200 and 7301 bundles include the selected router platform, a VPN hardware card, additional memory, and the Cisco IOS to run IPSec 3DES or AES encryption
- Cisco 820/830 Series, as well as 1711and 1712 offer embedded VPN acceleration

When to Sell

Sell This Product
Cisco VPN Security
Router Bundles

When a Customer Needs These Features

- Combating worms, viruses or threats from every gateway to the network (NAC, firewall, IPS)
- Deploying VPN on routers and want to have future option for VPN
- Planning to use the Internet for remote business communications (remote access VPN)
- When migrating from leased lines to VPN
- Need encryption to protect customer data (i.e HIPAA, Sarbanes-Oxley)
- Needs to integrate Voice and VPN Services (V3PN)
- Would like to integrate Security with Voice (V3PN bundles) or with Wireless routers
- Integrated Services Routers (Cisco 800, 1800, 2800, and 3800) have embedded VPN acceleration
- Corresponding Security bundles are necessary to enable the 3DES or AES encryption functionality

Specifications

Feature	Cisco VPN Security Router Bundles
All Bundles Include	Network Admission Control (NAC) Firewall with IPS; GRE and IPSec; High Availability/Failover; VPN QoS; AES in Hardware (excluding C1700 Bundles)
IPPCP Compression	Software: C800, C1800 Bundles Hardware: Cisco 1841 bundles, C2600XM, C2691-VPN, Cisco 2800 bundles, C3725-VPN, C3745-VPN, Cisco 3800, 7200, 7301 Bundles
Max Tunnel	C870 - 20, C1800: 50; Cisco 1841: 800.; Cisco 2800: 1500; Cisco 3800: 2500; 7200/7301 Bundles: 5000
Firewall Performance	C870 - 70Mbps, C1800: 100Mbps; Cisco 1841: 125 Mbps, Cisco 2800: 530Mbps; Cisco 3825: 855Mbps; Cisco 3845:1 Gbps, 7200/7301 Bundles: 1Gbps

For More Information

See Chapter 1: Routing for more details.



Content Networking

Content Networking at a Glance

Product	Features	Page
Cisco Content Engine 500 Series	- Content services edge delivery platform for Enterprise networks - Functions as edge node device in an Application and Content Networking (ACN) system - Responsible for delivery of cached or distributed content to the end-user - Enables customers to rapidly deliver strategic applications to branch personnel including web application and content acceleration, content filtering, software distribution, and business video - Lays the foundation for advanced services such as corporate communications, e-learning and business application acceleration	6-2
Cisco Content Engine 7300 Series	- Content services platform for Enterprise data center - Functions as data center node device in an Application and Content Networking (ACN) system - Offers transparent and Internet proxy caching to optimize website performance and WAN bandwidth utilization, Content/URL Filtering and AAA features for Web security and ECDN capabilities in a single platform - Accelerates both Web and streaming media content - Supports Content Distribution Manager (CDM) device mode to provide central control over acquisition and distribution of content in the ACNS network, including live video streams, video on demand, and software updates - Supports Content Router (CR) device mode to provide integrated global load balancing solution for content delivery networks	6-2
Content Engine Network Modules	- Content services edge delivery network module for 2600, 3600, 3700 branch routers - Functions as edge node device in an Application and Content Networking (ACN) system - Enables delivery of new applications and services via a Cisco branch router with no performance degradation of core routing services - Allows rapid delivery of strategic applications to branch personnel including web application and content acceleration, content filtering and business video	6-2
Cisco 11500 Series Content Services Switches (CSS)	- Provides an intelligent, distributed architecture to scale for today's e-business infrastructure - Offers Adaptive Session Redundancy (ASR)—a new industry standard in stateful failover - Delivers the greatest flexibility of any content switch in its class for customizing combinations of ports, performance, and services - Provides Server off-load service such as integrated and scalable SSL encryption and decryption along with HTTP compression	6-4
Content Switching Module (CSM) for the Catalyst 6500 Series Switches	- High performance Content Switching line card for Catalyst 6500 - L4 and L7, Firewall, VPN, Cache and Server load balancing - Intelligently balances client traffic across multiple devices - Full State and Sticky State redundancy; Full Regular Expression support	6-5
Cisco SSL Module for Catalyst 6500	- Offloads SSL encryption and decryption - Scalable performance - Stickiness	6-6
Cisco DistributedDirector	- Solves distributed server site selection problems. Enables a set of distributed servers to be 6-7 seen as a single virtual server - Uses DNS to redirect a client to the best site on the Internet based on a variety of options - Configurable as authoritative DNS caching name server and/or HTTP Session Redirector on a per-domain basis	6-7
Cisco GSS 4491 Global Site Selector	- Delivers global load balancing for multiple data centers - Offloads DNS servers by doing DNS resolution - Scales to support hundreds of data centers or server load balancers (SLBs) - Supports up to 20,000 DNS request per second - Delivers a unique DNS-based localization and persistence services	6-8
Product Ordering Website	To place an order, visit the Cisco Ordering Website: http://www.cisco.com/en/US/ordering/index.shtml	

Content Networking Overview

Cisco Content Networking solutions are designed to optimize the delivery of content to end users. To accomplish this, Cisco offers solutions for both data center and edge delivery with industry-leading products in both categories.

In the data center, Cisco Content Switching, or L4-7 Switching, solutions optimizes a network to dynamically enable faster responses to Web requests and decrease network bandwidth congestion. Content switching, or intelligent load balancing, insures high levels of content availability and security, and leverages investment in Cisco IP infrastructure.

Cisco's Application and ACN System allows enterprises to accelerate mission critical web applications such as Siebel and SAP, block viruses and inappropriate websites and deliver business video, while laying the foundation for advanced services such as e-learning and corporate communications.

Cisco Content Engines (CE)

Within Cisco's content-networking solutions portfolio, the Cisco ACNS Software enables a variety of services that optimize delivery of Web applications and content to the network edge to ensure enhanced speed, availability, and performance for users. ACNS Software combines the technologies of transparent caching and enterprise content-delivery network (ECDN) for accelerated delivery of Web objects, files, and streaming media from a single intelligent appliance, Cisco CE.



The Cisco ECDN solution provides a platform that delivers immediate benefits from entry-level applications such as content and business application acceleration and URL filtering, while laying the foundation for advanced services such as business video and e-learning.

When to Sell

Sell This Product

Content Engine 7325A

Content Engine 7305A

Content Engine 566

Content Engine 511

Content Engine Network Modules

When a Customer Needs These Features

- Ultra high-end Content Engine platform for delivering business video streaming, Web application acceleration, software distribution and Intra/Internet Web proxy and security applications to the enterprise datacenter.
- High-end Content Engine platform for delivering the ACNS capabilities and business applications to the enterprise datacenter or very large branch/office locations. Also supports the CDM and CR devices modes of ACNS in the datacenter.
- Mid-range Content Engine ideal for delivering the ACNS capabilities and business applications to larger branch offices. Also supports the CDM and CR device modes of ACNS in the datacenter.
- Entry-level Content Engine for delivering the ACNS capabilities and business applications into small to moderate size branch offices.
- Router-integrated caching and content delivery network modules for 2600, 3600, 3700 and 3800 Series branch access routers

Key Features

- **Video Distribution and Streaming**—Enables intelligent distribution of both live and on-demand video content making best use of existing WAN bandwidth preventing bottlenecks. Supports popular video streaming formats and is easily integrated with 3rd party business video creation, management and publishing applications via APIs to provide end-to-end business video solutions.
- **Caching/Web Application Acceleration**—Provides accelerated content delivery, improved performance of web-based business applications, WAN bandwidth cost savings, and protection vs. uncontrollable bottlenecks
- **Software Distribution**—Content Distribution features of ACNS can be leveraged to scale the distribution of software updates throughout the enterprise network helping to alleviate impact on WAN.

- Content Security and Filtering—Enables administrators to enforce Web access policies with existing AAA services (including NTLM and LDAP/AD) as well as block, monitor, and report on end users’ access to non-business and objectionable content via URL filtering. Supports both Secure Computing’s Smartfilter and Websense’s URL filtering solutions “on-box.” Other URL filtering and virus scanning servers can also be leveraged via the ICAP protocol.

Competitive Products

- Blue Coat: Blue Coat Server Accelerator 700 and 7000 Series and Blue Coat Systems Director
- Network Appliance: NetCache C1200/2100/6100 Series Appliances and Content Director
- Volera: Excelerator, Media Excelerator, Secure Excelerator

Specifications

Feature	7325A	7305A	566	511	Network Module	SA-7340
Supported Interfaces	Two 10/100/1000BASE-T X	Two 10/100/1000BASE-T X	Two 10/100/1000BASE-T X	Two 10/100/1000BASE-T X	One internal 10/100-Mbps Ethernet to router backplane; one external 10/100-Mbps Ethernet	
SDRAM	4 GB	2 GB	1 GB	512 MB	Up to 512 MB	
Max Storage	1,440 GB; U320 SCSI	936 GB; U320 SCSI	396 GB; U320 SCSI	160 GB; SATA	80 GB; IDE	1,008 GB; U320 SCSI
Maximum Internal Storage	432 GB; U320 SCSI	432 GB; U320 SCSI	144 GB; U320 SCSI	160 GB; SATA	40 GB or 80 GB; IDE	1,008 GB; U320 SCSI
Flash Memory	128 MB	128 MB	128 MB	128 MB	16 MB internal; optional Compact Flash Memory	
Storage Array Support	Yes	Yes	Yes ¹	No	No	
Rack Units	2 RU	2 RU	1 RU	1 RU	N/A	3 RU
Dimensions (HxWxD)	3.36 x 17.46 x 27.48 in	3.36 x 17.46 x 27.48 in.	1.72 x 17.3 x 20 in.	1.72 x 17.3 x 20 in.	One slot in 2600/2800/3700/3800 chassis	5.0 x 17.5 x 21.8 in
Max. Weight	62 lb.	62 lb.	28 lb.	28 lb.	1.5 lb.	82 lb.
Power	Hot-swappable redundant AC or DC	Hot-swappable redundant AC or DC	300W AC	300W AC	From chassis	500W AC

1. 7-Disk Default SA-7340 Configuration only

Selected Part Numbers and Ordering Information¹

Cisco Content Engine 7300 Series Hardware

- CE-7325A-K9 Content Engine 7325A AC Power, ACNS software
- CE-7305A-K9 Content Engine 7305A AC Power, ACNS software. Also runs as CDM or CR

Cisco Content Engine 500 Series Hardware

- CE-566-144G-K9 Cisco Content Engine 566, AC Power, ACNS software. Also runs as CDM or CR
- CE-511-K9 Cisco Content Engine 511 AC Power, ACNS software

Cisco Storage Array 7340

- SA-7340 Cisco Storage Array 7340, (7) 72 GB drives, AC power

Cisco Content Engine Network Module Hardware

- NM-CE-BP-40G-K9= Content Engine Network Module, basic performance, 20-GB IDE hard disk
- NM-CE-BP-80G-K9= Content Engine Network Module, basic performance, 40-GB IDE hard disk

1. This is only a small subset of all parts available via URL listed under “For More Information.”

For More Information

See the Cisco Content Engine Website:

<http://cisco.com/en/US/products/sw/conntsw/ps491/index.html>

Cisco CSS 11500 Series Content Services Switches



The Cisco CSS 11500 Series Content Services Switch is suitable for both enterprises and service providers seeking to reduce data center costs, boost e-business application performance, offer enhanced services, ensure online transaction integrity, and provide the best possible online experience for customers, business partners, and internal workers.

The Cisco CSS 11500 is available in as the standalone Cisco CSS 11501, the three-slot Cisco CSS 11503 and the six-slot Cisco CSS 11506.

When to Sell

Sell This Product

CSS 11501/ CSS 11501S

When a Customer Needs These Features

- Standalone, fixed-configuration switching platform with up to 8 Fast Ethernet ports and 1 optional Gigabit Ethernet port
- Cost-effective server, cache, and firewall load balancing
- Complex Web applications requiring high-level URL and cookie switching
- Server off-load feature such as integrated SSL encryption and decryption along with HTTP compression (11501S-C only)

CSS 11503

- Compact, high-performance, modular content switching platform with up to 32 Fast Ethernet ports or up to six Gigabit Ethernet ports
- Cost-effective server, cache, and firewall load balancing
- Server off-load feature such as integrated SSL encryption and decryption along with HTTP compression
- Complex Web applications requiring high-level URL and cookie switching

CSS 11506

- Compact, high-performance, modular content switching platform with up to 32 Fast Ethernet ports or up to six Gigabit Ethernet ports
- Cost-effective server, cache, and firewall load balancing
- Server off-load feature such as integrated SSL encryption and decryption along with HTTP compression
- Complex Web applications requiring high-level URL and cookie switching

Key Features

- Introduces an intelligent, distributed architecture
- Improves site availability and transaction integrity by introducing ASR
- Delivers customized combinations of ports, performance, and services
- Server off-loads through support of an integrated, high-capacity SSL module along with HTTP compression (WebNS 8.10)—Enables content switching functionality
- Protects investment by enabling upgrades of performance, ports, and services through modularity

Competitive Products

- Alteon/Nortel: ACEdirector and 700 Series
- F5 Networks: Big/IP and LAN switch Partners
- Foundry Networks: ServerIron
- Radware: Web Server Director (WSD)
- Resonate: Central Dispatch and Global Dispatch

Specifications

Feature	Cisco CSS 11501	Cisco CSS 11503	Cisco CSS 11506
Modular Slots	N/A	3	6
Base Configuration	Switch Control with 8 10/100 Ethernet; 1 GBIC port	Switch Control Module; 2 Gigabit Ethernet (GBIC) ports	Switch Control Module; 2 Gigabit Ethernet (GBIC) ports
Max GB Ethernet Ports	1	6	12
Max 10/100 Ethernet ports	8	32	80
2-port GB Ethernet I/O Module		Max: 2	Max: 5
16-port GB Ethernet I/O Module		Max: 2	Max: 5
8-port GB Ethernet I/O Module		Max: 2	Max: 5
SSL Module and HTTP Compression	CSS 11501S only	Max: 2	Max: 5
Session Accelerator modules	CSS 11501S only	Max: 2	Max: 5
Redundancy features	Active-active Layer 5 ASR Virtual IP Address (VIP) redundancy	Active-active Layer 5 ASR VIP redundancy	Active-active Layer 5; ASR; VIP redundancy; Active-standby SCM; Redundant switch fabric module; Redundant power supplies

Feature	Cisco CSS 11501	Cisco CSS 11503	Cisco CSS 11506
Height	1/75 in. (1 rack unit)	3.5" (2 rack units)	8.75" (5 rack units)
Bandwidth	Aggregate 6 Gbps	Aggregate 20 Gbps	Aggregate 40 Gbps
Storage	512 MB hard disk or 256 MB Flash disk	512-MB hard disk or 256-MB Flash memory disk	512-MB hard disk or 256-MB Flash memory disk
Power	Integrated AC supply	Integrated AC or DC	Up to 3 AC or 3 DC

Selected Part Numbers and Ordering Information¹

Cisco CSS 11500 Series Content Services Switches

CSS11506-2AC	Cisco 11506 Content Services Switch including SCM with 2 Gigabit Ethernet ports, hard disk, 2 switch modules, 2 AC power supplies, and a fan (requires SFP GBICs)
CSS11506-2DC	Cisco 11506 Content Services Switch including SCM with 2 Gigabit Ethernet ports, hard disk, 2 switch modules, 2 DC power supplies, and a fan (requires SFP GBICs)
CSS11503-AC	Cisco 11503 Content Services Switch including SCM with 2 Gigabit Ethernet ports, hard disk, and integrated AC power supply, integrated fan, and integrated switch module (requires SFP GBICs)
CSS11503-DC	Cisco 11503 Content Services Switch including SCM with 2 Gigabit Ethernet ports, hard disk, and integrated DC power supply, integrated fan, and integrated switch module (requires SFP GBICs)
CSS5-SCM-2GE	Cisco CSS 11500 System Control Module with 2 Gigabit Ethernet ports and hard disk (requires SFP GBICs)
CSS5-IOM-8FE	Cisco CSS 11500 Fast Ethernet I/O Module: 8-port TX
CSS5-IOM-16FE	Cisco CSS 11500 Fast Ethernet I/O Module: 16-port TX
CSS5-IOM-2GE	Cisco CSS 11500 Gigabit Ethernet I/O Module: 2-port (requires SFP GBICs)
CSS5-SAM	Cisco CSS 11500 Session Accelerator Module
CSS5-SSL-C	Cisco CSS 11500 SSL and HTTP Compression Module
CSS11501S-C-K9	Cisco CSS 11501 Content Services Switch-8 Fast Ethernet, hard disk, AC with integrated SSL and HTTP compression
CSS11501	Cisco CSS 11501 Content Services Switch-8 Fast Ethernet, hard disk, AC

1. This is only a small subset of all parts available via URL listed under "For More Information". Some parts have restricted access or are not available through distribution channels. Resellers: For latest part number and pricing info, see the *Distribution Product Reference Guide* at: <http://www.cisco.com/dprg> (limited country availability).

For More Information

See the CSS 11500 Series Website: <http://www.cisco.com/go/11500>

Cisco Content Switching Module (CSM)

The Cisco CSM is a Catalyst 6500 line card that balances client traffic to farms of servers, firewalls, SSL devices, or VPN termination devices. The CSM provides a high-performance, cost-effective load balancing solution for enterprise and ISP networks. The CSM meets the demands of high-speed Content Delivery Networks, tracking network sessions and server load conditions in real time and directing each session to the most appropriate server. Fault tolerant CSM configurations maintain full state information and provide true hitless failover required for mission-critical functions.

When to Sell

Sell This Product

Cisco Content Switching Module

When a Customer Needs These Features

- A high performance, L4 to L7 load balancing solution integrated with Cisco's Catalyst 6500
- Load balancing for the highest traffic sights
- Support for up to 1,000,000 concurrent TCP connections

Key Features

- Establishes up to 150,000 Layer 4 connections per second and provides high-speed content switching, while maintaining 1 million concurrent connections
- Outstanding price/performance value for large data centers and ISPs—Features a low connection cost and occupies a small footprint. The CSM slides into a slot in a new or existing Catalyst 6500 enabling all its ports for layer 4 through layer 7 content switching. Multiple CSMs can be installed in the same Catalyst 6500 for redundancy and scalable performance

- Uses the same Cisco IOS Command Line Interface (CLI) that is used to configure the Catalyst 6500 Switch

Competitive Products

- Alteon/Nortel: Web Switching Module, Application Switch, and Web Switches
- Foundry Networks: ServerIron
- Radware: Web Server Director (WSD)
- Resonate: Central Dispatch and Global Dispatch
- F5 Networks: Big/IP

Specifications

Feature	Cisco Content Switching Module (CSM)
Configuration Limits	512 total VLANs (client and server); 4000 virtual servers; 4000 server farms; 16,000 real servers; 4000 probes; 16,000 access control list (ACL) items
Connections	1,000,000 concurrent TCP connections 150,000 connection setups per second-Layer 4 75,000 connection setups per second-Layer 7
Throughput	4 Gigabits-per-second total combined (client-to-server and server-to-client) throughput 1.25 million packets per second
Catalyst Switch Platform Requirements	Native support (switch running Cisco IOS Software only) Hybrid Support (switch running IOS/CatOS) Functions as a bus enabled line card-not fabric enabled Multilayer switch feature card-MSFC or MSFC2

Selected Part Numbers and Ordering Information¹

Cisco Content Switching Module
WS-X6066-SLB-APC Catalyst 6500 Content Switching Module

For More Information

See the Cisco Content Switching Module (CSM) Website at: <http://www.cisco.com/go/csm>

Cisco SSL Module for Catalyst 6500

The SSL Services Module is an integrated service module for the Cisco Catalyst 6500 Series that offloads the processor-intensive tasks related to securing traffic with SSL and increases the number of secure connections supported by a website.

When to Sell

Sell This Product

When a Customer Needs These Features

- SSL Module for Catalyst 6500
- An integrated SSL encryption/decryption solution featuring Cisco's Catalyst 6500
 - Scalable SSL processing: 2,500 connection setups/second per module-10,000 per Chassis fully-populated with SSL modules

Key Features

- Server SSL offload—performs all SSL-related tasks, allowing servers to handle high-speed clear text traffic
- Scalable performance—provides a simple means of addressing increased performance requirements by installing additional SSL modules in a Catalyst 6500 switch
- Persistent—maintains persistence even when clients request new session IDs, in Integrated Mode with CSM
- Certificate optimization—provides cost savings by requiring only a single certificate copy vs. a copy for each server subject to customer and certificate authority agreement

Competitive Products

- F5 Networks eCommerce 540
- Nortel/Alteon iSD 410 SSL Accelerator

Specifications

Feature	Cisco SSL Module for Catalyst 6500
System Capacity and Performance	2500 connection setups/sec per module-10K per chassis; 60K concurrent client connections-240K per chassis; 300 Mbps bulk rate encryption-1.2 Gbps per chassis; 256 key pairs; 256 key certificates; Up to 2K key sizes-256 proxy servers
Scalability	Up to four SSL modules in the same Catalyst 6500
Integration with Server Load Balancing	Tightly integrated in the Cisco Catalyst 6500 Switch with the CSM

Selected Part Numbers and Ordering Information¹

Cisco SSL Module for Catalyst 6500	
WS-SVC-SSL-1-K9=	Cisco SSL Module for Catalyst 6500

For More Information

See the Catalyst 6500 Series Website at: <http://www.cisco.com/go/cat6500>

Cisco DistributedDirector¹

DistributedDirector provides dynamic, transparent, and scalable Internet traffic load distribution between multiple geographically-dispersed servers. DistributedDirector is a global Internet service-scaling solution that utilizes Cisco IOS software and leverages routing table information, delay characteristics, and other information to make “network intelligent” load distribution and site selection decisions.

DistributedDirector transparently redirects end-user service requests to the closest responsive server, which increases access performance and reduces transmission costs. Users need only a single subdomain name or URL-embedded hostname for accessing a distributed set of servers, thus providing the appearance of a single virtual server.

When to Sell

Sell This Product	When a Customer Needs These Features
Cisco Distributed Director	• Load distribution across geographically/topologically dispersed TCP/IP servers • High availability for dispersed mission-critical applications • Data center redundancy and failover

Key Features

- Transparent distribution of all IP Services (TCP and UDP), including HTTP, FTP, Telnet, and Gopher; provides global scalability for all IP-based network services
- Improves access performance by redirecting to the topologically closest server
- Calculates client-to-server round-trip times in real time; redirects clients to server with lowest client-to-server link latency, maximizing end-to-end performance
- Redirects clients only to responsive servers, resulting in maximized availability
- Cisco IOS Software & standard CLI for device configuration
- Transparently add and remove distributed servers, simplifying maintenance
- Supports multiple domains; cost-effective IP service scalability solution

1. DistributedDirector is available in Cisco IOS software for 2600/2600XM, 3600, and 7200 series routers, starting on release 12.2(4)T Enterprise Plus feature sets; Dedicated routers may be recommended for DistributedDirector to meet performance targets of both routing and load balancing; If no dedicated hardware platform is available for running DistributedDirector, it is recommended customers use the Configurable DD Cache feature (available in 12.2(8)T) to limit the memory DistributedDirector may consume for DNS caching; To take advantage of enhanced caching capabilities, routers should be configured with additional DRAM (128MB or more)

Competitive Products

- Alteon Networks: ACEdirector and Web Switches with WebOS GLSB
 - F5 Labs: 3DNS
 - Foundry Networks: ServerIron Switch with Internet IronWare
- Resonate, Inc.: Global Dispatch
 - RND Networks, Inc.: Web Server Director - Network Proximity (WSD-NP)

For More Information

See the DistributedDirector Website at <http://www.cisco.com/go/dd>

Cisco GSS 4491 Global Site Selector

The Cisco GSS 4491 is a networking product that globally load balances distributed data centers. The Cisco GSS 4491 acts as the cornerstone of multisite disaster recovery plans in deployments of Cisco’s market-leading content switches. Customers deploying new Cisco content switches such as the Cisco CSS 11500 Content Services Switch and the CSM for the Cisco Catalyst 6500 Series switches or have already deployed legacy switches such as the Cisco CSS 11000 and Cisco Local Directors can benefit from the new levels of traffic management and centralized command and control provided by the Cisco GSS 4491.

Key Features

- Provides resilient architecture critical for disaster recovery and multisite Web applications deployments
- Offers flexible heterogeneous support for all Cisco SLBs and DNS-capable networking products
- Provides centralized command and control of DNS resolution process for direct and precise control of global load-balancing process
- Offers site persistence for e-commerce applications
- Offers a unique DNS race feature-The Cisco GSS 4491 can in real time direct content consumers to the closest data center
- Supports a Web-based GUI and DNS wizard to simplify the DNS command and control

Competitive Products

- F5 Networks 3DNS
- Nortel/Alteon Content Director

Specifications

Feature	Cisco GSS 4491
Number of Ports	Two 10/100/1000Base TX Ports
Port Description	Network Ports: Two 10/100Base TX; Console Port
DNS requests per second	Up to 20,000, depending on configuration
Configuration Software OS Support	Windows NT 4.0; Red Hat Linux 5.0, 6.0, 6.1, 6.2
Network management	Console port-CLI Access to system via Telnet; Secure copy (SCP) or FTP; GUI-Secure HTTP (HTTPS) for Internet Explorer and Netscape Navigator
Storage	One 80-GB hard drive
Physical	One-rack unit size chassis; Network management serial portport; 1 GB RAM; Prescott 3.2-GHz CPU
Dimensions (H x W x D)	1.75 x 16.54 x 16.69 in. (44 x 424 x 430 mm)

Selected Part Numbers and Ordering Information¹

Cisco GSS 4491	
Cisco GSS 4491-K9	Global site selector
SF-GSS-V1.0-K9	SF-GSS-V1.0-K9Global site selector software

For More Information

See the Cisco GSS 4480 Website: <http://www.cisco.com/go/gss>



Broadband and Dial Access

Broadband and Dial Access Products at a Glance

Remote Dial Access—Data and Voice (VoIP)

Product	Features	Page
SS7 Signaling & Softswitch Products	- Cisco PGW 2200 Softswitch—Call Agent providing signaling and call control functionality for 7-3 PSTN Gateway and transit applications in international markets - Cisco BTS 10200 Softswitch—Class 4/5 softswitch for Voice over IP applications	

Broadband Cable

Product	Features	Page
Headend and Distribution Hub Equipment		
Cisco uBR7100 Series Universal Broadband Router	Entry-level, standards-based fixed-configuration CMTS and integrated router for lower-density 7-4 residential and MxU customers serviced by cable operators or ISPs. - Compact form factor (2RU) - Supports up to 2,000¹ broadband subscribers - Layer 2 bridging and full Layer 3 routing - DOCSIS 1.0, 1.1 and Euro--DOCSIS 1.0 qualified; supports DOCSIS Set-top Gateway (DSG) - Fixed-configuration models including: Cisco uBR7111, Cisco uBR7111E, Cisco uBR7114, and Cisco uBR7114E - Integrated upconverter/modulator - Embedded dual 10/100 BaseT Ethernet network interface - Selection of LAN and WAN interfaces	
Cisco uBR7246VXR Universal Broadband Router	Modular, standards-based communications-grade CMTS and integrated router for high-growth 7-5 broadband cable deployments Supports up to 10,000¹ broadband subscribers - Offers large variety of LAN and WAN interface options and processors - Full Layer 3 implementation - DOCSIS, 1.0, 1.1, Euro-DOCSIS 1.0, 1.1, 2.0 (ATDMA-only) and PacketCable 1.1 qualified; Supports Advanced Mode DSG - Selection of cable line cards that includes Cisco uBR7200 Series MC28U, MC28X, MC16U, and MC16X Broadband Processing Engines (BPEs)	
Cisco uBR10012 Universal Broadband Router	Highest-capacity communications-grade CMTS on the market today. Delivers the services, performance, scale, and carrier-class reliability large cable operators and ISPs demand - Supports up to 64,000¹ broadband subscribers - A-TDMA and advanced spectrum management - Full Layer 3 implementation - DOCSIS, 1.0, 1.1, Euro-DOCSIS 1.0, 1.1 and PacketCable 1.1 qualified; Supports Advanced Mode DSG - High-performance aggregation platform with Parallel Express Forwarding patented by Cisco - Cisco 5x20U Broadband Processing Engine (BPE) - Network interfaces that includes 1 Gbps over Gigabit Ethernet and OC-48-Dynamic Packet Transport (DPT) Interface Module Set	7-6
Cisco uBR3x10 RF Switch	- Exceeds PacketCable availability requirements - Enables a fully redundant CMTS with no single point of failure; works with the Cisco uBR7246VXR and uBR10012 - Maximizes density with more than 250 MCX-type connector	7-7

Product	Features	Page
Network Management		
Cisco Broadband Configurator	Provides a user interface to collect information needed to generate DOCSIS or PacketCable 7-8 configuration files	
Cisco Broadband Troubleshooter	- Provides a diagnostic tool for RF technicians to quickly and easily isolate problems in the cable 7-8 plant - Analyzes and sorts RF conditions into specific categories such as attenuation, provisioning, noise or packet corruption (CRC) errors - Provides dashboard views of network health, CMTS and CM statistics, and CM snapshots - Correlates CM to subscriber information - Works with an optional tool to map CMs and status to subscriber street-level views	

1. Numbers are for reference only. Actual numbers for specific systems will vary depending on network/service loading, traffic, and other parameters.

DSL (Digital Subscriber Line) Access

Product	Features	Page
DSL Access CPE¹	Wide variety of Cisco router-based DSL CPE solutions for business-class to small office applications	7-9
Broadband Services Aggregation	- Cisco 7200 Series Router—Up to 16000 broadband sessions on a 3 RU platform, including aggregation of PPP, PPPoE, and PPPoA - Cisco 7301 Series Router—1 RU Broadband Aggregation Router that is capable of delivering up to 16000 sessions per chassis	7-9

1. For ADSL, ISDN, and IDSL small office/home office (SOHO) customer premise equipment (CPE), see Chapter 1: Routing

ATM Multiservice WAN Switching

Product	Features	Page
Cisco MGX 8850 Series Advanced ATM Multiservice Switches	- Multiservice switch, scales from DS0 to OC-48c/STM-16 speeds - Serves as a stand-alone device for narrowband services, an integrated edge concentrator or a broadband edge switch when equipped with 45 Gbps switch card and broadband ATM modules - Supports PNNI routing	7-10
Cisco MGX 8830 Series Multiservice Switches	- Multiservice switch scales from DS0 to OC-3c/STM-1 speeds - A standalone switch with narrowband interfaces and broadband trunking to remote sites with low density and high service mix requirements with 1.2 Gbps or 45 Gbps switch fabric in the enhanced chassis - Supports PNNI routing	7-10

Long Reach Ethernet

Product	Features	Page
Cisco Catalyst 2950 LRE Switches	- Fixed configuration Ethernet switches for delivering converged voice, video, and data services over 7-11 existing category 1/2/3 wiring for the in-building MxU, Hospitality, and Enterprise markets 8 or 24 LRE ports + 2 10/100/1000BASE-T ports + 2 Small Form-Factor Pluggable (SFP) ports (two of the four uplinks active at one time), deliver Ethernet traffic (up to 15 Mbps) over standard copper cabling (up to 5000 feet); ideal for in-building applications - Co-exists with POTS and ISDN traffic on the same line and compatible with ADSL - Advanced QoS, security, and multicast features to support converged voice, video (broadcast and VoD), and high speed data services	
Cisco LRE CPE Devices	- Cisco 575 LRE CPE—Compact, includes one RJ-45 Ethernet connection and two RJ-11 connectors (for telephone) - Cisco 585 LRE CPE—Compact, includes four RJ-45 switched Ethernet connections and two RJ-11 connectors (for telephone). Supports 802.1p QoS	7-11
Cisco LRE POTS Splitter	Cisco LRE 48 POTS Splitter—48 ports in 1RU. Ensures that POTS service is separate, and never compromised by LRE switch reconfiguration or downtime	7-12
Cisco Broadband Building Service Manager	- Server system enables automated online activation, integrated billing, tiered service levels - Ideal for any form of broadband access technology, including Ethernet, LRE, Cable access, DSL, Wireless, or Fiber	7-13
Product Ordering Website	To place an order, visit the Cisco Ordering Website: http://www.cisco.com/en/US/ordering/index.shtml	

SS7 Signaling & Softswitch Products

Cisco PGW 2200 Softswitch

The Cisco PGW 2200 provides the signaling and call control functionality that enables SPs to bridge the boundary between the legacy PSTN. Combined with Cisco's award winning media gateways, the PGW 2200 is the catalyst for PSTN Gateway solutions enabling dial offload, transit, business voice, H.323 and SIP based applications. The PGW 2200 leverages its protocol library of 90+ SS7/C7 variants to enable interconnect worldwide. In signaling mode the PGW adds SS7/C7 to the AS5X00 gateways, giving service providers around the world a proven cost-saving and reliable solution for connecting VoIP and Internet Dial Access solutions to the PSTN. SS7 signaling allows service providers to enter into new markets, optimize their networks for both voice and data traffic, and save drastically on monthly interconnect fees.

Key Features

- Peer-to-peer Interconnect with the PSTN via SS7/C7
- SS7/C7 support for carrier-class Cisco AS5x00 network access servers and voice gateways
- Calling-party analysis (A-number analysis); Called-party number analysis (B-number analysis)
- ANI- or CLI-based number screening with on-board database
- Overload control; Automatic congestion control (ACC); Advice of charge (AOC)
- E.164 and North American numbering plan (NANP) support
- Over-decadic digits; Toll-free/800 number calls

For More Information

See PGW 2200 Website:

<http://www.cisco.com/en/US/products/hw/vcallcon/ps2027/index.html>

Cisco BTS 10200 Softswitch

The Cisco BTS 10200 Softswitch offers tremendous flexibility to service providers who want to deploy local and transit services and facilitates cost reduction through grooming. The standards-based Cisco BTS 10200 Softswitch enables new, innovative, easily differentiated services for a fortified broadband services offering. Services can be quickly deployed, and time-consuming and costly upgrades to each transport element are not required-the Cisco BTS 10200 Softswitch extracts and centralizes the call-control and service applications from the transport network. In addition to telecommunications services, service providers can offer a wider range of other business and residential services, including multiservice VPNs, Web hosting, and Internet access.

Leveraging the power of packet networks while seamlessly operating with legacy circuit switched infrastructures, the Cisco BTS 10200 Softswitch empowers service providers and carriers to gracefully transition to packet-based technology. Implementing the Cisco BTS 10200 Softswitch ensures rapid service deployment, carrier-grade reliability, service flexibility, scalability to millions of subscribers, and cost savings through investment optimization and operational

When to Sell

Sell This Product

Cisco BTS 10200
Softswitch

When a Customer Needs These Features

- Class 4/5 Functionality
- One network, one transport protocol, multiple services (voice, video, and data)
- Increased revenue, profits, and customer loyalty by delivering additional services over an existing infrastructure
- Fast deployment of advanced services such as voice messaging and video services
- Proven, industry-leading network components for reliable, scalable, carrier-class packet networks
- Structured architecture for flexible, high-performance network services
- Pure packet-based network infrastructure, reducing the operating costs required to run multiple networks

Key Features

- Comprehensive industry-standard protocol support
- Carrier-grade reliability with Network Equipment Building Systems (NEBS) compliance and redundant platform components
- Interoperable with numerous commercial feature servers
- Feature server architecture, which provides an open protocol
- Streamlined maintenance, provisioning, and service activation
- Integrated access device and IP Phone support
- GUI and CLI
- Comprehensive reporting features, including billing records
- Network scalability through deployment of multiple, centrally managed call agents

For More Information

See Cisco BTS 10200 Softswitch Website:

<http://www.cisco.com/en/US/products/hw/vcallcon/ps531/index.html>

Cisco uBR7100 Series Universal Broadband Router



The Cisco uBR7100 Series is a complete, compact, easy-to-use product that enables cost-effective, high-speed Internet access in the hospitality multidwelling (MDU) and multitenant (MTU) market space using the coaxial cable already in a building. The product requires exceptionally low capital investment and minimal setup time to provide online Internet access and support residential voice services. For Tier 2 or Tier 3 cable operators, it is the industry's most cost-effective, feature-rich CMTS and integrated router. The Cisco uBR7111 and Cisco uBR7114 models are CableLabs qualified to DOCSIS 1.0 and 1.1 specifications. The Cisco uBR7111E and Cisco uBR7114E models are tComLabs qualified to EuroDOCSIS 1.0 and and supports EuroDOCSIS 1.1 specifications. The series supports DSG. The Cisco uBR7111 and Cisco uBR7111E contain one downstream port and one upstream port. The Cisco uBR7114 and Cisco uBR7114E contain one downstream port and four upstream ports.

When to Sell

Sell This Product

Cisco uBR7100 Series

When a Customer Needs These Features

- For MxU customers: the Cisco uBR7100 Series enables high-value Internet and residential voice services over a DOCSIS or EuroDOCSIS cable infrastructure
- For cable operators: Given the small subscriber base of a typical multitenant/dwelling unit (MxU) setting, the challenge has been to deliver robust services quickly and cost-effectively for an accelerated break-even point and a quicker return on investment

Key Features

- Complete package that includes a full Layer 3 router and CMTS with an integrated upconverter, and embedded Network Interface
- Standards-based: DOCSIS and EuroDOCSIS
- Reliable operation to ensure the system remains online

Specifications

Feature	Cisco uBR7111 and uBR7114	Cisco uBR7111E and uBR7114E
Memory	Flash: 48 MB; System: 128 MB	Flash: 48 MB; System: 128 MB
Line Card with Integrated Upconverter (Cable Plant Interface)	uBR7111: 1 downstream and 1 upstream uBR7114: 2 downstream and 4 upstreams	uBR7111E: 1 downstream and 1 upstream uBR7114E: 2 downstream and 4 upstreams
Integrated Upconverter	DOCSIS Annex B, 6 MHz High level output: +61dBmV, 55 to 858 MHz Optimized for 64 and 256 QAM	DOCSIS Annex A, 8 MHz, High level output: +61 dBmV, 55 to 858 MHz Optimized for 64 and 256 QAM
Power Options	Single; 100 to 240 VAC input voltage	Same as Cisco uBR7111 and Cisco uBR7114
Recommended Cisco IOS Software Release	12.3(13)BC	12.3(13)BC
Port Adapter (WAN or backbone Interface)	Embedded dual 10/100 BaseT Ethernet (FETX) provided; Same as Cisco uBR7111 and Cisco uBR7114 supports one additional PA that includes: Ethernet, Serial, ATM, and POS.	

For More Information

See the Cisco uBR7100 series Website:

<http://www.cisco.com/en/US/products/hw/cable/ps2211/index.html>

Cisco uBR7246VXR Universal Broadband Router

The Cisco uBR7246VXR Universal Broadband Router, a member of the Cisco uBR7200 Series, provides a single, Layer 3 routing, multiservice, scalable platform that gives cable companies the ability to deliver IP data, voice and video services to DOCSIS, Euro-DOCSIS, and PacketCable-compliant cable modems, set-top boxes and multimedia terminal adapters.

**When to Sell**

Sell This Product
Cisco uBR7246VXR

When a Customer Needs These Features

- Flexible port expansion for multiservice deployment options
- Service support of up to 10,000 subscribers per chassis with 3.2 Gbps back plane¹
- Powerful processor and edge intelligence; Field proven and carrier class reliability
- Support for multimedia services
- High tolerance to HFC network/spectrum noise

1. Numbers are for reference only. Actual numbers for specific systems will vary depending on network/service loading, traffic, and other parameters

Key Features

- Modular design—1,000- 10,000 subscribers per chassis supported based on different configurations
- Five 9's availability for low cost maintenance
- Advanced PHY
- ATDMA / DOCSIS compliant; Euro-DOCSIS 2.0 (A-TDMA only), DOCSIS 1.1 qualified, and PacketCable 1.1 qualified; tComLabs qualified to Euro-DOCSIS 1.0, 1.1, and 2.0 (ATDMA-only) specifications. The product also supports Advanced Mode DSG.
- Powerful Layer 3 routing intelligence and sophistication

Specifications

Feature	Cisco uBR7246VXR
Number of Cable Line Card Slots	4
Supported cable line cards (Cable Plant Interfaces)	uBR7200 Series MC28U, MC28X, MC16U, and MC16X Broadband Processing Engines uBR-MC28C and uBR-MC16C Universal Broadband Line Cards
Port Adapter Slots (LAN/WAN interfaces)	2
Supported PA categories	Ethernet Serial, HSSI, ATM, POS, DPT
Power Supply Shots	2
Power Supply Option	AC; Dual AC; DC; Dual DC
Input/Output (I/O) controller	uBR7200-I/O-2FE/E, not required if uBR7200-NPE-G1 is installed in the system
I/O flash options for PCMCIA slots	Flash disk (48 MB); Flash disk (128 MB)
Network processing engines (NPE)	uBR7200-NPE-G1 and NPE-400
Add-on processor memory options	128 MB, 256 MB, or 512MB for NPE-400 256 MB, 512 MB, or 1 GB for uBR7200-NPE-G1
Router Bandwidth	3.2 Gbps

For More Information

See the uBR7200 Website:
<http://www.cisco.com/en/US/products/hw/cable/ps2217/index.html>

Cisco uBR10012 Universal Broadband Router

The Cisco uBR10012 Universal Broadband Router addresses the volume, capacity, and complexity of large cable headends or distribution hubs. The Cisco uBR10012 delivers the highest level of service availability and capacity of any production CMTS available today. It employs a mix of distributed, centralized, and parallel processing to enable consistently high, real-world performance. The Cisco uBR10012 is CableLabs qualified to PacketCable 1.1, DOCSIS 1.0 and 1.1 specifications. The product is also tComLabs qualified to EuroDOCSIS 1.0 and 1.1 specifications. The product further supports Advanced Mode DSG.



When to Sell

Sell This Product	When a Customer Needs These Features
Cisco uBR10012	• Large subscriber bases • Edge routing or aggregation of DOCSIS traffic • High-end throughput, capacity, and service handling • Advanced multimedia service delivery • Sophisticated Layer 3 routing intelligence • Complex network interface configurations

Key Features

- Highest density and capacity: 5,000 - 64,000 subscribers
- Powerful process and throughput
- Five 9's availability
- GE line rate -> OC-48
- Scalable performance
- A-TDMA / DOCSIS 2.0
- Advanced intelligence features

Specifications

Feature	Cisco uBR10012
Modular Slots	8 slots for cable line cards; 4 slots for LAN/WAN interfaces; 2 slots for Performance Routing Engines (PREs); 2 slots for Timing Communication and Control Plus (TCC+) modules
Supported Cards	Cable line cards that include Cisco 5X20U BPE Timing, Communications, and Control Plus (TCC+) card Gigabit Ethernet (GE) network uplink card and OC-48 DPT Interface

Feature	Cisco uBR10012
Processor Type	Parallel Express Forwarding (PXF)
Flash Memory	48 MB (default); 128 MB (maximum)
DRAM Memory	512 DRAM (default)
Software Supported	Cisco IOS Software Release 12.3(13)BC recommended; Minimum software requirement: Cisco IOS Software Release 12.2(11)BC1 minimum for the Cisco 5X20 BPE, Cisco IOS Software Release 12.2(13)BC minimum for the Cisco OC-48 DPT Interface, Cisco IOS Software Release 12.3(9)BC minimum to support the Cisco PRE-2
Power Supply	DC, AC
Hot-Swappable	Yes
Backplane Capacity	51.2 Gbps
Dimensions (H x W x D)	31.25 x 17.2 x 22.75 in. (79.4 x 43.7 x 57.8 cm)—18 rack units (RU) Mounting: 19 in. rack mountable (front or rear), 2 units per 7 ft. rack Note: Mounting in 23 in. racks is possible with optional third-party hardware
Weight	Weight: 235 lb (106.6 kg) fully configured chassis

For More Information

See the Cisco uBR10012 Website:

<http://www.cisco.com/en/US/products/hw/cable/ps2209/index.html>

Cisco uBR 3x10 RF Switch

The Cisco uBR 3x10 RF Switch works with the Cisco uBR10002 and uBR7246VXR universal broadband routers to provide a fully redundant CMTS. The Cisco uBR 3x10 RF Switch accommodates three downstream switch modules and 10 upstream modules.



When to Sell

Sell This Product
Cisco uBR 3x10 RF Switch

When a Customer Needs These Features

- Carrier class N+1 network and service architecture
- High density HA service support
- Scalability to tens of thousands of subscribers

Key Features

- Hot swap capability that eliminates downtime for RF paths
- Support of DOCSIS, Euro-DOCSIS and PacketCable RF performance specifications
- Most comprehensive set of high availability features
- Modular upstream and downstream capacity
- Fully passive working path
- Active components only in protect path
- Position-sensing latching relays
- Unmatched port density and flexibility
- N+1 redundancy

Specifications

Feature	Cisco uBR 3x10 RF Switch
Input Power Requirements	AC: 100 to 240 VAC, 50 or 60 Hz, operating range: 90 to 254 VAC DC: -48 to -60 VDC, operating range: -40.5 to -72 VDC, 200 mVpp ripple/noise
Environmental	Operational temperature range: 0 to +40°C Operating temperature range: -5 to +55°C
Unit Control	10BaseT Ethernet—SNMP Switching time from active (working) to standby (protect): 150 mS maximum after SNMP command
Connectors	RF connectors: MCX AC power: IEC320 type DC power: Three terminal block Ethernet: RJ-45 RS-232 Bus: 9-pin male D
Reliability	41,000 MTBF @ +50°C as calculated by Belcore 5, 80 percent confidence factor
Dimensions (H x W x D)	5.25 x 17.5 x 14.8 in. (13.335 x 44.45 x 37.592 cm)

Feature	Cisco uBR 3x10 RF Switch
Weight	36 lbs
RF requirements	Input/output impedance: 75 ohms Maximum RF input power: +15 dBm (63.75 dBmV) Switch type: Electro-mechanical, absorptive for working path, non-absorptive on the protect path Switch setting time per switch module: 20 ms maximum Downstream frequency range: 54 to 860 MHz Typical downstream insertion loss: +/-1.1 dB from CMTS to cable plant; +/- 2.1 dB from protect to cable plant; 5.5 dB from working to output; 8.0 dB from protect to output Downstream insertion loss flatness: +/- 1.1 dB from CMTS to cable plant; +/- 2.1 dB from protect to cable plant Downstream output return loss: >15.0dB at <450 MHz, > 12.0 dB at >= 450 MHz Downstream input return loss: >15.0 dB Downstream isolation: > 60 dB from channel to channel in working mode; > 52 dB from CMTS to protect when in protect mode Upstream frequency range: 5 to 70 MHz Typical upstream insertion loss: 4.1 dB from cable plant to CMTS; 5.2 dB from cable plant to protect Upstream insertion loss flatness: +/- 0.4 dB from cable plant to CMTS, +/- 0.6 dB from cable plant to protect Upstream input return loss> 16 dB Upstream isolation: > 60 dB from channel to channel in working mode; > 60 dB from CMTS to protect when in protect mode Protect mode: CMTS return loss >10 dB, cable plant return loss: >10dB

For More Information

See the Cisco uBR 3x10 RF Switch Website:
<http://www.cisco.com/en/US/products/hw/cable/ps2929/index.html>

Remote Cable Access—Network Management Products

Cisco Broadband Troubleshooter

Cisco Broadband Troubleshooter is an easy-to-use tool that gives network administrators and technicians a GUI that streamlines RF problem resolution. The tool dynamically monitors RF characteristics on a per modem or per upstream basis, provides a measurement interface for the upstream that looks and feels like a spectrum analyzer, decentralizes RF monitoring and analysis, and automatically sorts and categorizes RF problem conditions. The product provides a fault-analysis tool that enabling isolation of performance, cable plant, and CM problems. The product characterizes upstream and downstream trouble patterns. Operators can quickly discern CPE connectivity impairments by identifying noise, attenuation, provisioning, and packet-corruption issues.

For More Information

See the Cisco Broadband Troubleshooter Website:
<http://www.cisco.com/en/US/products/sw/netmgtsw/ps530/index.html>

Cisco Broadband Configurator

Cisco Broadband Configurator is an easy-to-navigate, Java-based application that simplifies the creation and maintenance of configuration files for PacketCable 1.1 media terminal adapters (MTAs) and DOCSIS 1.0 and 1.1 cable modems. The product provides a simple-to-use, forms-based approach that leads cable operators through the process of configuring or editing values of a configuration file. For More Information
 See the Cisco Broadband Configurator Website:
<http://www.cisco.com/en/US/products/sw/netmgtsw/ps819/index.html>

DSL Remote Access—Customer Premise Equipment (CPE)

Cisco offers the industry's broadest array of business-class DSL (G.SHDSL and ADSL) CPE solutions, from Enterprise to branch office, to SOHO applications. CPE offers firewall VPN, voice-over DSL support and IOS-based capabilities enabling QoS, policy management, and standardized set-up and configuration. Cisco CPE Products include:

- Cisco SOHO Series Ethernet, ADSL over ISDN, ADSL over POTS and G.SHDSL Routers
- Cisco 800 Series Routers Ethernet, ADSL over ISDN (ADSL, ADSL2, and ADSL2+), ADSL over POTS (ADSL, ADSL2, and ADSL2+), and G.SHDSL (2-wire & 4-wire)
- ADSL over ISDN, ADSL over POTS and G.SHDSL (2-wire & 4-wire) WAN Interface Cards (WICs) for 1700, 1800, 2600XM, 2800 and 3800 Series
- ADSL over ISDN (ADSL, ADSL2, and ADSL2+) and ADSL over POTS (ADSL, ADSL2, and ADSL2+) High-Speed WAN Interface cards (HWICs) for 1800, 2800 and 3800 series. (see Chapter 1: Routing)



Note Refer to Chapter 1: Routing section for easy-to-order xDSL bundles.

Broadband Services Aggregation

The Cisco broadband aggregation portfolio covers all possible broadband aggregation markets.

- Cisco 7301: Highest Density PPP aggregation per rack-unit
- Cisco 7200: Most versatile platform

Cisco 7200 Series

When ordered with the Cisco IOS 7200 Series Broadband User Services License, the 7200 delivers scaled PPP, RBE, and L2TP sessions and tunnels in addition to rich IP services. It enables service providers to provision broadband Internet access and supports all of the popular access technologies. It is ideal for low- to medium-density applications and is capable of handling up to 16000 subscribers in a single chassis.

Cisco 7301 Series

When ordered as 7301-BB-8K and 7301-BB-16K (16K License) the Cisco 7301 Series Router provides a compact, high-performance single-rack-unit (1RU) router coupled with a broad set of interfaces and Cisco IOS® Software features, which makes it ideal for Broadband applications. The Cisco is capable of handling up to 16,000 simultaneous sessions and allowing for a pay-as-you-grow “rack and stack” architecture.

ATM Multiservice WAN Switching

Cisco MGX 8850 ATM Multiservice Switch

The Cisco MGX 8850 ATM Multiservice Switch enables delivery of a complete portfolio of service offerings while scaling from DS0 to OC-48c/STM-16 speeds. It enables service providers to offer high-margin voice and data services. The MGX 8850 universal chassis provides a unified ATM architecture that delivers a complete portfolio of differentiated services -from circuit emulation to IP VPNs-all within a single chassis with 16 double-height slots, to enable service providers to easily add new services. Two different operation modes are offered:

- 1.2Gbps configuration—Operates as a stand alone switch for low density narrowband services, it includes a 1.2 Gbps switch card (PXM-1E)with PNNI routing. There are various PXM-1E integrated network interface cards such as the T1/E1, T3/E3 and OC-3/STM1; Supports up to 12 Double-Height / 24 Single-Height User Service Modules to support FR, ATM, CES, IP and Voice Services
- 45 Gbps configuration—Serves as a broadband edge switch and includes the 45 Gbps switch card (PXM-45) and broadband ATM modules. The PXM-45 configuration also supports standards-based PNNI routing; Supports up to 12 Double-Height / 24 Single-Height User Service Modules to support FR, ATM, CES, IP and Voice Services

Key Features

- Flexible ATM Multiservice platform
- Highly scalable-from 1.2 to 45 Gbps of non-blocking throughput in single chassis
- Highest reliability, availability, and serviceability in the industry
- IP VPNs using Cisco IOS software-based Multiprotocol Label Switching (MPLS)
- Market-leading Frame Relay capabilities, with price-per-port leadership and advanced QoS
- High-density Point-to-Point protocol (PPP) for Internet access and aggregation
- Full-featured narrowband ATM for managed data, voice, and video services; high-density broadband ATM for wholesale ATM services
- Circuit Emulation for Private Line replacement
- Highly scalable packet voice gateway providing VoIP and VoATM(AAL1 & AAL2),

For More Information

See the Cisco MGX 8850 Website: <http://www.cisco.com/go/mgx8850>

Cisco MGX 8830 ATM Multiservice Switch

The Cisco MGX 8830 Advanced ATM Multiservice Switch is a compact and cost-effective solution to extend a full suite of narrowband and broadband services, voice gateway functionality and broadband trunking to edge of service provider network. Interface speed ranges from DS0 to OC-12/STM-4. It features a 7-slot chassis for smaller footprint and lower power consumption than the MGX 8850. The Cisco MGX 8830/B chassis supports switching capacity of 1.2 Gbps or 45 Gbps and acts as a standalone switch. It inherits the proven reliability and shares the service modules with the MGX 8850. It offers a full range of service interfaces including ATM, FR, CE, MPLS, VoIP and VoATM(AAL1 & AAL2).

For More Information

See the Cisco MGX 8830 Series Website: <http://www.cisco.com/go/mgx8830>

Cisco Long Reach Ethernet Solution



Cisco LRE enables the transport of symmetrical, bi-directional data over unshielded, copper twisted-pair telephone wires originally intended for the frequency bands used for traditional telephone voice services (300 Hz and 3.4 KHz). The system employs Frequency Division Duplexing (FDD) to separate the downstream channel, the upstream channel, and POTS, ISDN, or PBX signaling services in the frequency domain. This enables users to overlay LRE on existing POTS, ISDN, or analog PBX signaling services without disruption, extending intelligent Ethernet services at distances of up to 5000 over existing phone or legacy wiring. Both LRE and POTS/ISDN/analog PBX services may be transmitted over the same line without interfering with each other.

The Cisco 2950 LRE solution includes the Cisco Catalyst 2950 LRE switches, the Cisco 575 and 585 LRE CPE devices, and the Cisco LRE POTS Splitter. Each LRE link is terminated with either the Cisco 575 or 585 LRE CPEs, and a POTS splitter is required when POTS traffic coexists with the LRE link over the same line.

Catalyst 2950 LRE Series Intelligent Ethernet Switches

The Cisco Catalyst® 2950 LRE switches are fixed-configuration, stackable models that provide wire-speed LRE and Gigabit Ethernet connectivity for small and midsized networks. The Catalyst 2950 Series is an affordable product line that brings enhanced security, high availability and advanced QoS, to the network edge-while maintaining the simplicity of traditional LAN switching. When a Catalyst 2950 LRE switch is combined with a Catalyst 3750 Series switch, the solution can enable IP routing from the edge to the core of the network. The Cisco Catalyst 2950 LRE switches are supported in the Cisco Network Assistant (CNA) application, which allows users to simultaneously configure and troubleshoot multiple Catalyst desktop switches, Integrated Services Routers, IP phones and Access Points using a PC based network management application.

The two built-in Gigabit Ethernet SFP ports support 1000BASE-SX and 1000BASE-LX modules. The dual SFP-based and copper Gigabit Ethernet implementation provides customers with tremendous deployment flexibility-allowing customers increased availability with the redundant uplinks. High levels of stack resiliency can also be implemented by deploying dual redundant Gigabit Ethernet uplinks and UplinkFast technologies for high-speed uplink and stack interconnection failover, and Per VLAN Spanning Tree Plus (PVST+) for uplink load balancing.

Cisco 575 and 585 LRE CPE Devices

Each LRE port is terminated in the room with either the Cisco 575 or 585 LRE CPE devices. These compact devices bridge LRE and Ethernet. The 575 CPE has one RJ-45 Ethernet connection and two RJ-11 connectors—one for the wall and one for a telephone. The 585 CPE has four RJ-45 switched Ethernet connections and two RJ-11 connectors and supports 802.1p QoS so that voice and video traffic are prioritized over normal data traffic. Both the Cisco 575 and 585 LRE CPE devices can be mounted on or under a desk, or on a wall. They ship with a mount lock-in mechanism and clip-on Ethernet cable guard to discourage theft. It supports voice (Plain Old Telephone Service—POTS) traffic-including ISDN or digital phones-that coexists over the same LRE line by splitting LRE and POTS traffic at the CPE device.

Cisco LRE 48 POTS Splitter

The Cisco LRE 48 POTS Splitter is a high-density, low-cost device that is ideal for building deployments where the PBX system is on-site and POTS traffic must coexist over the same copper wiring as LRE traffic. Unlike “splitterless” building broadband network solutions, the Cisco LRE 48 POTS Splitter ships as a separate, compact form factor to ensure that POTS service is separate, and never compromised by LRE switch reconfigurations or downtime.

The Cisco LRE 48 POTS Splitter supports 48 ports in a 1RU form factor. Each splitter has six RJ-21 connectors—two each for connectivity to the patch panel, the LRE switch(es), and the on-site PBX system.

Key Features

- Performance—Delivers 2-15 Mbps symmetric over existing category 1/2/3 wiring at distances up to 5000 feet. Rate Selection feature automates the process of selecting a data rate for a line for ease of installation and increased robustness.
- Powerful Gigabit Ethernet uplink options—1000BaseT and SFP ports
- Superior control through intelligent services—advanced QoS and security based on Layer 2 through Layer 4 parameters.
- Multicast support—Multicast VLAN Registration (MVR) and IGMPv3 Snooping.
- Enhanced Cisco IOS Services
- Network Management—CNA offers centralized management and configuration of Cisco networks to simplify deployment and ongoing maintenance by leveraging Cisco Smartports technology. CNA is a PC-based network management application; Optimized for networks with 20 devices or less; User-friendly GUI; Seamlessly apply common services such as configuration management, inventory reports, password synchronization and Drag and Drop IOS® Upgrade across Cisco SMB-Class switches, routers and access points; Available at no cost and downloadable at www.cisco.com/go/cna

Competitive Products

- Paradyne Networks: BitStorm solution (Etherloop) and ReachDSL products
- Tut Systems: IntelliPOP VDSL
- Huawei: Quidway s3026v

Specifications

Feature	Cisco 2950ST 24 LRE	Cisco 2950ST 8 LRE
Fixed Ports	24 LRE ports + 2 10/100/1000BASE-T ports + 2 Small Form-Factor Pluggable (SFP) ports (two of the four uplinks active at one time)	8 LRE ports + 2 10/100/1000BASE-T ports + 2 SFP ports (two of the four uplinks active at one time)
Backplane	8.8 Gbps	Same as Cisco 2950ST 24 LRE
Forwarding Rate	3.5 Mpps	3.2 Mpps
VLAN Maximum	250 port based VLANs or ISL/802.1Q trunks	Same as Cisco 2950ST 24 LRE
FEC	Yes	Same as Cisco 2950ST 24 LRE
802.1Q	Yes	Same as Cisco 2950ST 24 LRE
Multicast	IGMPv3 Snooping, IGMP Throttling	Same as Cisco 2950ST 24 LRE
QoS	802.1 p, 4 egress queues, WRR, Layer 3 and 4 services	Same as Cisco 2950ST 24 LRE
Management Capabilities	SNMP, Telnet, RMON, CW2000, CLI-based out-of-band, embedded Cisco Cluster Management Suite (CMS), Web-based interface	Same as Cisco 2950ST 24 LRE
Memory	84 MB (Flash); 32 MB (CPU DRAM)	Same as Cisco 2950ST 24 LRE
Embedded RMON	History, Events, Alarms, Statistics	Same as Cisco 2950ST 24 LRE
Dimensions (H x W x D)	1.75" (44.5 mm) x 17.5" (444.5 mm) x 9.7" (246.6 mm)	Same as Cisco 2950ST 24 LRE

Selected Part Numbers and Ordering Information¹**Catalyst 2950 LRE Series Switches**

WS-C2950ST-24-LRE	Catalyst 2950 LRE switch: 24-port LRE + 2 10/100/1000BASE-T ports + 2 SFP ports
WS-C2950ST-8-LRE	Catalyst 2950 LRE switch: 8-port LRE + 2 10/100/1000BASE-T ports + 2 SFP ports

Cisco 575 and 585 LRE CPE Device

CISCO575-LRE	Cisco 575 LRE CPE device: 1-port Ethernet + 2 RJ-11 connectors
CISCO575-LRE-6P	Cisco 575 LRE CPE device (6 pack): 1-port Ethernet + 2 RJ-11 connectors
CISCO575-LRE-24P	Cisco 575 LRE CPE device (24 pack): 1-port Ethernet + 2 RJ-11 connectors
CISCO585-LRE	Cisco 585 LRE CPE device: 4-port Ethernet + 2 RJ-11 connectors
CISCO585-LRE-6P	Cisco 585 LRE CPE device (6 pack): 4-port Ethernet + 2 RJ-11 connectors
CISCO585-LRE-24P	Cisco 585 LRE CPE device (24 pack): 4-port Ethernet + 2 RJ-11 connectors

Cisco LRE 48 POTS Splitter

PS-1M-LRE-48	Cisco LRE 48 POTS Splitter: 48 ports
--------------	--------------------------------------

1. This is only a small subset of all parts available via URL listed under "For More Information." Some parts have restricted access or are not available through distribution channels. Resellers: For latest part number and pricing info, see the *Distribution Product Reference Guide* at: <http://www.cisco.com/dprg> (limited country availability).

For More Information

See the LRE Website: <http://www.cisco.com/go/lre>

Cisco Building Broadband Service Manager (BBSM) Version 5.3

Cisco Building Broadband Service Manager (BBSM) is an access gateway for guest access networking that enables simple, plug-and-play access, end user self-provisioning of services, customizable portal and advertising platforms and Web-based management, reporting and configuration. Multiple authentication and billing options are supported, including access codes, RADIUS, credit card, and property management system (PMS). Cisco BBSM manages Internet access services without IT intervention, enabling venues to offer services in remote and unattended locations. It enables venues to create, market and operate broadband access services in markets such as higher-education, healthcare, retail, and enterprise guest access.

For More Information

See the BBSM Website: <http://www.cisco.com/go/bbsm>



Optical Networking


Optical Networking at a Glance

Product	Features	Page
Metro Core		
Cisco ONS 15600 Multiservice Switching Platform (SONET/SDH)	Allows service providers to seamlessly integrate their metro core and metro edge networks, 8-3 while dramatically reducing initial turn up costs. Provides 320 gigabits of switching, grooming, aggregation, and bandwidth management capacity in a single shelf Supports 32, OC-192/STM-64 long reach or 128, OC-48/STM-16 long reach optical interfaces in a single shelf Offers any service/any port (ASAP) service cards that hold up to four pluggable I/O (ASAP 4-PIO) modules each capable of supporting up to four - 2.5 Gbps SFP optics capable of both fixed-rate and multirate formats Combines the functionality of multiple metro systems including SONET/SDH multiplexers and digital cross-connect network elements Provides carrier-class availability, serviceability, and management Scalable, easy-to-use platform supports all metro topologies	8-3
Cisco ONS 15454 SONET/SDH Multiservice Provisioning Platform (MSPP)	Integrates the functions of legacy SONET or SDH network elements with next-generation SONET/SDH transport, integrated wavelength division multiplexing (WDM) optical networking, and multiservice interfaces: Aggregated lower-rate TDM services from DS-1/E1 over 2.5-Gbps and 10-Gbps wavelengths SONET/SDH wavelength and aggregated services—OC-3/STM-1, OC-12/STM-4, OC-48/STM-16, OC-192/STM-64 Data services—private-line, switched and wavelength-based, including 10/100BASE-T, Gigabit Ethernet, 10 Gigabit Ethernet LAN physical layer, and 10 Gigabit Ethernet WAN physical layer Storage services—1-Gbps and 2-Gbps Fibre Channel, 10-Gbps Fibre Channel, IBM Fiber Connection (FICON), and Enterprise Systems Connection (ESCON), ETR/CLO, ISC-1 Video services—D1 and high-definition television (HDTV) Combines multiplexing, optical networking, and switching functionality in one easy-to-use platform that supports all metro topologies	8-3
Metro DWDM		
Cisco ONS 15454 Multiservice Transport Platform (MSTP)	Delivers integrated, intelligent DWDM functionality, including fully reconfigurable optical add/drop multiplexer (ROADM) technology, for metropolitan and regional networks (up to 32 wavelengths per node): Aggregated lower-rate TDM services from DS-1/E1 over 2.5-Gbps and 10-Gbps wavelengths SONET/SDH wavelength and aggregated services—OC-3/STM-1, OC-12/STM-4, OC-48/STM-16, OC-192/STM-64 ROADM functionality—Zero to 32 channels of pass through or add/drop, A-Z wavelength provisioning and full, realtime power monitoring of each individual wavelength Data services—private-line, switched and wavelength-based, including 10/100BASE-T, Gigabit Ethernet, 10 Gigabit Ethernet LAN physical layer, and 10 Gigabit Ethernet WAN physical layer Storage services—1-Gbps and 2-Gbps Fibre Channel, 10-Gbps Fibre Channel, IBM Fiber Connection (FICON), and Enterprise Systems Connection (ESCON), ETR/CLO, ISC-1 Video services—D1 and high-definition television (HDTV)	8-4
Cisco ONS 15530 Metro DWDM Aggregation Platform	High-density and scalable DWDM multiservice aggregation platform Ideal for both enterprises and managed service providers Network consolidation of storage, data, and legacy applications Up to 8 Fibre Channel / FICON / GbE services or up to 40 ESCON services per wavelength Support for up to 4-ports of 2 Gbps Fibre Channel services per wavelength 8-port Multi Service Muxponder supports up to 8 multiservice interfaces (T1/E1, OC3-STM-1, ESCON, D1 Video, FE, GE, 1GFC, and ITS) per wavelength Scales from 2.5Gbps to 10Gbps Supports wide range of protocols over a highly-available optical infrastructure Highly resilient network with flexible topology design options	8-4

Product	Features	Page
Cisco ONS 15540 Extended Services Platform	Highly modular and scalable next-generation DWDM platform offering Industry Leading Wavelength Density Ideal for enterprises requiring Business Continuance (BC) and Disaster Recovery (DR) Solutions and service providers offering Enterprise BC and DR Managed Services Delivers the integration of data, storage and metro networking Ultra-high bandwidth intelligent optical infrastructure	8-5
Cisco ONS 15216 and 15501 Optical Transmission Families	Cisco ONS 15216 Metro DWDM Series Supports 32 ITU-grid wavelengths at 100 GHz spacing and provides unprecedented transport flexibility with optical filtering Combines wavelengths launched by the Cisco ONS 15454, and ONS 15530-creates a more desirable cost per-wavelength Optical Add/Drop Multiplexing (OADM) Optical Performance Monitoring and Amplification Compact, modular design Cisco ONS 15501 Optical Amplifier Constant flat gain of 17 dB over the 1530nm to 1563nm band simplifies network design. Metro optimized auto gain control and variable gain Low noise figure of <6.0 dB allows the use multiple amplifiers in cascade Input power range of -29 to 0 dBm	8-6
Metro Edge Access		
Cisco ONS 15327 SONET Multiservice Provisioning Platform (MSPP)	Integrated optical networking platform and unprecedented multiservices on demand for the metro access or customer location: Offers optimized bandwidth management, high-speed IP-based data services, rapid service provisioning, and multiple optical interfaces Aggregates and switches TDM, 10/100 BaseT Ethernet and GigE, data and video services Compact footprint (3 rack-units), modular design and industrially hardened	8-6
Cisco ONS 15310-CL SONET Multiservice Provisioning Platform (MSPP)	Compact 1 RU single system controller design, optimized for data and TDM services over protected SONET transport for the customer location. 1RU AC or dual-DC power chassis Single system controller/timing/synchronization 2x small form-factor pluggable (SFP) optical ports for rings 21 DS1s, 3 DS3s 1 expansion slot Fan-cooled	8-7
Cisco ONS 15302/15305 SDH Multiservice Provisioning Platforms (MSPPs)	Ultra-compact integrated systems that extend next-generation optical networks (access nodes or CPE): Low-cost access/customer premise equipment (CPE) platform E1, E3, DS3, 10/100 BaseT Ethernet and GigE STM-1 (15302) or STM-1/4/16 (15305)	8-7
Optical Network Management		
Cisco Transport Manager (CTM 6.0)	Advanced optical transport domain manager that delivers element and network management layer functionality: Efficiently manages the entire Cisco ONS product family and Cisco CR-12000 Series routers Provides a resilient, adaptable, and integrated carrier-class EMS solution Powerful GUI-based management system makes advanced management capabilities such as A-to-Z circuit provisioning easy to learn and use Cost-effective, using industry-standard platforms such as Sun Solaris, Oracle, and Microsoft Windows to fit smoothly into various IT environments Offers a variety of northbound interface options (e.g., SNMP, TL1 and CORBA)	8-8
Metro edge access routers		
Cisco 10720 Internet Router	Service provider-class metro access services router Equipped with 24 ports of Ethernet technology for customer access and dynamic packet transport (DPT) technology for metro optical connectivity With DPT architecture, enables optimal fiber connectivity as well as features such as IP class of service, TLS, VoIP and VPN services See Chapter 1—Routers for more information on the Cisco 10720 Internet Router	1-35
Product Ordering Website	To place an order, visit the Cisco Ordering Website: http://www.cisco.com/en/US/ordering/index.shtml	

Cisco ONS 15600 Multiservice Switching Platform

The Cisco ONS 15600 provides unparalleled flexibility in designing next generation metro networks. Fully engineered and optimized for metro applications, the Cisco ONS 15600 MSSP simplifies and revolutionizes bandwidth management in the metro core by allowing service providers to seamlessly integrate their metro core and metro edge networks, while dramatically reducing initial turn up costs. The Any Service Any Port (ASAP) interface cards of the Cisco ONS 15600 provide 1 to 16 ports of capacity to aggregate and transport mission-critical regional/metropolitan-area (metro) traffic using a modular, flexible and scalable design that allows single- and multiple-rate optics from OC-3 to OC-48, including Gigabit Ethernet SFP optics. Delivering scalability to 960 Gbps of traffic in a single rack, it complements the market-leading Cisco ONS 15454 MSPP by leveraging its proven architecture and operating software. This allows service providers to dramatically simplify their metro networks and realize immediate cost, space and operational benefits. The Cisco ONS 15600 MSSP provides complete integration of metro core and edge networks for service provisioning and network management.



For More Information

See the ONS 15600 Series Website: <http://www.cisco.com/go/ons15600>

Cisco ONS 15454 SONET/SDH Multiservice Transport Platform (MSTP)

The Cisco ONS 15454 Multiservice Transport Platform sets the industry benchmark for metropolitan and regional dense wavelength-division multiplexing solutions by using proven Cisco MSPP networking technologies to deliver simple, fast, and intelligent DWDM capabilities and lower capital and operating expenditures. A metropolitan network, being close to or on a customer's premises-unlike its long-haul counterpart-requires support for a great diversity of service interfaces. The service interfaces allow network providers to offer new tariffs and enable enterprise customers to natively transport a wide variety of services over a common transport network without unnecessary conversion stages and equipment. Additionally, a wide service mix simplifies the planning for services. The Cisco ONS 15454 MSTP, with its MSPP capabilities, supports a broad range of standards-based services in a single platform. Critical to offering a wide service mix is a DWDM system's ability to offer the level of transparency required by the service. The ultimate in network management flexibility is achieved through an industry leading, fully reconfigurable optical add/drop multiplexer (ROADM) that allows zero to 32 channels of pass through or add/drop, A-Z wavelength provisioning, and full realtime power monitoring of each individual wavelength. The Cisco ONS 15454 MSTP solution offers the choice of multiservice aggregation, wavelength aggregation, and wavelength transport, combined with integrated, intelligent DWDM transmission, in a single platform to optimize network costs for any mix of service types. Using digital-wrapper technology (defined in ITU-T G.709) enables transparency while still allowing enhanced wavelength management and providing extended optical reach with integrated Forward Error Correction (FEC).



For More Information

See the ONS 15454 MSTP Website:
<http://www.cisco.com/en/US/products/hw/optical/ps2006/ps5320/index.html>

Cisco ONS 15454 Multiservice Provisioning Platforms

The Cisco ONS 15454 Multi-service Provisioning Platforms (MSPP) are key building blocks in optical networks due to its unprecedented transport performance and economics. It offers supercharged transport capability by combining the best of traditional SONET time division multiplexing (TDM) and statistical multiplexing in single units. The Cisco ONS 15454 aggregates traditional facilities such as DS1, DS3, STS-1, OC-3, OC-12, and OC-48 including multi-wavelength DWDM optics, and also supports data interfaces for 10/100/GigE, data and video. This enables drastically improved efficiencies in the transport layer and breakthrough cost savings for initial and life cycle deployment. A single ONS 15454 shelf can support combinations of OC-3/c, OC-12/c, OC-48/c, and OC-192. It also offers an international optical transport solution that combines the best of traditional SDH TDM and statistical multiplexing in a single platform.



For More Information

See the ONS 15454 SONET Website: <http://www.cisco.com/go/ons15454>

See the ONS 15454 SDH Website: <http://www.cisco.com/go/15454sdh>

Cisco ONS 15530

The Cisco ONS 15530 is a highly scalable DWDM multiservice aggregation platform that integrates storage, data networking, and legacy applications over an ultra-high-bandwidth, intelligent optical infrastructure. The ONS 15530 supports Fibre Channel extension over DWDM via buffer-to-buffer credit support to significantly increase disaster recovery distances; Industry-leading aggregation of IBM Coupling Facility Links used in IBM GDPS storage networks; New Low-band Variable Rate SFP Optics for expanded protocol support.



Key Features

- ONS 15530 4-Port 1-Gbps/2-Gbps Fibre Channel Aggregation Card provides efficient wavelength usage by aggregating up to four 2-Gbps Fibre Channel, IBM Fiber Connection (FICON), and IBM Intersystem Channel (ISC) services onto a single 10-Gbps wavelength
- 8-port Multi Service Muxponder provides the aggregation of up to 8 low speed services such as T1/E1, OC3-STM-1, ESCON, D1 Video, FE, GE, 1 Gbps FC, and ITS per 2.5 Gbps wavelength
- Industry leading Service Aggregation—up to 4 ports of 2 Gbps Fibre Channel, up to 8 ports of Fibre Channel, FICON, or Gigabit Ethernet or up to 40 ports of ESCON per wavelength
- Capacity—Fiber capacity is maximized when used with a 32-wavelength system providing up to 256 Fibre Channel, FICON, or Gigabit Ethernet services or up to 1280 ESCON services on a single fiber pair.
- Scalability—up to 32 wavelengths ranging from 2.5 Gbps to 10 Gbps
- Multiservice Interfaces—Customers have a single scalable platform that supports low speed copper legacy services such as T1/E1 (PBX interconnect), OC-3/STM-1, Fast Ethernet and D1 Video, in addition to high density ESCON, GE, and 1Gb FC services

- Service mixing—Ability to mix a combination of Fibre Channel, FICON, ESCON, and Gigabit Ethernet services over the same wavelength
- Complete Amplification Solution—Enables enterprises and service providers to further expand their optical DWDM networks over greater distances when used with EDFA optical amplifiers

For More Information

See the Cisco ONS 15530 Website: <http://www.cisco.com/go/ons15530>

Cisco ONS 15540 Extended Services Platform (ESPx)

The ONS 15540 Extended Services Platform with external cross connect capability (ESPx) is a highly modular, flexible, and scalable next generation DWDM platform that integrates data networking, storage area networking (SAN), TDM Synchronous Optical Network (SONET) and Synchronous Digital Hierarchy (SDH) technologies over an ultra high bandwidth, intelligent optical infrastructure that can support any packet, over any wavelength on any platform.



- Flexible Multi-Protocol Support—The Cisco ONS 15540 offers both variable rate transparent and fixed rate multi-protocol transponders that feature user selectable SFPs and support a variety of industry standard data rates between 16Mbps to 2.5Gbps as well as 10Gb Ethernet
- Scalable, flexible, and modular architecture in a high-density compact footprint—Provides superior operational support and network expansion on an as needed basis through its hot swappable modular lines cards, transponders, and optical multiplexers
- Simple Network Consolidation and Comprehensive Multi Service Support provided by the available ONS 15540 2.5GB and 10GbE transponders
- Optical, Service, and Application Level Performance Monitoring—provides industry-leading supports for service level agreements (SLAs)
- High Availability for mission critical networks—Provides 99.999% availability for demanding Managed Network Service Providers and enterprise business continuance applications, with hardware redundancy and automatic protection switching to protect against fiber cuts and equipment failures
- Multi-Service Integration—Transports ESCON, FICON, 1Gb/2GB Fibre Channel for SAN, Fast and Gigabit Ethernet, and 10 Gb Ethernet for data networking, and SONET/SDH at OC-3/STM1, OC-12/STM4, and OC-48/STM12

Key Features:

- Compact modular design with external connectorization: External Direct Connect system from Line card to OADMs; Optional cross connect and fiber management system
- Tunable Type 2 Transponders with Multi Protocol Small form Factor Pluggables (SFPs): Variable data rate support between 16Mbps to 2.5Gbps; 16 Tunable transponders support 32 channels for reduced sparing costs; Multi-protocol SFP Support—Now featuring Variable Rate SFPs and support for IBM Sysplex/GDPS applications.
- Standards based Management support for SNMP, Ciscoview and CTM

- Protection Switch Module provides highly cost effective solution for fiber trunk protection
- Standards based Optical architecture conforming to ITU G.692 100GHz channel spacing
- This system has been qualified by IBM for Geographically Dispersed Parallel Sysplex (GDPS), and by EMC for Symmetrix Synchronous support as tested in their E-LAB environment

For More Information

See the Cisco ONS 15500 Series Website: <http://www.cisco.com/go/ons15500>

Cisco ONS 15216 Metro DWDM Series

The Cisco ONS 15216 Metro DWDM solution supercharges wavelength services by supporting up to 32 ITU-grid wavelengths, and provides unprecedented transport flexibility with optical filtering, Optical Add/Drop Multiplexing (OADM), Optical Performance Monitoring and Amplification. It allows service providers to deliver more services per wavelength and more wavelengths per fiber.



The Cisco ONS 15216 Metropolitan Dense Wavelength-Division Multiplexing (DWDM) FlexLayer filter solution is an ultraflexible filter architecture that allows cable multiple system operators and service providers to build “pay-as-you-grow” networks with the flexibility to upgrade in-service without preprovisioning channels that are not required. This approach creates a more desirable per-wavelength cost.

The FlexLayer architecture allows for deployment of point-to-point, point-to-multipoint, ring, bus, and tree-and-branch architectures. These networks can be deployed as unprotected or protected networks, and they may also be deployed in transmit-only applications for broadcast networks. This flexibility is inherent in the design of the FlexLayer architecture.

For More Information

See the ONS 15216 Metro DWDM System Website:

<http://www.cisco.com/en/US/products/hw/optical/ps1996/ps1999/index.html>

Cisco ONS 15327 SONET Multiservice Provisioning Platform

The Cisco ONS 15327 combines high-bandwidth capacity and service diversity in a very compact footprint, enabling service providers to achieve increased economics at the metro edge. Based on the same technology as the industry leading Cisco ONS 15454, the ONS 15327 supports high optical bandwidth and has the ability to support OC-3/12/48, DS1, DS3, 10/100 and Gigabit Ethernet. With the ability to support either customer located or metro access, the ONS 15327 includes comprehensive STS- and VT-level bandwidth management and integrated data switching. The Cisco ONS 15327 also may serve as a digital cross-connect without the need for additional equipment. It aggregates and switches TDM and Ethernet services, and can be managed using the Cisco Transport Controller (CTC) element management system and CTM for network management.



For More Information

See the ONS 15300 Website: <http://www.cisco.com/go/ons15300>

Cisco ONS 15310-CL SONET Multiservice Provisioning Platform



By extending the metropolitan (metro) edge to customer premises and providing direct high-speed LAN connectivity, the Cisco ONS 15310-CL allows service providers to cost-effectively offer scalable, high-speed data services over their transport networks. For the enterprise, the Cisco ONS 15310-CL offers the efficiency, scalability, and high availability to meet the bandwidth demands of the mission-critical e-business infrastructure. These features are available without implementing new technology or upgrading the existing transport network infrastructure.

Optimized for the customer location, this evolutionary platform is based on the same technology as the industry leading Cisco ONS 15454 and the ONS 15327, supporting high optical bandwidth and can support DS1, DS3 and layer 1/2 10/100 Ethernet. The Cisco ONS 15310-CL also provides comprehensive STS- and VT-level bandwidth management and integrated data switching.

The integrated multiservice optical networking functions of the Cisco ONS 15310-CL dramatically reduce service-delivery costs. Packaged in a 1RU, industrially temperature-hardened Network Equipment Building Standards (NEBS) 3-compliant assembly, the Cisco ONS 15310-CL delivers fast provisioning and low initial cost, while maintaining a small footprint and low operational cost throughout the life of the product and can be managed using the CTC element management system and CTM for network management.

For More Information

See the ONS 15300 Website: <http://www.cisco.com/go/ons15300>

Cisco ONS 15302/15305 SDH Multiservice Access Platforms (MSAP)



The Cisco ONS 15302/ONS 15305 Multiservice CPE and Aggregation solutions are ultra-compact integrated systems that offer cost effective solutions. These platforms provide native multiservice capabilities (i.e., TDM interfaces, multiplexing and Ethernet data interfaces).

The ONS 15302 CPE platform provides the STM-1 uplink (protected or unprotected STM-1 optical uplink, 1+1 MSP, future SNCP) and E1 customer interfaces (12 E1 ports) interfaces. It provides native Ethernet customer access via 4-port 10/100BaseT module that supports full layer 2 capacity, bridging, VLANs, spanning tree, and priority management. An optional WAN module is available for point to multi-point applications.

The ONS 15305 Aggregation platform provides the following TDM interfaces— protected or unprotected optical interfaces (8 port S-1.1 optical module, 2 port S-4.1 optical module, 1 port S-16.1 optical module, 1+1 MSP, SNCP, 2F MS-SPRing for STM-16) and electrical customer interfaces (8 and 63 port E1 modules and a 6 port E3/DS3 module). This product also provides native Ethernet customer access via an 8-port 10/100BaseT module and a 2-port GigE module (supports full layer 2 capacity, bridging, VLANs, spanning tree, and priority management). An optional WAN module is available for point to multi-point applications.

For More Information

See the ONS 15300 Website: <http://www.cisco.com/go/ons15300>

Cisco Transport Manager (CTM 6.0) (Optical Element/Network Management)

Cisco Transport Manager (CTM) is an integrated optical element management system for Cisco ONS 15000 series optical networking platforms. CTM manages configuration, fault isolation, performance, and security for Cisco optical network elements. With integrated support for SONET, SDH, DWDM and Ethernet, along with open interfaces to operations support systems (OSS), CTM delivers the full power of Cisco's wide range of advanced optical systems to today's network operators and enterprises.

CTM is a powerful tool that increases the productivity of the network operations staff. The system provides GUI-based point-and-click network management. As such, CTM has a low learning curve while providing advanced management capabilities such as A-to-Z circuit provisioning. Explorer-style navigation, the extensive use of wizards, tool tips, legends, and online help make it easy for an operator to perform tasks quickly and efficiently. Many otherwise tedious, time-consuming, and error-prone tasks can be fully streamlined using CTM's features.

CTM works for small networks, but can also scale up to 2500 network elements and 100 concurrent clients per server. This solution is appropriate for small enterprise networks as well as large service provider networks. CTM is extremely cost-effective (uses industry-standard platforms such as Sun Solaris, Oracle8i, and Microsoft Windows). CTM fits smoothly into most companies' information technology environments. Using scalable Sun server platforms, customers can minimize up-front investment, but still accommodate growth by adding additional processors, memory, and disk space.

For More Information

See the CTM Series Website:

<http://www.cisco.com/en/US/products/sw/opticsw/ps2204/index.html>



IOS® Software and Network Management

Cisco IOS® Software and Network Management at a Glance

Product	Features	Page
Cisco IOS Software	Advanced network infrastructure software supported on a wide range of Cisco products • A common IP fabric, functionality, and command-line interface (CLI) across network infrastructures • A vast array of key routing, multiservice, traffic shaping, security/firewall, and traffic monitoring features that run on many platforms	9-3
Cisco IOS Technologies	IOS Technologies supporting Cisco's product infrastructure and solutions	9-6
CiscoWorks Small Network Management Solution	Web-based network management solution designed for small to medium businesses (SMB) • Device auto-discovery using SNMP simplifies setup and reduces startup time • Standards-based, multi-vendor management • Event management and topology mapping application • Includes Cisco's popular CiscoView Element Management Tool	9-11
CiscoWorks LAN Management Solution	Provides key applications needed to manage Cisco switch-based Enterprise campus networks. This bundle includes: • Campus Manager • Device Fault Manager • Resource Manager Essentials • CiscoView • Internetwork Performance Manager	9-12
CiscoWorks VPN/Security Management Solution	Combines general device management tools for configuring, monitoring, and troubleshooting enterprise networks with powerful security solutions for managing VPNs, firewalls, and network and host-based intrusion prevention systems (IPS). • Firewall Management • IPS Management, network and host-based • Host Intrusion Prevention System Management • VPN Router Management • Security Monitoring • VPN Monitoring • Operational Management	9-13
CiscoWorks Security Information Management Solution and CiscoWorks Security Information Management Solution Engine	A solution that collects, analyzes, and correlates security event data from across the enterprise—letting you detect and respond to security events as they occur. The Solution Engine requires minimal setup and installation. • Event monitoring of multivendor security environments • Extensive reporting for operators and high-level administrators • Risk assessment information to understand overall vulnerability of critical network assets within the enterprise • Forensics tools to investigate attacks	9-15
CiscoWorks IP Communication Operations Manager and CiscoWorks IP Communications Service Monitor	Provides a unified view of the entire IP Communications infrastructure presenting the current operational status of each element of the IP Communications network: • Continuously monitors the current operational status of different IP Communications elements such as Cisco CallManager, Cisco CallManager Express, Cisco Unity, Cisco Unity Express, and Cisco IP Contact Center, as well as Cisco gateways, routers, and IP phones • Provides diagnostic capabilities for faster trouble isolation and resolution	9-16
CiscoWorks Voice Manager for Voice Gateways	Enables the management and monitoring of devices used as gateways between analog voice equipment and the data network. • Enhanced capabilities to configure and provision voice ports • Create and modify dial plans on voice-enabled Cisco routers for voice over IP (VoIP), voice over Frame Relay (VoFR), and voice over ATM (VoATM) network deployments	9-19

Product	Features	Page
CiscoWorks QoS Policy Manager	Enables centralized administration and automated deployment of bandwidth reservation and prioritization policies for network applications across converged voice, video and data networks. • Differentiates services of Web applications, voice traffic, and business-critical applications • Validate QoS settings and results with traffic analysis • Real time and historical reports for QoS troubleshooting • Control roles and privileges for policy view, modification and deployment	9-20
CiscoWorks Wireless LAN Solution Engine and CiscoWorks Wireless LAN Solution Express	• Centralized, systems-level application for managing and controlling an entire Cisco Aironet WLAN 9-22 infrastructure. • Ease Cisco Aironet wireless LAN (WLAN) deployments, enhance network security, maximize network availability, and reduce operating expenses	
Cisco Catalyst 6500 Series Network Analysis Modules 1 and 2	NAM is an integrated, network monitoring instrumentation and Web-browser based traffic analysis solution for the Catalyst 6500 based environments. It enables greater visibility into traffic at all layers of the network by providing real time traffic analysis and troubleshooting capabilities.	9-23
Cisco Network Analysis Module for Branch Routers - Cisco 2600/3660/3700 Series Network Analysis Module	The Cisco 2600/3660/3700 Series NAM is an integrated traffic-monitoring network module that enables network managers to gain application-level visibility into network traffic with the ultimate goal of improving performance, reducing failures, and maximizing return on network investments.	1-1
Cisco Secure Access Control Server for Windows and Cisco Secure Access Control Server Solution Engine	Highly scalable, high-performance access control server that provides a comprehensive identity networking solution and secure user experience for Cisco intelligent information networks. An important component of the Cisco Identity-Based Networking Services (IBNS) architecture. It supports several access connection types, including wired and wireless LANs, dialup, broadband, content, storage, VoIP, firewalls, and VPNs. It helps ensure enforcement of assigned policies by allowing network administrators to control: • Who can log in to the network • Privileges each user has in the network • Security audit or account billing information that is recorded	5-22
Cisco IOS Tools	List of essential IOS web-based tools available on Cisco.com	9-11
Product Ordering Website	To place an order, visit the Cisco Ordering Website: http://www.cisco.com/en/US/ordering/index.shtml	

Cisco IOS® Software

The family of Cisco IOS Software products (T, S and XR) enables Cisco to meet the network infrastructure requirements of Large and Small Enterprises, as well as Service Providers because each software product is architected to meet the needs of a given customer type. Customers benefit from shared intellectual property and technologies between family members. All Cisco IOS products deliver the consistent look and feel.

Key Features

- **Availability**—Resilient features enable applications, devices and network infrastructure components to automatically recover from errors and adapt when network infrastructure changes occur
- **Security**—Protects network devices allowing them to remain operative, and thereby controllable even during an attack. It protects your network traffic and ensures the safety of your business infrastructure
- **Manageability**—Embeds the management instrumentation required to manage your devices, technologies and network centrally via software or manually.
- **Flexibility**—Adapts to evolving requirements
- **Scalability**—Allows networks to expand in size and capability, while preserving hardware and network investments

IOS Feature Set Packaging

A feature set is a bundle of the features available for a release. Multiple feature sets can be used with a release. Cisco IOS 12.3 standard feature sets are eight sets of features that were added to legacy feature sets to simplify the feature selection process. The Cisco IOS 12.3 standard feature sets consolidate the number of features to simplify feature selection. For easier migration to Cisco IOS 12.3, Cisco offered customers either legacy images or the new feature sets on some platforms. The Cisco 1800, 2800 and 3800 support only the Cisco IOS 12.3 standard feature sets (no legacy feature sets).

The Cisco IOS 12.3 feature sets are also available on Release 12.3T for Cisco 3640 and will soon be available in Releases 12.2S on all hardware products that support Cisco IOS Software.

New Naming Convention Categories

Category	Naming Convention
Base	Entry level image, (i.e., IP Base)
Services	Addition of IP Telephony Service, MPLS, Net Flow, Voice over IP (VoIP), Voice over Frame Relay (VoFR), and ATM (i.e., SP Services, Enterprise Services)
Advanced	Addition of VPN, Cisco IOS Firewall, 3DES encryption, SSH, Cisco IOS IPSEC and Intrusion Prevention Systems (IPS) (i.e., Advanced Security, Advanced IP Services)
Enterprise	Additional of multi-protocols, including IBM, IPX, AppleTalk (i.e., Enterprise Base, Enterprise Services)

Cisco IOS Software Family

- Cisco IOS T—Satisfies the performance and price needs for a broad range of platforms and markets, but focuses on small to mid-range routers. Maintenance or feature changes to T releases usually occur every 14 to 16 weeks.
- Cisco IOS S—Focuses on enterprise and service provider edge markets and meets the high availability requirements of enterprises and service providers, and the 12.2S train has an innovative infrastructure helps ensure high availability along with new functionality key to these markets.
- IOS XR—Focuses on high-end routing and is optimized for terabyte-scale service provider core and massively distributed processing. It has a modular architecture that supports dual processors.

Types of Trains

Cisco train, or “major release,” is a series of releases that evolve from a common code base and numbering system. Trains, such as 12.4, are built from previous generation trains (12.3 and 12.3T). A higher numbered release incorporates the maintenance improvements that were made on a lower numbered release in the product line.

Product	Latest Train	Description
T	12.2	Derived from the last, lower-numbered T maintenance release from which it inherits features. For example, Release 12.4(1) is derived from Release 12.3T(14), and is functionally equivalent to Release 12.3T(14). Cisco generally does not add additional features to mainline trains.
	12.3	
	12.4	
	12.3T	Routinely enhanced with new features.
	12.4T	
S	12.2S	Supports Enterprise and Service Provider Edge platforms.
	12.2SB	Supports service provider edge and broadband aggregation.
	12.2SX	Supports service provider edge and enterprise networks: high-end switching, IP/MPLS edge, and metro Ethernet services.
	12.2SE	Supports mid-range & low-end switching.
	12.2EW/12.2SG	Supports mid-range and low-end switching. Cisco is changing the name of Release 12.2EW to 12.2SG to reflect its membership in the S product line.
XR	3.0	Powers the Cisco Carrier Routing System. Designed for always on, self-healing, and self-defending operation while scaling system capacity up to 92Tbps.

Cisco IOS T and S Product Line Release Types

- Maintenance releases—A maintenance release is a scheduled revision of Cisco IOS that introduces new features or bug fixes or both.
- Rebuild releases—Rebuilds are Cisco IOS releases that fix defects on an accelerated schedule.
- General Deployment (GD) releases—A legacy Cisco IOS Software release reaches GD certification after meeting strict standards and when its quality has been demonstrated by extensive deployment in diverse networks over extended periods of time. GD Release Criteria—wide exposure, minimal changes (no new features, minimal need for improvements or defect fixes); GD Life Cycle—After a release attains GD status, every subsequent revision of the release is also GD. When a release is declared GD, it enters a restricted maintenance phase; GD Releases—Cisco IOS 12.1 and 12.2 have attained GD status
- Special releases—A special release is a release that Cisco introduces to quickly meet market demands for new features or additional platform support. The new features and platforms offered by these releases benefit customers who need to deploy new network equipment or services.

Bug Synchronizing and Feature Integration

Bug fixes to maintenance releases on a mainline train are synchronized with subsequent maintenance releases on the child T train. New features are integrated into the T train only—the mainline train receives bug fixes only.

Train Lifecycle Milestones

At some point in the life of a release, Cisco stops selling, maintaining, and supporting it. Customers need to know when support for releases stop so they can migrate to supported releases.

- Cisco IOS Release Lifecycle Milestones:
 - FCS—First Customer Shipment—Release is first available to customers on Cisco.com.
 - EoS—End of Sale—Release can no longer be ordered, downloaded, or included in manufacturing shipments. Release no longer gets regularly scheduled bug fixes. Releases are removed from Software Center when they reach End of Sale.
 - EoE—End of Engineering—Requests for rebuilds to fix serious bugs no longer accepted.
 - EoL—End of Life—Release is no longer supported by Cisco Technical Assistance Center.

Milestones in the Life of a Train

The following table briefly describes the train lifecycle milestones

Milestone	Sold through Sales Channels	Bug Fixes ¹	TAC Support	Download from Cisco.com
FCS	Yes	Regularly Scheduled	Yes	Yes
EoS	No	Rebuild	Yes	No
EoE	No	No	Yes	No
EoL	No	No	No	No

1. Each new release receives regularly scheduled bug fixes prior to reaching EoS. Cisco considers requests for rebuilds of a discontinued release.

Interim Builds

An interim build is software from an internal Cisco engineering build process that TAC gives customers to use on a temporary basis to address a specific issue. Contact TAC for assistance in replacing the interim build.

Important Communications about Releases

Software advisories describe problems with Cisco IOS Software that are platform specific or occur under unusual circumstances, and therefore, do not affect most customers.

Critical Release Communication Types

Security Advisory	Product Security Incident Response Team (PSIRT) issues a security advisory to alert customers to security issues that directly impact Cisco products and to help customers repair the Cisco product.
Security Notices	Cisco issues Security Notices about issues that require a response to information posted to a public forum, or to make recommendations to mitigate general problems affecting network stability.
Deferral Advisory	Cisco issues a deferral advisory to announce the removal of a Cisco IOS image from Cisco's offerings and to introduce a replacement image. A deferral advisory is most often issued to correct a defect. At the time that the deferral of a Cisco IOS image is advised, customers are strongly urged to migrate from the affected image to the replacement image.

Cisco IOS Software Licenses

A Cisco IOS Software License includes the right to use a particular software release and feature set on one router. In some cases, additional value-added functionality is provided in software images but not covered by the “base” Cisco IOS Software License. The right to use these features is offered through a feature license. A feature license conveys the right to use a feature, but cannot add a feature to a software release that does not support it. For example, purchasing a WAN Packet Protocols/Net flow license for software Release 11.0 will not upgrade the software to support Net flow. Choose a software release that supports all required features, then choose any necessary feature licenses.

Cisco IOS Software Upgrade Licenses

Customers who purchase “base” software licenses may wish to increase their software functionality or feature set at some point. The following illustrates the benefits of software feature licenses as well as how they are used to provide increased software functionality.

Example	Description
Upgrade A Feature Set (Single)	If a customer purchased a Router with Enterprise software, earlier and now wants to upgrade to Enterprise with Firewall/IDS, the customer has one of two options • With a valid maintenance contract, the customer may purchase the software feature license, Firewall/IDS Upgrade, to upgrade from Enterprise to Enterprise with Firewall/IDS. • Without maintenance, the customer will need to purchase a new software license Enterprise/FW/IDS, in order to upgrade from Enterprise to Enterprise with Firewall/IDS.
Upgrade Feature Sets (Multiple)	If a customer purchased a router with IP software, product code and now wants to upgrade to Enterprise with IPSEC 56, the customer has one of two options • With a valid maintenance contract, the customer will need to purchase two software feature license: IP to Enterprise and IPSEC 56 Upgrade. The first license upgrades from IP to Enterprise, and the second upgrades from Enterprise to Enterprise/IPSEC 56. • Without maintenance, the customer will need to purchase a new software license, Enterprise/IPSEC 56, in order to upgrade from IP to Enterprise with IPSEC 56.

Cisco IOS® Technologies

Broadband

As Service Providers scale their offerings to meet growing demand for Broadband subscriptions, they must simplify operations and increase individual subscriber revenue. Broadband aggregation dynamically binds subscribers to critical, revenue-generating services that carriers must deliver. Cisco delivers Broadband Aggregation capabilities on a comprehensive set of routers and software to meet a variety of network requirements—from WiFi hotspots to carrier-grade aggregation—for millions of Digital Subscriber Line (DSL) and Cable subscribers. This portfolio enables Service Providers to cost-effectively deploy broadband services across a variety of access technologies including Cable, DSL, Ethernet, WiFi, and mobile networks. Cisco IOS Software solutions provide access-independent service selection, as well as subscriber and service management functionality that is widely deployed on broadband networks.

For More Information

See the Cisco IOS Broadband Website:
http://www.cisco.com/en/US/products/ps6549/products_ios_technology_home.html

High Availability

Cisco offers a comprehensive approach to High Availability Networking (HAN) that ensures non-stop access to mission-critical applications. Cisco HAN takes a network-wide approach in that it delivers a solution for combining reinforced network infrastructure, real-world design, realigned operations, real-time management, and relentless support.

For More Information

See the Cisco IOS High Availability Website:

http://www.cisco.com/en/US/products/ps6550/products_ios_technology_home.html

IPv6

- Internet Protocol version 6 (IPv6) is supported by over 20 platforms offering the most extensive product line in the industry
- Integrated into Cisco IOS
- Numerous innovative and advanced IPv6 features including co-existence technologies (tunneling, 6PE, NAT-PT), security (AAA, IPsec, IOS Firewall) quality of service and multicast
- IPv6 performance supported in software (CEFv6/dCEFv6) and hardware assisted forwarding across numerous platforms with the largest installed base in the world

For More Information

See the Cisco IOS IPv6 Website: **<http://www.cisco.com/go/ipv6>**

IP Mobility

Cisco IOS Software has supported Mobile IP since IOS Releases 12.0(1)T. Key Mobile IP components include Home Agent, Foreign Agent, Mobile Node, and Mobile Networks. Mobile IP, an IETF standard (RFC 2002), allows a host device to be identified by a single IP address even though the device may move its physical point of attachment from one network to another.

The mobile workforce needs the ability to communicate with customers, partners, and fellow workers anywhere, anytime and have access to relevant business applications, tools to carryout business effectively. Enterprise mobility is about providing ubiquitous connectivity to the mobile user, independent of the devices and access technologies. Utilizing Mobile IP, regardless of movement between different networks, connectivity at the different points is achieved seamlessly without user intervention. Roaming from a wired network to a wireless or wide-area network is also done with ease. Mobile IP is part of both IPv4 and IPv6 standards.

For More Information

See the Cisco IOS IP Mobility Website:

http://www.cisco.com/en/US/products/ps6551/products_ios_technology_home.html

IP Multicast

Multicast is a bandwidth-conserving technology that reduces traffic by simultaneously delivering a single stream of information to thousands of corporate recipients and homes. Applications that take advantage of multicast technologies include video conferencing, corporate communications, distance learning, and distribution of software, stock quotes, and news.

Key Features

- Efficiently deploys and scales distributed group applications across the Internet
- Creates a ubiquitous, enterprise-wide content distribution model
- Solves traffic congestion problems
- Allows service providers to deploy value-added streaming services that leverage their existing infrastructure.

For More Information

See the Cisco IOS IP Multicast Website:

http://www.cisco.com/en/US/products/ps6552/products_ios_technology_home.html

IP Routing

Cisco IOS Software offers the industry's widest variety of enterprise and service provider-class IP routing protocols.

- Protocols provide integration, and are integrated with each other, enabling the convergence of data, voice and video networking
- Routing Technology's adaptive behavior enables customer networks to evolve with user needs. And, it is critical to scalability allowing networks to expand in size and capability, while preserving hardware and network investments
- Advanced features help simplify operations and reduce cost of ownership including Optimized Edge Routing (OER), On Demand Routing (ODR), Routing Information Protocol (RIP), Interior Gateway Routing Protocol (IGRP), Open Shortest Path First (OSPF), IP Multicast, Integrated IS-IS, Enhanced Interior Gateway Routing Protocol (EIGRP), and Border Gateway Protocol (BGP)

For More Information

See the Cisco IOS IP Routing Website:

http://www.cisco.com/en/US/products/ps6599/products_ios_protocol_group_home.html

Management Instrumentation

Cisco IOS Software provides a rich set of features to efficiently manage networks regardless of scale while leveraging the Intelligence Information Network (IIN) strategy. The benefits from the embedded management instrumentation functionality include: lowered operating and maintenance costs, rapid incorporation of new network services and devices, management of the network as an integrated system, reduced downtime by adaptive fault management, and measurable and billable differentiated services.

Key Features

- NetFlow—efficiently provides a key set of services for IP applications, including network traffic accounting, usage-based network billing, network planning, security, Denial of Service monitoring, and network monitoring
- Simple Network Management Protocol (SNMP)—an application-layer protocol that provides a standardized framework and a common language for monitoring and managing devices in a network
- IP Service Level Agreements (SLAs)—enable customers to assure new business-critical IP applications, including IP services that utilize data, voice, and video, in an IP network. Users can verify service guarantees and increase network reliability by validating network performance, proactively identifying network issues

For More Information

See the Cisco IOS Management Instrumentation Website:

http://www.cisco.com/en/US/products/ps6555/products_ios_technology_home.html

Multiprotocol Label Switching (MPLS)

Cisco IOS MPLS is the protocol that Enterprises and Service Providers use on next-generation intelligent networks that deliver a wide variety of advanced, value-added services over a single infrastructure. This economical solution can be integrated seamlessly over any existing infrastructure, such as IP, Frame Relay, ATM, or Ethernet. MPLS enables efficient utilization of existing networks to meet growth demands and provide rapid fault correction of link and node failure. The technology also helps deliver highly scalable, differentiated end-to-end IP services with simpler configuration, management, and provisioning for both Internet providers and subscribers.

For More Information

See the Cisco IOS MPLS Website: <http://www.cisco.com/go/mpls>

Quality of Service (QoS)

QoS is the set of techniques to manage network resources. Achieving the required QoS by managing delay, delay variation (jitter), bandwidth, and packet loss parameters on a network becomes the secret to a successful end-to-end business solution. QoS is the set of techniques to manage network resources.

Key Features

- Differentiated Services—Performs Packet classification based on IP precedence and QoS group setting; Bandwidth management through various rate limiting features
- Integrated Services—RSVP typically perform admission control, Classification, policing, and scheduling of data packets on a per-flow basis and keeps a database of information for each flow
- Network-Based Application Recognition—Intelligent classification engine used with class-based features; Protocol Discovery and analysis

For More Information

See the Cisco IOS QOS Website:

http://www.cisco.com/en/US/products/ps6558/products_ios_technology_home.html

Security

Cisco IOS Software delivers a sophisticated set of security capabilities for a comprehensive, layered security approach throughout your network infrastructure.

Key Features

- Intrusion Prevention System (IPS)—an in-line, deep-packet inspection-based solution helping to mitigate a wide range of internal or external network attacks by accurately identifying, classifying, and stopping malicious or damaging traffic in real-time
- Firewall—provides stateful and application-based filtering; dynamic per-user authentication and authorization; defense against network attacks; Java blocking; and real-time alerts
- IPsec VPN—provides network data encryption at the IP packet level, offering a robust security solution that is standards-based
- SSL VPN—Cisco IOS WebVPN provides SSL VPN remote-access connectivity from almost any Internet-enabled location using only a Web browser and its native SSL encryption enabling companies remote-access connectivity to corporate resources from any Internet-enabled location
- Access Control Lists (ACL)—deny or permit network access by classifying traffic by source and destination addresses, the upper layer protocol, or other Layer 3 and Layer 4 information
- Trust and Identity—includes core technologies enabling network traffic security: Authentication, Authorization, and Accounting (AAA), PKI, SSH, SSL, and 802.1x.
- URL Filtering—prevents users from accessing websites based on a defined policy. It can be a static configured list of allowed or disallowed sites, or it can incorporate a third-party filter server

For More Information

See the Cisco IOS Security Website:

http://www.cisco.com/en/US/products/ps6586/products_ios_technology_home.html

Voice

Cisco IOS Software provides a wide variety of IP-based hardware and solutions to make VoIP applications secure, reliable, scalable, manageable, and cost-effective. These services scale to meet the needs of an enterprise campus, branch office, small office, or other environment.

Key Features

- Features support gateway functions allowing legacy systems to connect to the IP telephony environment
- Compression/decompression algorithms—squeeze voice traffic into a fraction of the space used in traditional circuit-based telephone systems
- Call management—deliver rich functionality to the phone system
- Programming interfaces allow applications to communicate with the voice services infrastructure
- Gatekeeper functions are also provided for points of control for voice and video components attached to an IP network, including IP telephony devices, IP PSTN gateways, and H.323 videoconferencing endpoints

Key Cisco IOS Tools

Tool	Description
Software Selector	Finds required features for a given technology. http://tools.cisco.com/ITDIT/ISTMAIN/servlet/index
Feature Navigator	Finds releases that support a set of software features and platforms, and compares releases. http://tools.cisco.com/ITDIT/CFN/jsp/index.jsp
Software Advisor	Compares IOS releases, matches IOS and CatOS features to releases, and finds out which software release supports a given hardware device. http://www.cisco.com/cgi-bin/front.x/Support/HWSWmatrix/hwswwmatrix.cgi
Cisco IOS Upgrade Planner	Finds releases by platform, release, and feature set, and downloads images of Cisco IOS Software. http://www.cisco.com/cgi-bin/Software/iosplanner/Planner-tool/iosplanner.cgi?
Bug Toolkit	Searches for known bugs based on software version, feature set, and keywords. http://www.cisco.com/cgi-bin/Support/Bugtool/launch_bugtool.pl

For More Information on Cisco IOS Software

See the Cisco IOS Software Website: <http://www.cisco.com/go/ios>

See the Cisco IOS Reference Website: <http://www.cisco.com/warp/customer/620/1.html>

Cisco Network Management Overview

Cisco is transforming traditional network management by focusing on the strengths of Internet-based architectures for greater accessibility and simplification of network management tools, tasks, and processes. Cisco's network management strategy calls for a Web-based model with the following characteristics:

- Simplification of tools, tasks, and processes
 - Web-level integration with NMS platforms and general management products
 - Capable of providing end-to-end solutions for managing routers, switches, and access servers
 - Creation of a management intranet by integrating discovered device knowledge with CCO and third-party application knowledge
-

CiscoWorks Small Network Management Solution (SNMS)

CiscoWorks Small Network Management Solution (SNMS) is a windows-based network management solution for small- to medium-sized organizations. CiscoWorks SNMS allowing users to monitor and set thresholds for each from an easy-to-interact-with topology map. In addition to providing basic troubleshooting and monitoring for more than one hundred general network devices, CiscoWorks SNMS also manages the information regarding configuration, Cisco IOS and Catalyst software, and inventory of up to forty critical Cisco backbone devices.

When to Sell

Sell This Product

CiscoWorks Small Network Management Solution

When a Customer Needs These Features

- Simple integrated installation, autodiscovery and automated import of devices using SNMP
- Standards-based multi vendor management
- Small and medium-sized enterprise and commercial customers needing to provide basic management of branch, campus, and WAN networks with multivendor devices
- Reduce the time and complexity of keeping the networks' configuration, software version and connectivity optimized

Key Features

- Discovers and monitors multivendor network hardware, printers, servers, and workstations; inventory information is discovered quickly and a mapping wizard graphically displays customizable hierarchical maps of networked devices
- Task wizards reduce the complexities and time associated with rolling out changes in the network
- Supports customized monitoring of services such as FTP and HTTP
- Real-time monitoring and tracking of key information and data relating to device performance, traffic, and environment, with metrics such as utilization percentage, frames transmitted and received, errors, and a variety of other device-specific indicators
- Management Information Base (MIB) compiler and browser for managing third-party SNMP devices

Specifications

Feature	CiscoWorks Small Network Management Solution
Server	Hardware: IBM PC-compatible system with 500 MHz Intel Pentium processor; Memory: 512 MB (minimum); Disk Space: Available drive—2 GB Software: Windows Server 2003 Standard and Enterprise Editions;Windows 2000 Professional Server and Advanced Server with Service Pack 3 (SP3); (English and Japanese)
Client	Hardware: IBM PC-compatible system with 500 MHz Intel Pentium processor; Disk Space: IBM PC-compatible system with 500 MHz Intel Pentium processor; Memory: 512 MB Software: Windows Server 2003, Standard and Enterprise Editions; Windows 2000 Professional Server and Advanced Server with SP3; Windows XP with SP1 or SP2; (English and Japanese)

Selected Part Numbers and Ordering Information

CiscoWorks Small Network Management Solution	
CWSNM-1.5-K9	CiscoWorks SNMS 1.5.1 for Windows with 40-device restricted usage license and 1 server-installation license; includes WhatsUp Gold 8.0, Resource Manager Essentials 3.5, CiscoView 6.0, and Common Services 2.2. Supports Windows Server 2003 (Standard and Enterprise Editions).
CWSNM-1.5-WINUP-K9	CiscoWorks SNMS 1.5.1 upgrade for CiscoWorks Windows 5.0, 6.0, and 6.1 customers.
CWSNM-MAR05-MR-K9	Minor update kit for existing CiscoWorks SNMS 1.x customers. Windows Server 2003 (Standard and Enterprise Editions) supported.

For More Information

See the CiscoWorks SNMS Website: <http://www.cisco.com/go/wrsnms>

CiscoWorks LAN Management Solution

The CiscoWorks LAN Management Solution (LMS) is a suite of management applications designed to simplify the day-to-day tasks of managing, troubleshooting and maintaining a Cisco network. The applications launch from a common desktop and share device information, credentials, and grouping information, thereby providing a consistent and integrated interface for management. Device and network-level details are collected centrally, giving network operators and administrators quick and easy access to configure, monitor and troubleshoot from a standard lightweight-based Web browser.

When to Sell

Sell This Product	When a Customer Needs These Features
LAN Management Solution	• A centralized system for sharing device information across all LMS applications, improving manageability and system-wide awareness of changes in the network • Network discovery, topology views, end-station tracking and VLAN management • Real-time network fault analysis with easy-to-deploy device specific best-practice templates • Hardware and software inventory management, centralized configuration tools, and Syslog monitoring • Network response time and availability monitoring and tracking • Real-time device, link, and port traffic management, analysis, and reporting • Flexible license model allowing CiscoWorks LMS to be effectively utilized in a wide range of enterprise deployments without restricting functionality or expandability

Key Features

- Detailed network inventory reporting; automated software and configuration distribution; audit of adds, moves, and changes
- Simplified fault policy deployment; correlation of real-time faults; intelligent analysis of errors
- Graphical and table views of topology; VLAN connectivity, paths, and user tracking; ATM management
- LAN and WAN response time, latency, and jitter analysis; selectable threshold tracking between pairs of devices
- Graphical views of devices with color-coding for at-a-glance operational, performance, and status monitoring

Specifications

Feature	Description
Server	Hardware: Single CPU 1 GHz or equivalent, SPARC IIIi or x86; Disk Space: 80 GB; Memory: 2 GB (CiscoWorks LMS 2.5 Enterprise) or 4 GB (LMS 2.5 Large Enterprise) Software: Windows 2000 Server and Advanced Server with SP4; Windows Server 2003 Standard and Enterprise Editions; Solaris 2.8, 2.9; (English and Japanese) Network Management Solution (NMS) Integration: CiscoWorks CiscoView with Network Management Integration Module (NMIM) and Device Fault Manager supports integration with Hewlett Packard OpenView Network Node Manager 6.4; IBM Tivoli NetView 7.1 and 7.1.4 are supported by Dynamic Contact Replication (DCR) and NMIM
Client	Hardware: Single CPU 1 GHz or equivalent, SPARC IIIi or Windows; Disk Space: 80 GB; Memory: 512 MB Software: Windows 2000 Professional, Server and Enterprise Server; Windows Server 2003 Standard and Enterprise Editions; Windows XP; Solaris 2.8, 2.9; (English and Japanese); Windows-Internet Explorer 6.0 SP1, Netscape 7.1, Mozilla 1.7; Solaris-Netscape 7.0, Mozilla 1.7; Java Plug-in 1.4.2_04 (CiscoWorks Campus Manager and Internetwork Performance Monitor only)

Selected Part Numbers and Ordering Information¹

LAN Management Solution

CWLMS-2.5-UR-K9

CiscoWorks LMS 2.5.1 Large Enterprise for Windows and Solaris, with unrestricted device license and one server-installation license.

CWLMS-2.5-R-K9

CiscoWorks LMS 2.5.1 Enterprise for Windows and Solaris, with 300-device restricted license and one server-installation license.

LAN Management Solution Upgrades

CWLMS-2.5-URUP-K9

Upgrade from CiscoWorks LMS 1.x or RWAN 1.x to CiscoWorks LMS 2.5.1 Large Enterprise for Windows and Solaris server systems with unrestricted device license and one server-installation license.

(Note: CiscoWorks SNMS 1.x customers must upgrade to CiscoWorks LMS 2.5.1 Enterprise through part number CWLMS-2.5-RUP-K9 before purchasing the conversion upgrade to CiscoWorks LMS 2.5.1 Large Enterprise through part number CWLMS-2.5-RCONV-K9.)

CWLMS-MAY03-MR-K9

Maintenance kit for customers that purchased LMS 2.X and want new device support and code updates; kit includes support for both Windows and Solaris platforms; includes updates to all LMS 2.X components. Customers with LMS 1.X will not be able to install DFM 1.2 (use PN# CWLMS-2.2-UP-K9 to purchase the LMS 2.2 upgrade with DFM)

1. This is only a small subset of all parts available via URL listed under "For More Information". Some parts have restricted access or are not available through distribution channels. Resellers: For latest part number and pricing info, see the *Distribution Product Reference Guide* at: <http://www.cisco.com/dprg> (limited country availability).

For More Information

See the LAN Management Solution Website: <http://www.cisco.com/go/lms>

CiscoWorks VPN/Security Management Solution (VMS)

CiscoWorks VPN/Security Management Solution (VMS), an integral part of the SAFE Blueprint for network security, combines Web-based tools for configuring, monitoring, and troubleshooting enterprise VPNs, firewalls, and network and host-based IPS. It offers the ability to monitor remote access links, and IPSec based site to site VPN links. VMS is a Web-based solution that provides a "dashboard" view of critical VPN resources and their performance, VPN hardware and configuration and troubleshooting reports.

When to Sell

Sell This Product

CiscoWorks VPN/Security Management Solution

When a Customer Needs These Features

- Complete management of a SAFE infrastructure environment
- Configuring and monitoring VPN, PIX, IOS routers, and IDS devices.
- Monitoring large remote access, and site-to-site hub and spoke VPNs from a single management console and focus on problem areas and performance.

Key Features

- Management and Monitoring Centers—Offering features such as a consistent user experience, auto update, command and control workflow, and role-based access control
- VPN Monitor—Allows network administrators to collect, store, and view information on IPSec VPN connections for remote-access or site-to-site VPN terminations. Multiple devices can be viewed from an easy-to-use dashboard that is configured using a Web browser
- Cisco IPS Host Sensor Console—Provides real-time analysis and reaction to network hacking attempts by identifying an attack and preventing access to critical server resources before any unauthorized transactions occur
- RME—Provides the tools needed to manage Cisco devices.
- CiscoWorks Server—Provides the common management desktop services and security across the CiscoWorks family of solutions. It also provides the foundation for integrating with other Cisco and third-party applications
- Support for secure browser communications with CiscoView and RME sessions via SSL and SSH protocol

Specifications

Feature	CiscoWorks VPN/Security Management Solution
Server	Hardware: IBM PC-compatible computer with 1-GHz or faster Pentium processor; Sun UltraSPARC 60 MP with 440-MHz or faster processor; Sun UltraSPARCIII (Sun Blade 1000 Workstation or Sun Fire 280R Workgroup Server) Software: Windows 2000 Professional, Server, and Advanced Server (Service Pack 3); Sun Solaris 2.8
Server	Hardware: IBM PC-compatible computer with 300-MHz or faster Pentium; Solaris SPARCstation or Sun Ultra 10 Software: Windows 2000 Server or Professional Edition with Service Pack 3, or Windows XP SP1 with Microsoft VM; Solaris 2.8 Browser: Internet Explorer 6.0 Service Pack 1, on Windows operating systems; Netscape Navigator 4.79, on Windows 2000 Server or Professional Edition with Service Pack 3, or Windows XP; Netscape Navigator 4.76 on Solaris 2.8

Selected Part Numbers and Ordering Information

CiscoWorks VPN/Security Management Solution

CWVMS-2.2-UR-K9	CiscoWorks VMS 2.2 Windows (unrestricted device usage; 1 server installation license); Includes: Management Center for Firewalls 1.1, for IDS Sensors 1.2, for Cisco Security Agents 4.0, and for VPN Routers 1.1, CiscoWorks Auto Update Server 1.1, CiscoWorks Monitoring Center for Security 1.2, CiscoWorks VPN Monitor 1.2, RME 3.5, and Common Services 2.2 ¹
CWVMS-2.2-WINR-K9	CiscoWorks VMS 2.2 Windows (20-device restricted usage; 1 server installation license); Includes: Management Center for Firewalls 1.1, for IDS Sensors 1.2, for Cisco Security Agents 4.0, and for VPN Routers 1.1, CiscoWorks Auto Update Server 1.1, CiscoWorks Monitoring Center for Security 1.2, CiscoWorks VPN Monitor 1.2, RME 3.5, and Common Services 2.2
CWVMS-2.2-WUPGR-K9	Upgrade from CSPM 2.x (unrestricted license), CiscoWorks VMS 1.X or 2.X (restricted licenses) to CiscoWorks VMS 2.2 for Windows and Solaris (unrestricted license)
CWVMS-2.2-UPGUR-K9	Upgrade from CSPM 2.X (restricted license) or CiscoWorks VMS 1.X (restricted license) to CiscoWorks VMS 2.2 for (20-device restricted license) ¹
CWVMS-DEC03URMR-K9	Minor update kit for existing VMS 2.X Windows and Solaris (unrestricted license) ¹
CWVMS-DEC03RMR-K9	Minor update kit for existing VMS 2.X Windows Only (20-device restricted license) ¹

1. Contains Windows-only versions of Management Center for Firewalls 1.1, for IDS Sensors 1.2, for Cisco Security Agents 4.0 and for VPN Routers 1.1, CiscoWorks Auto Update Server 1.1, and CiscoWorks Monitoring Center for Security 1.2

For More Information

See the CiscoWorks VPN/Security Management Solution Website:

<http://www.cisco.com/go/vms>

CiscoWorks Security Information Management Solution and CiscoWorks Security Information Management Solution Engine

The CiscoWorks Security Information Management Solution (SIMS) is a solution for effectively gathering and analyzing the overwhelming amount of security event data that companies receive through growing numbers of multi-vendor security devices and systems installed throughout their network. SIMS is based on technology from netForensics and incorporates powerful features to help companies better manage their growing security infrastructure and effectively monitor millions of event messages, without additional staff. The hardware based solution engine provides regional scalability for customers with small to medium deployments and the software only solution provides global scalability for larger deployments.

CiscoWorks SIMS helps focus security teams on real threats, providing them with both the information and tools needed to respond quickly, accurately, and efficiently. Rules Based Correlation, Incident Resolution Management, Vulnerability Correlation, Enterprise Security Portal, Quick Connect modules provide enhanced correlation, customization, reporting capability of security events monitoring and management.

When to Sell

Sell This Product

CiscoWorks Security Information Management Solution

When a Customer Needs These Features

- Security regulatory compliance and security policy enterprise-wide enforcement
- Managed security services for medium or large or global enterprises
- Security monitor with advanced visualization for quickly detecting known and unknown threats
- Manage and correlate events from SAFE and multi-vendor security environments

Key Features

- Regulatory compliance, auditing, and event monitoring of multi-vendor security environments
- Extensive reporting for operators and high-level administrators
- Risk assessment information to understand overall vulnerability of critical network assets within the enterprise
- Event correlation for rapidly detecting emerging attacks that may not be apparent from a single event

Specifications

Feature ¹	CiscoWorks Security Information Management Solution
Ciscoworks SIMS Version	3.3
Software Compatibility	For updates, Version 3.2.1.x must be installed and running
Supported Platforms	Red Hat Linux Advanced Server 2.1, 3.0, Solaris 8, 9.0
System Requirements	Java 2 Runtime Environment (JRE) 1.4.2_05 Java WebStart
Minimum Disk Space	270 MB
Minimum Hardware Requirements	
Processor	Linux: Dual Intel Pentium 4; 1.5 GHz (server class); Solaris: Dual UltraSPARC-IIi; 444 MHz (server class)
Memory	4-GB total system memory
Free Disk Space	18 GB (refer to the section "Disk Partitions" in the CiscoWorks SIMS Quick Start Guide)
Storage Device	CD-ROM
Software Packages	Linux: Anonymous FTP, development libraries, and kernel development; Solaris 8: Refer to Quick Start documentation

1. For complete Server and Client Hardware and Software requirements, please refer to the Product Literature or Installation documentation for specific details and requirements; Information on the CiscoWorks Security Information Management Solution Engine can be found in the Product Literature

Selected Part Numbers and Ordering Information¹

CiscoWorks Security Information Management Solution

CWSIM-ELTE-SL-K9	Enterprise Lite Bundle for Linux
CWSIM-ELTE-SS-K9	Enterprise Lite Bundle for Solaris
CWSIM-EPCK-SL-K9	Enterprise Pack Bundle for Linux
CWSIM-EPCK-SS-K9	Enterprise Pack Bundle for Solaris
CWSIM-ENG-N-K9	Distributed Engine n Additional Module
CWSIM-EQC-K9	Quick Connect n Additional Module
CWSIM-ESP-K9	Enterprise Security Portal n Additional Module
CWSIM-IRM-K9	Incident Resolution Management n Additional Module
CWSIM-RBC-K9	Rule Based Correlation Engine n Additional Module
CWSIM-VCE-K9	Vulnerability Correlation Engine n Additional Module

1. This is only a small subset of all parts available via URL listed under “For More Information”. Some parts have restricted access or are not available through distribution channels.

For More Information

See the CiscoWorks Security Information Management Solution Website:

<http://www.cisco.com/go/sims>

CiscoWorks IP Communications Operations Manager

CiscoWorks IP Communications Operations Manager monitors and evaluates the current status of both the IP Communications infrastructure and the underlying transport infrastructure in the network. It uses open interfaces such as SNMP and HTTP to remotely poll data from different devices in the IP Communications deployment. It does not deploy any agent software on the devices being monitored and thus is non-disruptive to system operations.

When to Sell

Sell This Product

**CiscoWorks IP
Communications Operations
Manager**

When a Customer Needs These Features

- Need real-time notifications and report the status of the network monitored to a higher-level entity (typically a manager of managers)
- Management of multi-site and multi-cluster IP Communications environments
- Reduced administrative overhead by sharing device and credential information with other CiscoWorks tools deployed in the enterprise

Key Features

- **Service-Level View**—A real-time auto-refresh display provides status information about all the IP Communications clusters and the elements of the clusters in the deployment. Drill down views show the operational status of each element of the IP Communications cluster and its interrelationships with other elements
- **Real-Time Alerts**—Built-in intelligence understand the role of every device in an IP Communications deployment and appropriately monitors those devices for any kind of faults or outages. These alerts are presented to the user through the Alerts and Events Display, which refreshes periodically to present the most up-to-date status of the IP Communications deployment monitored. The Phone Status Display provides instant access to signaling-related and IP connectivity-related outage information
- **Diagnostic Tests**—A rich set of diagnostic tests can be used to aid in trouble isolation and resolution. Synthetic tests serve to replicate user activity (getting dial tone, making phone calls, leaving voice mail, and creating/joining conference calls). Phone status tests can be used to determine the current operational status of the IP phones in terms of signaling and IP connectivity. Node-to-node tests use the services of IP service level agent in Cisco routers to simulate traffic in the network and then determine network characteristics such as reachability status, response time, latency, jitter, packet loss, and network quality

- **Service-Quality Reporting**—The service-quality alerts monitor and provide detailed information about IP connectivity and IP phones or IP Communications devices to enable further troubleshooting. It is also possible to initiate a probable path trace between the endpoints to identify any potential problems in intermediate nodes that could influence service quality
- **Reports**—The historical alert, event, and service-quality reports maintain information about all the alerts and events reported for up to 30 days. The customizable reports let network managers pick and choose what type of information they want and create a daily report that is available for review via e-mail or the CiscoWorks IP Communications Operations Manager GUI

Specifications

Feature	CiscoWorks IP Communications Operations Manager
Server	Up to 1,000 phones—Hardware: Server platform; Processor: Pentium 4 processor > 2 GHz; Memory: 2 GB RAM; Swap file: 4 GB swap file; Disk Space: 40 GB hard drive; Software: Windows 2003 Server Up to 10,000 phones—Hardware: Server platform; Processor: Pentium 4 or Xeon processor > 3 GHz; Memory: 4 GB RAM; Swap file: 8 GB swap file; Disk Space: 40 GB hard drive; Software: Windows 2003 Server Up to 30,000 phones—Hardware: Server platform; Processor: Dual Pentium 4 or Xeon processor > 3 GHz; Memory: 4 GB RAM; Swap file: 8 GB swap file; Disk Space: 40 GB hard drive; Software: Windows 2003 Server
Client	Hardware: Any PC/server platform Processor: Pentium 4 processor > 1 GHz Memory: 512 MB RAM Swap file: 1 GB swap file Software: Microsoft Internet Explorer 6.0, Mozilla 1.0 Windows XP Home, Windows XP Professional, Windows 2003 Server

Selected Part Numbers and Ordering Information

CiscoWorks IP Communications Operations Manager

CWIPCOM-1.0-K9	CiscoWorks IP Communications Operations Manager 1.0
CWIPCOM-1.0-1K-K9	CiscoWorks IP Communications Operations Manager 1.0 with restricted usage license up to 1000 phones.
CWIPCOM-1.0-2K-K9	CiscoWorks IP Communications Operations Manager 1.0 with restricted usage license up to 2000 phones.
CWIPCOM-1.0-5K-K9	CiscoWorks IP Communications Operations Manager 1.0 with restricted usage license up to 5000 phones.
CWIPCOM-1.0-10K-K9	CiscoWorks IP Communications Operations Manager 1.0 with restricted usage license up to 10,000 phones.
CWIPCOM-1.0-UR-K9	CiscoWorks IP Communications Operations Manager 1.0 with restricted usage license up to 30,000 phones.
CWIPCOM-1.0-UP-K9	CiscoWorks IP Communications Operations Manager 1.0 - Upgrade from ITEM and VHM.
CWIPCOMUP10-UR-K9	CiscoWorks IP Communications Operations Manager 1.0 UPG - Upgrade from ITEM and VHM with restricted usage license up to 30,000 phones.
CWIP-1.0-MB-1K-K9	CiscoWorks IP Communications Management Mid-Market Bundle (CiscoWorks IP Communications Operations Manager 1.0 - maximum 1000 phones + CiscoWorks IP Communications Service Monitor 1.0 + CiscoWorks 1040 Sensor A 1.0 - 2 pack)

For More Information

See the CiscoWorks IP Communications Operations Manager Website at:

<http://www.cisco.com/en/US/products/ps6535/index.html>

CiscoWorks IP Communications Service Monitor

CiscoWorks IP Communications Service Monitor 1.0 provides a low-cost, reliable method of monitoring and evaluating the quality of IP Communications-based telephony to help optimize the user experience. It continuously monitors active calls supported by Cisco IP Communications elements, including the Cisco CallManager, Cisco Unity, Cisco CallManager Express, Cisco Unity Express, Cisco MeetingPlace software, Cisco IP Contact Center, Cisco gateways, and routers, and provides real-time notification if the voice quality of a call fails to meet a user-defined quality metric.

When to Sell

Sell This Product
CiscoWorks IP Communications Service Monitor

When a Customer Needs These Features

- Need a real-time management information and diagnostic tools to help ensure an efficient deployment and subscriber satisfaction
- Need immediate monitoring and assessment of the quality of IP-based calls without elaborate setup or complicated installation issues

Key Features

- Evaluates the performance of the actual RTP data streams of the monitored calls
- Uses the standards-based ITU G.107 R-factor to evaluate and score the monitored call; IEEE 802.3af PoE; FCC Class B compliant and can be installed in any office environment
- Provides a distributed, scalable solution to facilitate cost-effective quality-of-voice monitoring
- Voice-quality alerts present the information in a specialized Service Quality Alerts display that provides a launching point for diagnostic tools and processes

Specifications

Feature	CiscoWorks IP Communications Service Monitor
Server	Hardware: Server platform Processor: Pentium 4 processor, 2 GHz or greater Memory: 2 GB RAM Swap file: 4 GB swap file Disk Space: 40 GB hard drive Software: Windows 2003 Server
Client	Hardware: Any PC/server platform Processor: Pentium 4 processor, 1 GHz or greater Memory: 512 MB RAM Swap file: 1 GB swap file Software: Windows XP Home, Windows XP Professional, Windows 2003 Server

Selected Part Numbers and Ordering Information

CiscoWorks IP Communications Service Monitor	
CWIPCSA-1040	CiscoWorks IP Communications Service Monitor
CWIPCSA-1.0-2PK	CiscoWorks IPC Sensor A 1.0 package with 2 sensors
CWIPCSA-1.0-6PK-K9	CiscoWorks IPC Sensor A 1.0 package with 6 sensors and CiscoWorks IPCSM 1.0 Software
CWIPCSM-1.0-K9	CiscoWorks IPC Service Monitor 1.0
CWIP-1.0-MB-1K-K9	CiscoWorks IP Communications Management Mid-Market Bundle (CiscoWorks IP Communications Operations Manager 1.0 - maximum 1000 phones + CiscoWorks IP Communications Service Monitor 1.0 + CiscoWorks 1040 Sensor A 1.0 - 2 pack)

For More Information

See the CiscoWorks IP Communications Service Monitor Website at:
<http://www.cisco.com/en/US/products/ps6535/index.html>

CiscoWorks Voice Manager for Voice Gateways

CiscoWorks Voice Manager 3.0 is client-server, Web-based software that provides enhanced capabilities to configure and provision voice ports, create and modify dial plans, and collect call history data on voice-enabled Cisco routers for voice-over-IP (VoIP), voice-over-Frame Relay (VoFR), and voice-over-ATM (VoATM) network deployments.

When to Sell

Sell This Product

Voice Manager for Voice Gateways

When a Customer Needs These Features

- Need to facilitate provisioning of voice ports for multiple types of protocols and efficiently deploys complex dial plans for Cisco IOS devices.
- Logical partitioning of large voice networks for operational simplicity and the display of a unified view of the entire voice deployment
- Automated configuration to reduce manual entry and duplicate data entry errors when performing such operations across multiple gateways, gatekeepers, Cisco CallManager Express, and SRST devices
- Tool to manage rapid network expansion and timely and efficient reconfiguration of the voice network

Key Features

- Voice configuration support for new Cisco devices: Cisco 2801, 2811, 2821, 2851, 3825, and 3845 routers and Cisco IAD2420, IAD2430, IAD2431, and IAD2432 integrated access devices
- Identification and management of voice gateways with Cisco CallManager Express and Survivable Remote Site Telephony (SRST) capabilities
- Support for CiscoWorks Common Services Release 3.0
- Support for the latest Cisco IOS Software version on all CiscoWorks Voice Manager 2.3 supported devices

Specifications

Feature	CiscoWorks Voice Manager for Voice Gateways
Server Hardware Requirements	Windows—Hardware: IBM PC-compatible system with 1 GHz or faster Intel Pentium processor; Color monitor; CD-ROM drive; Memory: 512 MB, 10 MB in Windows temporary directory; Available drive space: 8 GB; Paging file space equal to double the amount of memory (RAM); NTFS file system required for secure operation; At least 16 MB in Windows temporary directory (%TEMP%); Minimum 1024 MB swap space Solaris—Hardware: Sun SPARC IIIi based system; Color monitor; CD-ROM drive; Memory: 512 MB; Available drive space: 8 GB, Minimum 1024 MB swap space
Server Software Requirements	Windows—System Software: (One of the following) Windows 2000 Professional with Service Pack 3 (SP3) or SP4; Windows 2000 Server with SP3 or SP4; Windows 2000 Advanced Server with SP3 and SP4; Windows 2003 Server Standard Edition; Windows 2003 Server Enterprise Edition; Additional Software: Common Services 3.0; NTFS file system (required for security option) Solaris—System Software: Solaris 2.8 or Solaris 2.9; Additional Software: Common Services 3.0
Client Hardware Requirements	Windows—Hardware: IBM PC-compatible system with at least a 300-MHz Pentium processor; Memory: 256 MB Solaris—Hardware: Sun SPARC IIIi based system running Solaris 2.8 or 2.9; Color monitor with video card set to 256 colors; Memory: 256 MB
Client Software Requirements	Windows—Software: (One of the following) Windows 2000 with SP3 or SP4; Windows XP with SP1 or SP2; Windows 2003 Server and Enterprise Edition; Color monitor with video card set to 256 colors; Browser: (One of the following) Netscape Navigator 7.1; Microsoft Internet Explorer 6.0 (v6.0.2600) or Internet Explorer 6.0 with SP1 (v6.0.2800) for Windows 2000 and Windows XP and Internet Explorer 6.0.3790.0 for Windows 2003 Server; Java Virtual Machine (JVM) 5.0.0.3802 and later, and Java Plug-in Solaris—Software: Browser: Netscape Navigator 7.0

Selected Part Numbers and Ordering Information¹

CiscoWorks Voice Manager for Voice Gateways

CWVM-3.0-R-K9	CiscoWorks Voice Manager 3.0, Restricted, for small deployments (up to 500 voice ports)
CWVM-3.0-UR-K9	CiscoWorks Voice Manager 3.0, Unrestricted
CWVM-3.0-RUP-K9	Upgrade from CiscoWorks Voice Manager 2.x to the 3.0 Restricted version
CWVM-3.0-URUP-K9	Upgrade from CiscoWorks Voice Manager 2.x and 3.0 Restricted to the 3.0 Unrestricted version

1. This is only a small subset of all parts available via URL listed under "For More Information". Some parts have restricted access or are not available through distribution channels.

For More Information

See the Voice Manager for Voice Gateways Website at:

<http://www.cisco.com/en/US/products/sw/cscowork/ps2432/index.html>

CiscoWorks QoS Policy Manager

QoS Policy Manager allows you to centrally define and administer IOS and CAT parameters needed for differentiating network traffic. This ensures high availability and predictable performance for business-critical which rely on advanced voice and video services. Cisco QoS Policy Manager (QPM) 3.2 is a key enabler of end-to-end QoS for converged networks. It delivers differentiated services across network infrastructures with converged voice, video, and data applications, simply by taking advantage of Cisco IOS and Catalyst OS Software with built-in QoS mechanisms in LAN and WAN switching and routing equipment.

When to Sell

Sell This Product

Cisco QoS Policy Manager

When a Customer Needs These Features

- End-to-end QoS configuration and automated, reliable policy deployment, while eliminating device-by-device command streams
- Rules-based policies that combine static and dynamic port applications and host system traffic filters
- QoS Policy Manager's services, including congestion management & avoidance, and traffic-shaping
- Efficiently translate policies to specific QoS config commands, ensuring consistency across domains
- Validate policies prior to deploying them quickly and reliably to LAN and WAN policy domains
- Generate Web-based reports on QoS policies deployed in the network

Key Features

- Measure traffic throughput for top applications and service classes plus troubleshoot problems with real-time and historical QoS feedback
- Centrally define roles and permissions and take advantage of Cisco Secure ACS to control privileges for policy view, modification and deployment for different device groups
- Partition network into administrative and deployment domains and use policy libraries for global QoS configuration. Modify, scale and monitor IOS AutoQoS voice policies on routers
- Use the secure, Web-based GUI for accurate end-to-end QoS configuration and automated, reliable policy deployment, while eliminating device-by-device command streams; Setup wizard intelligently determines QoS policies and properties at each network point that requires IP telephony QoS configuration based on Cisco AVVID design recommendations; Achieve business-driven service levels across the enterprise network by configuring traffic classification and allowing QoS policy enforcement through Cisco devices
- Expose QoS policy conflicts, uploads existing device configurations, presents CLI syntax that corresponds to policies, allows previewing configuration changes before deployment, supports incremental ACL updates, defines ACL ranges, and restores or applies a previous version of a policy database and backup to a remote server
- An integral part of Cisco content networking, QPM 3.1 delivers the appropriate service levels to business-critical applications by supporting the extension of IP packet classification to include application signature, Web URLs, and negotiated ports
- Enables congestion management, congestion avoidance, and bandwidth control by selectively activating QoS mechanisms on intelligently grouped LAN and WAN interfaces and providing support for external APIs to trigger event-based policy distribution
- Extend security by defining access control policies to permit or deny transport of packets into or out of device interfaces

- Supports device inventory import from CiscoWorks Resource Manager Essentials shortens configuration time for devices targeted for policy enforcement and QoS monitoring

Specifications

Feature	Cisco QoS Policy Manager
Server	Hardware: PC-compatible computer with 1-GHz or faster Pentium processor, CD-ROM drive, 10BASE-T or faster connection, 1-GB RAM, 9-GB available disk drive space, 2-GB virtual memory, Server Operating System Software: Windows 2000 Professional, Server, and Advanced Server (Service Pack 3 or 4)
Client	Hardware—PC-compatible computer with 300-MHz or faster Pentium processor Client Operating System— Windows 2000 (Server or Professional Edition) with Service Pack 3 or 4, or Windows XP SP1 (Server or Professional) Client Browser—Windows with SP 3 and Windows XP clients: Microsoft Internet Explorer 6.0 or Internet Explorer 6.0 with Service Pack 1, Netscape Navigator 7.1; Windows clients with SP 4: Microsoft Internet Explorer 6.0 with Service Pack 1, Netscape Navigator 7.1
Port Usage	CiscoWorks QPM on Windows uses the following ports, in addition to the ports used by CiscoWorks Common Services: 51099 Java Naming and Directory Interface (JNDI) lookup port; 51199 JRMP lookup port; 51299 Admin page port; 10033 (Windows) Database port; 51899 Protocol Data Packet (PDP) port

Selected Part Numbers and Ordering Information¹

Cisco QoS Policy Manager

CWQPM-3.2-UR-K9	CiscoWorks QoS Policy Manager 3.2 for Windows; unrestricted device usage license; 1 server installation license; includes CiscoWorks QPM 3.2 and CiscoWorks Common Services 2.2 with Cisco View 5.5
CWQPM-3.2-R-K9	CiscoWorks QoS Policy Manager 3.2 for Windows; 20-device restricted usage license; 1 server installation license; includes QPM 3.2 and Common Services 2.2 with Cisco View 5.5
CWQPM-3.2-URUP-K9	Major upgrade kit for existing CiscoWorks QPM unrestricted versions 1.x and 2.x and 20-device restricted usage versions 3.0, 3.1 and 3.2 to CiscoWorks QPM unrestricted version 3.2. Customers with QPM 3.0 or 3.1 restricted or unrestricted device usage licenses that do not have a Software Application Support contract need to order the CiscoWorks QPM 3.2 minor update kit using part numbers CWQPM-3.2-R-MR-K9 or CWQPM-3.2-UR-MR-K9 respectively.
CWQPM-3.2-UR-MR-K9	Minor update kit for existing CiscoWorks QPM 3.X unrestricted device usage customers; includes updates to existing components
CWQPM-3.2-R-MR-K9	Minor update kit for existing CiscoWorks QPM 3.X restricted device usage customers; includes to existing components

1. This is only a small subset of all parts available via URL listed under “For More Information”. Some parts have restricted access or are not available through distribution channels. Resellers: For latest part number and pricing info, see the *Distribution Product Reference Guide* at: <http://www.cisco.com/dprg> (limited country availability).

For More Information

See the Cisco QoS Policy Manager Website: <http://www.cisco.com/go/qpm>

CiscoWorks Wireless LAN Solution Engine and CiscoWorks Wireless Solution Engine Express

CiscoWorks WLSE is a centralized network management solution for managing the Cisco Aironet WLAN infrastructure. The CiscoWorks WLSE Express is the integrated security and management solution for managing Cisco Aironet access points located in one or multiple locations. CiscoWorks WLSE and CiscoWorks WLSE Express both provide comprehensive air/radio frequency (RF) and device-management capabilities in ways that simplify deployment, reduce operational complexity, and provide administrators with visibility into the WLAN.

When to Sell

Sell This Product

CiscoWorks Wireless LAN Solution Engine and CiscoWorks Wireless LAN Solution Express

When a Customer Needs These Features

- Comprehensive air/radio frequency (RF) and device-management
- Simplified deployment and reduced operational complexity with visibility into the WLAN
- For remote branch office deployments with limited WAN bandwidth, an integrated and embedded user authentication and authorization server

Key Features

- Management component of the Cisco Systems Distributed WLAN Solution
- Zero-touch deployment—Device (access point/bridge)-specific settings such as host name, radio power, and channel can be imported into CiscoWorks WLSE Express via a comma-separated value (CSV) file, with unique Ethernet MAC address mapping allowing CiscoWorks WLSE Express to automatically apply device-specific settings without touching each access point
- Enhancements to the Site Survey Wizard—Specific RF settings such as channel and power can be applied to devices based on a schedule
- Friendly to rogue reclassification—Periodically monitor for changes in the status of rogue access points that are marked “friendly” to alert the administrator in case location or received signal strength indicator (RSSI) values change
- CiscoWorks WLSE Express—Supports popular Extensible Authentication Protocol (EAP) types, including Cisco LEAP, Protected EAP (PEAP), EAP-Flexible Authentication via Secure Tunneling (EAP-FAST), and EAP-Transport Layer Security (EAP-TLS); Standard version—Supports up to 500 users which supports 50 Cisco Aironet access points; License-upgraded version—Supports up to 1000 users which supports 100 Cisco Aironet access points

Selected Part Numbers and Ordering Information¹

CiscoWorks Wireless LAN Solution Engine and CiscoWorks Wireless LAN Solution Express

CWWLSE-1130-19-K9	Wireless LAN Solution Engine 2.12; includes the Cisco 1130 hardware platform and wireless LAN management software version 2.12
CWWLSE-2.12-SWUP-K9	Software only upgrade kit for Wireless LAN Solution Engine 1.x customers wanting to upgrade their Cisco 1130-19 hardware to Wireless LAN management software version 2.x to 2.12
CWWLSE-2.12-MR-K9	Maintenance release kit for customers with existing CiscoWorks 1130-19 for WLSE hardware that need CiscoWorks WLSE Software 2.12 and do not have a Cisco Software Application Support (SAS) contract.
CWWLSE-1030-K9	Includes the CiscoWorks 1030 for WLSE Express hardware platform and CiscoWorks WLSE Express Software 2.12.
CWWLSE-2.12EXLCUK9	CiscoWorks WLSE Express Software 2.12 license upgrade option from 50 Cisco Aironet access points with a maximum of 500 users to 100 Aironet access points with a maximum of 1000 users.
CWWLSE-2.12EX-MR-K9	Maintenance release kit for customers with existing CiscoWorks 1030 for WLSE express hardware that need CiscoWorks WLSE Express Software 2.12 and do not have a Cisco Software Application Support (SAS) contract.

For More Information

See the CiscoWorks Wireless LAN Solution Engine Website:

<http://www.cisco.com/go/wlse>

See the CiscoWorks Wireless LAN Solution Engine Express Website:

<http://www.cisco.com/en/US/products/ps6379/index.html>

Cisco Catalyst 6500 Series Network Analysis Module 1 and 2(with NAM software version 3.3)

The Cisco Network Analysis Module (NAM) 1 and 2, second generation high performance network analysis modules for the Cisco Catalyst 6500 Series provides network monitoring instrumentation and web-browser based traffic analysis for Catalyst based AVVID environments. The NAM enables network managers to gain application-level visibility into network traffic with the ultimate goal of improving performance, reducing failures, and maximizing returns on network investment. It comes with an embedded, Web-based traffic analyzer, which provides full scale remote monitoring and troubleshooting capabilities that are accessible through a Web browser.

When to Sell

Sell This Product

**Catalyst 6500 Series
Network Analysis Module
1 and 2 (with NAM
software version 3.3)**

When a Customer Needs These Features

- Needs Application-Level visibility built into the network
- Provides network managers visibility into all layers of network traffic
- Monitoring in a scalable switching environment that supports traffic monitoring in a scalable switching environment
- Offers investment protection by interfacing with both the bus and the crossbar switching fabric-based architectures in the Cisco Catalyst 6500 Series

Key Features

- Available in two models—NAM-1 and NAM-2—to meet diverse network analysis needs in a scalable switching environment running up to gigabit speeds.
- Provides application-level Remote Monitoring (RMON) functions based on RMON2 and other advanced Management Information Bases (MIBs)
- Collects statistics on both data and VoIP streams flowing through the host switch using the Switch Port Analyzer (SPAN) and NetFlow Data Export features of the Cisco Catalyst 6500 Series
- Collects data from remote switches using the remote SPAN (RSPAN) feature of the Cisco Catalyst 6500 and 4000 Series switches
- Easy to deploy and use at LAN aggregation where they can see most of the traffic, at service points where performance is critical and at important access points where quick troubleshooting is required
- Application monitoring can be done using RMON, RMON2, and several extended RMON MIBs, which can detect the applications on the network and provide detailed information about how these applications utilize the bandwidth, which hosts access those applications, and which client/server pairs generate the most traffic
- Performance management provides valuable information about the delays in server responses to client requests

Selected Part Numbers and Ordering Information¹

Cisco Catalyst 6500 Series Network Analysis Module 1 and 2(with NAM software version 3.3)

WS-SVC-NAM-1

Catalyst 6500 Series Network Analysis Module 1. To order the NAM individually, please use the spare part number of WS-SVC-NAM-1=

WS-SVC-NAM-2

Catalyst 6500 Series Network Analysis Module 2. To order the NAM individually, please use the spare part number of WS-SVC-NAM-2=

1. Some parts have restricted access or are not available through distribution channels.

For More Information

See the Cisco NAM Website:

<http://www.cisco.com/en/US/products/hw/modules/ps2706/ps5025/index.html>



Storage Networking

Storage Networking at a Glance

Product	Features	Page
Cisco MDS 9000 Family Multilayer Directors and Fabric Switches	• Industry-leading port densities across the Cisco MDS 9000 Family • Intelligent network services including VSANs, Port, Channels, embedded diagnostics and advanced security • Embedded Fabric Manager, open API and integration with CiscoWorks RME and other third party SAN management platforms • Multiprotocol support including Fibre Channel, FICON, Fibre Channel over IP (FCIP) and iSCSI. (Cisco MDS 9500 Series and Cisco MDS 9200 Series) • Open platform for hosting third party storage applications (Cisco MDS 9500 Series and Cisco MDS 9200 Series) via a FAIS based intelligent storage API (iSAPI) and SANTap Protocol • High availability directors with non-disruptive software upgrades, stateful processor restart/failover and redundancy of all major components	10-2
Additional Storage Networking Solutions	• Cisco MDS 9000 Port Analyzer Adapter encapsulates Fibre Channel frames into Ethernet packets for low cost Ethernet based storage/SCSI protocol analysis • Cisco Coarse Wave Division Multiplexing (CWDM) Extended Distance Solution offers Small Form-Factor Pluggable (SFP) optics in 8 different wavelengths, enabling 2/1 Gbps Fibre Channel and 1 Gbps Ethernet ports to be directly connected to passive add/drop CWDM multiplexers. • Cisco 7200 FCIP Port Adapter for long distance SAN connectivity over an IP network infrastructure • Cisco ONS 15530/15540/15454 are Dense Wave Division Multiplexing (DWDM) platforms that provide transport across dark fibre for business continuance applications	10-7
Product Ordering Website	To place an order, visit the Cisco Ordering Website: http://www.cisco.com/en/US/ordering/index.shtml	

Cisco MDS 9000 Family Multilayer Directors and Fabric Switches



The Cisco MDS 9000 SAN switch series delivers multiple layers of integrated intelligence including multi-protocol integration (Fibre Channel, iSCSI, FCIP, FICON), intelligent network services (VSANs/InterVSAN Routing, embedded diagnostics, role-based security, encryption), an open platform for hosting intelligent storage services (virtualization, backup, data migration/replication), and comprehensive, integrated management. With these industry-leading innovations, companies can achieve a lower total cost of ownership and improved business continuance for their storage infrastructure. Consisting of the Cisco MDS 9500 Series of Multilayer Directors, the semi-modular Cisco MDS 9200 Series Multilayer Fabric Switches, and the fixed configuration MDS 9100 Series Multilayer Fabric Switches and the MDS 9020 Fabric Switch, the Cisco MDS 9000 Family provides a full line of products to meet requirements for storage networks of all sizes and architectures.

When to Sell

Sell This Product

When a Customer Needs These Features

Cisco MDS 9500 Multilayer Directors

- Maximum port densities—Up to 224 Fibre Channel ports in a single 9-slot and 6-slot chassis
- High availability—non-disruptive software upgrades, stateful processor restart/failover and redundancy of all major components
- High performance—1.44 Terabit/sec backplane to provide 10Gbps future readiness
- Multiprotocol support—integration of Fibre Channel, FICON, FCIP, and iSCSI in single platform for optimal consolidation and SAN extension
- Hosting intelligent storage applications (network-based virtualization, volume management, data replication, backup, and snapshot capabilities)
- Optimal for data center consolidation
- Modularity and flexibility for future growth

Cisco MDS 9200 Multilayer Fabric Switches

- Moderate port densities - Up to 48 Fibre Channel ports in a single 2-slot chassis
- Multiprotocol support - integration of Fibre Channel, FCIP, and iSCSI in single platform for optimal consolidation and SAN extension
- Hosting intelligent storage applications (network-based virtualization, volume management, data replication, backup, and snapshot capabilities)
- Modularity and flexibility for future growth

Cisco MDS 9100 Series Fabric Switches

- Lower port count—20 ports for Cisco MDS 9120; 40 ports for Cisco MDS 9140
- 1RU for space-constrained environments
- Fibre Channel-only connectivity
- Entry-level SAN where price per port more important than future modularity/flexibility

Cisco MDS 9020 Fabric Switch

- Compact 1-RU form factor, with 20 4-Gbps FC ports
- Priced and built specifically to meet the needs to a small and medium-sized customer or entry-level SAN
- Integrated, GUI-based Fabric Management for ease of use and deployment
- A cost-effective, scalable solution with full compatibility with the entire Cisco MDS product family

Key Features

- **High-Availability Director**—combines non-disruptive software upgrades, stateful process restart and failover, and full redundancy of all major components; Supports up to 528 1/2/4-Gbps autosensing Fibre Channel ports in a single chassis and up to 1584 Fibre Channel ports in a single rack-up to 2.2 Tbps of internal system bandwidth ensures smooth integration of future high-speed interfaces as new standards emerge; Delivers fully redundant crossbar bandwidth
- **High-Performance**—Supports up to 16 links in a single port channel-links can span any port on any module within a chassis for added scalability and resilience
- **Security**—Supports RADIUS authentication, SNMPv1, SNMPv2, role-based access control, ACLs, SSH Protocol and WWN-based zoning; Includes TACACS+ authentication, SNMPv3, Secure File Transfer Protocol (SFTP), Fibre Channel Security Protocol (FC-SP), VSANs, hardware-enforced zoning, logical unit number (LUN) zoning, read-only zones, ACLs, port security, and VSAN-based access control
- **Flexibility and Investment Protection**—Share common switching modules across all Cisco MDS 9500 Series products as well as Cisco MDS 9200 Series multilayer fabric switches; Supports up to 64 Fibre Channel ports in a fabric switch configuration; Provides a 3-RU base system consisting of either sixteen 2/1-Gbps autosensing Fibre Channel ports or fourteen 2/1-Gbps autosensing Fibre Channel ports and two Gigabit Ethernet ports; Expandable with a variety of optional modules
- **Cost-Effective**—Offers advanced management tools for overall low total cost of ownership (TCO); Integrated VSAN technology for hardware-enforced, isolated environments within a single physical fabric for secure sharing of physical infrastructure, and integrated IVR (InterVSAN Routing) further decreasing TCO
- **Sophisticated Diagnostics**—Provides intelligent diagnostics, protocol, decoding, and network analysis tools as well as integrated call-home capability for added reliability, faster problem resolution, and reduced service costs
- **Configurable**—Provides embedded Cisco Fabric Manager, open APIs and integration and third party SAN and network management platforms
- **Open Platform**—For hosting intelligent storage services such as network-based volume management, data migration, and Network Accelerated Serverless Backup
- **Integrated Mainframe Support**—Cisco MDS 9500 Series and MDS 9200 Series multilayer fabric switches are mainframe-ready, with full support for IBM zSeries FICON and Linux environments. The switches support cascaded FICON fabrics, as well as intermix of FICON and open systems Fibre Channel Protocol (FCP) traffic on the same switch

Specifications

Feature	MDS 9509 Director	MDS 9506 Director	MDS 9216i Fabric Switch	MDS 9216a Fabric Switch	MDS 9100 Fabric Switch	MDS 9020 Fabric Switch
Modular Slots	9 slots: 2 for supervisors, 7 for connectivity	6 slots: 2 for supervisors, 4 for connectivity	2 slots: 1 fixed configuration - 14 Fibre Channel ports and 2 GE ports: 1 open slot for connectivity	2 slots: 1 fixed configuration 16 Fibre Channel ports: 1 slot for connectivity	fixed configuration, Fibre Channel ports	fixed auto-sensing 4/2/1-Gbps Fibre Channel ports
Maximum Number of Ports per Switch	224 Fibre Channel ports	128 Fibre Channel ports	46 Fibre Channel ports + 2 GE ports	48 Fibre Channel ports	MDS 9120/9140: 20 Fibre Channel ports and 40 Fibre Channel ports, respectively	20 Fibre Channel ports
Multiprotocol/Multitransport	Yes: Fibre Channel, FCIP, iSCSI, IP-FC and FICON	Yes: Fibre Channel, FCIP, iSCSI, IP-FC and FICON	Yes: Fibre Channel, FCIP, iSCSI, IP-FC and FICON	Yes: Fibre Channel, FCIP, iSCSI, IP-FC and FICON	No: Fibre Channel only	No: Fibre Channel only

Feature	MDS 9509 Director	MDS 9506 Director	MDS 9216i Fabric Switch	MDS 9216a Fabric Switch	MDS 9100 Fabric Switch	MDS 9020 Fabric Switch
High Availability:	Non-disruptive software upgrades, stateful failover, process re-startability, system health monitoring, hot swap: optics, power supplies, fans, supervisors, switching and services modules	Same as MDS 9509 Director	Stateful failover, process re-startability, system health monitoring, hot swap: optics, power supplies, fans, switching and services modules	Stateful failover, process re-startability, system health monitoring, hot swap: optics, power supplies, fans, switching and services modules	Stateful failover, process re-startability, system health monitoring, hot swap: optics, power supplies, and fans	Stateful failover, process re-startability, system health monitoring, hot swap: optics, power supplies, and fans
Intelligent Network Services: VSANs, PortChannels, Diagnostics, Security, Traffic Mgmt, QoS	Yes	Yes	Yes	Yes	Yes	Yes
Platform for Hosting network-based storage applications (virtualization, volume mgmt, data replication)	Yes	Yes	Yes	Yes	No	No
Embedded Fabric Management, open API, integration with CiscoWorks, third party SAN and network mgmt platforms	Yes	Yes	Yes	Yes	Yes	Yes
Dimensions (H x W x D)	24.5 x 17.25 x 18.4 in.	12.25 x 17.37 x 21.75 in	5.25 x 17.32 x 22.66 in	5.25 x 17.32 x 22.66 in	1.75 x 17.2 x 23.1 in	1.7 x 12 x 17 in
Max Buffer Credits per port	255 per port in the 16 port line card; 12 per port in the 32 port line card	Same as MDS 9509 Director	3500 per port on the base FC ports; 255 per port in the 16 port line card; 12 per port in the 32 port line card	255 per port in the 16 port line card and in the fixed module; 12 per port in the 32 port line card	255 per port (target-optimized ports); 12 per port (host-optimized ports)	Buffer credits: 16 per port
Port Channel	Up to 16 ports per Port Channel across switching modules	Up to 16 ports per Port Channel across switching modules	Up to 16 ports per Port Channel across switching modules	Up to 16 ports per Port Channel across switching modules	Cisco MDS 9120: No Up to 7 ports; Cisco MDS 9140: up to 15 ports	No
Optics Support	Fibre Channel Ethernet and CWDM	Same as MDS 9509 Director	Same as MDS 9509 Director	Same as MDS 9509 Director	Same as MDS 9509 Director	Same as MDS 9509 Director
HW enforced Zoning Support	N_Port WWN, F_Port WWN, N_Port FCID, Port Broadcast,	Same as MDS 9509 Director	Same as MDS 9509 Director	Same as MDS 9509 Director	Same as MDS 9509 Director	Yes
Default, LUN, Read Only	Yes	Yes	Yes	Yes	Yes	Yes
Security	Role-based access control, VSAN-based access control, Port security, RADIUS, TACACS+, SNMPv3, FC-SP, SSH, SSL, SFTP and IPsec	Same as MDS 9509 Director	Same as MDS 9509 Director	Same as MDS 9509 Director	Role-based access control, VSAN-based access control, Port security, RADIUS, TACACS+, SNMPv3, FC-SP, SSH, SSL, and SFTP	Network security, Access Control Lists, Fibre Channel N_Port WWN Zoning, Management access, SSH v2, SNMPv2

Selected Part Numbers and Ordering Information¹

MDS 9500 Base Configuration

DS-C9506	MDS 9506 Chassis
DS-C9506=	MDS 9506 Chassis, Spare
DS-C9509	MDS 9509 Chassis
DS-C9509=	MDS 9509 Chassis, Spare
DS-X9530-SF1-K9	MDS 9500 Supervisor/Fabric I
DS-X9530-SF1-K9=	MDS 9500 Supervisor/Fabric I, Spare

MDS 9000 Modules

DS-X9016	MDS 9000 16-port 1 / 2 Gbps FC Module
DS-X9016=	MDS 9000 16-port 1 / 2 Gbps FC Module, Spare
DS-X9032	MDS 9000 32-port 1 / 2 Gbps FC Module
DS-X9032=	MDS 9000 32-port 1 / 2 Gbps FC Module, Spare
DS-X9032-SMV	MDS 9000 Advanced Services Module
DS-X9032-SMV=	MDS 9000 Advanced Services Module, Spare
DS-X9032-SSM	MDS 9000 Storage Services Module
DS-X9032-SSM=	MDS 9000 Storage Services Module, Spare
DS-X9302-14K9	MDS 9000 2-port GE and 14-port FC Module
DS-X9302-14K9=	MDS 9000 2-port GE and 14-port FC Module, Spare
DS-X9304-SMIP	MDS 9000 4-port 1GE IP Storage Services Module
DS-X9304-SMIP=	MDS 9000 4-port 1GE IP Storage Services Module, Spare
DS-X9308-SMIP	MDS 9000 8-port 1GE IP Storage Services Module
DS-X9308-SMIP=	MDS 9000 8-port 1GE IP Storage Services Module, Spare
DS-SFP-FC-2G-SW	2 Gbps Fibre Channel-SW SFP, LC
DS-SFP-FC-2G-SW=	2 Gbps Fibre Channel-SW SFP, LC, Spare
DS-SFP-FC-2G-LW	2 Gbps Fibre Channel-LW SFP, LC
DS-SFP-FC-2G-LW=	2 Gbps Fibre Channel-LW SFP, LC, Spare
DS-SFP-FCGE-SW	1 Gbps Ethernet and 2 Gbps Fibre Channel-SW SFP, LC
DS-SFP-FCGE-SW=	1 Gbps Ethernet and 2 Gbps Fibre Channel-SW SFP, LC, Spare
DS-SFP-FCGE-LW	1 Gbps Ethernet and 2 Gbps Fibre Channel-LW SFP, LC
DS-SFP-FCGE-LW=	1 Gbps Ethernet and 2 Gbps Fibre Channel-LW SFP, LC, Spare

MDS 9500 Power Supplies and Cord Options

CAB-2500W-US1	Power Cord, 250VAC 20A, Straight C19, NEMA 6-20 Plug, US
CAB-2500W-US2	Power Cord, 250VAC 20A, Straight C19, NEMA L6-20 Plug, US
CAB-2500W-EU	Power Cord, 250VAC 16A, Straight C19, CEE 7/7 Plug, EU
CAB-2500W-INT	Power Cord, 250VAC 20A, Straight C19, IEC 309 Plug, INTL
CAB-2500W-SW	Power Cord, 250VAC 16A, Straight C19, 23G Plug, SWITZ
CAB-2500W-SA	Power Cord, 250VAC 16A, Straight C19, South Africa
DS-CAC-2500W	2500W AC Power Supply
DS-CAC-2500W=	2500W AC Power Supply, Spare
DS-CDC-2500W	2500W DC Power Supply
DS-CDC-2500W=	2500W DC Power Supply, Spare
DS-CAC-4000W-US	4000W AC Power Supply for US (cable attached)
DS-CAC-4000W-US=	4000W AC Power Supply for US (cable attached), spare
DS-CAC-4000W-INT	4000W AC Power Supply International (cable attached)
DS-CAC-4000W-INT=	4000W AC Power Supply International (cable attached), spare
DS-CAC-1900W	1900W AC Power Supply
DS-CAC-1900W=	1900W AC Power Supply, Spare

Additional MDS 9500 Power Cord Options

CAB-1900W-US1	Power Cord, 250VAC 20A, Right Angle C19, NEMA 6-20 Plug, US
CAB-1900W-US2	Power Cord, 250Vac 20A, Right Angle C19, NEMA L6-20 Plug, US
CAB-1900W-EU	Power Cord, 250VAC 16A, Right Angle C19, CEE 7/7 Plug, EU
CAB-1900W-INT	Power Cord, 250Vac 20A, Right Angle C19, IEC 309 Plug, INTL
DS-CDC-1900W	1900W DC Power Supply
DS-CDC-1900W=	1900W DC Power Supply, Spare

MDS 9500 Memory Options

MEM-MDS-FLD512M	MDS 9500 Sup Compact Flash Disk, 512MB
MEM-MDS-FLD512M=	MDS 9500 Sup Compact Flash Disk, 512MB, Spare

MDS 9200 Base Configuration

DS-C9216-K9	MDS 9216 16-port 2Gbps FC + 1-slot Modular Switch
DS-C9216A-K9	MDS 9216A 16-port 2Gbps FC + 1-slot Modular Switch
DS-C9216i-K9	MDS 9216i 14-port FC and 2-port GE + 1-slot Modular Switch

MDS 9200 Power Supplies and Cord Options

CAB-7KAC	AC Power Cord (North America)
CAB-7KACA	AC Power Cord (Australia)
CAB-7KACE	AC Power Cord (Europe)
CAB-7KACI	AC Power Cord (Italy)
CAB-7KACU	AC Power Cord (UK)
CAB-7KACR	AC Power Cord (Argentina)
CAB-7KACSW	AC Power Cord, 250VAC 10A, Straight C15, MP232 Plug, SWITZ
CAB-7KACSA	AC Power Cord (South Africa)
DS-CAC-845W	845W AC Power Supply
DS-CAC-845W=	845W AC Power Supply, Spare

MDS 9100 Base Configuration

DS-C9120-K9	MDS 9120 20-Port Fibre Channel Fabric Switch
DS-CAC-300W	300W AC Power Supply
DS-CAC-300W=	300W AC Power Supply, Spare

Cisco MDS 9020 Fabric Switch Base Configuration

DS-C9020-20K9	Cisco MDS 9020 Fabric Switch
---------------	------------------------------

Small Form-Factor Pluggable (SFP) Optics Options

DS-SFP-FC4G-SW	Cisco MDS 9000 Family 4/2/1-Gbps Fibre Channel-SW, SFP, LC
DS-SFP-FC4G-LW	Cisco MDS 9000 Family 4/2/1 Gbps Fibre Channel-LW, SFP, LC

Spare Components

DS-SFP-FC4G-SW=	Cisco MDS 9000 Family 4/2/1-Gbps Fibre Channel-SW, SFP, LC, Spare
DS-SFP-FC4G-LW=	Cisco MDS 9000 Family 4/2/1-Gbps Fibre Channel-LW, SFP, LC, Spare

MDS Software

M95S1K9-1.3.4	MDS 9500 Supervisor/Fabric-I, Enterprise SW, Release 1.3.4
M92S1K9-1.3.4	MDS 9200 Supervisor/Fabric-I, Enterprise SW, Release 1.3.4
M91S1K9-1.3.4	MDS 9100 Supervisor/Fabric-I, Enterprise SW, Release 1.3.4
M95S1K9-2.0.1	MDS 9500 Supervisor/Fabric-I, SAN-OS Software Release 2.0.1
M92S1K9-2.0.1	MDS 9200 Supervisor/Fabric-I, SAN-OS Software Release 2.0.1
M91S1K9-2.0.1	MDS 9100 Supervisor/Fabric-I, SAN-OS Software Release 2.0.1

MDS licensed features

M9500EXT1K9	FCIP license for 1 8-Port IP Storage module in MDS9500
M9500EXT1K9=	FCIP license for 1 8-Port IP Storage module in MDS9500, spare
M9200EXT1K9	FCIP license for 1 8-Port IP Storage module in MDS9200
M9200EXT1K9=	FCIP license for 1 8-Port IP Storage module in MDS9200, spare
M9500EXT14K9	FCIP license for 1 4-Port IP Storage module in MDS9500
M9500EXT14K9=	FCIP license for 1 4-Port IP Storage module in MDS9500, spare
M9200EXT14K9	FCIP license for 1 4-Port IP Storage module in MDS9200
M9200EXT14K9=	FCIP license for 1 4-Port IP Storage module in MDS9200, spare
M9500FIC1K9	MDS 9500 Mainframe Package license for 1 MDS 9500 switch
M9500FIC1K9=	MDS 9500 Mainframe Package license for 1 MDS 9500 switch, spare
M9200FIC1K9	MDS 9200 Mainframe Package license for 1 MDS 9200 switch
M9200FIC1K9=	MDS 9200 Mainframe Package license for 1 MDS 9200 switch, spare
M9500SSE1K9	Storage Services Enabler pkg: 1 ASM on 1 MDS9500
M9500SSE1K9=	Storage Services Enabler pkg: 1 ASM on 1 MDS9500, Spare
M9200SSE1K9	Storage Services Enabler pkg: 1 ASM on 1 MDS9200
M9200SSE1K9=	Storage Services Enabler pkg: 1 ASM on 1 MDS9200, Spare
M9500FMS1K9	MDS 9500 Fabric Manager Server license for 1 MDS 9500 switch
M9500FMS1K9=	MDS 9500 Fabric Manager Server license for 1 MDS 9500 switch, Spare
M9200FMS1K9	MDS 9200 Fabric Manager Server license for 1 MDS 9200 switch
M9200FMS1K9=	MDS 9200 Fabric Manager Server license for 1 MDS 9200 switch, Spare
M9100FMS1K9	MDS 9100 Fabric Manager Server license for 1 MDS 9100 switch
M9100FMS1K9=	MDS 9100 Fabric Manager Server license for 1 MDS 9100 switch, Spare
M9500ENT1K9	MDS 9500 Enterprise Package license for 1 MDS 9500 switch
M9500ENT1K9=	MDS 9500 Enterprise Package license for 1 MDS 9500 switch, spare
M9200ENT1K9	MDS 9200 Enterprise Package license for 1 MDS 9200 switch
M9200ENT1K9=	MDS 9200 Enterprise Package license for 1 MDS 9200 switch, spare
M9100ENT1K9	MDS 9100 Enterprise Package license for 1 MDS 9100 switch
M9100ENT1K9=	MDS 9100 Enterprise Package license for 1 MDS 9100 switch, spare
M9200EXT12K9	MDS 9200 14 + 2 SAN Extension over IP License, 1 count
M9200EXT12K9=	MDS 9200 14 + 2 SAN Extension over IP License, 1 count, spare
M9500EXT12K9	MDS 9500 14 + 2 SAN Extension over IP License, 1 count
M9500EXT12K9=	MDS 9500 14 + 2 SAN Extension over IP License, 1 count, spare

Port Analyzer Adapter

DS-PAA-2

MDS 9000 Port Analyzer Adapter

Port Analyzer Adapter Power Cord Options

CAB-2WIRE-ARG

Power Cord, 250VAC 2.5A, C7 coupler, Argentina

CAB-2WIRE-AUS

Power Cord, 250VAC 2.5A, C7 coupler, BS 1363 plug, Australia

CAB-2WIRE-EU

Power Cord, 250VAC 2.5A, C7 coupler, EN 50075 plug, EU

CAB-2WIRE-US

Power Cord, 125VAC 3A, C7 coupler, NEMA 1-15P plug, US

CAB-2WIRE-UK

Power Cord, 250VAC 2.5A, C7 coupler, AS 3112 plug, UK

CAB-2WIRE-KOR

Power Cord, 250VAC 2.5A, C7 coupler, Korea

Fiber Optic Cables

CAB-MM-LCLC-1M

Fiber Optic Cable, Multimode, LC/LC, 1 Meter

CAB-MM-LCLC-5M

Fiber Optic Cable, Multimode, LC/LC, 5 Meter

CAB-MM-LCLC-25M

Fiber Optic Cable, Multimode, LC/LC, 25 Meter

CAB-CP-SCLC-8IN

Fiber Optic Cable, Coupler, SC/LC, 8 Inch

CAB-CP-LCSC-2M

Fiber Optic Cable, Coupler, LC/SC, 2 Meter

CWDM Solution

CWDM-SFP-1470=

1470 NM CWDM Gigabit Ethernet and 2 Gbps FC SFP

CWDM-SFP-1490=

1490 NM CWDM Gigabit Ethernet and 2 Gbps FC SFP

CWDM-SFP-1510=

1510 NM CWDM Gigabit Ethernet and 2 Gbps FC SFP

CWDM-SFP-1530=

1530 NM CWDM Gigabit Ethernet and 2 Gbps FC SFP

CWDM-SFP-1550=

1550 NM CWDM Gigabit Ethernet and 2 Gbps FC SFP

CWDM-SFP-1570=

1570 NM CWDM Gigabit Ethernet and 2 Gbps FC SFP

CWDM-SFP-1590=

1590 NM CWDM Gigabit Ethernet and 2 Gbps FC SFP

CWDM-SFP-1610=

1610 NM CWDM Gigabit Ethernet and 2 Gbps FC SFP

CWDM-MUX-4=

4 Wavelength Add/Drop MUX for CWDM-CHASSIS-2=

CWDM-MUX-8=

8 Wavelength Mux/Demux Plug in Module for CWDM-CHASSIS-2=

CWDM-CHASSIS-2=

2 Slot Chassis for CWDM Mux Plug in Modules

CAB-SM-LCSC-1M

Fiber Optic Cable, Single mode, LC/SC, 1 Meter

CAB-SM-LCSC-5M

Fiber Optic Cable, Single mode, LC/SC, 5 Meter

For More Information

See the Cisco MDS 9000 Family Website: <http://www.cisco.com/go/storagenetworking>

Additional Storage Networking Solutions**Cisco MDS 9000 Port Analyzer Adapter—Reducing Time to Problem Resolution**

The Cisco MDS 9000 Port Analyzer Adapter enables effective, low-cost analysis of Fibre Channel traffic anywhere in the network at any time, simplifying debug of network problems and reducing time to problem resolution. The device is a “plug-and-play” accessory for the Cisco MDS 9000 Family that enables simple, transparent analysis of Fibre Channel traffic in a switched fabric, eliminating the need for expensive standalone protocol analyzers.

Cisco MDS 9000 Optical Modules—Optimizing SAN Interconnect

The Cisco MDS 9000 Family optical interface modules offer a broad range of SAN connectivity solutions for both local and extended reach. SFP modules for the Cisco MDS 9000 are available in either short-wave or long-wave options supporting Fibre Channel and Gigabit Ethernet connections over distances of up to 500 meters and 10 kilometers, respectively. Cisco CWDM SFPs and passive add/drop multiplexers provide cost-effective, multiprotocol, extended-distance connectivity by optimizing the use of the existing optical infrastructure.

