

## Modular Patch Panels for Snap-In Connectors

Patch Panel 24 Snap-In Fixed White

Nexans ref.: N521.661

- Compatible with all Snap-In connectors
- 24 Snap-In ports with shutters
- Clip-on mechanism
- Exclusive Auto-Connect Earthing system
- Universal design supporting Unscreened and Screened connectors
- Also available in black

### Description

Nexans Snap-In range of patch panels are designed to accommodate any of the Snap-In connectors in the LANmark product family (LANmark-7A, LANmark-7, LANmark-6A, LANmark-6, and LANmark-5).

The Snap-In panels feature an exclusive Clip-On system to secure the connector in the panel and to provide a simple means of earthing shielded connectors to facilitate installation. Connection of the panel to earth is achieved with a unique Auto-Connect feature removing the need for individual bonding conductors.

The panels also have a series of complementary cable management products such as blank panels and patch cord guides.

The patch panels are designed for standard 19" enclosures, are 1U high, and support the following common features:

- 24 Ports with shutters
- Designed for Screened and Unscreened Snap-In connectors
- Compatible with all performance categories of connector
- Clip-On mechanism for simple earthing
- Exclusive rear cable management facilities
- Robust construction
- Printed numbering for port labelling



**LANmark**

### Standards

**International**  
Manufacturer specification

## Modular Patch Panels for Snap-In Connectors

Patch Panel 24 Snap-In Fixed White

Nexans ref.: N521.661

### Characteristics

| Construction characteristics |                            |
|------------------------------|----------------------------|
| Colour                       | White                      |
| Material                     | Steel                      |
| Dimensional characteristics  |                            |
| Heightunit                   | 1 U                        |
| Depth                        | 75 mm                      |
| Width                        | 19 in                      |
| Usage characteristics        |                            |
| Field of application         | Fixed installations        |
| Resistance to vibrations     | High                       |
| Mechanical Resistance        | Good mechanical resistance |
| Number of ports              | 24                         |
| Packaging                    | Box                        |